

## Safety Data Sheet according to WHS Regulations

Printing date 03.06.2019

Version number 3

Revision: 03.06.2019

### 1 Identification

- **Product identifier**
- **Trade name:** VP404 ETCHING PRIMER
- **Article number:** VP404
- **Relevant identified uses of the substance or mixture and uses advised against**  
No further relevant information available.
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
Payless Services Pty Ltd  
103 Eldridge Road Bankstown 2200 NSW  
Australia  
Importer Business Phone numbers:  
+61 2 9 708 5698 Fax +61 2 9 796 2357
- **Further information obtainable from:** Product safety department
- **Emergency telephone number:**  
Emergency US – 1-800-535-5053 Outside US - +1-352-323-3500 InfoTrac Contract 89244

### 2 Hazard(s) Identification

- **Classification of the substance or mixture**



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS08 health hazard

Carc. 1A H350 May cause cancer.



GHS07

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- **Label elements**

- **GHS label elements**

The product is classified and labelled according to the Globally Harmonised System (GHS).

(Contd. on page 2)

# Safety Data Sheet

## according to WHS Regulations

Printing date 03.06.2019

Version number 3

Revision: 03.06.2019

**Trade name: VP404 ETCHING PRIMER**

(Contd. of page 1)

- **Hazard pictograms**



GHS02 GHS07 GHS08

- **Signal word** Danger

- **Hazard-determining components of labelling:**

ethanol  
 butanone  
 titanium dioxide  
 propan-2-ol

- **Hazard statements**

Highly flammable liquid and vapour.  
 Causes serious eye irritation.  
 May cause cancer.  
 May cause drowsiness or dizziness.

- **Precautionary statements**

Obtain special instructions before use.  
 Do not handle until all safety precautions have been read and understood.  
 Keep away from heat/sparks/open flames/hot surfaces. No smoking.  
 Ground/bond container and receiving equipment.  
 Use explosion-proof electrical/ventilating/lighting equipment.  
 Use only non-sparking tools.  
 Take precautionary measures against static discharge.  
 Avoid breathing dust/fume/gas/mist/vapours/spray.  
 Wash thoroughly after handling.  
 Use only outdoors or in a well-ventilated area.  
 Wear protective gloves/protective clothing/eye protection/face protection.  
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.  
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.  
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 IF exposed or concerned: Get medical advice/attention.  
 Call a POISON CENTER/doctor if you feel unwell.  
 If eye irritation persists: Get medical advice/attention.  
 In case of fire: Use for extinction: CO<sub>2</sub>, powder or water spray.  
 Store in a well-ventilated place. Keep container tightly closed.  
 Store in a well-ventilated place. Keep cool.  
 Store locked up.  
 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Other hazards**

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

### 3 Composition and Information on Ingredients

- **Chemical characterisation: Mixtures**

- **Description:** Mixture of substances listed below with nonhazardous additions.

(Contd. on page 3)

# Safety Data Sheet

## according to WHS Regulations

Printing date 03.06.2019

Version number 3

Revision: 03.06.2019

**Trade name: VP404 ETCHING PRIMER**

(Contd. of page 2)

· <b>Dangerous components:</b>		
78-93-3	butanone	25-50%
67-63-0	propan-2-ol	10-25%
64-17-5	ethanol	10-25%
13463-67-7	titanium dioxide	2.5-10%
110-43-0	heptan-2-one	2.5-10%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

### 4 First Aid Measures

- **Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Immediately rinse with water.
- **After eye contact:**  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**  
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

### 5 Fire Fighting Measures

- **Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

### 6 Accidental Release Measures

- **Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**  
Do not allow product to reach sewage system or any water course.  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.

(Contd. on page 4)

# Safety Data Sheet

## according to WHS Regulations

Printing date 03.06.2019

Version number 3

Revision: 03.06.2019

**Trade name: VP404 ETCHING PRIMER**

See Section 13 for disposal information.

(Contd. of page 3)

### 7 Handling and Storage

- **Handling:**
- **Precautions for safe handling**  
 Ensure good ventilation/exhaustion at the workplace.  
 Open and handle receptacle with care.  
 Prevent formation of aerosols.
- **Information about fire - and explosion protection:**  
 Keep ignition sources away - Do not smoke.  
 Protect against electrostatic charges.  
 Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**  
 Keep container tightly sealed.  
 Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

### 8 Exposure controls and personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **Control parameters**

**Ingredients with limit values that require monitoring at the workplace:**
**78-93-3 butanone**

NES Short-term value: 890 mg/m<sup>3</sup>, 300 ppm  
 Long-term value: 445 mg/m<sup>3</sup>, 150 ppm

WES Short-term value: 890 mg/m<sup>3</sup>, 300 ppm  
 Long-term value: 445 mg/m<sup>3</sup>, 150 ppm

**67-63-0 propan-2-ol**

NES Short-term value: 1230 mg/m<sup>3</sup>, 500 ppm  
 Long-term value: 983 mg/m<sup>3</sup>, 400 ppm

WES Short-term value: 1230 mg/m<sup>3</sup>, 500 ppm  
 Long-term value: 983 mg/m<sup>3</sup>, 400 ppm

**64-17-5 ethanol**

NES Long-term value: 1880 mg/m<sup>3</sup>, 1000 ppm

WES Long-term value: 1880 mg/m<sup>3</sup>, 1000 ppm

**110-43-0 heptan-2-one**

NES Long-term value: 233 mg/m<sup>3</sup>, 50 ppm

WES Long-term value: 233 mg/m<sup>3</sup>, 50 ppm

- **Additional information:** The lists valid during the making were used as basis.

- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**  
 Keep away from foodstuffs, beverages and feed.

(Contd. on page 5)

# Safety Data Sheet

## according to WHS Regulations

Printing date 03.06.2019

Version number 3

Revision: 03.06.2019

**Trade name: VP404 ETCHING PRIMER**

(Contd. of page 4)

*Immediately remove all soiled and contaminated clothing*

*Wash hands before breaks and at the end of work.*

*Store protective clothing separately.*

*Avoid contact with the eyes.*

*Avoid contact with the eyes and skin.*

· **Respiratory protection:**

*In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.*

· **Protection of hands:**



Protective gloves

*The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.*

*Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.*

*Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation*

· **Material of gloves**

*The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.*

· **Penetration time of glove material**

*The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.*

· **Eye protection:**



Tightly sealed goggles

## 9 Physical and Chemical Properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

· <b>Form:</b>	Liquid
· <b>Colour:</b>	Light brown
· <b>Odour:</b>	Characteristic
· <b>Odour threshold:</b>	Not determined.

· **pH-value:** Not determined.

· **Change in condition**

· <b>Melting point/freezing point:</b>	Undetermined.
· <b>Initial boiling point and boiling range:</b>	78 °C

· **Flash point:** -4 °C

· **Flammability (solid, gas):** Not applicable.

· **Ignition temperature:** 425 °C

(Contd. on page 6)

# Safety Data Sheet

## according to WHS Regulations

Printing date 03.06.2019

Version number 3

Revision: 03.06.2019

Trade name: VP404 ETCHING PRIMER

(Contd. of page 5)

· <b>Decomposition temperature:</b>	Not determined.
· <b>Auto-ignition temperature:</b>	Product is not selfigniting.
· <b>Explosive properties:</b>	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· <b>Explosion limits:</b>	
<b>Lower:</b>	1.8 Vol %
<b>Upper:</b>	15 Vol %
· <b>Vapour pressure at 20 °C:</b>	105 hPa
· <b>Density at 20 °C:</b>	0.835 g/cm <sup>3</sup>
· <b>Relative density</b>	Not determined.
· <b>Vapour density</b>	Not determined.
· <b>Evaporation rate</b>	Not determined.
· <b>Solubility in / Miscibility with water:</b>	Not miscible or difficult to mix.
· <b>Partition coefficient: n-octanol/water:</b>	Not determined.
· <b>Viscosity:</b>	
<b>Dynamic:</b>	Not determined.
<b>Kinematic:</b>	Not determined.
· <b>Solvent content:</b>	
<b>Organic solvents:</b>	74.5 %
<b>VOC (EC)</b>	68.69 %
<b>Solids content:</b>	31.3 %
· <b>Other information</b>	No further relevant information available.

### 10 Stability and Reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

### 11 Toxicological Information

- **Information on toxicological effects**
  - **Acute toxicity**
- |  |                         |
|--|-------------------------|
| · <b>LD/LC50 values relevant for classification:</b> |                         |
| 7779-90-0 trizinc bis(orthophosphate)                |                         |
| Oral   | LD50 >5,000 mg/kg (rat) |
- **Primary irritant effect:**
  - **Skin corrosion/irritation** No irritant effect.
  - **Serious eye damage/irritation** Irritating effect.

(Contd. on page 7)

-AU

# Safety Data Sheet

## according to WHS Regulations

Printing date 03.06.2019

Version number 3

Revision: 03.06.2019

**Trade name: VP404 ETCHING PRIMER**

(Contd. of page 6)

- **Respiratory or skin sensitisation** No sensitising effects known.
- **Additional toxicological information:**  
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:  
Irritant
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**  
Carc. 1A

### 12 Ecological Information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behaviour in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water  
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

### 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation**  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

### 14 Transport information

- |                                  |   |
|----------------------------------|---|
| · <b>UN-Number</b>               |   |
| · <b>ADG, IMDG, IATA</b>         | UN1263  |
| · <b>UN proper shipping name</b> |   |
| · <b>ADG</b>                     | 1263 PAINT, ENVIRONMENTALLY HAZARDOUS                 |
| · <b>IMDG</b>                    | PAINT (trizinc bis(orthophosphate)), MARINE POLLUTANT |
| · <b>IATA</b>                    | PAINT   |

(Contd. on page 8)

-AU

# Safety Data Sheet

## according to WHS Regulations

Printing date 03.06.2019

Version number 3

Revision: 03.06.2019

Trade name: VP404 ETCHING PRIMER

(Contd. of page 7)

· **Transport hazard class(es)**· **ADG, IMDG**

· **Class** 3 Flammable liquids.  
 · **Label** 3

· **IATA**

· **Class** 3 Flammable liquids.  
 · **Label** 3

· **Packing group**  
 · **ADG, IMDG, IATA** II

· **Environmental hazards:**  
 · **Marine pollutant:** Yes  
 Symbol (fish and tree)  
 · **Special marking (ADG):** Symbol (fish and tree)

· **Special precautions for user** Warning: Flammable liquids.  
 · **Danger code (Kemler):** 33  
 · **EMS Number:** F-E, S-E  
 · **Stowage Category** B

· **Transport in bulk according to Annex II of Marpol and the IBC Code** Not applicable.

· **Transport/Additional information:**

· **ADG**  
 · **Limited quantities (LQ)** 5L  
 · **Excepted quantities (EQ)** Code: E2  
 Maximum net quantity per inner packaging: 30 ml  
 Maximum net quantity per outer packaging: 500 ml  
 · **Transport category** 2  
 · **Tunnel restriction code** D/E

· **IMDG**  
 · **Limited quantities (LQ)** 5L  
 · **Excepted quantities (EQ)** Code: E2  
 Maximum net quantity per inner packaging: 30 ml  
 Maximum net quantity per outer packaging: 500 ml

· **UN "Model Regulation":** UN 1263 PAINT, 3, II, ENVIRONMENTALLY HAZARDOUS

AU

(Contd. on page 9)



# Safety Data Sheet

## according to WHS Regulations

Printing date 03.06.2019

Version number 3

Revision: 03.06.2019

**Trade name: VP404 ETCHING PRIMER**

(Contd. of page 8)

### 15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**

- **Australian Inventory of Chemical Substances**

All ingredients are listed.

- **Standard for the Uniform Scheduling of Medicines and Poisons**

78-93-3 butanone

S5

- **Australia: Priority Existing Chemicals**

None of the ingredients is listed.

- **GHS label elements**

The product is classified and labelled according to the Globally Harmonised System (GHS).

- **Hazard pictograms**



GHS02

GHS07

GHS08

- **Signal word** *Danger*

- **Hazard-determining components of labelling:**

ethanol

butanone

titanium dioxide

propan-2-ol

- **Hazard statements**

Highly flammable liquid and vapour.

Causes serious eye irritation.

May cause cancer.

May cause drowsiness or dizziness.

- **Precautionary statements**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapours/spray.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

**IF ON SKIN (or hair):** Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

**IF INHALED:** Remove victim to fresh air and keep at rest in a position comfortable for breathing.

**IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

**IF exposed or concerned:** Get medical advice/attention.

Call a POISON CENTER/doctor if you feel unwell.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use for extinction: CO<sub>2</sub>, powder or water spray.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

(Contd. on page 10)

# Safety Data Sheet

## according to WHS Regulations

Printing date 03.06.2019

Version number 3

Revision: 03.06.2019

**Trade name: VP404 ETCHING PRIMER**

(Contd. of page 9)

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category**  
E2 Hazardous to the Aquatic Environment  
P5c FLAMMABLE LIQUIDS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 200 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **National regulations:**
- **Additional classification according to Decree on Hazardous Materials, Annex II:**  
Carcinogenic hazardous material group III (dangerous).
- **Information about limitation of use:**  
Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.
- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### 16 Other information

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

- **Department issuing SDS:** Environment protection department.
- **Contact:** Mr. Roberts
- **Abbreviations and acronyms:**  
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
IMDG: International Maritime Code for Dangerous Goods  
IATA: International Air Transport Association  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service (division of the American Chemical Society)  
VOC: Volatile Organic Compounds (USA, EU)  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
PBT: Persistent, Bioaccumulative and Toxic  
vPvB: very Persistent and very Bioaccumulative  
Flam. Liq. 2: Flammable liquids – Category 2  
Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A  
Carc. 1A: Carcinogenicity – Category 1A  
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
- **\* Data compared to the previous version altered.**

AU