

## Safety Data Sheet according to WHS Regulations

Printing date 04.06.2019

Version number 3

Revision: 04.06.2019

### 1 Identification

- **Product identifier**
- **Trade name:** GBINDER BASECOAT BINDER
- **Article number:** GBINDER
- **Relevant identified uses of the substance or mixture and uses advised against**  
No further relevant information available.
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
Payless Services Pty Ltd  
103 Eldridge Road Bankstown 2200 NSW  
Australia  
Importer Business Phone numbers:  
+61 2 9 708 5698 Fax +61 2 9 796 2357
- **Further information obtainable from:** Product safety department
- **Emergency telephone number:**  
Emergency US – 1-800-535-5053 Outside US - +1-352-323-3500 InfoTrac Contract 89244

### 2 Hazard(s) Identification

- **Classification of the substance or mixture**



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS08 health hazard

Carc. 2 H351 Suspected of causing cancer.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- **Label elements**

- **GHS label elements**

The product is classified and labelled according to the Globally Harmonised System (GHS).

(Contd. on page 2)

# Safety Data Sheet

## according to WHS Regulations

Printing date 04.06.2019

Version number 3

Revision: 04.06.2019

**Trade name: GBINDER BASECOAT BINDER**

(Contd. of page 1)

**· Hazard pictograms**


GHS02 GHS07 GHS08

**· Signal word Danger**
**· Hazard-determining components of labelling:**

*n*-butyl acetate  
acetone

**· Hazard statements**

*Highly flammable liquid and vapour.*  
*Causes skin irritation.*  
*Causes serious eye irritation.*  
*Suspected of causing cancer.*  
*May cause drowsiness or dizziness.*

**· Precautionary statements**

*Obtain special instructions before use.*  
*Do not handle until all safety precautions have been read and understood.*  
*Keep away from heat/sparks/open flames/hot surfaces. No smoking.*  
*Ground/bond container and receiving equipment.*  
*Use explosion-proof electrical/ventilating/lighting equipment.*  
*Use only non-sparking tools.*  
*Take precautionary measures against static discharge.*  
*Avoid breathing dust/fume/gas/mist/vapours/spray.*  
*Wash thoroughly after handling.*  
*Use only outdoors or in a well-ventilated area.*  
*Wear protective gloves/protective clothing/eye protection/face protection.*  
*IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.*  
*IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.*  
*IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.*  
*IF exposed or concerned: Get medical advice/attention.*  
*Call a POISON CENTER/doctor if you feel unwell.*  
*Specific treatment (see on this label).*  
*Take off contaminated clothing and wash it before reuse.*  
*If skin irritation occurs: Get medical advice/attention.*  
*If eye irritation persists: Get medical advice/attention.*  
*In case of fire: Use for extinction: CO<sub>2</sub>, powder or water spray.*  
*Store in a well-ventilated place. Keep container tightly closed.*  
*Store in a well-ventilated place. Keep cool.*  
*Store locked up.*  
*Dispose of contents/container in accordance with local/regional/national/international regulations.*

**· Other hazards**
**· Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

-AU-

(Contd. on page 3)

# Safety Data Sheet

## according to WHS Regulations

Printing date 04.06.2019

Version number 3

Revision: 04.06.2019

Trade name: **GBINDER BASECOAT BINDER**

(Contd. of page 2)

### 3 Composition and Information on Ingredients

- **Chemical characterisation: Mixtures**
- **Description:** Mixture of substances listed below with nonhazardous additions.

- **Dangerous components:**

|           |  |         |
|-----------|--|---------|
| 123-86-4  | <i>n</i> -butyl acetate                            | 50-100% |
| 1330-20-7 | xylene   | 2.5-10% |
| 98-56-6   | 4-chloro- $\alpha,\alpha,\alpha$ -trifluorotoluene | 2.5-10% |
| 67-64-1   | acetone  | 2.5-10% |
| 119-64-2  | 1,2,3,4-tetrahydronaphthalene                      | ≤2.5%   |
| 100-41-4  | ethylbenzene                                       | ≤2.5%   |

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

### 4 First Aid Measures

- **Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**  
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

### 5 Fire Fighting Measures

- **Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

### 6 Accidental Release Measures

- **Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- **Reference to other sections**  
See Section 7 for information on safe handling.

(Contd. on page 4)

# Safety Data Sheet

## according to WHS Regulations

Printing date 04.06.2019

Version number 3

Revision: 04.06.2019

**Trade name: GBINDER BASECOAT BINDER**

(Contd. of page 3)

See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

### 7 Handling and Storage

- **Handling:**
- **Precautions for safe handling**  
Ensure good ventilation/exhaustion at the workplace.  
Open and handle receptacle with care.  
Prevent formation of aerosols.
- **Information about fire - and explosion protection:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.  
Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**  
Keep container tightly sealed.  
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

### 8 Exposure controls and personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

#### 123-86-4 n-butyl acetate

|     |   |
|-----|---|
| NES | Short-term value: 950 mg/m <sup>3</sup> , 200 ppm<br>Long-term value: 713 mg/m <sup>3</sup> , 150 ppm |
| WES | Short-term value: 950 mg/m <sup>3</sup> , 200 ppm<br>Long-term value: 713 mg/m <sup>3</sup> , 150 ppm |

#### 1330-20-7 xylene

|     |  |
|-----|--|
| NES | Short-term value: 655 mg/m <sup>3</sup> , 150 ppm<br>Long-term value: 350 mg/m <sup>3</sup> , 80 ppm |
| WES | Short-term value: 655 mg/m <sup>3</sup> , 150 ppm<br>Long-term value: 350 mg/m <sup>3</sup> , 80 ppm |

#### 67-64-1 acetone

|     |  |
|-----|--|
| NES | Short-term value: 2375 mg/m <sup>3</sup> , 1000 ppm<br>Long-term value: 1185 mg/m <sup>3</sup> , 500 ppm |
| WES | Short-term value: 2375 mg/m <sup>3</sup> , 1000 ppm<br>Long-term value: 1185 mg/m <sup>3</sup> , 500 ppm |

#### 100-41-4 ethylbenzene

|     |   |
|-----|---|
| NES | Short-term value: 543 mg/m <sup>3</sup> , 125 ppm<br>Long-term value: 434 mg/m <sup>3</sup> , 100 ppm |
| WES | Short-term value: 543 mg/m <sup>3</sup> , 125 ppm<br>Long-term value: 434 mg/m <sup>3</sup> , 100 ppm |

(Contd. on page 5)

# Safety Data Sheet

## according to WHS Regulations

Printing date 04.06.2019

Version number 3

Revision: 04.06.2019

**Trade name: GBINDER BASECOAT BINDER**

(Contd. of page 4)

- **Additional information:** The lists valid during the making were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**  
 Keep away from foodstuffs, beverages and feed.  
 Immediately remove all soiled and contaminated clothing  
 Wash hands before breaks and at the end of work.  
 Store protective clothing separately.  
 Avoid contact with the eyes and skin.
- **Respiratory protection:**  
 In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**  
 The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**  
 The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:**



Tightly sealed goggles

## 9 Physical and Chemical Properties

- **Information on basic physical and chemical properties**
  - **General Information**
  - **Appearance:**

|                |        |
|----------------|--------|
| <b>Form:</b>   | Liquid |
| <b>Colour:</b> | Cloudy |
  - **Odour:** Characteristic
  - **Odour threshold:** Not determined.
- 
- **pH-value:** Not determined.
- 
- **Change in condition**

|   |               |
|---|---------------|
| <b>Melting point/freezing point:</b>            | Undetermined. |
| <b>Initial boiling point and boiling range:</b> | 55 °C         |

(Contd. on page 6)

# Safety Data Sheet

## according to WHS Regulations

Printing date 04.06.2019

Version number 3

Revision: 04.06.2019

**Trade name: GBINDER BASECOAT BINDER**

(Contd. of page 5)

|  |   |
|--|---|
| · <b>Flash point:</b>                            | -17 °C  |
| · <b>Flammability (solid, gas):</b>              | Not applicable.   |
| · <b>Ignition temperature:</b>                   | 370 °C  |
| · <b>Decomposition temperature:</b>              | Not determined.   |
| · <b>Auto-ignition temperature:</b>              | Product is not selfigniting.  |
| · <b>Explosive properties:</b>                   | Product is not explosive. However, formation of explosive air/vapour mixtures are possible. |
| · <b>Explosion limits:</b>                       |   |
| Lower:   | 1.2 Vol %   |
| Upper:   | 7.5 Vol %   |
| · <b>Vapour pressure at 20 °C:</b>               | 10.7 hPa  |
| · <b>Density at 20 °C:</b>                       | 0.9623 g/cm <sup>3</sup>  |
| · <b>Relative density</b>                        | Not determined.   |
| · <b>Vapour density</b>                          | Not determined.   |
| · <b>Evaporation rate</b>                        | Not determined.   |
| · <b>Solubility in / Miscibility with water:</b> | Not miscible or difficult to mix.   |
| · <b>Partition coefficient: n-octanol/water:</b> | Not determined.   |
| · <b>Viscosity:</b>                              |   |
| Dynamic:   | Not determined.   |
| Kinematic:                                       | Not determined.   |
| · <b>Solvent content:</b>                        |   |
| Organic solvents:                                | 67.0 %  |
| VOC (EC)   | 76.56 %   |
| Solids content:                                  | 23.6 %  |
| · <b>Other information</b>                       | No further relevant information available.  |

### 10 Stability and Reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

AU

(Contd. on page 7)

# Safety Data Sheet

## according to WHS Regulations

Printing date 04.06.2019

Version number 3

Revision: 04.06.2019

Trade name: **GBINDER BASECOAT BINDER**

(Contd. of page 6)

### 11 Toxicological Information

- **Information on toxicological effects**
- **Acute toxicity**

- **LD/LC50 values relevant for classification:**

#### 1330-20-7 xylene

|        |      |                      |
|--------|------|----------------------|
| Oral   | LD50 | 4,300 mg/kg (rat)    |
| Dermal | LD50 | 2,000 mg/kg (rabbit) |

- **Primary irritant effect:**
- **Skin corrosion/irritation** Irritant to skin and mucous membranes.
- **Serious eye damage/irritation** Irritating effect.
- **Respiratory or skin sensitisation** No sensitising effects known.
- **Additional toxicological information:**  
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:  
Irritant
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**  
Carc. 2

### 12 Ecological Information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behaviour in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

### 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation**  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

AU

(Contd. on page 8)

# Safety Data Sheet

## according to WHS Regulations

Printing date 04.06.2019


Version number 3

Revision: 04.06.2019

Trade name: **GBINDER BASECOAT BINDER**

(Contd. of page 7)

### 14 Transport information

|   |   |
|---|---|
| · UN-Number   |   |
| · ADG, IMDG, IATA   | UN1263  |
| · UN proper shipping name   |   |
| · ADG   | 1263 PAINT  |
| · IMDG, IATA  | PAINT   |
| · Transport hazard class(es)  |   |
| · ADG, IMDG, IATA   |   |
|  |   |
| · Class   | 3 Flammable liquids.  |
| · Label   | 3   |
| · Packing group   |   |
| · ADG, IMDG, IATA   | II  |
| · Environmental hazards:  |   |
| · Marine pollutant:   | No  |
| · Special precautions for user  | Warning: Flammable liquids.   |
| · Danger code (Kemler):   | 33  |
| · EMS Number:   | F-E, S-E  |
| · Stowage Category  | B   |
| · Transport in bulk according to Annex II of Marpol and the IBC Code              | Not applicable.   |
| · Transport/Additional information:   |   |
| · ADG   |   |
| · Limited quantities (LQ)   | 5L  |
| · Excepted quantities (EQ)  | Code: E2<br>Maximum net quantity per inner packaging: 30 ml<br>Maximum net quantity per outer packaging: 500 ml |
| · Transport category  | 2   |
| · Tunnel restriction code   | D/E   |
| · IMDG  |   |
| · Limited quantities (LQ)   | 5L  |
| · Excepted quantities (EQ)  | Code: E2<br>Maximum net quantity per inner packaging: 30 ml<br>Maximum net quantity per outer packaging: 500 ml |
| · UN "Model Regulation":  | UN 1263 PAINT, 3, II  |

### 15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
  - Australian Inventory of Chemical Substances
- All ingredients are listed.

(Contd. on page 9)

AU



# Safety Data Sheet

## according to WHS Regulations

Printing date 04.06.2019

Version number 3

Revision: 04.06.2019

**Trade name: GBINDER BASECOAT BINDER**

(Contd. of page 8)

**Standard for the Uniform Scheduling of Medicines and Poisons**

|           |         |    |
|-----------|---------|----|
| 1330-20-7 | xylene  | S6 |
| 67-64-1   | acetone | S5 |

**Australia: Priority Existing Chemicals**

None of the ingredients is listed.

**GHS label elements**

The product is classified and labelled according to the Globally Harmonised System (GHS).

**Hazard pictograms**


GHS02 GHS07 GHS08

**Signal word** *Danger*
**Hazard-determining components of labelling:**

*n*-butyl acetate  
acetone

**Hazard statements**

*Highly flammable liquid and vapour.*  
*Causes skin irritation.*  
*Causes serious eye irritation.*  
*Suspected of causing cancer.*  
*May cause drowsiness or dizziness.*

**Precautionary statements**

*Obtain special instructions before use.*  
*Do not handle until all safety precautions have been read and understood.*  
*Keep away from heat/sparks/open flames/hot surfaces. No smoking.*  
*Ground/bond container and receiving equipment.*  
*Use explosion-proof electrical/ventilating/lighting equipment.*  
*Use only non-sparking tools.*  
*Take precautionary measures against static discharge.*  
*Avoid breathing dust/fume/gas/mist/vapours/spray.*  
*Wash thoroughly after handling.*  
*Use only outdoors or in a well-ventilated area.*  
*Wear protective gloves/protective clothing/eye protection/face protection.*  
*IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.*  
*IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.*  
*IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.*  
*IF exposed or concerned: Get medical advice/attention.*  
*Call a POISON CENTER/doctor if you feel unwell.*  
*Specific treatment (see on this label).*  
*Take off contaminated clothing and wash it before reuse.*  
*If skin irritation occurs: Get medical advice/attention.*  
*If eye irritation persists: Get medical advice/attention.*  
*In case of fire: Use for extinction: CO<sub>2</sub>, powder or water spray.*  
*Store in a well-ventilated place. Keep container tightly closed.*  
*Store in a well-ventilated place. Keep cool.*  
*Store locked up.*  
*Dispose of contents/container in accordance with local/regional/national/international regulations.*

(Contd. on page 10)

# Safety Data Sheet

## according to WHS Regulations

Printing date 04.06.2019

Version number 3

Revision: 04.06.2019

**Trade name: GBINDER BASECOAT BINDER**

(Contd. of page 9)

- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category P5c** FLAMMABLE LIQUIDS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t
- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### 16 Other information

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

- **Department issuing SDS:** Environment protection department.
- **Contact:** Mr. Roberts
- **Abbreviations and acronyms:**  
 ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
 IMDG: International Maritime Code for Dangerous Goods  
 IATA: International Air Transport Association  
 EINECS: European Inventory of Existing Commercial Chemical Substances  
 ELINCS: European List of Notified Chemical Substances  
 CAS: Chemical Abstracts Service (division of the American Chemical Society)  
 VOC: Volatile Organic Compounds (USA, EU)  
 LC50: Lethal concentration, 50 percent  
 LD50: Lethal dose, 50 percent  
 PBT: Persistent, Bioaccumulative and Toxic  
 vPvB: very Persistent and very Bioaccumulative  
 Flam. Liq. 2: Flammable liquids – Category 2  
 Skin Irrit. 2: Skin corrosion/irritation – Category 2  
 Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A  
 Carc. 2: Carcinogenicity – Category 2  
 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
- **\* Data compared to the previous version altered.**

AU