

Safety Data Sheet according to WHS Regulations

Printing date 03.06.2019

Version number 4

Revision: 03.06.2019

1 Identification

- **Product identifier**
- **Trade name:** 150B 150 SERIES BINDER
- **Article number:** 150B
- **Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Payless Services Pty Ltd
103 Eldridge Road Bankstown 2200 NSW
Australia
Importer Business Phone numbers:
+61 2 9 708 5698 Fax +61 2 9 796 2357
- **Further information obtainable from:** Product safety department
- **Emergency telephone number:**
Emergency US – 1-800-535-5053 Outside US - +1-352-323-3500 InfoTrac Contract 89244

2 Hazard(s) Identification

- **Classification of the substance or mixture**



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS08 health hazard

Muta. 1B H340 May cause genetic defects.

Carc. 1B H350 May cause cancer.

STOT RE 1 H372 Causes damage to the central nervous system through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- **Label elements**
- **GHS label elements**

The product is classified and labelled according to the Globally Harmonised System (GHS).

(Contd. on page 2)

Safety Data Sheet

according to WHS Regulations

Printing date 03.06.2019

Version number 4

Revision: 03.06.2019

Trade name: 150B 150 SERIES BINDER

(Contd. of page 1)

- **Hazard pictograms**



GHS02 GHS07 GHS08

- **Signal word** Danger

- **Hazard-determining components of labelling:**

Stoddard solvent
 Naphtha (petroleum), hydrotreated light
 Solvent naphtha (petroleum), light arom.
 ethylbenzene
 2-butanone oxime

- **Hazard statements**

Flammable liquid and vapour.
 Causes skin irritation.
 May cause an allergic skin reaction.
 May cause genetic defects.
 May cause cancer.
 Causes damage to the central nervous system through prolonged or repeated exposure.
 May be fatal if swallowed and enters airways.

- **Precautionary statements**

Obtain special instructions before use.
 Do not handle until all safety precautions have been read and understood.
 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
 Keep container tightly closed.
 Ground/bond container and receiving equipment.
 Use explosion-proof electrical/ventilating/lighting equipment.
 Use only non-sparking tools.
 Take precautionary measures against static discharge.
 Do not breathe dust/fume/gas/mist/vapours/spray.
 Wash thoroughly after handling.
 Do not eat, drink or smoke when using this product.
 Contaminated work clothing should not be allowed out of the workplace.
 Wear protective gloves/protective clothing/eye protection/face protection.
 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
 Specific treatment (see on this label).
 Do NOT induce vomiting.
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
 IF exposed or concerned: Get medical advice/attention.
 Get medical advice/attention if you feel unwell.
 Take off contaminated clothing and wash it before reuse.
 If skin irritation or rash occurs: Get medical advice/attention.
 Wash contaminated clothing before reuse.
 In case of fire: Use for extinction: CO₂, powder or water spray.
 Store in a well-ventilated place. Keep cool.
 Store locked up.
 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Other hazards**

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

(Contd. on page 3)

Safety Data Sheet

according to WHS Regulations

Printing date 03.06.2019

Version number 4

Revision: 03.06.2019

Trade name: 150B 150 SERIES BINDER

· **vPvB:** Not applicable.

(Contd. of page 2)

3 Composition and Information on Ingredients

- **Chemical characterisation: Mixtures**
- **Description:** Mixture of substances listed below with nonhazardous additions.

- **Dangerous components:**

1330-20-7	xylene	25-50%
64742-49-0	Naphtha (petroleum), hydrotreated light	2.5-10%
8052-41-3	Stoddard solvent	2.5-10%
64742-95-6	Solvent naphtha (petroleum), light arom.	2.5-10%
96-29-7	2-butanone oxime	≤2.5%
136-52-7	cobalt(II) 2-ethylhexanoate	≤2.5%

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

4 First Aid Measures

- **Description of first aid measures**
- **General information:**
Immediately remove any clothing soiled by the product.
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
· **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire Fighting Measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental Release Measures

- **Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.

(Contd. on page 4)

Safety Data Sheet

according to WHS Regulations

Printing date 03.06.2019

Version number 4

Revision: 03.06.2019

Trade name: 150B 150 SERIES BINDER

(Contd. of page 3)

Wear protective equipment. Keep unprotected persons away.

· **Environmental precautions:**

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and Storage

· **Handling:**

· **Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· **Information about fire - and explosion protection:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

· **Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:** No special requirements.

· **Information about storage in one common storage facility:** Not required.

· **Further information about storage conditions:** Keep container tightly sealed.

· **Specific end use(s)** No further relevant information available.

8 Exposure controls and personal protection

· **Additional information about design of technical facilities:** No further data; see item 7.

· **Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

1330-20-7 xylene

NES	Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 350 mg/m ³ , 80 ppm
-----	--

WES	Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 350 mg/m ³ , 80 ppm
-----	--

8052-41-3 Stoddard solvent

NES	Long-term value: 790 mg/m ³
-----	--

WES	Long-term value: 790 mg/m ³
-----	--

· **Additional information:** The lists valid during the making were used as basis.

(Contd. on page 5)

Safety Data Sheet

according to WHS Regulations

Printing date 03.06.2019

Version number 4

Revision: 03.06.2019

Trade name: 150B 150 SERIES BINDER

(Contd. of page 4)

- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
 Keep away from foodstuffs, beverages and feed.
 Immediately remove all soiled and contaminated clothing
 Wash hands before breaks and at the end of work.
 Store protective clothing separately.
 Avoid contact with the skin.
 Avoid contact with the eyes and skin.
- **Respiratory protection:**
 In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**
 The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**
 The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:**



Tightly sealed goggles

9 Physical and Chemical Properties

- **Information on basic physical and chemical properties**
 - **General Information**
 - **Appearance:**

Form:	Liquid
Colour:	Light brown
 - **Odour:** Characteristic
 - **Odour threshold:** Not determined.
-
- **pH-value:** Not determined.
-
- **Change in condition**

Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	137 °C

(Contd. on page 6)

Safety Data Sheet

according to WHS Regulations

Printing date 03.06.2019

Version number 4

Revision: 03.06.2019

Trade name: 150B 150 SERIES BINDER

(Contd. of page 5)

· Flash point:	30 °C
· Flammability (solid, gas):	Not applicable.
· Ignition temperature:	230 °C
· Decomposition temperature:	Not determined.
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits:	
Lower:	1.1 Vol %
Upper:	7 Vol %
· Vapour pressure at 20 °C:	6.7-8.2 hPa
· Density at 20 °C:	0.962 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	50.3 %
VOC (EC)	54.48 %
· Solids content:	43.5 %
· Other information	No further relevant information available.

10 Stability and Reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

AU

(Contd. on page 7)

Safety Data Sheet

according to WHS Regulations

Printing date 03.06.2019

Version number 4

Revision: 03.06.2019

Trade name: 150B 150 SERIES BINDER

(Contd. of page 6)

11 Toxicological Information

- **Information on toxicological effects**
- **Acute toxicity**

- **LD/LC50 values relevant for classification:**

1330-20-7 xylene

Oral	LD50	4,300 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)

64742-95-6 Solvent naphtha (petroleum), light arom.

Oral	LD50	>6,800 mg/kg (rat)
Dermal	LD50	>3,400 mg/kg (rab)
Inhalative	LC50/4 h	>10.2 mg/l (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Irritant to skin and mucous membranes.
- **Serious eye damage/irritation** No irritating effect.
- **Respiratory or skin sensitisation** Sensitisation possible through skin contact.
- **Additional toxicological information:**
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:
Irritant
The product can cause inheritable damage.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
Muta. 1B, Carc. 1B

12 Ecological Information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behaviour in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 8)

AU

Safety Data Sheet

according to WHS Regulations

Printing date 03.06.2019

Version number 4


Revision: 03.06.2019

Trade name: 150B 150 SERIES BINDER

(Contd. of page 7)

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

<ul style="list-style-type: none"> · UN-Number · ADG, IMDG, IATA 	UN1263
<ul style="list-style-type: none"> · UN proper shipping name · ADG · IMDG, IATA 	1263 PAINT PAINT
<ul style="list-style-type: none"> · Transport hazard class(es) · ADG, IMDG, IATA 	<div style="text-align: center;">  </div>
<ul style="list-style-type: none"> · Class · Label 	3 Flammable liquids. 3
<ul style="list-style-type: none"> · Packing group · ADG, IMDG, IATA 	III
<ul style="list-style-type: none"> · Environmental hazards: · Marine pollutant: 	No
<ul style="list-style-type: none"> · Special precautions for user · Danger code (Kemler): · EMS Number: · Stowage Category 	Warning: Flammable liquids. 30 F-E, S-E A
<ul style="list-style-type: none"> · Transport in bulk according to Annex II of Marpol and the IBC Code 	Not applicable.
<ul style="list-style-type: none"> · Transport/Additional information: 	
<ul style="list-style-type: none"> · ADG · Limited quantities (LQ) · Excepted quantities (EQ) 	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
<ul style="list-style-type: none"> · Transport category · Tunnel restriction code 	3 D/E
<ul style="list-style-type: none"> · IMDG · Limited quantities (LQ) · Excepted quantities (EQ) 	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
<ul style="list-style-type: none"> · UN "Model Regulation": 	UN 1263 PAINT, 3, III

AU

(Contd. on page 9)

Safety Data Sheet

according to WHS Regulations

Printing date 03.06.2019

Version number 4

Revision: 03.06.2019

Trade name: 150B 150 SERIES BINDER

(Contd. of page 8)

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**

- **Australian Inventory of Chemical Substances**

All ingredients are listed.

- **Standard for the Uniform Scheduling of Medicines and Poisons**

1330-20-7	xylene	S6
96-29-7	2-butanone oxime	S6
112-34-5	2-(2-butoxyethoxy)ethanol	S5
122-99-6	2-Phenoxyethanol	S6
149-57-5	2-ethylhexanoic acid	S6

- **Australia: Priority Existing Chemicals**

None of the ingredients is listed.

- **GHS label elements**

The product is classified and labelled according to the Globally Harmonised System (GHS).

- **Hazard pictograms**



GHS02 GHS07 GHS08

- **Signal word Danger**

- **Hazard-determining components of labelling:**

Stoddard solvent

Naphtha (petroleum), hydrotreated light

Solvent naphtha (petroleum), light arom.

ethylbenzene

2-butanone oxime

- **Hazard statements**

Flammable liquid and vapour.

Causes skin irritation.

May cause an allergic skin reaction.

May cause genetic defects.

May cause cancer.

Causes damage to the central nervous system through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

- **Precautionary statements**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Contaminated work clothing should not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

(Contd. on page 10)

Safety Data Sheet

according to WHS Regulations

Printing date 03.06.2019

Version number 4

Revision: 03.06.2019

Trade name: 150B 150 SERIES BINDER

(Contd. of page 9)

IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

Specific treatment (see on this label).

Do NOT induce vomiting.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/ shower.

IF exposed or concerned: Get medical advice/attention.

Get medical advice/attention if you feel unwell.

Take off contaminated clothing and wash it before reuse.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

In case of fire: Use for extinction: CO₂, powder or water spray.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Directive 2012/18/EU**

· **Named dangerous substances - ANNEX I** None of the ingredients is listed.

· **Seveso category P5c** FLAMMABLE LIQUIDS

· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t

· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t

· **National regulations:**

· **Additional classification according to Decree on Hazardous Materials, Annex II:**

Carcinogenic hazardous material group III (dangerous).

· **Information about limitation of use:**

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Environment protection department.

· **Contact:** Mr. Roberts

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Muta. 1B: Germ cell mutagenicity – Category 1B

Carc. 1B: Carcinogenicity – Category 1B

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

Asp. Tox. 1: Aspiration hazard – Category 1

· *** Data compared to the previous version altered.**