

Page 1/12

Safety Data Sheet acc. to OSHA HCS

Printing date 02/27/2024

Reviewed on 02/27/2024

1 Identification

· Product identifier

· Trade name: LC3030 MS CLEAR

· Article number: LC3030

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

GlobalStar is a product of Lusid Technologies Inc.

4725 S Camp Kearns Road

Kearns, UT 84118 (801) 966-5300

info@lusidtechnologies.com

· Information department: Product safety department

Emergency telephone number:

24 Hrs Emergency Contact:

INFOTRAC 1-800-535-5053

2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flammable Liquids 2

H225 Highly flammable liquid and vapor.



GHS07

Skin Irritation 2

H315 Causes skin irritation.

Eye Irritation 2A H319 Causes serious eye irritation.

Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms





GHS02 GHS07

- · Signal word Danger
- Hazard-determining components of labeling: n-butyl acetate acetone

(Contd. on page 2)

Printing date 02/27/2024 Reviewed on 02/27/2024

Trade name: LC3030 MS CLEAR

(Contd. of page 1)

· Hazard statements

Highly flammable liquid and vapor.

Causes skin irritation.

Causes serious eye irritation.

May cause drowsiness or dizziness.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Call a poison center/doctor if you feel unwell.

Specific treatment (see on this label).

Take off contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

If eve irritation persists: Get medical advice/attention.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- Classification system:
- NFPA ratings (scale 0 4)



Health = 2Fire = 3Reactivity = 0

· HMIS-ratings (scale 0 - 4)



2 Health = 2 Fire = 3

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.
- · Dangerous components:

123-86-4 n-butyl acetate

25-50%

(Contd. on page 3)

Printing date 02/27/2024 Reviewed on 02/27/2024

Trade name: LC3030 MS CLEAR

		(Contd. of page 2)
67-64-1	acetone	10-25%
1330-20-7	xylene	10-25%

4 First-aid measures

- · Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Prevent seepage into sewage system, workpits and cellars.

Dilute with plenty of water.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Protective Action Criteria for Chemicals

PAC-1:			
123-86-4	n-butyl acetate		5 ppm
67-64-1	acetone		200 ppm
1330-20-7	xylene		130 ppm
110-43-0	heptan-2-one		150 ppm
868-77-9	2-hydroxyethyl methacrylate		1.9 mg/m
		(Coi	ntd. on page

a. on page 4)

Printing date 02/27/2024 Reviewed on 02/27/2024

Trade name: LC3030 MS CLEAR

100-41-4	ethylbenzene	(Contd. of page 33 ppm
	dibutyltin dilaurate	1.1 mg/m
	2-phenoxyethanol	1.5 ppm
	2-ethylhexyl acrylate	1.5 ppm
108-88-3	• •	67 ppm
	tolderie	ον ρριτι
PAC-2:	To both to color	1000
	n-butyl acetate	200 ppm
	acetone	3200* ppr
1330-20-7		920* ppm
110-43-0	heptan-2-one	670 ppm
868-77-9	2-hydroxyethyl methacrylate	21 mg/m³
100-41-4	ethylbenzene	1100* ppr
77-58-7	dibutyltin dilaurate	8 mg/m³
122-99-6	2-phenoxyethanol	16 ppm
103-11-7	2-ethylhexyl acrylate	120 ppm
108-88-3	toluene	560 ppm
PAC-3:		
123-86-4	n-butyl acetate	3000* ppm
67-64-1	acetone	5700* ppm
1330-20-7	xylene	2500* ppm
110-43-0	heptan-2-one	4000* ppm
868-77-9	2-hydroxyethyl methacrylate	1,000 mg/m
100-41-4	ethylbenzene	1800* ppm
77-58-7	dibutyltin dilaurate	48 mg/m³
122-99-6	2-phenoxyethanol	97 ppm
103-11-7	2-ethylhexyl acrylate	150 ppm
108-88-3	toluene	3700* ppm

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

(Contd. on page 5)

Printing date 02/27/2024 Reviewed on 02/27/2024

Trade name: LC3030 MS CLEAR

· Specific end use(s) No further relevant information available.

(Contd. of page 4)

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters

· Components with limit values that require monitoring at the workplace:

123-86-4 n-butyl acetate

PEL Long-term value: 710 mg/m³, 150 ppm REL Short-term value: 950 mg/m³, 200 ppm

Long-term value: 710 mg/m³, 150 ppm

TLV Short-term value: 150 ppm Long-term value: 50 ppm

67-64-1 acetone

PEL Long-term value: 2400 mg/m³, 1000 ppm REL Long-term value: 590 mg/m³, 250 ppm

TLV Short-term value: 500 ppm Long-term value: 250 ppm

A4, BEI

1330-20-7 xylene

PEL Long-term value: 435 mg/m³, 100 ppm REL Short-term value: 655 mg/m³, 150 ppm Long-term value: 435 mg/m³, 100 ppm

TLV Long-term value: 20 ppm

BEI, A4

Ingredients with biological limit values:

67-64-1 acetone

BEI 25 ma/L

Medium: urine Time: end of shift

Parameter: Acetone (nonspecific)

1330-20-7 xylene

BEI 1.5 g/g creatinine

Medium: urine Time: end of shift

Parameter: Methylhippuric acids

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

(Contd. on page 6)

(Contd. of page 5)

Safety Data Sheet acc. to OSHA HCS

Printing date 02/27/2024 Reviewed on 02/27/2024

Trade name: LC3030 MS CLEAR

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

Information on basic physical and	chemical properties
· Appearance:	
Form:	Liquid
Color:	Clear
· Odor:	Characteristic
· Odor threshold:	Not determined.
pH-value:	Not determined (pH N/A in solvent coatings)
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	55.8-56.6 °C (132.4-133.9 °F)
Flash point:	<-18 °C (<-0.4 °F)
Flammability (solid, gaseous):	Highly flammable.
· Auto igniting:	370 °C (698 °F)
Decomposition temperature:	Not determined.
Ignition temperature:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air vapor mixtures are possible.
Explosion limits:	
Lower:	1.1 Vol %

(Contd. on page 7)

Printing date 02/27/2024 Reviewed on 02/27/2024

Trade name: LC3030 MS CLEAR

		(Contd. of page 6
Upper:	13 Vol %	
· Vapor pressure at 20 °C (68 °F):	233 hPa (174.8 mm Hg)	
Vapor pressure at 50 °C (122 °F):	800 hPa (600 mm Hg)	
· Density at 20 °C (68 °F):	0.9299 g/cm³ (7.76 lbs/gal)	
Relative density	Not determined.	
· Vapor density	Not determined.	
Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
Water:	Fully miscible.	
· Partition coefficient (n-octanol/wate	r): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	≥70.7-<71 %	
VOC content:	≥52.43-<52.67 %	
	591.1 g/l / 4.93 lb/gal	
Solids content:	32.5 %	
· Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

1330-20-7 xylene

Oral LD50 4,300 mg/kg (rat)
Dermal LD50 2,000 mg/kg (rabbit)

- Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

(Contd. on page 8)

Printing date 02/27/2024 Reviewed on 02/27/2024

Trade name: LC3030 MS CLEAR

(Contd. of page 7) Irritant · Carcinogenic categories · IARC (International Agency for Research on Cancer) 1330-20-7 xylene 3 100-41-4 ethylbenzene 2B 103-11-7 2-ethylhexyl acrylate 2B 108-88-3 toluene 3 · NTP (National Toxicology Program) None of the ingredients is listed. OSHA-Ca (Occupational Safety & Health Administration) None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes: Not hazardous for water.
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- vPvB: Not applicable.
- Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

14 T	rans	port	info	rma	tio	n

· UN-Number · DOT, IMDG, IATA	UN1263

· UN proper shipping name

· DOT Paint · IMDG, IATA PAINT

(Contd. on page 9)

Printing date 02/27/2024 Reviewed on 02/27/2024

Trade name: LC3030 MS CLEAR

(Contd. of page 8)

· Transport hazard class(es)

· DOT



· Class 3 Flammable liquids

· Label 3

· IMDG, IATA



· Class 3 Flammable liquids

· Label

Packing group

· DOT, IMDG, IATA

· Environmental hazards: Not applicable.

· Special precautions for user Warning: Flammable liquids

· Hazard identification number (Kemler code): 33 · EMS Number: F-E,S-E

· Stowage Category B

Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

· Transport/Additional information:

· DOT

· **Quantity limitations** On passenger aircraft/rail: 5 L

On cargo aircraft only: 60 L

· IMDG

· Limited quantities (LQ) 5L

· Excepted quantities (EQ) Code: E2

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

· UN "Model Regulation": UN 1263 PAINT, 3, II

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

Section 313 (Specific toxic chemical listings):

1330-20-7 xylene

(Contd. on page 10)

Printing date 02/27/2024 Reviewed on 02/27/2024

Trade name: LC3030 MS CLEAR

(Contd. of page 9) 100-41-4 ethylbenzene 122-99-6 2-phenoxyethanol 108-88-3 toluene · TSCA (Toxic Substances Control Act): All components have the value ACTIVE. · Hazardous Air Pollutants 1330-20-7 xylene 100-41-4 ethylbenzene 108-88-3 toluene Proposition 65 · Chemicals known to cause cancer: 100-41-4 ethylbenzene 103-11-7 2-ethylhexyl acrylate · Chemicals known to cause reproductive toxicity for females: None of the ingredients is listed. · Chemicals known to cause reproductive toxicity for males: None of the ingredients is listed. · Chemicals known to cause developmental toxicity: 108-88-3 toluene · Carcinogenic categories · EPA (Environmental Protection Agency) 67-64-1 acetone 1330-20-7 xylene Ī 100-41-4 ethylbenzene D 108-88-3 toluene Ш · TLV (Threshold Limit Value) 67-64-1 acetone Α4 Α4 1330-20-7 xylene *A3* 100-41-4 ethylbenzene

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

77-58-7 dibutyltin dilaurate

· GHS label elements

108-88-3 toluene

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms





GHS02 GHS07

· Signal word Danger

· Hazard-determining components of labeling: n-butyl acetate

(Contd. on page 11)

A4 A4

Printing date 02/27/2024 Reviewed on 02/27/2024

Trade name: LC3030 MS CLEAR

(Contd. of page 10)

acetone

· Hazard statements

Highly flammable liquid and vapor.

Causes skin irritation.

Causes serious eye irritation.

May cause drowsiness or dizziness.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Call a poison center/doctor if you feel unwell.

Specific treatment (see on this label).

Take off contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact: Product Safety Dept.
- · Date of preparation / last revision 02/27/2024
- · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

(Contd. on page 12)

Printing date 02/27/2024 Reviewed on 02/27/2024

Trade name: LC3030 MS CLEAR

(Contd. of page 11)

TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit BEI: Biological Exposure Limit

Flammable Liquids 2: Flammable liquids – Category 2
Skin Irritation 2: Skin corrosion/irritation – Category 2
Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A
Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3

* Data compared to the previous version altered.

USA