



Safety Data Sheet

acc. to OSHA HCS

Printing date 05/31/2023

Reviewed on 05/31/2023

1 Identification

- **Product identifier**
- **Trade name:** P6.3.K1 1K LOW VOC HIGH PERFORMANCE PRIMER
- **Article number:** P6.3.K1
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Lusid Technologies
4725 S Camp Kearns Road
Kearns, UT 840118
- **Information department:** Product safety department
- **Emergency telephone number:**
24 Hrs Emergency Contact:
INFOTRAC
1-800-535-5053

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flammable Liquids 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Germ Cell Mutagenicity 1B H340 May cause genetic defects.
Carcinogenicity 1B H350 May cause cancer.



GHS07

Skin Irritation 2 H315 Causes skin irritation.
Eye Irritation 2A H319 Causes serious eye irritation.
Sensitization - Skin 1 H317 May cause an allergic skin reaction.
Aquatic Acute 3 H402 Harmful to aquatic life.
Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- **Label elements**
- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/31/2023

Reviewed on 05/31/2023

Trade name: P6.3.K1 1K LOW VOC HIGH PERFORMANCE PRIMER

(Contd. of page 1)

- **Hazard pictograms**



GHS02 GHS07 GHS08

- **Signal word** Danger

- **Hazard-determining components of labeling:**

4-chloro-alpha,alpha,alpha-trifluorotoluene

Stoddard solvent

titanium dioxide

ethylbenzene

2-butanone oxime

- **Hazard statements**

Highly flammable liquid and vapor.

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

May cause genetic defects.

May cause cancer.

Harmful to aquatic life with long lasting effects.

- **Precautionary statements**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

Avoid release to the environment.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Specific treatment (see on this label).

Take off contaminated clothing and wash it before reuse.

If skin irritation or rash occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

Wash contaminated clothing before reuse.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Classification system:**

- **NFPA ratings (scale 0 - 4)**



Health = 2

Fire = 3

Reactivity = 0

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/31/2023

Reviewed on 05/31/2023

Trade name: P6.3.K1 1K LOW VOC HIGH PERFORMANCE PRIMER

(Contd. of page 2)

- **HMIS-ratings (scale 0 - 4)**

HEALTH	2	Health = *2
FIRE	3	Fire = 3
REACTIVITY	0	Reactivity = 0

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene	25-50%
107-87-9	pentan-2-one	25-50%
110-43-0	heptan-2-one	2.5-10%
123-86-4	n-butyl acetate	2.5-10%
13463-67-7	titanium dioxide	2.5-10%
7727-43-7	barium sulphate, natural	2.5-10%
7779-90-0	trizinc bis(orthophosphate)	≤2.5%
100-41-4	ethylbenzene	≤2.5%
8052-41-3	Stoddard solvent	≤2.5%
96-29-7	2-butanone oxime	≤2.5%
136-52-7	cobalt(II) 2-ethylhexanoate	≤2.5%

4 First-aid measures

- **Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

USA

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/31/2023

Reviewed on 05/31/2023

Trade name: P6.3.K1 1K LOW VOC HIGH PERFORMANCE PRIMER

(Contd. of page 3)

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Dilute with plenty of water.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· PAC-1:

107-87-9	pentan-2-one	150 ppm
110-43-0	heptan-2-one	150 ppm
123-86-4	n-butyl acetate	5 ppm
13463-67-7	titanium dioxide	30 mg/m ³
7727-43-7	barium sulphate, natural	15 mg/m ³
7779-90-0	trizinc bis(orthophosphate)	12 mg/m ³
100-41-4	ethylbenzene	33 ppm
108-38-3	m-xylene	130 ppm
8052-41-3	Stoddard solvent	300 mg/m ³
96-29-7	2-butanone oxime	30 ppm
64742-48-9	Naphtha (petroleum), hydrotreated heavy	350 mg/m ³
112-34-5	2-(2-butoxyethoxy)ethanol	30 ppm
149-57-5	2-ethylhexanoic acid	15 mg/m ³

· PAC-2:

107-87-9	pentan-2-one	830 ppm
110-43-0	heptan-2-one	670 ppm
123-86-4	n-butyl acetate	200 ppm
13463-67-7	titanium dioxide	330 mg/m ³
7727-43-7	barium sulphate, natural	170 mg/m ³
7779-90-0	trizinc bis(orthophosphate)	36 mg/m ³

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/31/2023

Reviewed on 05/31/2023

Trade name: P6.3.K1 1K LOW VOC HIGH PERFORMANCE PRIMER

(Contd. of page 4)

100-41-4	ethylbenzene	1100* ppm
108-38-3	m-xylene	920 ppm
8052-41-3	Stoddard solvent	1,800 mg/m ³
96-29-7	2-butanone oxime	56 ppm
64742-48-9	Naphtha (petroleum), hydrotreated heavy	1,800 mg/m ³
112-34-5	2-(2-butoxyethoxy)ethanol	33 ppm
149-57-5	2-ethylhexanoic acid	99 mg/m ³

· PAC-3:

107-87-9	pentan-2-one	5000* ppm
110-43-0	heptan-2-one	4000* ppm
123-86-4	n-butyl acetate	3000* ppm
13463-67-7	titanium dioxide	2,000 mg/m ³
7727-43-7	barium sulphate, natural	990 mg/m ³
7779-90-0	trizinc bis(orthophosphate)	220 mg/m ³
100-41-4	ethylbenzene	1800* ppm
108-38-3	m-xylene	2500* ppm
8052-41-3	Stoddard solvent	29500** mg/m ³
96-29-7	2-butanone oxime	250 ppm
64742-48-9	Naphtha (petroleum), hydrotreated heavy	40,000 mg/m ³
112-34-5	2-(2-butoxyethoxy)ethanol	200 ppm
149-57-5	2-ethylhexanoic acid	590 mg/m ³

7 Handling and storage

· Handling:

· Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

· Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by storerooms and receptacles: Store in a cool location.

· Information about storage in one common storage facility: Not required.

· Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) No further relevant information available.

* 8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see section 7.

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/31/2023

Reviewed on 05/31/2023

Trade name: P6.3.K1 1K LOW VOC HIGH PERFORMANCE PRIMER

(Contd. of page 5)

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

107-87-9 pentan-2-one

PEL Long-term value: 700 mg/m³, 200 ppm

REL Long-term value: 530 mg/m³, 150 ppm

TLV Short-term value: 150 ppm

110-43-0 heptan-2-one

PEL Long-term value: 465 mg/m³, 100 ppm

REL Long-term value: 465 mg/m³, 100 ppm

TLV Long-term value: 50 ppm

123-86-4 n-butyl acetate

PEL Long-term value: 710 mg/m³, 150 ppm

REL Short-term value: 950 mg/m³, 200 ppm

Long-term value: 710 mg/m³, 150 ppm

TLV Short-term value: 150 ppm

Long-term value: 50 ppm

7727-43-7 barium sulphate, natural

PEL Long-term value: 15* 5** mg/m³

*total dust **respirable fraction

REL Long-term value: 10* 5** mg/m³

*total dust **respirable fraction

TLV Long-term value: 5* mg/m³

*inhalable fraction; E

100-41-4 ethylbenzene

PEL Long-term value: 435 mg/m³, 100 ppm

REL Short-term value: 545 mg/m³, 125 ppm

Long-term value: 435 mg/m³, 100 ppm

TLV Long-term value: 20 ppm

OTO, BEI, A3

8052-41-3 Stoddard solvent

PEL Long-term value: 2900 mg/m³, 500 ppm

REL Long-term value: 350 mg/m³

Ceiling limit value: 1800* mg/m³

*15-min

TLV Long-term value: 100 ppm

96-29-7 2-butanone oxime

WEEL Long-term value: 10 ppm

DSEN

136-52-7 cobalt(II) 2-ethylhexanoate

TLV Long-term value: 0.02* mg/m³

as Co, A3; *inhalable; DSEN; RSEN; BEI

(Contd. on page 7)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/31/2023

Reviewed on 05/31/2023

Trade name: P6.3.K1 1K LOW VOC HIGH PERFORMANCE PRIMER

(Contd. of page 6)

- **Ingredients with biological limit values:**

- **100-41-4 ethylbenzene**

- **BEI** 0.15 g/g creatinine

- **Medium:** urine

- **Time:** end of shift at end of workweek

- **Parameter:** Sum of mandelic acid and phenylglyoxylic acid (nonspecific)

- **Additional information:** The lists that were valid during the creation were used as basis.

- **Exposure controls**

- **Personal protective equipment:**

- **General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.

- Immediately remove all soiled and contaminated clothing.

- Wash hands before breaks and at the end of work.

- Store protective clothing separately.

- Avoid contact with the eyes and skin.

- **Breathing equipment:**

- In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

- **Form:**

Liquid

- **Color:**

According to product specification

- **Odor:**

Product specific

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/31/2023

Reviewed on 05/31/2023

Trade name: P6.3.K1 1K LOW VOC HIGH PERFORMANCE PRIMER

(Contd. of page 7)

· Odor threshold:	Not determined.
· pH-value:	Not determined (pH N/A in solvent coatings)
· Change in condition Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	101.7 °C (215.1 °F)
· Flash point:	7 °C (44.6 °F)
· Flammability (solid, gaseous):	Highly flammable.
· Auto igniting:	370 °C (698 °F)
· Decomposition temperature:	Not determined.
· Ignition temperature:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits: Lower:	1.5 Vol %
Upper:	8.2 Vol %
· Vapor pressure at 20 °C (68 °F):	16 hPa (12 mm Hg)
· Vapor pressure at 50 °C (122 °F):	92 hPa (69 mm Hg)
· Density at 20 °C (68 °F):	1.598 g/cm ³ (13.3353 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	Fully miscible.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity: Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content: Organic solvents:	41.1 %
VOC content:	41.21 % 250.2 g/l / 2.09 lb/gal
Solids content:	58.4 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/31/2023

Reviewed on 05/31/2023

Trade name: P6.3.K1 1K LOW VOC HIGH PERFORMANCE PRIMER

(Contd. of page 8)

· **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

· **Information on toxicological effects**· **Acute toxicity:**· **LD/LC50 values that are relevant for classification:****107-87-9 pentan-2-one**

Oral LD50 1,600 mg/kg (rat)

Dermal LD50 6,500 mg/kg (rabbit)

· **Primary irritant effect:**· **on the skin:** Irritant to skin and mucous membranes.· **on the eye:** Irritating effect.· **Sensitization:** Sensitization possible through skin contact.· **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

The product can cause inheritable damage.

· **Carcinogenic categories**· **IARC (International Agency for Research on Cancer)**

98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene	2B
14807-96-6	Talc (Mg3H2(SiO3)4)	3
13463-67-7	titanium dioxide	2B
95-47-6	o-xylene	3
100-41-4	ethylbenzene	2B
106-42-3	p-xylene	3
108-38-3	m-xylene	3
136-52-7	cobalt(II) 2-ethylhexanoate	2B

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

· **Toxicity**· **Aquatic toxicity:** No further relevant information available.· **Persistence and degradability** No further relevant information available.· **Behavior in environmental systems:**· **Bioaccumulative potential** No further relevant information available.· **Mobility in soil** No further relevant information available.· **Ecotoxicological effects:**· **Remark:** Harmful to fish· **Additional ecological information:**· **General notes:**

Water hazard class 3 (Self-assessment): extremely hazardous for water

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/31/2023

Reviewed on 05/31/2023

Trade name: P6.3.K1 1K LOW VOC HIGH PERFORMANCE PRIMER

(Contd. of page 9)

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

Harmful to aquatic organisms

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **Other adverse effects** No further relevant information available.

13 Disposal considerations

· **Waste treatment methods**

· **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packagings:**

· **Recommendation:** Disposal must be made according to official regulations.

· **Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport information

· **UN-Number**

· **DOT, IMDG, IATA**

UN1263

· **UN proper shipping name**

· **DOT**

Paint

· **IMDG, IATA**

PAINT

· **Transport hazard class(es)**

· **DOT**



· **Class**

3 Flammable liquids

· **Label**

3

· **IMDG, IATA**



· **Class**

3 Flammable liquids

· **Label**

3

· **Packing group**

· **DOT, IMDG, IATA**

II

· **Environmental hazards:**

Not applicable.

· **Special precautions for user**

Warning: Flammable liquids

· **Hazard identification number (Kemler code):** 33

· **EMS Number:**

F-E,S-E

(Contd. on page 11)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/31/2023

Reviewed on 05/31/2023

Trade name: P6.3.K1 1K LOW VOC HIGH PERFORMANCE PRIMER

(Contd. of page 10)

· Stowage Category	B
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· DOT	
· Quantity limitations	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, II

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

7727-43-7	barium sulphate, natural
7779-90-0	trizinc bis(orthophosphate)
95-47-6	o-xylene
100-41-4	ethylbenzene
106-42-3	p-xylene
108-38-3	m-xylene
136-52-7	cobalt(II) 2-ethylhexanoate
112-34-5	2-(2-butoxyethoxy)ethanol

· TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

· Hazardous Air Pollutants

95-47-6	o-xylene
100-41-4	ethylbenzene
106-42-3	p-xylene
108-38-3	m-xylene
136-52-7	cobalt(II) 2-ethylhexanoate

· Proposition 65

· Chemicals known to cause cancer:

98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene
13463-67-7	titanium dioxide
100-41-4	ethylbenzene

(Contd. on page 12)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/31/2023

Reviewed on 05/31/2023

Trade name: P6.3.K1 1K LOW VOC HIGH PERFORMANCE PRIMER

(Contd. of page 11)

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

7727-43-7	barium sulphate, natural	D, CBD(inh), NL(oral)
7779-90-0	trizinc bis(orthophosphate)	D, I, II
95-47-6	o-xylene	I
100-41-4	ethylbenzene	D
106-42-3	p-xylene	I
108-38-3	m-xylene	I

· **TLV (Threshold Limit Value)**

14807-96-6	Talc (Mg ₃ H ₂ (SiO ₃) ₄)	A4
13463-67-7	titanium dioxide	A4
95-47-6	o-xylene	A4
100-41-4	ethylbenzene	A3
106-42-3	p-xylene	A4
108-38-3	m-xylene	A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

13463-67-7	titanium dioxide
------------	------------------

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**

4-chloro-alpha,alpha,alpha-trifluorotoluene

Stoddard solvent

titanium dioxide

ethylbenzene

2-butanone oxime

· **Hazard statements**

Highly flammable liquid and vapor.

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

May cause genetic defects.

May cause cancer.

Harmful to aquatic life with long lasting effects.

(Contd. on page 13)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/31/2023

Reviewed on 05/31/2023

Trade name: P6.3.K1 1K LOW VOC HIGH PERFORMANCE PRIMER

(Contd. of page 12)

· **Precautionary statements**

Obtain special instructions before use.
 Do not handle until all safety precautions have been read and understood.
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
 Keep container tightly closed.
 Ground/bond container and receiving equipment.
 Use explosion-proof electrical/ventilating/lighting/equipment.
 Use only non-sparking tools.
 Take precautionary measures against static discharge.
 Avoid breathing dust/fume/gas/mist/vapors/spray
 Wash thoroughly after handling.
 Contaminated work clothing must not be allowed out of the workplace.
 Avoid release to the environment.
 Wear protective gloves/protective clothing/eye protection/face protection.
 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 IF exposed or concerned: Get medical advice/attention.
 Specific treatment (see on this label).
 Take off contaminated clothing and wash it before reuse.
 If skin irritation or rash occurs: Get medical advice/attention.
 If eye irritation persists: Get medical advice/attention.
 Wash contaminated clothing before reuse.
 In case of fire: Use CO₂, powder or water spray to extinguish.
 Store in a well-ventilated place. Keep cool.
 Store locked up.
 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **National regulations:**

· **Information about limitation of use:**

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Environment protection department.

· **Contact:** Product Safety Dept.

· **Date of preparation / last revision** 05/31/2023

· **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

(Contd. on page 14)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/31/2023

Reviewed on 05/31/2023

Trade name: P6.3.K1 1K LOW VOC HIGH PERFORMANCE PRIMER

(Contd. of page 13)

*TLV: Threshold Limit Value**PEL: Permissible Exposure Limit**REL: Recommended Exposure Limit**BEI: Biological Exposure Limit**Flammable Liquids 2: Flammable liquids – Category 2**Skin Irritation 2: Skin corrosion/irritation – Category 2**Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A**Sensitization - Skin 1: Skin sensitisation – Category 1**Germ Cell Mutagenicity 1B: Germ cell mutagenicity – Category 1B**Carcinogenicity 1B: Carcinogenicity – Category 1B**Aquatic Acute 3: Hazardous to the aquatic environment - acute aquatic hazard – Category 3**Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3**** Data compared to the previous version altered.**

USA