

Page 1/11

# Safety Data Sheet acc. to OSHA HCS

Printing date 08/06/2018 Reviewed on 12/05/2017

### 1 Identification

· Product identifier

· Trade name: AD263 FISHEYE ELIMINATOR

- Article number: AD263

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

Lusid Technologies 5195 West 4700 South KEARNS, UT 84118 USA

www.lusid.biz

- · Information department: Product safety department
- Emergency telephone number:

24 Hrs Emergency Contact:

**INFOTRAC** 1-800-535-5053

# 2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

H351 Suspected of causing cancer.

STOT RE 2 H373 May cause damage to the hearing organs through prolonged or repeated exposure.



Skin Irrit. 2 H315 Causes skin irritation.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

(Contd. of page 1)

# Safety Data Sheet acc. to OSHA HCS

Printing date 08/06/2018 Reviewed on 12/05/2017

Trade name: AD263 FISHEYE ELIMINATOR

#### Hazard pictograms







GHS02

# · **Signal word** Danger

#### · Hazard-determining components of labeling:

ethylbenzene

#### · Hazard statements

Highly flammable liquid and vapor.

Causes skin irritation.

Suspected of causing cancer.

May cause damage to the hearing organs through prolonged or repeated exposure.

## · Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF exposed or concerned: Get medical advice/attention.

Specific treatment (see on this label).

Get medical advice/attention if you feel unwell.

Take off contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

In case of fire: Use for extinction: CO2, powder or water spray.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

#### Classification system:

#### NFPA ratings (scale 0 - 4)



Health = 1 Fire = 3 Reactivity = 0

#### · HMIS-ratings (scale 0 - 4)



Health = 1 Fire = 3 Reactivity = 0

· Other hazards

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.

(Contd. on page 3)

Printing date 08/06/2018 Reviewed on 12/05/2017

Trade name: AD263 FISHEYE ELIMINATOR

· vPvB: Not applicable.

(Contd. of page 2)

### 3 Composition/information on ingredients

- Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

| · Dangerous components: |                    |         |
|-------------------------|--------------------|---------|
| 540-88-5                | tert-butyl acetate | 25-50%  |
| 1330-20-7               | xylene             | 25-50%  |
| 122-99-6                | 2-Phenoxyethanol   | 2.5-10% |
| 100-41-4                | ethylbenzene       | 2.5-10% |

#### 4 First-aid measures

- · Description of first aid measures
- General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eve contact: Rinse opened eve for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed

No further relevant information available.

· Indication of any immediate medical attention and special treatment needed

No further relevant information available.

### 5 Fire-fighting measures

- Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
- · Protective equipment: No special measures required.

#### 6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures
- Wear protective equipment. Keep unprotected persons away.
- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Reference to other sections

See Section 7 for information on safe handling.

(Contd. on page 4)

Printing date 08/06/2018 Reviewed on 12/05/2017

Trade name: AD263 FISHEYE ELIMINATOR

(Contd. of page 3)

See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

| · Protective | Action Criteria for Chemicals |            |
|--------------|-------------------------------|------------|
| · PAC-1:     |                               |            |
| 540-88-5     | tert-butyl acetate            | 600 ppm    |
| 1330-20-7    | xylene                        | 130 ppm    |
| 122-99-6     | 2-Phenoxyethanol              | 1.5 ppm    |
| 100-41-4     | ethylbenzene                  | 33 ppm     |
| · PAC-2:     |                               |            |
| 540-88-5     | tert-butyl acetate            | 1,700 ppm  |
| 1330-20-7    | xylene                        | 920* ppm   |
| 122-99-6     | 2-Phenoxyethanol              | 16 ppm     |
| 100-41-4     | ethylbenzene                  | 1100* ppm  |
| · PAC-3:     |                               |            |
| 540-88-5     | tert-butyl acetate            | 10,000 ppm |
| 1330-20-7    | xylene                        | 2500* ppm  |
| 122-99-6     | 2-Phenoxyethanol              | 97 ppm     |
| 100-41-4     | ethylbenzene                  | 1800* ppm  |

# 7 Handling and storage

- Handling:
- · Precautions for safe handling No special precautions are necessary if used correctly.
- Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage.
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) No further relevant information available.

# 8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

#### 540-88-5 tert-butyl acetate

PEL Long-term value: 950 mg/m<sup>3</sup>, 200 ppm

(Contd. on page 5)

(Contd. of page 4)

# Safety Data Sheet acc. to OSHA HCS

Printing date 08/06/2018 Reviewed on 12/05/2017

Trade name: AD263 FISHEYE ELIMINATOR

REL Long-term value: 950 mg/m³, 200 ppm TLV Short-term value: 712 mg/m³, 150 ppm Long-term value: 238 mg/m³, 50 ppm

### 1330-20-7 xylene

PEL Long-term value: 435 mg/m³, 100 ppm
REL Short-term value: 655 mg/m³, 150 ppm
Long-term value: 435 mg/m³, 100 ppm
TLV Short-term value: 651 mg/m³, 150 ppm
Long-term value: 434 mg/m³, 100 ppm
BEI

#### 100-41-4 ethylbenzene

PEL Long-term value: 435 mg/m³, 100 ppm
REL Short-term value: 545 mg/m³, 125 ppm
Long-term value: 435 mg/m³, 100 ppm
TLV Long-term value: 87 mg/m³, 20 ppm
BEI

## Ingredients with biological limit values:

#### 1330-20-7 xylene

1000-20-7 Xyle

BEI 1.5 g/g creatinine Medium: urine Time: end of shift

Parameter: Methylhippuric acids

#### 100-41-4 ethylbenzene

BEI 0.7 g/g creatinine

Medium: urine

Time: end of shift at end of workweek

Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)

Medium: end-exhaled air

Time: not critical

Parameter: Ethyl benzene (semi-quantitative)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

#### Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Protection of hands:



Printing date 08/06/2018 Reviewed on 12/05/2017

Trade name: AD263 FISHEYE ELIMINATOR

(Contd. of page 5)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

### Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

## 9 Physical and chemical properties

| Information on basic physical and General Information                                 | chemical properties  |
|---|--|
| · Appearance:<br>Form:<br>Color:<br>· Odor:<br>· Odor threshold:                      | Liquid<br>Clear<br>Characteristic<br>Not determined.                                       |
| · pH-value:   | Not determined (pH N/A in solvent coatings)  |
| · Change in condition<br>Melting point/Melting range:<br>Boiling point/Boiling range: | Undetermined.<br>97 ℃ (206.6 ℉)  |
| · Flash point:  | 15 ℃ (59 F)  |
| · Flammability (solid, gaseous):  | Not applicable.  |
| Ignition temperature:   | 430 °C (806 °F)  |
| Decomposition temperature:  | Not determined.  |
| · Auto igniting:  | Product is not selfigniting.   |
| · Danger of explosion:  | Product is not explosive. However, formation of explosive air/vapor mixtures are possible. |
| · Explosion limits:<br>Lower:<br>Upper:   | 1.1 Vol %<br>7 Vol %   |
| Vapor pressure at 20 ℃ (68 ℉):  | 41 hPa (30.8 mm Hg)  |
| · Density at 20 °C (68 °F):<br>· Relative density<br>· Vapor density                  | 0.89 g/cm³ (7.4271 lbs/gal)<br>Not determined.<br>Not determined.                          |

(Contd. on page 7)

Printing date 08/06/2018 Reviewed on 12/05/2017

Trade name: AD263 FISHEYE ELIMINATOR

|   |   | (Contd. of page 6 |
|---|---|-------------------|
| · Evaporation rate                              | Not determined.                                     |                   |
| · Solubility in / Miscibility with Water:       | Not miscible or difficult to mix.                   |                   |
| · Partition coefficient (n-octanol/w            | ater): Not determined.                              |                   |
| · Viscosity:<br>Dynamic:<br>Kinematic:          | Not determined.<br>Not determined.                  |                   |
| Solvent content: Organic solvents: VOC content: | 92.8 %<br>44.70 %<br>818.5 g/l / 6.83 lb/gal        |                   |
| Solids content:  Other information              | 7.2 %<br>No further relevant information available. |                   |

# 10 Stability and reactivity

- · Reactivity No further relevant information available.
- Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

# 11 Toxicological information

- · Information on toxicological effects

| · Acute | Acute toxicity:  |                       |  |  |
|---------|--|-----------------------|--|--|
| · LD/LC | · LD/LC50 values that are relevant for classification: |                       |  |  |
| 1330-2  | 1330-20-7 xylene                                       |                       |  |  |
| Oral    | LD50   | 4,300 mg/kg (rat)     |  |  |
| Derma   | l LD50   | 2,000 mg/kg (rabbit)  |  |  |
|         | 100-41-4 ethylbenzene                                  |                       |  |  |
| Oral    | LD50   | 3,500 mg/kg (rat)     |  |  |
| Derma   | l LD50   | 17,800 mg/kg (rabbit) |  |  |

- Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

(Contd. on page 8)

Printing date 08/06/2018 Reviewed on 12/05/2017

Trade name: AD263 FISHEYE ELIMINATOR

(Contd. of page 7)

| · Carcinogenic categories                               |              |    |
|---|--------------|----|
| · IARC (International Agency for Research on Cancer)    |              |    |
| 1330-20-7   | xylene       | 3  |
| 100-41-4  | ethylbenzene | 2B |
| · NTP (National Toxicology Program)                     |              |    |
| None of the ingredients is listed.                      |              |    |
| · OSHA-Ca (Occupational Safety & Health Administration) |              |    |

# 12 Ecological information

None of the ingredients is listed.

- · Toxicity
- Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- vPvB: Not applicable.
- Other adverse effects No further relevant information available.

# 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · **Recommendation:** Disposal must be made according to official regulations.

| Transport information   |        |                 |
|-------------------------|--------|-----------------|
| · UN-Number             |        |                 |
| · DOT, IMDG, IATA       | UN1263 |                 |
| UN proper shipping name |        |                 |
| DOT                     | Paint  |                 |
| IMDG, IATA              | PAINT  |                 |
|                         |        | (Contd. on page |

(Conta. on page 9)

Printing date 08/06/2018 Reviewed on 12/05/2017

Trade name: AD263 FISHEYE ELIMINATOR

(Contd. of page 8)

· Transport hazard class(es)

· DOT



3 Flammable liquids · Class

· Label

· IMDG, IATA



· Class 3 Flammable liquids

· Label

· Packing group DOT, IMDG, IATA II

· Environmental hazards:

· Marine pollutant: No

· Special precautions for user Warning: Flammable liquids

Danger code (Kemler): 33 · EMS Number: F-E,S-E · Stowage Category В

· Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

· Transport/Additional information:

· Quantity limitations On passenger aircraft/rail: 5 L

On cargo aircraft only: 60 L

· IMDG

· Limited quantities (LQ) 1L

Excepted quantities (ÉQ) Code: E2

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

· UN "Model Regulation": UN 1263 PAINT, 3, II

# 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture · Sara
- Section 355 (extremely hazardous substances):

None of the ingredients is listed.

Section 313 (Specific toxic chemical listings):

1330-20-7 xylene

(Contd. on page 10)

Printing date 08/06/2018 Reviewed on 12/05/2017

Trade name: AD263 FISHEYE ELIMINATOR

|   | (Contd. of page 9 |
|---|-------------------|
| 122-99-6 2-Phenoxyethanol                                     | (coma. c. page c  |
| 100-41-4 ethylbenzene   |                   |
| TSCA (Toxic Substances Control Act):                          |                   |
| All ingredients are listed.                                   |                   |
| · Proposition 65  |                   |
| · Chemicals known to cause cancer:                            |                   |
| 100-41-4 ethylbenzene   |                   |
| Chemicals known to cause reproductive toxicity for females    | :                 |
| None of the ingredients is listed.                            |                   |
| · Chemicals known to cause reproductive toxicity for males:   |                   |
| None of the ingredients is listed.                            |                   |
| · Chemicals known to cause developmental toxicity:            |                   |
| None of the ingredients is listed.                            |                   |
| · Carcinogenic categories                                     |                   |
| · EPA (Environmental Protection Agency)                       |                   |
| 1330-20-7 xylene  | 1                 |
| 100-41-4 ethylbenzene   | D                 |
| TLV (Threshold Limit Value established by ACGIH)              |                   |
| 1330-20-7 xylene  | A4                |
| 100-41-4 ethylbenzene   | A3                |
| · NIOSH-Ca (National Institute for Occupational Safety and He | ealth)            |
| None of the ingredients is listed.                            |                   |
|   |                   |

#### · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

### · Hazard pictograms







GHS02 GHS07 GHS08

· Signal word Danger

· Hazard-determining components of labeling:

ethylbenzene

#### Hazard statements

Highly flammable liquid and vapor.

Causes skin irritation.

Suspected of causing cancer.

May cause damage to the hearing organs through prolonged or repeated exposure.

#### · Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

(Contd. on page 11)

(Contd. of page 10)

# Safety Data Sheet acc. to OSHA HCS

Printing date 08/06/2018 Reviewed on 12/05/2017

Trade name: AD263 FISHEYE ELIMINATOR

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF exposed or concerned: Get medical advice/attention.

Specific treatment (see on this label).

Get medical advice/attention if you feel unwell.

Take off contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

In case of fire: Use for extinction: CO2, powder or water spray.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact: Product Safety Dept.
- · Date of preparation / last revision 08/06/2018 / 2
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Liq. 2: Flammable liquids – Category 2

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Carc. 2: Carcinogenicity - Category 2

STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2

\* Data compared to the previous version altered.

USA