

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/28/2025

Reviewed on 08/28/2025

1 Identification

- **Product identifier**
- **Trade name:** 828B DTM BINDER
- **Article number:** 828B
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
 NorthStar is a product of Lusid Technologies Inc
 4725 S Camp Kearns Road
 Kearns, UT 84118
 (801) 966-5300
 info@lusidtechnologies.com
- **Information department:** Product safety department
- **Emergency telephone number:**
 24 Hrs Emergency Contact:
 INFOTRAC
 1-800-535-5053

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flammable Liquids 2

H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Carcinogenicity 1A

H350 May cause cancer.



GHS07

Eye Irritation 2A

H319 Causes serious eye irritation.

Sensitization - Skin 1

H317 May cause an allergic skin reaction.

Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02



GHS07



GHS08

(Contd. on page 2)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/28/2025

Reviewed on 08/28/2025

Trade name: 828B DTM BINDER

(Contd. of page 1)

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

n-butyl acetate
bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate
ethylbenzene
acetone

· **Hazard statements**

Highly flammable liquid and vapor.
Causes serious eye irritation.
May cause an allergic skin reaction.
May cause cancer.
May cause drowsiness or dizziness.

· **Precautionary statements**

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting/equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Avoid breathing dust/fume/gas/mist/vapors/spray
Wash thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Contaminated work clothing must not be allowed out of the workplace.
Wear protective gloves/protective clothing/eye protection/face protection.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
IF exposed or concerned: Get medical advice/attention.
Call a poison center/doctor if you feel unwell.
Specific treatment (see on this label).
If skin irritation or rash occurs: Get medical advice/attention.
If eye irritation persists: Get medical advice/attention.
Wash contaminated clothing before reuse.
In case of fire: Use CO₂, powder or water spray to extinguish.
Store in a well-ventilated place. Keep container tightly closed.
Store in a well-ventilated place. Keep cool.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 2
Fire = 3
Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**



Health = *2
Fire = 3
Reactivity = 0

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/28/2025

Reviewed on 08/28/2025

Trade name: 828B DTM BINDER

(Contd. of page 2)

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

123-86-4	n-butyl acetate	25-50%
67-64-1	acetone	10-25%
110-43-0	heptan-2-one	2.5-10%
41556-26-7	bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate	≤2.5%
1330-20-7	xylene	≤2.5%
100-41-4	ethylbenzene	≤2.5%
64-17-5	ethanol	≤2.5%
7779-90-0	trizinc bis(orthophosphate)	≤2.5%

4 First-aid measures

- **Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

—USA—

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/28/2025

Reviewed on 08/28/2025

Trade name: 828B DTM BINDER

(Contd. of page 3)

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Environmental precautions:

Prevent seepage into sewage system, workpits and cellars.

Dilute with plenty of water.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Protective Action Criteria for Chemicals

PAC-1:

123-86-4	n-butyl acetate	5 ppm
67-64-1	acetone	200 ppm
110-43-0	heptan-2-one	150 ppm
1330-20-7	xylene	130 ppm
100-41-4	ethylbenzene	33 ppm
64-17-5	ethanol	1,800 ppm
7779-90-0	trizinc bis(orthophosphate)	12 mg/m ³
67-56-1	methanol	530 ppm
77-58-7	dibutyltin dilaurate	1.1 mg/m ³
7784-30-7	Aluminium phosphate	14 mg/m ³
122-99-6	2-phenoxyethanol	1.5 ppm
1314-13-2	zinc oxide	10 mg/m ³
67-63-0	propan-2-ol	400 ppm
108-88-3	toluene	67 ppm

PAC-2:

123-86-4	n-butyl acetate	200 ppm
67-64-1	acetone	3200* ppm
110-43-0	heptan-2-one	670 ppm
1330-20-7	xylene	920* ppm
100-41-4	ethylbenzene	1100 ppm
64-17-5	ethanol	3300* ppm
7779-90-0	trizinc bis(orthophosphate)	36 mg/m ³
67-56-1	methanol	2100 ppm
77-58-7	dibutyltin dilaurate	3.8 mg/m ³
7784-30-7	Aluminium phosphate	200 mg/m ³
122-99-6	2-phenoxyethanol	16 ppm
1314-13-2	zinc oxide	15 mg/m ³
67-63-0	propan-2-ol	2000* ppm
108-88-3	toluene	560 ppm

(Contd. on page 5)

-USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/28/2025

Reviewed on 08/28/2025

Trade name: 828B DTM BINDER

(Contd. of page 4)

· PAC-3:		
123-86-4	<i>n</i> -butyl acetate	3000* ppm
67-64-1	acetone	5700* ppm
110-43-0	heptan-2-one	4000* ppm
1330-20-7	xylene	2500* ppm
100-41-4	ethylbenzene	1800 ppm
64-17-5	ethanol	15000* ppm
7779-90-0	trizinc bis(orthophosphate)	220 mg/m ³
67-56-1	methanol	7200 ppm
77-58-7	dibutyltin dilaurate	23 mg/m ³
7784-30-7	Aluminium phosphate	1,200 mg/m ³
122-99-6	2-phenoxyethanol	97 ppm
1314-13-2	zinc oxide	2,500 mg/m ³
67-63-0	propan-2-ol	12000** ppm
108-88-3	toluene	3700 ppm

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
 Ensure good ventilation/exhaustion at the workplace.
 Open and handle receptacle with care.
 Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
 Keep ignition sources away - Do not smoke.
 Protect against electrostatic charges.
 Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
 Keep receptacle tightly sealed.
 Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see section 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
 The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
 At this time, the other constituents have no known exposure limits.

123-86-4 *n*-butyl acetate

PEL	Long-term value: 710 mg/m ³ , 150 ppm
-----	--

(Contd. on page 6)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/28/2025

Reviewed on 08/28/2025

Trade name: 828B DTM BINDER

(Contd. of page 5)

REL Short-term value: 950 mg/m³, 200 ppm
Long-term value: 710 mg/m³, 150 ppm

TLV Short-term value: 712 mg/m³, 150 ppm
Long-term value: 238 mg/m³, 50 ppm

67-64-1 acetone

PEL Long-term value: 2400 mg/m³, 1000 ppm

REL Long-term value: 590 mg/m³, 250 ppm

TLV Short-term value: 1187 mg/m³, 500 ppm
Long-term value: 594 mg/m³, 250 ppm
A4, BEI

110-43-0 heptan-2-one

PEL Long-term value: 465 mg/m³, 100 ppm

REL Long-term value: 465 mg/m³, 100 ppm

TLV Long-term value: 50 ppm

1330-20-7 xylene

PEL Long-term value: 435 mg/m³, 100 ppm

REL Short-term value: 655 mg/m³, 150 ppm
Long-term value: 435 mg/m³, 100 ppm

TLV Long-term value: 20 ppm
BEI, A4

100-41-4 ethylbenzene

PEL Long-term value: 435 mg/m³, 100 ppm

REL Short-term value: 545 mg/m³, 125 ppm
Long-term value: 435 mg/m³, 100 ppm

TLV Long-term value: 20 ppm
OTO, BEI, A3

64-17-5 ethanol

PEL Long-term value: 1900 mg/m³, 1000 ppm

REL Long-term value: 1900 mg/m³, 1000 ppm

TLV Short-term value: 1880 mg/m³, 1000 ppm
A3

Ingredients with biological limit values:**67-64-1 acetone**

BEI 25 mg/L
Medium: urine
Time: end of shift
Parameter: Acetone (nonspecific)

1330-20-7 xylene

BEI 0.3 g/g creatinine
Medium: urine
Time: end of shift
Parameter: Methylhippuric acids

100-41-4 ethylbenzene

BEI 0.15 g/g creatinine
Medium: urine
Time: end of shift
Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific)

(Contd. on page 7)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/28/2025

Reviewed on 08/28/2025

Trade name: 828B DTM BINDER

(Contd. of page 6)

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
 Keep away from foodstuffs, beverages and feed.
 Immediately remove all soiled and contaminated clothing.
 Wash hands before breaks and at the end of work.
 Store protective clothing separately.
 Avoid contact with the eyes.
 Avoid contact with the eyes and skin.
- **Breathing equipment:**
 In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**
 The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**
 The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form:

Liquid

Color:

According to product specification

· Odor:

Product specific

· Odor threshold:

Not determined.

· pH-value:

Not determined (pH N/A in solvent coatings)

· Change in condition

Melting point/Melting range:

Undetermined.

(Contd. on page 8)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/28/2025

Reviewed on 08/28/2025

Trade name: 828B DTM BINDER

(Contd. of page 7)

Boiling point/Boiling range:	55.8-56.6 °C (132.4-133.9 °F)
· Flash point:	<-18 °C (<-0.4 °F)
· Flammability:	Highly flammable.
· Auto igniting:	370 °C (698 °F)
· Decomposition temperature:	Not determined.
· Ignition temperature:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits:	
Lower:	1.2 Vol %
Upper:	13 Vol %
· Vapor pressure at 20 °C (68 °F):	233 hPa (174.8 mm Hg)
· Vapor pressure at 50 °C (122 °F):	800 hPa (600 mm Hg)
· Density at 20 °C (68 °F):	0.9672 g/cm ³ (8.0713 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	Fully miscible.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	49.1 %
VOC content:	38.60 %
	392.2 g/l / 3.27 lb/gal
· Solids content:	55.2 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

- USA -

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/28/2025

Reviewed on 08/28/2025

Trade name: 828B DTM BINDER

(Contd. of page 8)

11 Toxicological information

- **Information on toxicological effects**

- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

123-86-4 n-butyl acetate

Oral	LD50	13,100 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit)
Inhalative	LC50/4 h	>21 mg/l (rat)

- **Primary irritant effect:**

- **on the skin:** No irritant effect.

- **on the eye:** Irritating effect.

- **Sensitization:** Sensitization possible through skin contact.

- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

1330-20-7	xylene	3
100-41-4	ethylbenzene	2B
64-17-5	ethanol	1
67-63-0	propan-2-ol	3
108-88-3	toluene	3

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**

- **Aquatic toxicity:** No further relevant information available.

- **Persistence and degradability** No further relevant information available.

- **Behavior in environmental systems:**

- **Bioaccumulative potential** No further relevant information available.

- **Mobility in soil** No further relevant information available.

- **Additional ecological information:**

- **General notes:** Not hazardous for water.

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

- **Other adverse effects** No further relevant information available.

USA

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/28/2025

Reviewed on 08/28/2025

Trade name: 828B DTM BINDER

(Contd. of page 9)

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport information

- | | |
|--|---|
| · UN-Number | UN1263 |
| · DOT, IMDG, IATA | |
| · UN proper shipping name | Paint |
| · DOT | PAINT |
| · IMDG, IATA | |
| · Transport hazard class(es) | |
| · DOT | |
| | |
| · Class | 3 Flammable liquids |
| · Label | 3 |
| · IMDG, IATA | |
| | |
| · Class | 3 Flammable liquids |
| · Label | 3 |
| · Packing group | II |
| · DOT, IMDG, IATA | |
| · Environmental hazards: | Not applicable. |
| · Special precautions for user | Warning: Flammable liquids |
| · Hazard identification number (Kemler code): | 33 |
| · EMS Number: | F-E, S-E |
| · Stowage Category | B |
| · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | Not applicable. |
| · Transport/Additional information: | |
| · DOT | |
| · Quantity limitations | On passenger aircraft/rail: 5 L
On cargo aircraft only: 60 L |

(Contd. on page 11)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/28/2025

Reviewed on 08/28/2025

Trade name: 828B DTM BINDER

(Contd. of page 10)

- | | |
|--|---|
| <ul style="list-style-type: none"> · IMDG · Limited quantities (LQ) · Excepted quantities (EQ) | 5L
Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml |
| <ul style="list-style-type: none"> · UN "Model Regulation": | UN 1263 PAINT, 3, II |

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**

- **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

- **Section 313 (Specific toxic chemical listings):**

1330-20-7	xylene
100-41-4	ethylbenzene
7779-90-0	trizinc bis(orthophosphate)
67-56-1	methanol
122-99-6	2-phenoxyethanol
1314-13-2	zinc oxide
67-63-0	propan-2-ol
108-88-3	toluene

- **TSCA (Toxic Substances Control Act):**

All components have the value ACTIVE.

- **Hazardous Air Pollutants**

1330-20-7	xylene
100-41-4	ethylbenzene
67-56-1	methanol
108-88-3	toluene

- **Proposition 65**

- **Chemicals known to cause cancer:**

100-41-4	ethylbenzene
----------	--------------

- **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

- **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

- **Chemicals known to cause developmental toxicity:**

64-17-5	ethanol
67-56-1	methanol
108-88-3	toluene

- **Carcinogenic categories**

- **EPA (Environmental Protection Agency)**

67-64-1	acetone
---------	---------

I

(Contd. on page 12)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/28/2025

Reviewed on 08/28/2025

Trade name: 828B DTM BINDER

(Contd. of page 11)

1330-20-7	xylene	I
100-41-4	ethylbenzene	D
7779-90-0	trizinc bis(orthophosphate)	D, I, II
1314-13-2	zinc oxide	D, I, II
108-88-3	toluene	II

· **TLV (Threshold Limit Value)**

67-64-1	acetone	A4
1330-20-7	xylene	A4
100-41-4	ethylbenzene	A3
64-17-5	ethanol	A3
77-58-7	dibutyltin dilaurate	A4
67-63-0	propan-2-ol	A4
108-88-3	toluene	A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**

n-butyl acetate
bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate
ethylbenzene
acetone

· **Hazard statements**

Highly flammable liquid and vapor.
Causes serious eye irritation.
May cause an allergic skin reaction.
May cause cancer.
May cause drowsiness or dizziness.

· **Precautionary statements**

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting/equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Avoid breathing dust/fume/gas/mist/vapors/spray
Wash thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Contaminated work clothing must not be allowed out of the workplace.
Wear protective gloves/protective clothing/eye protection/face protection.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

(Contd. on page 13)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/28/2025

Reviewed on 08/28/2025

Trade name: 828B DTM BINDER

(Contd. of page 12)

IF INHALED: Remove person to fresh air and keep comfortable for breathing.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
IF exposed or concerned: Get medical advice/attention.
Call a poison center/doctor if you feel unwell.
Specific treatment (see on this label).
If skin irritation or rash occurs: Get medical advice/attention.
If eye irritation persists: Get medical advice/attention.
Wash contaminated clothing before reuse.
In case of fire: Use CO2, powder or water spray to extinguish.
Store in a well-ventilated place. Keep container tightly closed.
Store in a well-ventilated place. Keep cool.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.

- **National regulations:**

- **Information about limitation of use:**

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** Environment protection department.

- **Contact:** Product Safety Dept.

- **Date of preparation / last revision** 08/28/2025 / 5

- **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flammable Liquids 2: Flammable liquids – Category 2

Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A

Sensitization - Skin 1: Skin sensitisation – Category 1

Carcinogenicity 1A: Carcinogenicity – Category 1A

Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3

- *** Data compared to the previous version altered.**