

## Safety Data Sheet acc. to OSHA HCS

Printing date 07/22/2026

Reviewed on 07/22/2026

### 1 Identification

- **Product identifier**
- **Trade name:** L11.4.K1 FLAT DTM BINDER
- **Article number:** L11.4.K1
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
GlobalStar is a product of Lusid Technologies Inc.  
4725 S Camp Kearns Road  
Kearns, UT 84118  
(801) 966-5300  
info@lusidtechnologies.com
- **Information department:** Product safety department
- **Emergency telephone number:**  
24 Hrs Emergency Contact:  
INFOTRAC  
1-800-535-5053

### 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flammable Liquids 2

H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Carcinogenicity 1A

H350 May cause cancer.



GHS07

Sensitization - Skin 1

H317 May cause an allergic skin reaction.

Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness.

Aquatic Acute 3

H402 Harmful to aquatic life.

Aquatic Chronic 3

H412 Harmful to aquatic life with long lasting effects.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 07/22/2026

Reviewed on 07/22/2026

Trade name: L11.4.K1 FLAT DTM BINDER

(Contd. of page 1)

## · Hazard pictograms



GHS02 GHS07 GHS08

## · Signal word Danger

## · Hazard-determining components of labeling:

*n*-butyl acetate  
 bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate  
 ethylbenzene  
 acetone

## · Hazard statements

Highly flammable liquid and vapor.  
 May cause an allergic skin reaction.  
 May cause cancer.  
 May cause drowsiness or dizziness.  
 Harmful to aquatic life with long lasting effects.

## · Precautionary statements

Obtain special instructions before use.  
 Do not handle until all safety precautions have been read and understood.  
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
 Ground/bond container and receiving equipment.  
 Use explosion-proof electrical/ventilating/lighting/equipment.  
 Use only non-sparking tools.  
 Take precautionary measures against static discharge.  
 Avoid breathing dust/fume/gas/mist/vapors/spray  
 Use only outdoors or in a well-ventilated area.  
 Contaminated work clothing must not be allowed out of the workplace.  
 Avoid release to the environment.  
 Wear protective gloves/protective clothing/eye protection/face protection.  
 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 IF exposed or concerned: Get medical advice/attention.  
 Call a poison center/doctor if you feel unwell.  
 Specific treatment (see on this label).  
 If skin irritation or rash occurs: Get medical advice/attention.  
 Wash contaminated clothing before reuse.  
 In case of fire: Use CO<sub>2</sub>, powder or water spray to extinguish.  
 Store in a well-ventilated place. Keep container tightly closed.  
 Store in a well-ventilated place. Keep cool.  
 Store locked up.  
 Dispose of contents/container in accordance with local/regional/national/international regulations.

## · Classification system:

## · NFPA ratings (scale 0 - 4)



Health = 0  
 Fire = 3  
 Reactivity = 0

(Contd. on page 3)

USA

# Safety Data Sheet

acc. to OSHA HCS

Printing date 07/22/2026

Reviewed on 07/22/2026

Trade name: L11.4.K1 FLAT DTM BINDER

(Contd. of page 2)

## · HMIS-ratings (scale 0 - 4)

|            |   |                |
|------------|---|----------------|
| HEALTH     | 0 | Health = *0    |
| FIRE       | 3 | Fire = 3       |
| REACTIVITY | 0 | Reactivity = 0 |

- Other hazards
- Results of PBT and vPvB assessment
- PBT: Not applicable
- vPvB: Not applicable

## 3 Composition/information on ingredients

- Chemical characterization: Mixtures
- Description: Mixture of the substances listed below with nonhazardous additions.

### · Dangerous components:

|            |                                                |         |
|------------|------------------------------------------------|---------|
| 123-86-4   | n-butyl acetate                                | 25-50%  |
| 67-64-1    | acetone                                        | 2.5-10% |
| 110-43-0   | heptan-2-one                                   | 2.5-10% |
| 557-05-1   | zinc distearate, pure                          | 2.5-10% |
|            | +A157 DISPERBYK-2008                           | ≤2.5%   |
| 41556-26-7 | bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate | ≤2.5%   |
| 1330-20-7  | xylene                                         | ≤2.5%   |
| 7779-90-0  | trizinc bis(orthophosphate)                    | ≤2.5%   |
| 100-41-4   | ethylbenzene                                   | ≤2.5%   |
| 64-17-5    | ethanol                                        | ≤2.5%   |

## 4 First-aid measures

- Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- After inhalation:  
Supply fresh air and to be sure call for a doctor.  
In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- Most important symptoms and effects, both acute and delayed  
No further relevant information available.
- Indication of any immediate medical attention and special treatment needed  
No further relevant information available.

## 5 Fire-fighting measures

- Extinguishing media
- Suitable extinguishing agents:  
CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- Special hazards arising from the substance or mixture No further relevant information available.

(Contd. on page 4)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 07/22/2026

Reviewed on 07/22/2026

Trade name: L11.4.K1 FLAT DTM BINDER

(Contd. of page 3)

- **Advice for firefighters**
- **Protective equipment:** No special measures required.

## 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**  
Do not allow product to reach sewage system or any water course.  
Prevent seepage into sewage system, workpits and cellars.  
Inform respective authorities in case of seepage into water course or sewage system.  
Dilute with plenty of water.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to section 13.  
Ensure adequate ventilation.
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

### · PAC-1:

|           |                             |           |
|-----------|-----------------------------|-----------|
| 123-86-4  | n-butyl acetate             | 5.0 ppm   |
| 67-64-1   | acetone                     | 200 ppm   |
| 110-43-0  | heptan-2-one                | 75 ppm    |
| 557-05-1  | zinc distearate, pure       | 20 mg/m3  |
| 1330-20-7 | xylene                      | 130 ppm   |
| 7779-90-0 | trizinc bis(orthophosphate) | 1.8 mg/m3 |
| 100-41-4  | ethylbenzene                | 33 ppm    |
| 7784-30-7 | Aluminium phosphate         | 18 mg/m3  |
| 64-17-5   | ethanol                     | 1800 ppm  |
| 67-56-1   | methanol                    | 530 ppm   |
| 77-58-7   | dibutyltin dilaurate        | 1.1 mg/m3 |
| 1314-13-2 | zinc oxide                  | 10 mg/m3  |
| 122-99-6  | 2-phenoxyethanol            | 5.7 mg/m3 |
| 67-63-0   | propan-2-ol                 | 400 ppm   |
| 108-88-3  | toluene                     | 67 ppm    |

### · PAC-2:

|           |                             |           |
|-----------|-----------------------------|-----------|
| 123-86-4  | n-butyl acetate             | 200 ppm   |
| 67-64-1   | acetone                     | 3200 ppm  |
| 110-43-0  | heptan-2-one                | 130 ppm   |
| 557-05-1  | zinc distearate, pure       | 900 mg/m3 |
| 1330-20-7 | xylene                      | 920 ppm   |
| 7779-90-0 | trizinc bis(orthophosphate) | 20 mg/m3  |
| 100-41-4  | ethylbenzene                | 1100 ppm  |
| 7784-30-7 | Aluminium phosphate         | 200 mg/m3 |
| 64-17-5   | ethanol                     | 3300 ppm  |

(Contd. on page 5)

USA

# Safety Data Sheet

acc. to OSHA HCS

Printing date 07/22/2026

Reviewed on 07/22/2026

Trade name: L11.4.K1 FLAT DTM BINDER

(Contd. of page 4)

|               |                             |            |
|---------------|-----------------------------|------------|
| 67-56-1       | methanol                    | 2100 ppm   |
| 77-58-7       | dibutyltin dilaurate        | 3.8 mg/m3  |
| 1314-13-2     | zinc oxide                  | 15 mg/m3   |
| 122-99-6      | 2-phenoxyethanol            | 42 mg/m3   |
| 67-63-0       | propan-2-ol                 | 2000 ppm   |
| 108-88-3      | toluene                     | 560 ppm    |
| <b>PAC-3:</b> |                             |            |
| 123-86-4      | n-butyl acetate             | 3000 ppm   |
| 67-64-1       | acetone                     | 5700 ppm   |
| 110-43-0      | heptan-2-one                | 800 ppm    |
| 557-05-1      | zinc distearate, pure       | 5400 mg/m3 |
| 1330-20-7     | xylene                      | 2500 ppm   |
| 7779-90-0     | trizinc bis(orthophosphate) | 120 mg/m3  |
| 100-41-4      | ethylbenzene                | 1800 ppm   |
| 7784-30-7     | Aluminium phosphate         | 1200 mg/m3 |
| 64-17-5       | ethanol                     | 15000 ppm  |
| 67-56-1       | methanol                    | 7200 ppm   |
| 77-58-7       | dibutyltin dilaurate        | 23 mg/m3   |
| 1314-13-2     | zinc oxide                  | 2500 mg/m3 |
| 122-99-6      | 2-phenoxyethanol            | 250 mg/m3  |
| 67-63-0       | propan-2-ol                 | 12000 ppm  |
| 108-88-3      | toluene                     | 3700 ppm   |

## 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**  
Ensure good ventilation/exhaustion at the workplace.  
Open and handle receptacle with care.  
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.  
Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required
- **Further information about storage conditions:**  
Keep receptacle tightly sealed.  
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

## 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see section 7.

(Contd. on page 6)

-USA-

# Safety Data Sheet

acc. to OSHA HCS

Printing date 07/22/2026

Reviewed on 07/22/2026

Trade name: L11.4.K1 FLAT DTM BINDER

(Contd. of page 5)

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

**123-86-4 n-butyl acetate**

|     |                                                                                                       |
|-----|-------------------------------------------------------------------------------------------------------|
| PEL | Long-term value: 710 mg/m <sup>3</sup> , 150 ppm                                                      |
| REL | Short-term value: 950 mg/m <sup>3</sup> , 200 ppm<br>Long-term value: 710 mg/m <sup>3</sup> , 150 ppm |
| TLV | Short-term value: 712 mg/m <sup>3</sup> , 150 ppm<br>Long-term value: 238 mg/m <sup>3</sup> , 50 ppm  |

**67-64-1 acetone**

|     |                                                                                                                   |
|-----|-------------------------------------------------------------------------------------------------------------------|
| PEL | Long-term value: 2400 mg/m <sup>3</sup> , 1000 ppm                                                                |
| REL | Long-term value: 590 mg/m <sup>3</sup> , 250 ppm                                                                  |
| TLV | Short-term value: 1187 mg/m <sup>3</sup> , 500 ppm<br>Long-term value: 594 mg/m <sup>3</sup> , 250 ppm<br>A4, BEI |

**110-43-0 heptan-2-one**

|     |                                                  |
|-----|--------------------------------------------------|
| PEL | Long-term value: 465 mg/m <sup>3</sup> , 100 ppm |
| REL | Long-term value: 465 mg/m <sup>3</sup> , 100 ppm |
| TLV | Long-term value: 50 ppm                          |

**557-05-1 zinc distearate, pure**

|     |                                                                                                |
|-----|------------------------------------------------------------------------------------------------|
| PEL | Long-term value: 15* 5** mg/m <sup>3</sup><br>*total dust **respirable fraction                |
| REL | Long-term value: 10* 5** mg/m <sup>3</sup><br>*total dust **respirable fraction                |
| TLV | Long-term value: 10* 3** mg/m <sup>3</sup><br>*inhalable, **respirable particulate matter, *A4 |

**1330-20-7 xylene**

|     |                                                                                                       |
|-----|-------------------------------------------------------------------------------------------------------|
| PEL | Long-term value: 435 mg/m <sup>3</sup> , 100 ppm                                                      |
| REL | Short-term value: 655 mg/m <sup>3</sup> , 150 ppm<br>Long-term value: 435 mg/m <sup>3</sup> , 100 ppm |
| TLV | Long-term value: 20 ppm<br>BEI, A4                                                                    |

**100-41-4 ethylbenzene**

|     |                                                                                                       |
|-----|-------------------------------------------------------------------------------------------------------|
| PEL | Long-term value: 435 mg/m <sup>3</sup> , 100 ppm                                                      |
| REL | Short-term value: 545 mg/m <sup>3</sup> , 125 ppm<br>Long-term value: 435 mg/m <sup>3</sup> , 100 ppm |
| TLV | Long-term value: 20 ppm<br>OTO, BEI, A3                                                               |

**64-17-5 ethanol**

|     |                                                           |
|-----|-----------------------------------------------------------|
| PEL | Long-term value: 1900 mg/m <sup>3</sup> , 1000 ppm        |
| REL | Long-term value: 1900 mg/m <sup>3</sup> , 1000 ppm        |
| TLV | Short-term value: 1880 mg/m <sup>3</sup> , 1000 ppm<br>A3 |

(Contd. on page 7)

USA

# Safety Data Sheet

acc. to OSHA HCS

Printing date 07/22/2026

Reviewed on 07/22/2026

Trade name: L11.4.K1 FLAT DTM BINDER

(Contd. of page 6)

## Ingredients with biological limit values:

### 67-64-1 acetone

BEI 25 mg/L  
 Medium: urine  
 Time: end of shift  
 Parameter: Acetone (nonspecific)

### 1330-20-7 xylene

BEI 0.3 g/g creatinine  
 Medium: urine  
 Time: end of shift  
 Parameter: Methylhippuric acids

### 100-41-4 ethylbenzene

BEI 0.15 g/g creatinine  
 Medium: urine  
 Time: end of shift  
 Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific)

· **Additional information:** The lists that were valid during the creation were used as basis.

## Exposure controls

### Personal protective equipment:

#### General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.  
 Immediately remove all soiled and contaminated clothing.  
 Wash hands before breaks and at the end of work.  
 Store protective clothing separately.

#### Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

#### Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 8)

USA

# Safety Data Sheet

acc. to OSHA HCS

Printing date 07/22/2026

Reviewed on 07/22/2026

Trade name: L11.4.K1 FLAT DTM BINDER

(Contd. of page 7)

## · Eye protection:



Tightly sealed goggles

## 9 Physical and chemical properties

## · Information on basic physical and chemical properties

## · General Information

## · Appearance:

Form:

Liquid

Color:

According to product specification

## · Odor:

Characteristic

## · Odor threshold:

Not determined

## · pH-value:

Not determined (pH N/A in solvent coatings)

## · Change in condition

Melting point/Melting range:

Undetermined

Boiling point/Boiling range:

55.8-56.6 °C (132.4-133.9 °F)

## · Flash point:

&lt;-18 °C (&lt;-0.4 °F)

## · Flammability:

Highly flammable.

## · Auto igniting:

370 °C (698 °F)

## · Decomposition temperature:

Not determined

## · Ignition temperature:

Product is not selfigniting.

## · Danger of explosion:

Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

## · Explosion limits:

Lower:

1.2 Vol %

Upper:

7.5 Vol %

## · Vapor pressure at 20 °C (68 °F):

10.7 hPa (8 mm Hg)

## · Vapor pressure at 50 °C (122 °F):

55 hPa (41.3 mm Hg)

## · Density at 20 °C (68 °F):

1.0646 g/cm<sup>3</sup> (8.8841 lbs/gal)

## · Relative density

Not determined

## · Vapor density

Not determined

## · Evaporation rate

Not determined

## · Solubility in / Miscibility with

Water:

Fully miscible.

## · Partition coefficient (n-octanol/water):

Not determined

## · Viscosity:

Dynamic:

Not determined

Kinematic:

Not determined

## · Solvent content:

Organic solvents:

45.6 %

(Contd. on page 9)

USA

# Safety Data Sheet

acc. to OSHA HCS

Printing date 07/22/2026

Reviewed on 07/22/2026

Trade name: L11.4.K1 FLAT DTM BINDER

(Contd. of page 8)

|                          |                                            |
|--------------------------|--------------------------------------------|
| <b>VOC content:</b>      | 36.34 %<br>362.3 g/l / 3.02 lb/gal         |
| <b>Solids content:</b>   | 62.3 %                                     |
| <b>Other information</b> | No further relevant information available. |

## 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

## 11 Toxicological information

- **Information on toxicological effects**

- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

### 123-86-4 n-butyl acetate

|            |          |                       |
|------------|----------|-----------------------|
| Oral       | LD50     | 13,100 mg/kg (rat)    |
| Dermal     | LD50     | >5,000 mg/kg (rabbit) |
| Inhalative | LC50/4 h | >21 mg/l (rat)        |

- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:  
Irritant

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

|           |              |    |
|-----------|--------------|----|
| 1330-20-7 | xylene       | 3  |
| 100-41-4  | ethylbenzene | 2B |
| 64-17-5   | ethanol      | 1  |
| 67-63-0   | propan-2-ol  | 3  |
| 108-88-3  | toluene      | 3  |

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

(Contd. on page 10)

USA

# Safety Data Sheet

acc. to OSHA HCS

Printing date 07/22/2026

Reviewed on 07/22/2026

Trade name: L11.4.K1 FLAT DTM BINDER

(Contd. of page 9)

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

## 12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**  
Not hazardous for water.  
Harmful to aquatic organisms
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable
- **vPvB:** Not applicable
- **Other adverse effects** No further relevant information available.

## 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**  
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

## 14 Transport information

- **UN-Number**
- **DOT, IMDG, IATA** UN1263

- **UN proper shipping name**
- **DOT** Paint
- **IMDG, IATA** PAINT

- **Transport hazard class(es)**

- **DOT**



- **Class** 3 Flammable liquids

(Contd. on page 11)

USA

# Safety Data Sheet

acc. to OSHA HCS

Printing date 07/22/2026

Reviewed on 07/22/2026

Trade name: L11.4.K1 FLAT DTM BINDER

(Contd. of page 10)

|                                                                                   |                                                                                                                 |
|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------|
| · <b>Label</b>                                                                    | 3                                                                                                               |
| · <b>IMDG, IATA</b>                                                               |                                                                                                                 |
|  |                                                                                                                 |
| · <b>Class</b>                                                                    | 3 Flammable liquids                                                                                             |
| · <b>Label</b>                                                                    | 3                                                                                                               |
| · <b>Packing group</b>                                                            |                                                                                                                 |
| · <b>DOT, IMDG, IATA</b>                                                          | II                                                                                                              |
| · <b>Environmental hazards:</b>                                                   | Not applicable                                                                                                  |
| · <b>Special precautions for user</b>                                             | Warning: Flammable liquids                                                                                      |
| · <b>Hazard identification number (Kemler code):</b>                              | 33                                                                                                              |
| · <b>EMS Number:</b>                                                              | F-E, S-E                                                                                                        |
| · <b>Stowage Category</b>                                                         | B                                                                                                               |
| · <b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b>  | Not applicable                                                                                                  |
| · <b>Transport/Additional information:</b>                                        |                                                                                                                 |
| · <b>DOT</b>                                                                      |                                                                                                                 |
| · <b>Quantity limitations</b>                                                     | On passenger aircraft/rail: 5 L<br>On cargo aircraft only: 60 L                                                 |
| · <b>IMDG</b>                                                                     |                                                                                                                 |
| · <b>Limited quantities (LQ)</b>                                                  | 5L                                                                                                              |
| · <b>Excepted quantities (EQ)</b>                                                 | Code: E2<br>Maximum net quantity per inner packaging: 30 ml<br>Maximum net quantity per outer packaging: 500 ml |
| · <b>UN "Model Regulation":</b>                                                   | UN 1263 PAINT, 3, II                                                                                            |

## 15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**  
 · **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

|           |                             |
|-----------|-----------------------------|
| 557-05-1  | zinc distearate, pure       |
| 1330-20-7 | xylene                      |
| 7779-90-0 | trizinc bis(orthophosphate) |
| 100-41-4  | ethylbenzene                |
| 67-56-1   | methanol                    |
| 1314-13-2 | zinc oxide                  |
| 122-99-6  | 2-phenoxyethanol            |
| 67-63-0   | propan-2-ol                 |
| 108-88-3  | toluene                     |

(Contd. on page 12)

USA

# Safety Data Sheet

acc. to OSHA HCS

Printing date 07/22/2026

Reviewed on 07/22/2026

Trade name: L11.4.K1 FLAT DTM BINDER

(Contd. of page 11)

**TSCA (Toxic Substances Control Act):**

|            |                                                  |        |
|------------|--------------------------------------------------|--------|
| 123-86-4   | <i>n</i> -butyl acetate                          | ACTIVE |
| 67-64-1    | acetone                                          | ACTIVE |
| 110-43-0   | heptan-2-one                                     | ACTIVE |
| 557-05-1   | zinc distearate, pure                            | ACTIVE |
| 41556-26-7 | bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate   | ACTIVE |
| 1330-20-7  | xylene                                           | ACTIVE |
| 7779-90-0  | trizinc bis(orthophosphate)                      | ACTIVE |
| 100-41-4   | ethylbenzene                                     | ACTIVE |
| 82919-37-7 | methyl 1,2,2,6,6-pentamethyl-4-piperidylsebacate | ACTIVE |
| 7784-30-7  | Aluminium phosphate                              | ACTIVE |
| 64-17-5    | ethanol                                          | ACTIVE |
| 67-56-1    | methanol                                         | ACTIVE |
| 77-58-7    | dibutyltin dilaurate                             | ACTIVE |
| 1314-13-2  | zinc oxide                                       | ACTIVE |
| 122-99-6   | 2-phenoxyethanol                                 | ACTIVE |
| 67-63-0    | propan-2-ol                                      | ACTIVE |
| 108-88-3   | toluene                                          | ACTIVE |

**Hazardous Air Pollutants**

|           |                  |
|-----------|------------------|
| 1330-20-7 | xylene           |
| 100-41-4  | ethylbenzene     |
| 67-56-1   | methanol         |
| 122-99-6  | 2-phenoxyethanol |
| 108-88-3  | toluene          |

**Proposition 65**
**Chemicals known to cause cancer:**

|          |              |       |
|----------|--------------|-------|
| 100-41-4 | ethylbenzene | 0.42% |
|----------|--------------|-------|

**Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

**Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

**Chemicals known to cause developmental toxicity:**

|          |          |        |
|----------|----------|--------|
| 64-17-5  | ethanol  | 0.157% |
| 67-56-1  | methanol | 0.064% |
| 108-88-3 | toluene  | 0.001% |

**Carcinogenic categories**
**EPA (Environmental Protection Agency)**

|           |                             |          |
|-----------|-----------------------------|----------|
| 67-64-1   | acetone                     | I        |
| 557-05-1  | zinc distearate, pure       | D, I, II |
| 1330-20-7 | xylene                      | I        |
| 7779-90-0 | trizinc bis(orthophosphate) | D, I, II |
| 100-41-4  | ethylbenzene                | D        |
| 1314-13-2 | zinc oxide                  | D, I, II |

(Contd. on page 13)

USA

# Safety Data Sheet

acc. to OSHA HCS

Printing date 07/22/2026

Reviewed on 07/22/2026

Trade name: L11.4.K1 FLAT DTM BINDER

(Contd. of page 12)

|                                      |                      |    |
|--------------------------------------|----------------------|----|
| 108-88-3                             | toluene              | II |
| <b>· TLV (Threshold Limit Value)</b> |                      |    |
| 67-64-1                              | acetone              | A4 |
| 1330-20-7                            | xylene               | A4 |
| 100-41-4                             | ethylbenzene         | A3 |
| 64-17-5                              | ethanol              | A3 |
| 77-58-7                              | dibutyltin dilaurate | A4 |
| 67-63-0                              | propan-2-ol          | A4 |
| 108-88-3                             | toluene              | A4 |

**· NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

**· GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

**· Hazard pictograms**

GHS02 GHS07 GHS08

**· Signal word** Danger**· Hazard-determining components of labeling:**

n-butyl acetate  
 bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate  
 ethylbenzene  
 acetone

**· Hazard statements**

Highly flammable liquid and vapor.  
 May cause an allergic skin reaction.  
 May cause cancer.  
 May cause drowsiness or dizziness.  
 Harmful to aquatic life with long lasting effects.

**· Precautionary statements**

Obtain special instructions before use.  
 Do not handle until all safety precautions have been read and understood.  
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
 Ground/bond container and receiving equipment.  
 Use explosion-proof electrical/ventilating/lighting/equipment.  
 Use only non-sparking tools.  
 Take precautionary measures against static discharge.  
 Avoid breathing dust/fume/gas/mist/vapors/spray  
 Use only outdoors or in a well-ventilated area.  
 Contaminated work clothing must not be allowed out of the workplace.  
 Avoid release to the environment.  
 Wear protective gloves/protective clothing/eye protection/face protection.  
 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 IF exposed or concerned: Get medical advice/attention.  
 Call a poison center/doctor if you feel unwell.  
 Specific treatment (see on this label).  
 If skin irritation or rash occurs: Get medical advice/attention.

(Contd. on page 14)

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 07/22/2026

Reviewed on 07/22/2026

Trade name: **L11.4.K1 FLAT DTM BINDER**

(Contd. of page 13)

Wash contaminated clothing before reuse.  
 In case of fire: Use CO<sub>2</sub>, powder or water spray to extinguish.  
 Store in a well-ventilated place. Keep container tightly closed.  
 Store in a well-ventilated place. Keep cool.  
 Store locked up.  
 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **National regulations:**

· **Information about limitation of use:**

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Contact:**

· **Date of preparation / last revision** 07/22/2026 / 3

· **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flammable Liquids 2: Flammable liquids – Category 2

Sensitization - Skin 1: Skin sensitisation – Category 1

Carcinogenicity 1A: Carcinogenicity – Category 1A

Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3

Aquatic Acute 3: Hazardous to the aquatic environment - acute aquatic hazard – Category 3

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· **\* Data compared to the previous version altered.**

USA