



## Safety Data Sheet acc. to OSHA HCS

Printing date 05/31/2023

Reviewed on 05/31/2023

### 1 Identification

- **Product identifier**
- **Trade name:** EH.001 QUICK EPOXY HARDENER
- **Article number:** EH.001
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
Lusid Technologies  
4725 S Camp Kearns Road  
Kearns, UT 840118
- **Information department:** Product safety department
- **Emergency telephone number:**  
24 Hrs Emergency Contact:  
INFOTRAC  
1-800-535-5053

### 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flammable Liquids 2

H225 Highly flammable liquid and vapor.



GHS07

Eye Irritation 2A

H319 Causes serious eye irritation.

Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02 GHS07

- **Signal word** Danger

- **Hazard-determining components of labeling:**

acetone

- **Hazard statements**

Highly flammable liquid and vapor.

(Contd. on page 2)

USA

# Safety Data Sheet

acc. to OSHA HCS

Printing date 05/31/2023

Reviewed on 05/31/2023

Trade name: **EH.001 QUICK EPOXY HARDENER**

(Contd. of page 1)

Causes serious eye irritation.

May cause drowsiness or dizziness.

· **Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Call a poison center/doctor if you feel unwell.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use CO<sub>2</sub>, powder or water spray to extinguish.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 2

Fire = 3

Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**



Health = 2

Fire = 3

Reactivity = 0

· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

## 3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

540-88-5	tert-butyl acetate	25-50%
67-64-1	acetone	25-50%
110-43-0	heptan-2-one	2.5-10%

USA

(Contd. on page 3)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 05/31/2023

Reviewed on 05/31/2023

Trade name: EH.001 QUICK EPOXY HARDENER

(Contd. of page 2)

## 4 First-aid measures

- **Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Immediately rinse with water.
- **After eye contact:**  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**  
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

## 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

## 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**  
Dilute with plenty of water.  
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to section 13.  
Ensure adequate ventilation.
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

- **PAC-1:**

540-88-5	tert-butyl acetate	600 ppm
67-64-1	acetone	200 ppm
25036-25-3	phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis[oxirane]	12 mg/m <sup>3</sup>
110-43-0	heptan-2-one	150 ppm

- **PAC-2:**

540-88-5	tert-butyl acetate	1,700 ppm
67-64-1	acetone	3200* ppm

(Contd. on page 4)

USA

# Safety Data Sheet

acc. to OSHA HCS

Printing date 05/31/2023

Reviewed on 05/31/2023

Trade name: **EH.001 QUICK EPOXY HARDENER**

(Contd. of page 3)

25036-25-3	phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis[oxirane]	130 mg/m <sup>3</sup>
110-43-0	heptan-2-one	670 ppm
<b>· PAC-3:</b>		
540-88-5	tert-butyl acetate	10,000 ppm
67-64-1	acetone	5700* ppm
25036-25-3	phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis[oxirane]	790 mg/m <sup>3</sup>
110-43-0	heptan-2-one	4000* ppm

## 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**  
Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**  
Keep receptacle tightly sealed.  
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

## 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see section 7.
- **Control parameters**

### · Components with limit values that require monitoring at the workplace:

#### 540-88-5 tert-butyl acetate

PEL	Long-term value: 950 mg/m <sup>3</sup> , 200 ppm
REL	Long-term value: 950 mg/m <sup>3</sup> , 200 ppm
TLV	Short-term value: 150 ppm Long-term value: 50 ppm

#### 67-64-1 acetone

PEL	Long-term value: 2400 mg/m <sup>3</sup> , 1000 ppm
REL	Long-term value: 590 mg/m <sup>3</sup> , 250 ppm
TLV	Short-term value: 500 ppm Long-term value: 250 ppm A4, BEI

#### 110-43-0 heptan-2-one

PEL	Long-term value: 465 mg/m <sup>3</sup> , 100 ppm
-----	--

(Contd. on page 5)

USA

# Safety Data Sheet

acc. to OSHA HCS

Printing date 05/31/2023

Reviewed on 05/31/2023

Trade name: **EH.001 QUICK EPOXY HARDENER**

(Contd. of page 4)

REL Long-term value: 465 mg/m<sup>3</sup>, 100 ppm

TLV Long-term value: 50 ppm

· **Ingredients with biological limit values:**

**67-64-1 acetone**

BEI 25 mg/L

Medium: urine

Time: end of shift

Parameter: Acetone (nonspecific)

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

## 9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:

Liquid

(Contd. on page 6)

USA

# Safety Data Sheet

acc. to OSHA HCS

Printing date 05/31/2023

Reviewed on 05/31/2023

Trade name: EH.001 QUICK EPOXY HARDENER

(Contd. of page 5)

· <b>Color:</b>	Clear
· <b>Odor:</b>	Characteristic
· <b>Odor threshold:</b>	Not determined.
· <b>pH-value:</b>	Not determined (pH N/A in solvent coatings)
· <b>Change in condition</b>	
<b>Melting point/Melting range:</b>	Undetermined.
<b>Boiling point/Boiling range:</b>	55.8-56.6 °C (132.4-133.9 °F)
· <b>Flash point:</b>	<-18 °C (<-0.4 °F)
· <b>Flammability (solid, gaseous):</b>	Highly flammable.
· <b>Auto igniting:</b>	393 °C (739.4 °F)
· <b>Decomposition temperature:</b>	Not determined.
· <b>Ignition temperature:</b>	Product is not selfigniting.
· <b>Danger of explosion:</b>	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· <b>Explosion limits:</b>	
<b>Lower:</b>	2.6 Vol %
<b>Upper:</b>	13 Vol %
· <b>Vapor pressure at 20 °C (68 °F):</b>	233 hPa (174.8 mm Hg)
· <b>Density at 20 °C (68 °F):</b>	0.9297 g/cm <sup>3</sup> (7.7583 lbs/gal)
· <b>Relative density</b>	Not determined.
· <b>Vapor density</b>	Not determined.
· <b>Evaporation rate</b>	Not determined.
· <b>Solubility in / Miscibility with Water:</b>	Fully miscible.
· <b>Partition coefficient (n-octanol/water):</b>	Not determined.
· <b>Viscosity:</b>	
<b>Dynamic:</b>	Not determined.
<b>Kinematic:</b>	Not determined.
· <b>Solvent content:</b>	
<b>Organic solvents:</b>	70.5 %
<b>VOC content:</b>	9.39 %
	198.0 g/l / 1.65 lb/gal
<b>Solids content:</b>	37.4 %
· <b>Other information</b>	No further relevant information available.

## 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.

(Contd. on page 7)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 05/31/2023

Reviewed on 05/31/2023

Trade name: EH.001 QUICK EPOXY HARDENER

(Contd. of page 6)

- **Hazardous decomposition products:** No dangerous decomposition products known.

## 11 Toxicological information

- **Information on toxicological effects**

- **Acute toxicity:**

- **Primary irritant effect:**

- **on the skin:** No irritant effect.

- **on the eye:** Irritating effect.

- **Sensitization:** No sensitizing effects known.

- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

None of the ingredients is listed.

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

## 12 Ecological information

- **Toxicity**

- **Aquatic toxicity:** No further relevant information available.

- **Persistence and degradability** No further relevant information available.

- **Behavior in environmental systems:**

- **Bioaccumulative potential** No further relevant information available.

- **Mobility in soil** No further relevant information available.

- **Additional ecological information:**

- **General notes:**

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

- **Other adverse effects** No further relevant information available.

## 13 Disposal considerations

- **Waste treatment methods**

- **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- **Uncleaned packagings:**

- **Recommendation:** Disposal must be made according to official regulations.

(Contd. on page 8)

USA

# Safety Data Sheet

acc. to OSHA HCS

Printing date 05/31/2023

Reviewed on 05/31/2023

Trade name: **EH.001 QUICK EPOXY HARDENER**

(Contd. of page 7)

· **Recommended cleansing agent:** Water, if necessary with cleansing agents.

## 14 Transport information

· **UN-Number**  
 · **DOT, IMDG, IATA** UN1263

· **UN proper shipping name**  
 · **DOT** Paint  
 · **IMDG, IATA** PAINT

· **Transport hazard class(es)**  
 · **DOT**



· **Class** 3 Flammable liquids  
 · **Label** 3

· **IMDG, IATA**



· **Class** 3 Flammable liquids  
 · **Label** 3

· **Packing group**  
 · **DOT, IMDG, IATA** II

· **Environmental hazards:**  
 · **Marine pollutant:** No

· **Special precautions for user** Warning: Flammable liquids  
 · **Hazard identification number (Kemler code):** 33  
 · **EMS Number:** F-E, S-E  
 · **Stowage Category** B

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.

· **Transport/Additional information:**

· **DOT**  
 · **Quantity limitations** On passenger aircraft/rail: 5 L  
 On cargo aircraft only: 60 L

· **IMDG**  
 · **Limited quantities (LQ)** 5L  
 · **Excepted quantities (EQ)** Code: E2  
 Maximum net quantity per inner packaging: 30 ml  
 Maximum net quantity per outer packaging: 500 ml

(Contd. on page 9)

USA



# Safety Data Sheet

acc. to OSHA HCS

Printing date 05/31/2023

Reviewed on 05/31/2023

Trade name: EH.001 QUICK EPOXY HARDENER

(Contd. of page 8)

· UN "Model Regulation": UN 1263 PAINT, 3, II

## 15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**  
No further relevant information available.

· **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

None of the ingredients is listed.

· **TSCA (Toxic Substances Control Act):**

All components have the value ACTIVE.

· **Hazardous Air Pollutants**

None of the ingredients is listed.

· **Proposition 65**

· **Chemicals known to cause cancer:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

67-64-1 acetone

I

· **TLV (Threshold Limit Value)**

67-64-1 acetone

A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS07

· **Signal word** Danger

· **Hazard-determining components of labeling:**

acetone

· **Hazard statements**

Highly flammable liquid and vapor.

(Contd. on page 10)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 05/31/2023

Reviewed on 05/31/2023

**Trade name: EH.001 QUICK EPOXY HARDENER**

(Contd. of page 9)

Causes serious eye irritation.

May cause drowsiness or dizziness.

· **Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Call a poison center/doctor if you feel unwell.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use CO<sub>2</sub>, powder or water spray to extinguish.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Environment protection department.

· **Contact:** Product Safety Dept.

· **Date of preparation / last revision** 05/31/2023

· **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flammable Liquids 2: Flammable liquids – Category 2

Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A

Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3

· \* **Data compared to the previous version altered.**