

## Safety Data Sheet acc. to OSHA HCS

Printing date 04/03/2020

Reviewed on 02/27/2020

### 1 Identification

- **Product identifier**
- **Trade name:** L6.1.K1 LOW VOC HIGH GLOSS UHS POLYURETHANE
- **Article number:** L6.1.K1
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
Lusid Technologies  
4725 S Camp Kearns Road  
Kearns, UT 84118  
USA  
[www.lusidtechnologies.com](http://www.lusidtechnologies.com)
- **Information department:** Product safety department
- **Emergency telephone number:**  
24 Hrs Emergency Contact:  
INFOTRAC  
1-800-535-5053

### 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Carc. 1A H350 May cause cancer.

STOT RE 2 H373 May cause damage to the hearing organs through prolonged or repeated exposure.



GHS07

Acute Tox. 4 H332 Harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H336 May cause drowsiness or dizziness.

(Contd. on page 2)

USA

# Safety Data Sheet

acc. to OSHA HCS

Printing date 04/03/2020

Reviewed on 02/27/2020

**Trade name: L6.1.K1 LOW VOC HIGH GLOSS UHS POLYURETHANE**

(Contd. of page 1)

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02   GHS07   GHS08

- **Signal word** *Danger*

- **Hazard-determining components of labeling:**

4-chloro-alpha,alpha,alpha-trifluorotoluene  
xylene

n-butyl acetate

ethylbenzene

bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate

- **Hazard statements**

Highly flammable liquid and vapor.

Harmful if inhaled.

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

May cause cancer.

May cause drowsiness or dizziness.

May cause damage to the hearing organs through prolonged or repeated exposure.

- **Precautionary statements**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Call a poison center/doctor if you feel unwell.

Specific treatment (see on this label).

Get medical advice/attention if you feel unwell.

Take off contaminated clothing and wash it before reuse.

If skin irritation or rash occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

Wash contaminated clothing before reuse.

In case of fire: Use for extinction: CO<sub>2</sub>, powder or water spray.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

(Contd. on page 3)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 04/03/2020

Reviewed on 02/27/2020

**Trade name: L6.1.K1 LOW VOC HIGH GLOSS UHS POLYURETHANE**

(Contd. of page 2)

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 2  
Fire = 3  
Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**



Health = \*2  
Fire = 3  
Reactivity = 0

· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

### 3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

|            |  |         |
|------------|--|---------|
| 98-56-6    | 4-chloro-alpha,alpha,alpha-trifluorotoluene    | 25-50%  |
| 123-86-4   | n-butyl acetate                                | 10-25%  |
| 1330-20-7  | xylene   | 2.5-10% |
| 67-64-1    | acetone  | 2.5-10% |
| 100-41-4   | ethylbenzene                                   | 2.5-10% |
| 1330-20-7  | xylene   | ≤2.5%   |
| 41556-26-7 | bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate | ≤2.5%   |
| 64-17-5    | ethanol  | ≤2.5%   |
| 123-54-6   | pentane-2,4-dione                              | ≤2.5%   |
| 67-56-1    | methanol                                       | ≤2.5%   |

### 4 First-aid measures

· **Description of first aid measures**

· **General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· **After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:** If symptoms persist consult doctor.

(Contd. on page 4)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 04/03/2020

Reviewed on 02/27/2020

**Trade name: L6.1.K1 LOW VOC HIGH GLOSS UHS POLYURETHANE**

(Contd. of page 3)

- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**  
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

## 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture**  
During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

## 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Mount respiratory protective device.  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**  
Dilute with plenty of water.  
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

- **PAC-1:**

|           |                      |                       |
|-----------|----------------------|-----------------------|
| 123-86-4  | n-butyl acetate      | 5 ppm                 |
| 67-64-1   | acetone              | 200 ppm               |
| 100-41-4  | ethylbenzene         | 33 ppm                |
| 1330-20-7 | xylene               | 130 ppm               |
| 64-17-5   | ethanol              | 1,800 ppm             |
| 123-54-6  | pentane-2,4-dione    | 75 ppm                |
| 67-56-1   | methanol             | 530 ppm               |
| 122-99-6  | 2-Phenoxyethanol     | 1.5 ppm               |
| 77-58-7   | dibutyltin dilaurate | 1.1 mg/m <sup>3</sup> |
| 67-63-0   | propan-2-ol          | 400 ppm               |

- **PAC-2:**

|          |                 |           |
|----------|-----------------|-----------|
| 123-86-4 | n-butyl acetate | 200 ppm   |
| 67-64-1  | acetone         | 3200* ppm |
| 100-41-4 | ethylbenzene    | 1100* ppm |

(Contd. on page 5)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 04/03/2020

Reviewed on 02/27/2020

**Trade name: L6.1.K1 LOW VOC HIGH GLOSS UHS POLYURETHANE**

(Contd. of page 4)

|           |                      |                     |
|-----------|----------------------|---------------------|
| 1330-20-7 | xylene               | 920* ppm            |
| 64-17-5   | ethanol              | 3300* ppm           |
| 123-54-6  | pentane-2,4-dione    | 110 ppm             |
| 67-56-1   | methanol             | 2,100 ppm           |
| 122-99-6  | 2-Phenoxyethanol     | 16 ppm              |
| 77-58-7   | dibutyltin dilaurate | 8 mg/m <sup>3</sup> |
| 67-63-0   | propan-2-ol          | 2000* ppm           |

**· PAC-3:**

|           |                      |                      |
|-----------|----------------------|----------------------|
| 123-86-4  | n-butyl acetate      | 3000* ppm            |
| 67-64-1   | acetone              | 5700* ppm            |
| 100-41-4  | ethylbenzene         | 1800* ppm            |
| 1330-20-7 | xylene               | 2500* ppm            |
| 64-17-5   | ethanol              | 15000* ppm           |
| 123-54-6  | pentane-2,4-dione    | 200 ppm              |
| 67-56-1   | methanol             | 7200* ppm            |
| 122-99-6  | 2-Phenoxyethanol     | 97 ppm               |
| 77-58-7   | dibutyltin dilaurate | 48 mg/m <sup>3</sup> |
| 67-63-0   | propan-2-ol          | 12000** ppm          |

## 7 Handling and storage

**· Handling:**

**· Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.  
Open and handle receptacle with care.  
Prevent formation of aerosols.

**· Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.  
Keep respiratory protective device available.

**· Conditions for safe storage, including any incompatibilities**

**· Storage:**

**· Requirements to be met by storerooms and receptacles:** Store in a cool location.

**· Information about storage in one common storage facility:** Not required.

**· Further information about storage conditions:**

Keep receptacle tightly sealed.  
Store in cool, dry conditions in well sealed receptacles.

**· Specific end use(s)** No further relevant information available.

## 8 Exposure controls/personal protection

**· Additional information about design of technical systems:** No further data; see item 7.

**· Control parameters**

**· Components with limit values that require monitoring at the workplace:**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

(Contd. on page 6)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 04/03/2020

Reviewed on 02/27/2020

**Trade name: L6.1.K1 LOW VOC HIGH GLOSS UHS POLYURETHANE**

(Contd. of page 5)

**123-86-4 n-butyl acetate**

|     |   |
|-----|---|
| PEL | Long-term value: 710 mg/m <sup>3</sup> , 150 ppm  |
| REL | Short-term value: 950 mg/m <sup>3</sup> , 200 ppm<br>Long-term value: 710 mg/m <sup>3</sup> , 150 ppm |
| TLV | Short-term value: 712 mg/m <sup>3</sup> , 150 ppm<br>Long-term value: 238 mg/m <sup>3</sup> , 50 ppm  |

**1330-20-7 xylene**

|     |  |
|-----|--|
| PEL | Long-term value: 435 mg/m <sup>3</sup> , 100 ppm   |
| REL | Short-term value: 655 mg/m <sup>3</sup> , 150 ppm<br>Long-term value: 435 mg/m <sup>3</sup> , 100 ppm        |
| TLV | Short-term value: 651 mg/m <sup>3</sup> , 150 ppm<br>Long-term value: 434 mg/m <sup>3</sup> , 100 ppm<br>BEI |

**67-64-1 acetone**

|     |   |
|-----|---|
| PEL | Long-term value: 2400 mg/m <sup>3</sup> , 1000 ppm  |
| REL | Long-term value: 590 mg/m <sup>3</sup> , 250 ppm  |
| TLV | Short-term value: 1187 mg/m <sup>3</sup> , 500 ppm<br>Long-term value: 594 mg/m <sup>3</sup> , 250 ppm<br>BEI |

**100-41-4 ethylbenzene**

|     |   |
|-----|---|
| PEL | Long-term value: 435 mg/m <sup>3</sup> , 100 ppm  |
| REL | Short-term value: 545 mg/m <sup>3</sup> , 125 ppm<br>Long-term value: 435 mg/m <sup>3</sup> , 100 ppm |
| TLV | Long-term value: 87 mg/m <sup>3</sup> , 20 ppm<br>BEI   |

**1330-20-7 xylene**

|     |  |
|-----|--|
| PEL | Long-term value: 435 mg/m <sup>3</sup> , 100 ppm   |
| REL | Short-term value: 655 mg/m <sup>3</sup> , 150 ppm<br>Long-term value: 435 mg/m <sup>3</sup> , 100 ppm        |
| TLV | Short-term value: 651 mg/m <sup>3</sup> , 150 ppm<br>Long-term value: 434 mg/m <sup>3</sup> , 100 ppm<br>BEI |

**64-17-5 ethanol**

|     |   |
|-----|---|
| PEL | Long-term value: 1900 mg/m <sup>3</sup> , 1000 ppm  |
| REL | Long-term value: 1900 mg/m <sup>3</sup> , 1000 ppm  |
| TLV | Short-term value: 1880 mg/m <sup>3</sup> , 1000 ppm |

**123-54-6 pentane-2,4-dione**

|     |   |
|-----|---|
| TLV | Long-term value: 102 mg/m <sup>3</sup> , 25 ppm<br>Skin |
|-----|---|

**67-56-1 methanol**

|     |  |
|-----|--|
| PEL | Long-term value: 260 mg/m <sup>3</sup> , 200 ppm   |
| REL | Short-term value: 325 mg/m <sup>3</sup> , 250 ppm<br>Long-term value: 260 mg/m <sup>3</sup> , 200 ppm<br>Skin      |
| TLV | Short-term value: 328 mg/m <sup>3</sup> , 250 ppm<br>Long-term value: 262 mg/m <sup>3</sup> , 200 ppm<br>Skin; BEI |

(Contd. on page 7)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 04/03/2020

Reviewed on 02/27/2020

**Trade name: L6.1.K1 LOW VOC HIGH GLOSS UHS POLYURETHANE**

(Contd. of page 6)

**· Ingredients with biological limit values:**

**1330-20-7 xylene**

BEI 1.5 g/g creatinine  
 Medium: urine  
 Time: end of shift  
 Parameter: Methylhippuric acids

**67-64-1 acetone**

BEI 50 mg/L  
 Medium: urine  
 Time: end of shift  
 Parameter: Acetone (nonspecific)

**100-41-4 ethylbenzene**

BEI 0.7 g/g creatinine  
 Medium: urine  
 Time: end of shift at end of workweek  
 Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)

-  
 Medium: end-exhaled air  
 Time: not critical  
 Parameter: Ethyl benzene (semi-quantitative)

**1330-20-7 xylene**

BEI 1.5 g/g creatinine  
 Medium: urine  
 Time: end of shift  
 Parameter: Methylhippuric acids

**67-56-1 methanol**

BEI 15 mg/L  
 Medium: urine  
 Time: end of shift  
 Parameter: Methanol (background, nonspecific)

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.  
 Immediately remove all soiled and contaminated clothing.  
 Wash hands before breaks and at the end of work.  
 Store protective clothing separately.  
 Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Contd. on page 8)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 04/03/2020

Reviewed on 02/27/2020

**Trade name: L6.1.K1 LOW VOC HIGH GLOSS UHS POLYURETHANE**

(Contd. of page 7)

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Tightly sealed goggles

## 9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

|                        |                 |
|------------------------|-----------------|
| <b>Form:</b>           | Liquid          |
| <b>Color:</b>          | Whitish         |
| <b>Odor:</b>           | Characteristic  |
| <b>Odor threshold:</b> | Not determined. |

- **pH-value:** Not determined (pH N/A in solvent coatings)

- **Change in condition**

|                                     |                              |
|-------------------------------------|------------------------------|
| <b>Melting point/Melting range:</b> | Undetermined.                |
| <b>Boiling point/Boiling range:</b> | 55.8-56.6 °C (132.4-69.9 °F) |

- **Flash point:** <-18 °C (<-0.4 °F)

- **Flammability (solid, gaseous):** Not applicable.

- **Ignition temperature:** 465 °C (869 °F)

- **Decomposition temperature:** Not determined.

- **Auto igniting:** Product is not selfigniting.

- **Danger of explosion:** Product is not explosive. However, formation of explosive air/ vapor mixtures are possible.

- **Explosion limits:**

|               |           |
|---------------|-----------|
| <b>Lower:</b> | 1.2 Vol % |
| <b>Upper:</b> | 7.5 Vol % |

- **Vapor pressure at 20 °C (68 °F):** 10.7 hPa (8 mm Hg)

- **Density at 20 °C (68 °F):** 1.1296 g/cm<sup>3</sup> (9.4265 lbs/gal)

- **Relative density** Not determined.

- **Vapor density** Not determined.

- **Evaporation rate** Not determined.

(Contd. on page 9)



# Safety Data Sheet

acc. to OSHA HCS

Printing date 04/03/2020

Reviewed on 02/27/2020

**Trade name: L6.1.K1 LOW VOC HIGH GLOSS UHS POLYURETHANE**

(Contd. of page 8)

- |   |  |
|---|--|
| <b>· Solubility in / Miscibility with Water:</b>  | Fully miscible.                            |
| <b>· Partition coefficient (n-octanol/water):</b> | Not determined.                            |
| <b>· Viscosity:</b>                               |  |
| <b>Dynamic:</b>                                   | Not determined.                            |
| <b>Kinematic:</b>                                 | Not determined.                            |
| <b>· Solvent content:</b>                         |  |
| <b>Organic solvents:</b>                          | 38.1-41.9 %                                |
| <b>VOC content:</b>                               | 29.13-32.98 %<br>272.7 g/l / 2.28 lb/gal   |
| <b>Solids content:</b>                            | 24.6 %                                     |
| <b>· Other information</b>                        | No further relevant information available. |

## 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

## 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**  
The product shows the following dangers according to internally approved calculation methods for preparations:  
Harmful  
Irritant
- **Carcinogenic categories**

**· IARC (International Agency for Research on Cancer)**

|           |   |    |
|-----------|---|----|
| 98-56-6   | 4-chloro-alpha, alpha, alpha-trifluorotoluene | 2B |
| 1330-20-7 | xylene  | 3  |
| 100-41-4  | ethylbenzene                                  | 2B |
| 1330-20-7 | xylene  | 3  |
| 64-17-5   | ethanol                                       | 1  |
| 67-63-0   | propan-2-ol                                   | 3  |

(Contd. on page 10)

USA

# Safety Data Sheet

acc. to OSHA HCS

Printing date 04/03/2020

Reviewed on 02/27/2020

**Trade name: L6.1.K1 LOW VOC HIGH GLOSS UHS POLYURETHANE**

(Contd. of page 9)

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

## 12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
 Water hazard class 2 (Self-assessment): hazardous for water  
 Do not allow product to reach ground water, water course or sewage system.  
 Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

## 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**  
 Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

## 14 Transport information

· **UN-Number**  
 · **DOT, IMDG, IATA** UN1263

· **UN proper shipping name**  
 · **DOT** Paint  
 · **IMDG, IATA** PAINT

· **Transport hazard class(es)**  
 · **DOT**



· **Class** 3 Flammable liquids

(Contd. on page 11)

USA

# Safety Data Sheet


acc. to OSHA HCS

Printing date 04/03/2020

Reviewed on 02/27/2020

**Trade name: L6.1.K1 LOW VOC HIGH GLOSS UHS POLYURETHANE**

(Contd. of page 10)

|   |   |
|---|---|
| · <b>Label</b>  | 3   |
| · <b>IMDG, IATA</b>   |   |
|  |   |
| · <b>Class</b>  | 3 Flammable liquids   |
| · <b>Label</b>  | 3   |
| · <b>Packing group</b>  | II  |
| · <b>DOT, IMDG, IATA</b>  | II  |
| · <b>Environmental hazards:</b>   | Not applicable.   |
| · <b>Special precautions for user</b>   | Warning: Flammable liquids  |
| · <b>Hazard identification number (Kemler code):</b>                              | 33  |
| · <b>EMS Number:</b>  | F-E, S-E  |
| · <b>Stowage Category</b>   | B   |
| · <b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b>  | Not applicable.   |
| · <b>Transport/Additional information:</b>  |   |
| · <b>DOT</b>  |   |
| · <b>Quantity limitations</b>   | On passenger aircraft/rail: 5 L<br>On cargo aircraft only: 60 L   |
| · <b>IMDG</b>   |   |
| · <b>Limited quantities (LQ)</b>  | 5L  |
| · <b>Excepted quantities (EQ)</b>   | Code: E2<br>Maximum net quantity per inner packaging: 30 ml<br>Maximum net quantity per outer packaging: 500 ml |
| · <b>UN "Model Regulation":</b>   | UN 1263 PAINT, 3, II  |

## 15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

**Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

**Section 313 (Specific toxic chemical listings):**

100-41-4 ethylbenzene

1330-20-7 xylene

67-56-1 methanol

122-99-6 2-Phenoxyethanol

67-63-0 propan-2-ol

**TSCA (Toxic Substances Control Act):**

98-56-6 4-chloro-alpha, alpha, alpha-trifluorotoluene

ACTIVE

123-86-4 n-butyl acetate

ACTIVE

67-64-1 acetone

ACTIVE

(Contd. on page 12)

USA

# Safety Data Sheet

acc. to OSHA HCS

Printing date 04/03/2020

Reviewed on 02/27/2020

**Trade name: L6.1.K1 LOW VOC HIGH GLOSS UHS POLYURETHANE**

(Contd. of page 11)

|            |  |        |
|------------|--|--------|
| 100-41-4   | ethylbenzene                                     | ACTIVE |
| 1330-20-7  | xylene   | ACTIVE |
| 41556-26-7 | bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate   | ACTIVE |
| 64-17-5    | ethanol  | ACTIVE |
| 123-54-6   | pentane-2,4-dione                                | ACTIVE |
| 67-56-1    | methanol   | ACTIVE |
| 82919-37-7 | methyl 1,2,2,6,6-pentamethyl-4-piperidylsebacate | ACTIVE |
| 122-99-6   | 2-Phenoxyethanol                                 | ACTIVE |
| 77-58-7    | dibutyltin dilaurate                             | ACTIVE |
| 67-63-0    | propan-2-ol                                      | ACTIVE |

· **Hazardous Air Pollutants**

|           |              |
|-----------|--------------|
| 100-41-4  | ethylbenzene |
| 1330-20-7 | xylene       |
| 67-56-1   | methanol     |

· **Proposition 65**

· **Chemicals known to cause cancer:**

|          |   |
|----------|---|
| 98-56-6  | 4-chloro-alpha, alpha, alpha-trifluorotoluene |
| 100-41-4 | ethylbenzene                                  |

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

|         |          |
|---------|----------|
| 64-17-5 | ethanol  |
| 67-56-1 | methanol |

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

|           |              |   |
|-----------|--------------|---|
| 1330-20-7 | xylene       | I |
| 67-64-1   | acetone      | I |
| 100-41-4  | ethylbenzene | D |
| 1330-20-7 | xylene       | I |

· **TLV (Threshold Limit Value established by ACGIH)**

|           |                      |    |
|-----------|----------------------|----|
| 1330-20-7 | xylene               | A4 |
| 67-64-1   | acetone              | A4 |
| 100-41-4  | ethylbenzene         | A3 |
| 1330-20-7 | xylene               | A4 |
| 64-17-5   | ethanol              | A3 |
| 77-58-7   | dibutyltin dilaurate | A4 |
| 67-63-0   | propan-2-ol          | A4 |

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 13)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 04/03/2020

Reviewed on 02/27/2020

Trade name: L6.1.K1 LOW VOC HIGH GLOSS UHS POLYURETHANE

(Contd. of page 12)

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**

4-chloro-alpha,alpha,alpha-trifluorotoluene  
xylene  
n-butyl acetate  
ethylbenzene  
bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate

· **Hazard statements**

Highly flammable liquid and vapor.  
Harmful if inhaled.  
Causes skin irritation.  
Causes serious eye irritation.  
May cause an allergic skin reaction.  
May cause cancer.  
May cause drowsiness or dizziness.  
May cause damage to the hearing organs through prolonged or repeated exposure.

· **Precautionary statements**

Obtain special instructions before use.  
Do not handle until all safety precautions have been read and understood.  
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
Ground/bond container and receiving equipment.  
Use explosion-proof electrical/ventilating/lighting/equipment.  
Use only non-sparking tools.  
Take precautionary measures against static discharge.  
Do not breathe dust/fume/gas/mist/vapors/spray.  
Wash thoroughly after handling.  
Use only outdoors or in a well-ventilated area.  
Contaminated work clothing must not be allowed out of the workplace.  
Wear protective gloves/protective clothing/eye protection/face protection.  
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
IF exposed or concerned: Get medical advice/attention.  
Call a poison center/doctor if you feel unwell.  
Specific treatment (see on this label).  
Get medical advice/attention if you feel unwell.  
Take off contaminated clothing and wash it before reuse.  
If skin irritation or rash occurs: Get medical advice/attention.  
If eye irritation persists: Get medical advice/attention.  
Wash contaminated clothing before reuse.  
In case of fire: Use for extinction: CO<sub>2</sub>, powder or water spray.  
Store in a well-ventilated place. Keep container tightly closed.  
Store in a well-ventilated place. Keep cool.  
Store locked up.  
Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 14)

USA

# Safety Data Sheet

acc. to OSHA HCS

Printing date 04/03/2020

Reviewed on 02/27/2020

**Trade name: L6.1.K1 LOW VOC HIGH GLOSS UHS POLYURETHANE**

(Contd. of page 13)

- **National regulations:**
- **Additional classification according to Decree on Hazardous Materials:**  
Carcinogenic hazardous material group III (dangerous).
- **Information about limitation of use:**  
Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.
- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** Environment protection department.
- **Contact:** Product Safety Dept.
- **Date of preparation / last revision** 04/03/2020 / 3
- **Abbreviations and acronyms:**  
 IMDG: International Maritime Code for Dangerous Goods  
 DOT: US Department of Transportation  
 IATA: International Air Transport Association  
 ACGIH: American Conference of Governmental Industrial Hygienists  
 EINECS: European Inventory of Existing Commercial Chemical Substances  
 ELINCS: European List of Notified Chemical Substances  
 CAS: Chemical Abstracts Service (division of the American Chemical Society)  
 NFPA: National Fire Protection Association (USA)  
 HMIS: Hazardous Materials Identification System (USA)  
 VOC: Volatile Organic Compounds (USA, EU)  
 PBT: Persistent, Bioaccumulative and Toxic  
 vPvB: very Persistent and very Bioaccumulative  
 NIOSH: National Institute for Occupational Safety  
 OSHA: Occupational Safety & Health  
 TLV: Threshold Limit Value  
 PEL: Permissible Exposure Limit  
 REL: Recommended Exposure Limit  
 BEI: Biological Exposure Limit  
 Flam. Liq. 2: Flammable liquids – Category 2  
 Acute Tox. 4: Acute toxicity – Category 4  
 Skin Irrit. 2: Skin corrosion/irritation – Category 2  
 Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A  
 Skin Sens. 1: Skin sensitisation – Category 1  
 Carc. 1A: Carcinogenicity – Category 1A  
 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3  
 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
- **\* Data compared to the previous version altered.**

USA