

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/29/2025

Reviewed on 07/29/2025

1 Identification

- **Product identifier**
- **Trade name:** 0D7.044 COARSE ALUMINUM (HV)
- **Article number:** 0D7.044
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
GlobalStar is a product of Lusid Technologies Inc.
4725 S Camp Kearns Road
Kearns, UT 84118
(801) 966-5300
info@lusidtechnologies.com
- **Information department:** Product safety department
- **Emergency telephone number:**
24 Hrs Emergency Contact:
INFOTRAC
1-800-535-5053

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flammable Liquids 3

H226 Flammable liquid and vapor.

Substances and mixtures which, in contact with water, emit flammable gases 1

H260 In contact with water releases flammable gases, which may ignite spontaneously.



GHS08 Health hazard

Germ Cell Mutagenicity 1B

H340 May cause genetic defects.

Carcinogenicity 1B

H350 May cause cancer.



GHS07

Skin Irritation 2

H315 Causes skin irritation.

Specific Target Organ Toxicity - Single Exposure 3

H336 May cause drowsiness or dizziness.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/29/2025

Reviewed on 07/29/2025

Trade name: 0D7.044 COARSE ALUMINUM (HV)

(Contd. of page 1)

· Hazard pictograms



GHS02 GHS07 GHS08

· Signal word Danger

· Hazard-determining components of labeling:

n-butyl acetate

Naphtha (petroleum), hydrotreated heavy

Solvent naphtha (petroleum), light arom.

ethylbenzene

· Hazard statements

*Flammable liquid and vapor.**In contact with water releases flammable gases, which may ignite spontaneously.**Causes skin irritation.**May cause genetic defects.**May cause cancer.**May cause drowsiness or dizziness.*

· Precautionary statements

*Obtain special instructions before use.**Do not handle until all safety precautions have been read and understood.**Keep away from heat/sparks/open flames/hot surfaces. - No smoking.**Do not allow contact with water.**Handle under inert gas. Protect from moisture.**Ground/bond container and receiving equipment.**Use explosion-proof electrical/ventilating/lighting/equipment.**Use only non-sparking tools.**Take precautionary measures against static discharge.**Avoid breathing dust/fume/gas/mist/vapors/spray**Wash thoroughly after handling.**Use only outdoors or in a well-ventilated area.**Wear protective gloves/protective clothing/eye protection/face protection.**If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.**IF INHALED: Remove person to fresh air and keep comfortable for breathing.**IF exposed or concerned: Get medical advice/attention.**Call a poison center/doctor if you feel unwell.**Specific treatment (see on this label).**Take off contaminated clothing and wash it before reuse.**If skin irritation occurs: Get medical advice/attention.**Brush off loose particles from skin. Immerse in cool water/wrap in wet bandages.**In case of fire: Use CO₂, sand, extinguishing powder to extinguish.**Store in a dry place. Store in a closed container.**Store in a well-ventilated place. Keep container tightly closed.**Store in a well-ventilated place. Keep cool.**Store locked up.**Dispose of contents/container in accordance with local/regional/national/international regulations.*

(Contd. on page 3)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/29/2025

Reviewed on 07/29/2025

Trade name: 0D7.044 COARSE ALUMINUM (HV)

(Contd. of page 2)

- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



Health = 1
Fire = 3
Reactivity = 2

The substance demonstrates unusual reactivity with water.

- **HMIS-ratings (scale 0 - 4)**

HEALTH	*1
FIRE	3
REACTIVITY	2

Health = *1
Fire = 3
Reactivity = 2

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

123-86-4	<i>n</i> -butyl acetate	25-50%
1330-20-7	xylene	10-25%
7429-90-5	aluminium powder (stabilised)	2.5-10%
110-43-0	heptan-2-one	2.5-10%
64742-48-9	Naphtha (petroleum), hydrotreated heavy	2.5-10%
64742-95-6	Solvent naphtha (petroleum), light arom.	≤2.5%
111-76-2	2-butoxyethanol	≤2.5%
100-41-4	ethylbenzene	≤2.5%

4 First-aid measures

- **Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

USA

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/29/2025

Reviewed on 07/29/2025

Trade name: 0D7.044 COARSE ALUMINUM (HV)

(Contd. of page 3)

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
 - Extinguishing powder. Do not use water.
 - CO2. Do not use water.
 - Sand. Do not use water.
 - Special powder for metal fires. Do not use water.
 - CO2, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
 - Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
 - Dilute with plenty of water.
 - Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
 - Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
 - Dispose contaminated material as waste according to section 13.
 - Ensure adequate ventilation.
 - Do not flush with water or aqueous cleansing agents
- **Reference to other sections**
 - See Section 7 for information on safe handling.
 - See Section 8 for information on personal protection equipment.
 - See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· PAC-1:		
123-86-4	<i>n</i> -butyl acetate	5 ppm
1330-20-7	xylene	130 ppm
110-43-0	heptan-2-one	150 ppm
64742-48-9	Naphtha (petroleum), hydrotreated heavy	350 mg/m ³
111-76-2	2-butoxyethanol	60 ppm
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
107-98-2	1-methoxy-2-propanol	100 ppm
100-41-4	ethylbenzene	33 ppm
71-36-3	butan-1-ol	60 ppm
64-17-5	ethanol	1,800 ppm
7447-41-8	lithium chloride	2.3 mg/m ³
67-56-1	methanol	530 ppm
67-63-0	propan-2-ol	400 ppm

· PAC-2:		
123-86-4	<i>n</i> -butyl acetate	200 ppm
1330-20-7	xylene	920* ppm

(Contd. on page 5)

USA

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/29/2025

Reviewed on 07/29/2025

Trade name: 0D7.044 COARSE ALUMINUM (HV)

(Contd. of page 4)

110-43-0	heptan-2-one	670 ppm
64742-48-9	Naphtha (petroleum), hydrotreated heavy	1,800 mg/m ³
111-76-2	2-butoxyethanol	120 ppm
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm
107-98-2	1-methoxy-2-propanol	160 ppm
100-41-4	ethylbenzene	1100 ppm
71-36-3	butan-1-ol	800 ppm
64-17-5	ethanol	3300* ppm
7447-41-8	lithium chloride	17 mg/m3
67-56-1	methanol	2100 ppm
67-63-0	propan-2-ol	2000* ppm

· PAC-3:

123-86-4	n-butyl acetate	3000* ppm
1330-20-7	xylene	2500* ppm
110-43-0	heptan-2-one	4000* ppm
64742-48-9	Naphtha (petroleum), hydrotreated heavy	40,000 mg/m ³
111-76-2	2-butoxyethanol	700 ppm
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm
107-98-2	1-methoxy-2-propanol	660 ppm
100-41-4	ethylbenzene	1800 ppm
71-36-3	butan-1-ol	8000** ppm
64-17-5	ethanol	15000* ppm
7447-41-8	lithium chloride	100 mg/m3
67-56-1	methanol	7200 ppm
67-63-0	propan-2-ol	12000** ppm

7 Handling and storage

· Handling:

· Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

· Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by storerooms and receptacles: No special requirements.

· Information about storage in one common storage facility: Not required.

· Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

(Contd. on page 6)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/29/2025

Reviewed on 07/29/2025

Trade name: 0D7.044 COARSE ALUMINUM (HV)

(Contd. of page 5)

- **Specific end use(s)** No further relevant information available.

* 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see section 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
At this time, the other constituents have no known exposure limits.

123-86-4 n-butyl acetate	
PEL	Long-term value: 710 mg/m ³ , 150 ppm
REL	Short-term value: 950 mg/m ³ , 200 ppm Long-term value: 710 mg/m ³ , 150 ppm
TLV	Short-term value: 712 mg/m ³ , 150 ppm Long-term value: 238 mg/m ³ , 50 ppm
1330-20-7 xylene	
PEL	Long-term value: 435 mg/m ³ , 100 ppm
REL	Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV	Long-term value: 20 ppm BEI, A4
110-43-0 heptan-2-one	
PEL	Long-term value: 465 mg/m ³ , 100 ppm
REL	Long-term value: 465 mg/m ³ , 100 ppm
TLV	Long-term value: 50 ppm
111-76-2 2-butoxyethanol	
PEL	Long-term value: 240 mg/m ³ , 50 ppm Skin
REL	Long-term value: 24 mg/m ³ , 5 ppm Skin
TLV	Long-term value: 97 mg/m ³ , 20 ppm BEI, A3
100-41-4 ethylbenzene	
PEL	Long-term value: 435 mg/m ³ , 100 ppm
REL	Short-term value: 545 mg/m ³ , 125 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV	Long-term value: 20 ppm OTO, BEI, A3
• Ingredients with biological limit values:	
1330-20-7 xylene	
BEI	0.3 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids

(Contd. on page 7)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/29/2025

Reviewed on 07/29/2025

Trade name: 0D7.044 COARSE ALUMINUM (HV)

(Contd. of page 6)

111-76-2 2-butoxyethanol

BEI 200 mg/g creatinine

Medium: urine

Time: end of shift

Parameter: Butoxyacetic acid (BAA) (with hydrolysis)

100-41-4 ethylbenzene

BEI 0.15 g/g creatinine

Medium: urine

Time: end of shift

Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific)

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

USA

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/29/2025

Reviewed on 07/29/2025

Trade name: 0D7.044 COARSE ALUMINUM (HV)

(Contd. of page 7)

9 Physical and chemical properties

· Information on basic physical and chemical properties	
· General Information	
· Appearance:	
Form:	Liquid
Color:	According to product specification
· Odor:	Characteristic
· Odor threshold:	Not determined.
· pH-value:	Not determined (pH N/A in solvent coatings)
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	124-128 °C (255.2-262.4 °F)
· Flash point:	27 °C (80.6 °F)
· Flammability:	Flammable. Contact with water liberates extremely flammable gases.
· Auto igniting:	370 °C (698 °F)
· Decomposition temperature:	Not determined.
· Ignition temperature:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits:	
Lower:	1.1 Vol %
Upper:	7.5 Vol %
· Vapor pressure at 20 °C (68 °F):	10.7 hPa (8 mm Hg)
· Vapor pressure at 50 °C (122 °F):	55 hPa (41.3 mm Hg)
· Density at 20 °C (68 °F):	1.0512 g/cm³ (8.7723 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	Fully miscible.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	59.5 %
VOC content:	59.53 % 500.3 g/l / 4.17 lb/gal
· Solids content:	52.4 %
· Other information	No further relevant information available.

USA

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/29/2025

Reviewed on 07/29/2025

Trade name: 0D7.044 COARSE ALUMINUM (HV)

(Contd. of page 8)

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** Contact with water releases flammable gases.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**

- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

1330-20-7 xylene

Oral	LD50	4,300 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)

- **Primary irritant effect:**

- **on the skin:** Irritant to skin and mucous membranes.

- **on the eye:** No irritating effect.

- **Sensitization:** No sensitizing effects known.

- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

The product can cause inheritable damage.

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

1330-20-7	xylene	3
111-76-2	2-butoxyethanol	3
100-41-4	ethylbenzene	2B
64-17-5	ethanol	1
67-63-0	propan-2-ol	3

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**

- **Aquatic toxicity:** No further relevant information available.

- **Persistence and degradability:** No further relevant information available.

- **Behavior in environmental systems:**

- **Bioaccumulative potential:** No further relevant information available.

- **Mobility in soil:** No further relevant information available.

(Contd. on page 10)
USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/29/2025

Reviewed on 07/29/2025

Trade name: 0D7.044 COARSE ALUMINUM (HV)

(Contd. of page 9)

- **Additional ecological information:**

- **General notes:**

Water hazard class 3 (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**

- **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- **Uncleaned packagings:**

- **Recommendation:** Disposal must be made according to official regulations.

- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport information

- **UN-Number**

- **DOT, IMDG, IATA**

UN1263

- **UN proper shipping name**

- **DOT**

Paint

- **IMDG, IATA**

PAINT

- **Transport hazard class(es)**

- **DOT**



- **Class**

- **Label**

3 Flammable liquids

3

- **IMDG, IATA**



- **Class**

- **Label**

3 Flammable liquids

3

- **Packing group**

- **DOT, IMDG, IATA**

III

- **Environmental hazards:**

Not applicable.

- **Special precautions for user**

Warning: Flammable liquids

(Contd. on page 11)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/29/2025

Reviewed on 07/29/2025

Trade name: 0D7.044 COARSE ALUMINUM (HV)

(Contd. of page 10)

· Hazard identification number (Kemler code): 30	
· EMS Number:	<u>F-E,S-E</u>
· Stowage Category	A
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	
	Not applicable.
· Transport/Additional information:	
· DOT	
· Quantity limitations	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, III

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture	
· Sara	
· Section 355 (extremely hazardous substances):	
	None of the ingredients is listed.
· Section 313 (Specific toxic chemical listings):	
1330-20-7	xylene
111-76-2	2-butoxyethanol
100-41-4	ethylbenzene
71-36-3	butan-1-ol
67-56-1	methanol
67-63-0	propan-2-ol
· TSCA (Toxic Substances Control Act):	
123-86-4	n-butyl acetate
1330-20-7	xylene
110-43-0	heptan-2-one
9004-36-8	Cellulose Acetate Butyrate
64742-48-9	Naphtha (petroleum), hydrotreated heavy
64742-95-6	Solvent naphtha (petroleum), light arom.
4394-85-8	4-morpholinecarbaldehyde
111-76-2	2-butoxyethanol
108-65-6	2-methoxy-1-methylethyl acetate
107-98-2	1-methoxy-2-propanol
100-41-4	ethylbenzene
71-36-3	butan-1-ol
64-17-5	ethanol
7447-41-8	lithium chloride

(Contd. on page 12)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/29/2025

Reviewed on 07/29/2025

Trade name: 0D7.044 COARSE ALUMINUM (HV)

(Contd. of page 11)

67-56-1	methanol	ACTIVE
67-63-0	propan-2-ol	ACTIVE

· Hazardous Air Pollutants

1330-20-7	xylene
100-41-4	ethylbenzene
67-56-1	methanol

· Proposition 65

· Chemicals known to cause cancer:

100-41-4	ethylbenzene
----------	--------------

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.	
------------------------------------	--

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.	
------------------------------------	--

· Chemicals known to cause developmental toxicity:

64-17-5	ethanol
67-56-1	methanol

· Carcinogenic categories

· EPA (Environmental Protection Agency)

1330-20-7	xylene	I
111-76-2	2-butoxyethanol	NL
100-41-4	ethylbenzene	D
71-36-3	butan-1-ol	D

· TLV (Threshold Limit Value)

1330-20-7	xylene	A4
111-76-2	2-butoxyethanol	A3
100-41-4	ethylbenzene	A3
64-17-5	ethanol	A3
67-63-0	propan-2-ol	A4

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.	
------------------------------------	--

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



GHS02 GHS07 GHS08

· Signal word Danger

· Hazard-determining components of labeling:

n-butyl acetate

Naphtha (petroleum), hydrotreated heavy

Solvent naphtha (petroleum), light arom.

ethylbenzene

(Contd. on page 13)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/29/2025

Reviewed on 07/29/2025

Trade name: 0D7.044 COARSE ALUMINUM (HV)

(Contd. of page 12)

· Hazard statements

Flammable liquid and vapor.

In contact with water releases flammable gases, which may ignite spontaneously.

Causes skin irritation.

May cause genetic defects.

May cause cancer.

May cause drowsiness or dizziness.

· Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Do not allow contact with water.

Handle under inert gas. Protect from moisture.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF exposed or concerned: Get medical advice/attention.

Call a poison center/doctor if you feel unwell.

Specific treatment (see on this label).

Take off contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

Brush off loose particles from skin. Immerse in cool water/wrap in wet bandages.

In case of fire: Use CO₂, sand, extinguishing powder to extinguish.

Store in a dry place. Store in a closed container.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· National regulations:

· Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Environment protection department.

· Contact: Product Safety Dept.

· Date of preparation / last revision 07/29/2025 / 2

· Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

(Contd. on page 14)

USA

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/29/2025

Reviewed on 07/29/2025

Trade name: 0D7.044 COARSE ALUMINUM (HV)

(Contd. of page 13)

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flammable Liquids 3: Flammable liquids – Category 3

Substances and mixtures which, in contact with water, emit flammable gases 1: Substances and mixtures which in contact with water emit flammable gases – Category 1

Skin Irritation 2: Skin corrosion/irritation – Category 2

Germ Cell Mutagenicity 1B: Germ cell mutagenicity – Category 1B

Carcinogenicity 1B: Carcinogenicity – Category 1B

Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3

* Data compared to the previous version altered.

USA