

## Safety Data Sheet acc. to OSHA HCS

Printing date 08/11/2025

Reviewed on 08/11/2025

### 1 Identification

- **Product identifier**
- **Trade name:** 135B 135 SERIES BINDER
- **Article number:** 135B
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
 NorthStar is a product of Lusid Technologies Inc  
 4725 S Camp Kearns Road  
 Kearns, UT 84118  
 (801) 966-5300  
 info@lusidtechnologies.com
- **Information department:** Product safety department
- **Emergency telephone number:**  
 24 Hrs Emergency Contact:  
 INFOTRAC  
 1-800-535-5053

### 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flammable Liquids 2

H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Germ Cell Mutagenicity 1B

H340 May cause genetic defects.

Carcinogenicity 1B

H350 May cause cancer.



GHS07

Skin Irritation 2

H315 Causes skin irritation.

Eye Irritation 2A

H319 Causes serious eye irritation.

Sensitization - Skin 1

H317 May cause an allergic skin reaction.

Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 08/11/2025

Reviewed on 08/11/2025

Trade name: 135B 135 SERIES BINDER

(Contd. of page 1)

· **Hazard pictograms**

GHS02 GHS07 GHS08

· **Signal word** Danger· **Hazard-determining components of labeling:**

4-chloro-alpha,alpha,alpha-trifluorotoluene  
acetone  
Solvent naphtha (petroleum), light arom.  
Stoddard solvent  
2-butanone oxime

· **Hazard statements**

Highly flammable liquid and vapor.  
Causes skin irritation.  
Causes serious eye irritation.  
May cause an allergic skin reaction.  
May cause genetic defects.  
May cause cancer.  
May cause drowsiness or dizziness.

· **Precautionary statements**

Obtain special instructions before use.  
Do not handle until all safety precautions have been read and understood.  
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
Ground/bond container and receiving equipment.  
Use explosion-proof electrical/ventilating/lighting/equipment.  
Use only non-sparking tools.  
Take precautionary measures against static discharge.  
Avoid breathing dust/fume/gas/mist/vapors/spray  
Wash thoroughly after handling.  
Use only outdoors or in a well-ventilated area.  
Contaminated work clothing must not be allowed out of the workplace.  
Wear protective gloves/protective clothing/eye protection/face protection.  
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
If exposed or concerned: Get medical advice/attention.  
Call a poison center/doctor if you feel unwell.  
Specific treatment (see on this label).  
Take off contaminated clothing and wash it before reuse.  
If skin irritation or rash occurs: Get medical advice/attention.  
If eye irritation persists: Get medical advice/attention.  
Wash contaminated clothing before reuse.  
In case of fire: Use CO2, powder or water spray to extinguish.  
Store in a well-ventilated place. Keep container tightly closed.  
Store in a well-ventilated place. Keep cool.  
Store locked up.  
Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 3)

USA

# Safety Data Sheet

acc. to OSHA HCS

Printing date 08/11/2025

Reviewed on 08/11/2025

Trade name: 135B 135 SERIES BINDER

(Contd. of page 2)

- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



Health = 2  
Fire = 3  
Reactivity = 0

- **HMIS-ratings (scale 0 - 4)**



Health = \*2  
Fire = 3  
Reactivity = 0

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

## 3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

### · **Dangerous components:**

67-64-1	acetone	10-25%
1330-20-7	xylene	10-25%
98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene	10-25%
64742-49-0	Naphtha (petroleum), hydrotreated light	2.5-10%
107-87-9	pentan-2-one	≤2.5%
110-43-0	heptan-2-one	≤2.5%
64742-95-6	Solvent naphtha (petroleum), light arom.	≤2.5%
96-29-7	2-butanone oxime	≤2.5%
8052-41-3	Stoddard solvent	≤2.5%
136-52-7	cobalt(II) 2-ethylhexanoate	≤2.5%

## 4 First-aid measures

- **Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:**  
Supply fresh air and to be sure call for a doctor.  
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**  
No further relevant information available.

(Contd. on page 4)

USA

# Safety Data Sheet

acc. to OSHA HCS

Printing date 08/11/2025

Reviewed on 08/11/2025

Trade name: 135B 135 SERIES BINDER

(Contd. of page 3)

- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

## 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

## 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**  
Dilute with plenty of water.  
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to section 13.  
Ensure adequate ventilation.
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

### · PAC-1:

67-64-1	acetone	200 ppm
1330-20-7	xylene	130 ppm
107-87-9	pentan-2-one	150 ppm
110-43-0	heptan-2-one	150 ppm
95-63-6	1,2,4-trimethylbenzene	140 ppm
96-29-7	2-butanone oxime	8.0 mg/m <sup>3</sup>
8052-41-3	Stoddard solvent	1700 mg/m <sup>3</sup>
77-58-7	dibutyltin dilaurate	1.1 mg/m <sup>3</sup>
112-34-5	2-(2-butoxyethoxy)ethanol	200 mg/m <sup>3</sup>
122-99-6	2-phenoxyethanol	1.5 ppm
100-41-4	ethylbenzene	33 ppm
149-57-5	2-ethylhexanoic acid	15 mg/m <sup>3</sup>

### · PAC-2:

67-64-1	acetone	3200* ppm
1330-20-7	xylene	920* ppm
107-87-9	pentan-2-one	830 ppm
110-43-0	heptan-2-one	670 ppm
95-63-6	1,2,4-trimethylbenzene	360 ppm

(Contd. on page 5)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 08/11/2025

Reviewed on 08/11/2025

Trade name: 135B 135 SERIES BINDER

(Contd. of page 4)

96-29-7	2-butanone oxime	150 mg/m <sup>3</sup>
8052-41-3	Stoddard solvent	1800 mg/m <sup>3</sup>
77-58-7	dibutyltin dilaurate	3.8 mg/m <sup>3</sup>
112-34-5	2-(2-butoxyethoxy)ethanol	220 mg/m <sup>3</sup>
122-99-6	2-phenoxyethanol	16 ppm
100-41-4	ethylbenzene	1100 ppm
149-57-5	2-ethylhexanoic acid	99 mg/m <sup>3</sup>

· **PAC-3:**

67-64-1	acetone	5700* ppm
1330-20-7	xylene	2500* ppm
107-87-9	pentan-2-one	5000* ppm
110-43-0	heptan-2-one	4000* ppm
95-63-6	1,2,4-trimethylbenzene	470 ppm
96-29-7	2-butanone oxime	880 mg/m <sup>3</sup>
8052-41-3	Stoddard solvent	20000 mg/m <sup>3</sup>
77-58-7	dibutyltin dilaurate	23 mg/m <sup>3</sup>
112-34-5	2-(2-butoxyethoxy)ethanol	1300 mg/m <sup>3</sup>
122-99-6	2-phenoxyethanol	97 ppm
100-41-4	ethylbenzene	1800 ppm
149-57-5	2-ethylhexanoic acid	590 mg/m <sup>3</sup>

## 7 Handling and storage

· **Handling:**· **Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· **Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

· **Conditions for safe storage, including any incompatibilities**· **Storage:**· **Requirements to be met by storerooms and receptacles:** Store in a cool location.· **Information about storage in one common storage facility:** Not required.· **Further information about storage conditions:**

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· **Specific end use(s)** No further relevant information available.

## 8 Exposure controls/personal protection

· **Additional information about design of technical systems:** No further data; see section 7.

(Contd. on page 6)

USA

# Safety Data Sheet

acc. to OSHA HCS

Printing date 08/11/2025

Reviewed on 08/11/2025

Trade name: 135B 135 SERIES BINDER

(Contd. of page 5)

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

**67-64-1 acetone**

PEL	Long-term value: 2400 mg/m <sup>3</sup> , 1000 ppm
REL	Long-term value: 590 mg/m <sup>3</sup> , 250 ppm
TLV	Short-term value: 1187 mg/m <sup>3</sup> , 500 ppm Long-term value: 594 mg/m <sup>3</sup> , 250 ppm A4, BEI

**1330-20-7 xylene**

PEL	Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
REL	Short-term value: 655 mg/m <sup>3</sup> , 150 ppm Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
TLV	Long-term value: 20 ppm BEI, A4

**64742-49-0 Naphtha (petroleum), hydrotreated light**

TLV	Long-term value: 100 ppm Skin, A3
-----	--------------------------------------

**107-87-9 pentan-2-one**

PEL	Long-term value: 700 mg/m <sup>3</sup> , 200 ppm
REL	Long-term value: 530 mg/m <sup>3</sup> , 150 ppm
TLV	Short-term value: 529 mg/m <sup>3</sup> , 150 ppm

**110-43-0 heptan-2-one**

PEL	Long-term value: 465 mg/m <sup>3</sup> , 100 ppm
REL	Long-term value: 465 mg/m <sup>3</sup> , 100 ppm
TLV	Long-term value: 50 ppm

**96-29-7 2-butanone oxime**

WEEL	Long-term value: 10 ppm DSEN
------	---------------------------------

**8052-41-3 Stoddard solvent**

PEL	Long-term value: 2900 mg/m <sup>3</sup> , 500 ppm
REL	Long-term value: 350 mg/m <sup>3</sup> Ceiling limit value: 1800* mg/m <sup>3</sup> *15-min
TLV	Long-term value: 525 mg/m <sup>3</sup> , 100 ppm

**136-52-7 cobalt(II) 2-ethylhexanoate**

TLV	Long-term value: 0.02* mg/m <sup>3</sup> as Co, A3; *inhalable; DSEN; RSEN; BEI
-----	--

· **Ingredients with biological limit values:**

**67-64-1 acetone**

BEI	25 mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific)
-----	--

(Contd. on page 7)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 08/11/2025

Reviewed on 08/11/2025

Trade name: 135B 135 SERIES BINDER

(Contd. of page 6)

**1330-20-7 xylene**

BEI 0.3 g/g creatinine  
 Medium: urine  
 Time: end of shift  
 Parameter: Methylhippuric acids

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**  
 Keep away from foodstuffs, beverages and feed.  
 Immediately remove all soiled and contaminated clothing.  
 Wash hands before breaks and at the end of work.  
 Store protective clothing separately.  
 Avoid contact with the eyes and skin.
- **Breathing equipment:**  
 In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**  
 The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**  
 The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:**



Tightly sealed goggles

## 9 Physical and chemical properties

- **Information on basic physical and chemical properties**
- **General Information**
- **Appearance:**

Form:	Liquid
Color:	Brown
Odor:	Characteristic
Odor threshold:	Not determined.

(Contd. on page 8)



# Safety Data Sheet

acc. to OSHA HCS

Printing date 08/11/2025

Reviewed on 08/11/2025

Trade name: 135B 135 SERIES BINDER

(Contd. of page 7)

· <b>pH-value:</b>	Not determined (pH N/A in solvent coatings)
· <b>Change in condition</b>	
<b>Melting point/Melting range:</b>	Undetermined.
<b>Boiling point/Boiling range:</b>	55.8-56.6 °C (132.4-133.9 °F)
· <b>Flash point:</b>	<-18 °C (<-0.4 °F)
· <b>Flammability:</b>	Highly flammable.
· <b>Auto igniting:</b>	465 °C (869 °F)
· <b>Decomposition temperature:</b>	Not determined.
· <b>Ignition temperature:</b>	Product is not selfigniting.
· <b>Danger of explosion:</b>	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· <b>Explosion limits:</b>	
<b>Lower:</b>	1.1 Vol %
<b>Upper:</b>	13 Vol %
· <b>Vapor pressure at 20 °C (68 °F):</b>	233 hPa (174.8 mm Hg)
· <b>Vapor pressure at 50 °C (122 °F):</b>	800 hPa (600 mm Hg)
· <b>Density at 20 °C (68 °F):</b>	0.9969 g/cm <sup>3</sup> (8.3191 lbs/gal)
· <b>Relative density</b>	Not determined.
· <b>Vapor density</b>	Not determined.
· <b>Evaporation rate</b>	Not determined.
· <b>Solubility in / Miscibility with Water:</b>	Fully miscible.
· <b>Partition coefficient (n-octanol/water):</b>	Not determined.
· <b>Viscosity:</b>	
<b>Dynamic:</b>	Not determined.
<b>Kinematic:</b>	Not determined.
· <b>Solvent content:</b>	
<b>Organic solvents:</b>	48.1 %
<b>VOC content:</b>	27.80 %
	410.7 g/l / 3.43 lb/gal
<b>Solids content:</b>	40.6 %
· <b>Other information</b>	No further relevant information available.

## 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.

(Contd. on page 9)

USA



# Safety Data Sheet

acc. to OSHA HCS

Printing date 08/11/2025

Reviewed on 08/11/2025

Trade name: 135B 135 SERIES BINDER

(Contd. of page 8)

· **Hazardous decomposition products:** No dangerous decomposition products known.

## 11 Toxicological information

· **Information on toxicological effects**· **Acute toxicity:**· **LD/LC50 values that are relevant for classification:****1330-20-7 xylene**

Oral LD50 4,300 mg/kg (rat)

Dermal LD50 2,000 mg/kg (rabbit)

· **Primary irritant effect:**· **on the skin:** Irritant to skin and mucous membranes.· **on the eye:** Irritating effect.· **Sensitization:** Sensitization possible through skin contact.· **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

The product can cause inheritable damage.

· **Carcinogenic categories**· **IARC (International Agency for Research on Cancer)**

1330-20-7	xylene	3
98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene	2B
136-52-7	cobalt(II) 2-ethylhexanoate	2A
100-41-4	ethylbenzene	2B

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

## 12 Ecological information

· **Toxicity**· **Aquatic toxicity:** No further relevant information available.· **Persistence and degradability** No further relevant information available.· **Behavior in environmental systems:**· **Bioaccumulative potential** No further relevant information available.· **Mobility in soil** No further relevant information available.· **Additional ecological information:**· **General notes:**

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

· **Results of PBT and vPvB assessment**· **PBT:** Not applicable.· **vPvB:** Not applicable.

(Contd. on page 10)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 08/11/2025

Reviewed on 08/11/2025

Trade name: 135B 135 SERIES BINDER



(Contd. of page 9)

· **Other adverse effects** No further relevant information available.

## 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**  
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

## 14 Transport information

- |   |                            |
|---|----------------------------|
| · <b>UN-Number</b>  | UN1263                     |
| · <b>DOT, IMDG, IATA</b>  |                            |
| · <b>UN proper shipping name</b>  | Paint                      |
| · <b>DOT</b>  | PAINT                      |
| · <b>IMDG, IATA</b>   |                            |
| · <b>Transport hazard class(es)</b>   |                            |
| · <b>DOT</b>  |                            |
|  |                            |
| · <b>Class</b>  | 3 Flammable liquids        |
| · <b>Label</b>  | 3                          |
| · <b>IMDG, IATA</b>   |                            |
|  |                            |
| · <b>Class</b>  | 3 Flammable liquids        |
| · <b>Label</b>  | 3                          |
| · <b>Packing group</b>  | II                         |
| · <b>DOT, IMDG, IATA</b>  |                            |
| · <b>Environmental hazards:</b>   |                            |
| · <b>Marine pollutant:</b>  | No                         |
| · <b>Special precautions for user</b>   | Warning: Flammable liquids |
| · <b>Hazard identification number (Kemler code):</b>                                | 33                         |
| · <b>EMS Number:</b>  | F-E, S-E                   |
| · <b>Stowage Category</b>   | B                          |
| · <b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b>    | Not applicable.            |

(Contd. on page 11)

USA

# Safety Data Sheet

acc. to OSHA HCS

Printing date 08/11/2025

Reviewed on 08/11/2025

Trade name: 135B 135 SERIES BINDER

(Contd. of page 10)

· **Transport/Additional information:**

· **DOT**

· **Quantity limitations**

On passenger aircraft/rail: 5 L

On cargo aircraft only: 60 L

· **IMDG**

· **Limited quantities (LQ)**

5L

· **Excepted quantities (EQ)**

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

· **UN "Model Regulation":**

UN 1263 PAINT, 3, II

## 15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

1330-20-7 xylene

95-63-6 1,2,4-trimethylbenzene

136-52-7 cobalt(II) 2-ethylhexanoate

112-34-5 2-(2-butoxyethoxy)ethanol

122-99-6 2-phenoxyethanol

100-41-4 ethylbenzene

· **TSCA (Toxic Substances Control Act):**

67-64-1 acetone

ACTIVE

1330-20-7 xylene

ACTIVE

98-56-6 4-chloro-alpha,alpha,alpha-trifluorotoluene

ACTIVE

107-87-9 pentan-2-one

ACTIVE

110-43-0 heptan-2-one

ACTIVE

64742-95-6 Solvent naphtha (petroleum), light arom.

ACTIVE

95-63-6 1,2,4-trimethylbenzene

ACTIVE

96-29-7 2-butanone oxime

ACTIVE

8052-41-3 Stoddard solvent

ACTIVE

136-52-7 cobalt(II) 2-ethylhexanoate

ACTIVE

77-58-7 dibutyltin dilaurate

ACTIVE

112-34-5 2-(2-butoxyethoxy)ethanol

ACTIVE

122-99-6 2-phenoxyethanol

ACTIVE

100-41-4 ethylbenzene

ACTIVE

149-57-5 2-ethylhexanoic acid

ACTIVE

· **Hazardous Air Pollutants**

1330-20-7 xylene

136-52-7 cobalt(II) 2-ethylhexanoate

(Contd. on page 12)

USA

# Safety Data Sheet

acc. to OSHA HCS

Printing date 08/11/2025

Reviewed on 08/11/2025

Trade name: 135B 135 SERIES BINDER

(Contd. of page 11)

100-41-4 ethylbenzene

· **Proposition 65**· **Chemicals known to cause cancer:**

98-56-6 4-chloro-alpha,alpha,alpha-trifluorotoluene

100-41-4 ethylbenzene

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenic categories**· **EPA (Environmental Protection Agency)**

67-64-1 acetone

I

1330-20-7 xylene

I

95-63-6 1,2,4-trimethylbenzene

II

100-41-4 ethylbenzene

D

· **TLV (Threshold Limit Value)**

67-64-1 acetone

A4

1330-20-7 xylene

A4

77-58-7 dibutyltin dilaurate

A4

100-41-4 ethylbenzene

A3

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**

GHS02 GHS07 GHS08

· **Signal word Danger**· **Hazard-determining components of labeling:**

4-chloro-alpha,alpha,alpha-trifluorotoluene

acetone

Solvent naphtha (petroleum), light arom.

Stoddard solvent

2-butanone oxime

· **Hazard statements**

Highly flammable liquid and vapor.

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

May cause genetic defects.

May cause cancer.

(Contd. on page 13)

USA

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 08/11/2025

Reviewed on 08/11/2025

**Trade name: 135B 135 SERIES BINDER**

(Contd. of page 12)

*May cause drowsiness or dizziness.***Precautionary statements***Obtain special instructions before use.**Do not handle until all safety precautions have been read and understood.**Keep away from heat/sparks/open flames/hot surfaces. - No smoking.**Ground/bond container and receiving equipment.**Use explosion-proof electrical/ventilating/lighting/equipment.**Use only non-sparking tools.**Take precautionary measures against static discharge.**Avoid breathing dust/fume/gas/mist/vapors/spray**Wash thoroughly after handling.**Use only outdoors or in a well-ventilated area.**Contaminated work clothing must not be allowed out of the workplace.**Wear protective gloves/protective clothing/eye protection/face protection.**If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.**IF INHALED: Remove person to fresh air and keep comfortable for breathing.**If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.**IF exposed or concerned: Get medical advice/attention.**Call a poison center/doctor if you feel unwell.**Specific treatment (see on this label).**Take off contaminated clothing and wash it before reuse.**If skin irritation or rash occurs: Get medical advice/attention.**If eye irritation persists: Get medical advice/attention.**Wash contaminated clothing before reuse.**In case of fire: Use CO2, powder or water spray to extinguish.**Store in a well-ventilated place. Keep container tightly closed.**Store in a well-ventilated place. Keep cool.**Store locked up.**Dispose of contents/container in accordance with local/regional/national/international regulations.***National regulations:****Additional classification according to Decree on Hazardous Materials:***Carcinogenic hazardous material group III (dangerous).***Information about limitation of use:***Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.**Chemical safety assessment: A Chemical Safety Assessment has not been carried out.***16 Other information***This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.**Department issuing SDS: Environment protection department.**Contact: Product Safety Dept.**Date of preparation / last revision 08/11/2025 / 5***Abbreviations and acronyms:***IMDG: International Maritime Code for Dangerous Goods**DOT: US Department of Transportation**IATA: International Air Transport Association**EINECS: European Inventory of Existing Commercial Chemical Substances**ELINCS: European List of Notified Chemical Substances**CAS: Chemical Abstracts Service (division of the American Chemical Society)**NFPA: National Fire Protection Association (USA)**HMIS: Hazardous Materials Identification System (USA)**VOC: Volatile Organic Compounds (USA, EU)*

(Contd. on page 14)

USA

# Safety Data Sheet

acc. to OSHA HCS

Printing date 08/11/2025

Reviewed on 08/11/2025

**Trade name: 135B 135 SERIES BINDER**

(Contd. of page 13)

*LC50: Lethal concentration, 50 percent**LD50: Lethal dose, 50 percent**PBT: Persistent, Bioaccumulative and Toxic**vPvB: very Persistent and very Bioaccumulative**NIOSH: National Institute for Occupational Safety**OSHA: Occupational Safety & Health**TLV: Threshold Limit Value**PEL: Permissible Exposure Limit**REL: Recommended Exposure Limit**BEI: Biological Exposure Limit**Flammable Liquids 2: Flammable liquids – Category 2**Skin Irritation 2: Skin corrosion/irritation – Category 2**Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A**Sensitization - Skin 1: Skin sensitisation – Category 1**Germ Cell Mutagenicity 1B: Germ cell mutagenicity – Category 1B**Carcinogenicity 1B: Carcinogenicity – Category 1B**Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3**\* Data compared to the previous version altered.*

USA