



Safety Data Sheet acc. to OSHA HCS

Printing date 11/18/2020

Reviewed on 11/18/2020

1 Identification

- **Product identifier**
- **Trade name:** SX01 ADHESION PROMOTER
- **Article number:** SX01
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Lusid Technologies
4725 S Camp Kearns Road
Kearns, UT 84118
USA
www.lusidtechnologies.com
- **Information department:** Product safety department
- **Emergency telephone number:**
24 Hrs Emergency Contact:
INFOTRAC
1-800-535-5053

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Sol. 1 H228 Flammable solid.



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT SE 2 H371 May cause damage to the central nervous system and the visual organs.

STOT RE 2 H373 May cause damage to the hearing organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Acute Tox. 4 H312 Harmful in contact with skin.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/18/2020

Reviewed on 11/18/2020

Trade name: **SX01 ADHESION PROMOTER**

(Contd. of page 1)

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02 GHS07 GHS08

- **Signal word** *Danger*

- **Hazard-determining components of labeling:**

xylene

toluene

ethylbenzene

methanol

- **Hazard statements**

Flammable solid.

Harmful in contact with skin.

Causes skin irritation.

Causes serious eye irritation.

Suspected of causing cancer.

Suspected of damaging fertility or the unborn child.

May cause damage to the central nervous system and the visual organs.

May cause drowsiness or dizziness.

May cause damage to the hearing organs through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

- **Precautionary statements**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Immediately call a poison center/doctor.

Specific treatment (see on this label).

Do NOT induce vomiting.

If on skin: Wash with plenty of water.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Call a poison center/doctor if you feel unwell.

Get medical advice/attention if you feel unwell.

Take off contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use for extinction: CO2, powder or water spray.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/18/2020

Reviewed on 11/18/2020

Trade name: **SX01 ADHESION PROMOTER**

(Contd. of page 2)

- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



Health = 2
Fire = 2
Reactivity = 0

- **HMIS-ratings (scale 0 - 4)**



Health = *2
Fire = 2
Reactivity = 0

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

| | | |
|-----------|---------------|---------|
| 108-88-3 | toluene | 25-50% |
| 1330-20-7 | xylene | 10-25% |
| 100-41-4 | ethylbenzene | 2.5-25% |
| 67-56-1 | methanol | 0-10% |
| 78-93-3 | butanone | 0-10% |
| 141-78-6 | ethyl acetate | 0-10% |

4 First-aid measures

- **Description of first aid measures**
- **General information:**
Immediately remove any clothing soiled by the product.
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

USA

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/18/2020

Reviewed on 11/18/2020

Trade name: **SX01 ADHESION PROMOTER**

(Contd. of page 3)

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

- **PAC-1:**

| | | |
|----------|---------------|-----------|
| 108-88-3 | toluene | 67 ppm |
| 100-41-4 | ethylbenzene | 33 ppm |
| 67-56-1 | methanol | 530 ppm |
| 78-93-3 | butanone | 200 ppm |
| 141-78-6 | ethyl acetate | 1,200 ppm |

- **PAC-2:**

| | | |
|----------|---------------|-----------|
| 108-88-3 | toluene | 560 ppm |
| 100-41-4 | ethylbenzene | 1100* ppm |
| 67-56-1 | methanol | 2,100 ppm |
| 78-93-3 | butanone | 2700* ppm |
| 141-78-6 | ethyl acetate | 1,700 ppm |

- **PAC-3:**

| | | |
|----------|---------------|-------------|
| 108-88-3 | toluene | 3700* ppm |
| 100-41-4 | ethylbenzene | 1800* ppm |
| 67-56-1 | methanol | 7200* ppm |
| 78-93-3 | butanone | 4000* ppm |
| 141-78-6 | ethyl acetate | 10000** ppm |

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/18/2020

Reviewed on 11/18/2020

Trade name: SX01 ADHESION PROMOTER

(Contd. of page 4)

Open and handle receptacle with care.

· **Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

· **Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:** No special requirements.

· **Information about storage in one common storage facility:** Not required.

· **Further information about storage conditions:** Keep receptacle tightly sealed.

· **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

· **Additional information about design of technical systems:** No further data; see item 7.

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

108-88-3 toluene

PEL Long-term value: 200 ppm
Ceiling limit value: 300; 500* ppm
*10-min peak per 8-hr shift

REL Short-term value: 560 mg/m³, 150 ppm
Long-term value: 375 mg/m³, 100 ppm

TLV Long-term value: 20 ppm
BEI, NIC-OTO

1330-20-7 xylene

PEL Long-term value: 435 mg/m³, 100 ppm

REL Short-term value: 655 mg/m³, 150 ppm
Long-term value: 435 mg/m³, 100 ppm

TLV Short-term value: 651 mg/m³, 150 ppm
Long-term value: 434 mg/m³, 100 ppm
BEI

100-41-4 ethylbenzene

PEL Long-term value: 435 mg/m³, 100 ppm

REL Short-term value: 545 mg/m³, 125 ppm
Long-term value: 435 mg/m³, 100 ppm

TLV Long-term value: 87 mg/m³, 20 ppm
BEI

67-56-1 methanol

PEL Long-term value: 260 mg/m³, 200 ppm

REL Short-term value: 325 mg/m³, 250 ppm
Long-term value: 260 mg/m³, 200 ppm
Skin

TLV Short-term value: 328 mg/m³, 250 ppm
Long-term value: 262 mg/m³, 200 ppm
Skin; BEI

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/18/2020

Reviewed on 11/18/2020

Trade name: **SX01 ADHESION PROMOTER**

(Contd. of page 5)

78-93-3 butanone

| | |
|-----|--|
| PEL | Long-term value: 590 mg/m ³ , 200 ppm |
| REL | Short-term value: 885 mg/m ³ , 300 ppm Long-term value: 590 mg/m ³ , 200 ppm |
| TLV | Short-term value: 885 mg/m ³ , 300 ppm Long-term value: 590 mg/m ³ , 200 ppm BEI |

141-78-6 ethyl acetate

| | |
|-----|---|
| PEL | Long-term value: 1400 mg/m ³ , 400 ppm |
| REL | Long-term value: 1400 mg/m ³ , 400 ppm |
| TLV | Long-term value: 1440 mg/m ³ , 400 ppm |

Ingredients with biological limit values:**108-88-3 toluene**

| | |
|-----|--|
| BEI | 0.02 mg/L Medium: blood Time: prior to last shift of workweek Parameter: Toluene |
| | 0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene |
| | 0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background) |

1330-20-7 xylene

| | |
|-----|--|
| BEI | 1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids |
|-----|--|

100-41-4 ethylbenzene

| | |
|-----|---|
| BEI | 0.7 g/g creatinine Medium: urine Time: end of shift at end of workweek Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative) |
| | - Medium: end-exhaled air Time: not critical Parameter: Ethyl benzene (semi-quantitative) |

67-56-1 methanol

| | |
|-----|---|
| BEI | 15 mg/L Medium: urine Time: end of shift Parameter: Methanol (background, nonspecific) |
|-----|---|

(Contd. on page 7)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/18/2020

Reviewed on 11/18/2020

Trade name: **SX01 ADHESION PROMOTER**

(Contd. of page 6)

78-93-3 butanone

BEI 2 mg/L
 Medium: urine
 Time: end of shift
 Parameter: MEK

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
 Keep away from foodstuffs, beverages and feed.
 Immediately remove all soiled and contaminated clothing.
 Wash hands before breaks and at the end of work.
 Store protective clothing separately.
 Avoid contact with the eyes and skin.
- **Breathing equipment:**
 In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**
 The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**
 The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:**
 Safety glasses



Tightly sealed goggles

9 Physical and chemical properties

- **Information on basic physical and chemical properties**
- **General Information**
- **Appearance:**

| | |
|---------------|----------|
| Form: | Liquid |
| Color: | Clear |
| Odor: | Aromatic |

(Contd. on page 8)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/18/2020

Reviewed on 11/18/2020

Trade name: **SX01 ADHESION PROMOTER**

(Contd. of page 7)

| | |
|---|--|
| · Odor threshold: | Not determined. |
| · pH-value: | Not applicable. |
| · Change in condition Melting point/Melting range: | Undetermined. |
| Boiling point/Boiling range: | 64.7 °C (148.5 °F) |
| · Flash point: | 15 °C (59 °F) |
| · Flammability (solid, gaseous): | Not determined. |
| · Ignition temperature: | 430 °C (806 °F) |
| · Decomposition temperature: | Not determined. |
| · Auto igniting: | Product is not selfigniting. |
| · Danger of explosion: | Product is not explosive. However, formation of explosive air/vapor mixtures are possible. |
| · Explosion limits: Lower: | 1 Vol % |
| Upper: | 7.8 Vol % |
| · Vapor pressure at 20 °C (68 °F): | 29 hPa (21.8 mm Hg) |
| · Density at 20 °C (68 °F): | 0.86 g/cm ³ (7.1767 lbs/gal) |
| · Relative density | Not determined. |
| · Vapor density | Not applicable. |
| · Evaporation rate | Not applicable. |
| · Solubility in / Miscibility with Water: | Soluble. |
| · Partition coefficient (n-octanol/water): | Not determined. |
| · Viscosity: Dynamic: | Not applicable. |
| Kinematic: | Not applicable. |
| · Solvent content: Organic solvents: | 63.8-100 % |
| VOC content: | 63.85-100 % |
| Solids content: | 5.0 % |
| · Other information | No further relevant information available. |

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

USA

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/18/2020

Reviewed on 11/18/2020

Trade name: **SX01 ADHESION PROMOTER**

(Contd. of page 8)

11 Toxicological information

- **Information on toxicological effects**

- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

108-88-3 toluene

| | | |
|------------|----------|-----------------------|
| Oral | LD50 | 5,000 mg/kg (rat) |
| Dermal | LD50 | 12,124 mg/kg (rabbit) |
| Inhalative | LC50/4 h | 5,320 mg/l (mouse) |

100-41-4 ethylbenzene

| | | |
|--------|------|-----------------------|
| Oral | LD50 | 3,500 mg/kg (rat) |
| Dermal | LD50 | 17,800 mg/kg (rabbit) |

67-56-1 methanol

| | | |
|--------|------|-----------------------|
| Oral | LD50 | 5,628 mg/kg (rat) |
| Dermal | LD50 | 15,800 mg/kg (rabbit) |

- **Primary irritant effect:**

- **on the skin:** Irritant to skin and mucous membranes.

- **on the eye:** Irritating effect.

- **Sensitization:** No sensitizing effects known.

- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful

Irritant

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

| | | |
|-----------|--------------|----|
| 108-88-3 | toluene | 3 |
| 1330-20-7 | xylene | 3 |
| 100-41-4 | ethylbenzene | 2B |

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**

- **Aquatic toxicity:** No further relevant information available.

- **Persistence and degradability** No further relevant information available.

- **Behavior in environmental systems:**

- **Bioaccumulative potential** No further relevant information available.

- **Mobility in soil** No further relevant information available.

- **Additional ecological information:**

- **General notes:**

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/18/2020

Reviewed on 11/18/2020

Trade name: SX01 ADHESION PROMOTER



(Contd. of page 9)

- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport information

- | | |
|---|--|
| <ul style="list-style-type: none"> · UN-Number · DOT, IMDG, IATA | <p style="text-align: right;">UN1325</p> |
| <ul style="list-style-type: none"> · UN proper shipping name · DOT · IMDG, IATA | <p style="text-align: right;"><i>Flammable solids, organic, n.o.s. (Toluene, Ethylbenzene)</i> FLAMMABLE SOLID, ORGANIC, N.O.S. (TOLUENE, ETHYLBENZENE)</p> |
| <ul style="list-style-type: none"> · Transport hazard class(es) · DOT | <div style="text-align: center;">  </div> |
| <ul style="list-style-type: none"> · Class · Label | <p style="text-align: right;">4.1 Flammable solids, self-reactive substances and solid desensitised explosives 4.1</p> |
| <ul style="list-style-type: none"> · IMDG, IATA | <div style="text-align: center;">  </div> |
| <ul style="list-style-type: none"> · Class · Label | <p style="text-align: right;">4.1 Flammable solids, self-reactive substances and solid desensitised explosives 4.1</p> |
| <ul style="list-style-type: none"> · Packing group · DOT, IMDG, IATA | <p style="text-align: right;">II</p> |
| <ul style="list-style-type: none"> · Environmental hazards: · Marine pollutant: | <p style="text-align: right;">No</p> |

(Contd. on page 11)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/18/2020

Reviewed on 11/18/2020

Trade name: **SX01 ADHESION PROMOTER**

(Contd. of page 10)

- | | |
|---|---|
| <ul style="list-style-type: none"> · Special precautions for user · Hazard identification number (Kemler code): 40 · EMS Number: · Stowage Category | <p>Warning: <i>Flammable solids, self-reactive substances and solid desensitised explosives</i></p> <p>F-A, S-G</p> <p>B</p> |
| <ul style="list-style-type: none"> · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | <p>Not applicable.</p> |
| <ul style="list-style-type: none"> · Transport/Additional information: · DOT · Quantity limitations | <p>On passenger aircraft/rail: 15 kg On cargo aircraft only: 50 kg</p> |
| <ul style="list-style-type: none"> · IMDG · Limited quantities (LQ) · Excepted quantities (EQ) | <p>1 kg Code: E2 Maximum net quantity per inner packaging: 30 g Maximum net quantity per outer packaging: 500 g</p> |
| <ul style="list-style-type: none"> · UN "Model Regulation": | <p>UN 1325 FLAMMABLE SOLID, ORGANIC, N.O.S. (TOLUENE, ETHYLBENZENE), 4.1, II</p> |

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
No further relevant information available.
- **Sara**

- **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

- **Section 313 (Specific toxic chemical listings):**

| | |
|----------|---------|
| 108-88-3 | toluene |
|----------|---------|

| | |
|----------|--------------|
| 100-41-4 | ethylbenzene |
|----------|--------------|

| | |
|---------|----------|
| 67-56-1 | methanol |
|---------|----------|

- **TSCA (Toxic Substances Control Act):**

| | | | | |
|----------|---------|--|--|--------|
| 108-88-3 | toluene | | | ACTIVE |
|----------|---------|--|--|--------|

| | | | | |
|----------|--------------|--|--|--------|
| 100-41-4 | ethylbenzene | | | ACTIVE |
|----------|--------------|--|--|--------|

| | | | | |
|---------|----------|--|--|--------|
| 67-56-1 | methanol | | | ACTIVE |
|---------|----------|--|--|--------|

| | | | | |
|---------|----------|--|--|--------|
| 78-93-3 | butanone | | | ACTIVE |
|---------|----------|--|--|--------|

| | | | | |
|----------|---------------|--|--|--------|
| 141-78-6 | ethyl acetate | | | ACTIVE |
|----------|---------------|--|--|--------|

- **Hazardous Air Pollutants**

| | |
|----------|---------|
| 108-88-3 | toluene |
|----------|---------|

| | |
|----------|--------------|
| 100-41-4 | ethylbenzene |
|----------|--------------|

| | |
|---------|----------|
| 67-56-1 | methanol |
|---------|----------|

- **Proposition 65**

- **Chemicals known to cause cancer:**

| | |
|----------|--------------|
| 100-41-4 | ethylbenzene |
|----------|--------------|

(Contd. on page 12)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/18/2020

Reviewed on 11/18/2020

Trade name: **SX01 ADHESION PROMOTER**

(Contd. of page 11)

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

108-88-3 toluene

67-56-1 methanol

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

108-88-3 toluene

II

1330-20-7 xylene

I

100-41-4 ethylbenzene

D

78-93-3 butanone

I

· **TLV (Threshold Limit Value established by ACGIH)**

108-88-3 toluene

A4

1330-20-7 xylene

A4

100-41-4 ethylbenzene

A3

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**

xylene

toluene

ethylbenzene

methanol

· **Hazard statements**

Flammable solid.

Harmful in contact with skin.

Causes skin irritation.

Causes serious eye irritation.

Suspected of causing cancer.

Suspected of damaging fertility or the unborn child.

May cause damage to the central nervous system and the visual organs.

May cause drowsiness or dizziness.

May cause damage to the hearing organs through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

· **Precautionary statements**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

(Contd. on page 13)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/18/2020

Reviewed on 11/18/2020

Trade name: SX01 ADHESION PROMOTER

(Contd. of page 12)

Ground/bond container and receiving equipment.
 Use explosion-proof electrical/ventilating/lighting/equipment.
 Do not breathe dust/fume/gas/mist/vapors/spray.
 Wash thoroughly after handling.
 Do not eat, drink or smoke when using this product.
 Wear protective gloves/protective clothing/eye protection/face protection.
 If swallowed: Immediately call a poison center/doctor.
 Specific treatment (see on this label).
 Do NOT induce vomiting.
 If on skin: Wash with plenty of water.
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 IF exposed or concerned: Get medical advice/attention.
 Call a poison center/doctor if you feel unwell.
 Get medical advice/attention if you feel unwell.
 Take off contaminated clothing and wash it before reuse.
 If skin irritation occurs: Get medical advice/attention.
 If eye irritation persists: Get medical advice/attention.
 In case of fire: Use for extinction: CO₂, powder or water spray.
 Store locked up.
 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

- **Department issuing SDS:** Environment protection department.
- **Contact:** Product Safety Dept.
- **Date of preparation / last revision** 11/18/2020 / 5
- **Abbreviations and acronyms:**
 - IMDG: International Maritime Code for Dangerous Goods
 - DOT: US Department of Transportation
 - IATA: International Air Transport Association
 - ACGIH: American Conference of Governmental Industrial Hygienists
 - EINECS: European Inventory of Existing Commercial Chemical Substances
 - ELINCS: European List of Notified Chemical Substances
 - CAS: Chemical Abstracts Service (division of the American Chemical Society)
 - NFPA: National Fire Protection Association (USA)
 - HMIS: Hazardous Materials Identification System (USA)
 - VOC: Volatile Organic Compounds (USA, EU)
 - LC50: Lethal concentration, 50 percent
 - LD50: Lethal dose, 50 percent
 - PBT: Persistent, Bioaccumulative and Toxic
 - vPvB: very Persistent and very Bioaccumulative
 - NIOSH: National Institute for Occupational Safety
 - OSHA: Occupational Safety & Health
 - TLV: Threshold Limit Value
 - PEL: Permissible Exposure Limit
 - REL: Recommended Exposure Limit
 - BEI: Biological Exposure Limit
 - Flam. Sol. 1: Flammable solids – Category 1
 - Acute Tox. 4: Acute toxicity – Category 4
 - Skin Irrit. 2: Skin corrosion/irritation – Category 2
 - Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A
 - Carc. 2: Carcinogenicity – Category 2
 - Repr. 2: Reproductive toxicity – Category 2
 - STOT SE 2: Specific target organ toxicity (single exposure) – Category 2
 - STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
 - Asp. Tox. 1: Aspiration hazard – Category 1
- *** Data compared to the previous version altered.**