

Printing date 07/03/2023

Reviewed on 07/03/2023

Page 1/11

1 Identification

- · Product identifier
- · Trade name: SHS11 JET BLACK MIXING TINT
- · Article number: SHS11
- · Details of the supplier of the safety data sheet
- Manufacturer/Supplier: Lusid Technologies
 4725 S Camp Kearns Road Kearns, UT 840118
- Information department: Product safety department
 Emergency telephone number: 24 Hrs Emergency Contact: INFOTRAC 1-800-535-5053

2 Hazard(s) identification

· Classification of the substance or mixture



Flammable Liquids 3

H226 Flammable liquid and vapor.



GHS08 Health hazard

Germ Cell Mutagenicity 1B Carcinogenicity 1B

H340 May cause genetic defects. H350 May cause cancer.

GHS07

Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness.

· Label elements

- · GHS label elements
- The product is classified and labeled according to the Globally Harmonized System (GHS). Hazard pictograms



(Contd. on page 2)



Printing date 07/03/2023

Reviewed on 07/03/2023

Trade name: SHS11 JET BLACK MIXING TINT

Signal word Danger	(Contd. of page 1)
Hazard-determining components of labeling:	
n-butyl acetate	
Carbon black	
Solvent naphtha (petroleum), light arom.	
Hazard statements	
Flammable liquid and vapor.	
May cause genetic defects.	
May cause cancer.	
May cause drowsiness or dizziness.	
Precautionary statements	
Obtain special instructions before use.	
Do not handle until all safety precautions have been read and understood.	
Keep away from heat/sparks/open flames/hot surfaces No smoking.	
Ground/bond container and receiving equipment.	
Use explosion-proof electrical/ventilating/lighting/equipment.	
Use only non-sparking tools.	
Take precautionary measures against static discharge.	
Avoid breathing dust/fume/gas/mist/vapors/spray	
Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.	
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin wi	th water/shower
IF INHALED: Remove person to fresh air and keep comfortable for breathing.	in water/snower.
IF exposed or concerned: Get medical advice/attention.	
Call a poison center/doctor if you feel unwell.	
In case of fire: Use CO2, powder or water spray to extinguish.	
Store in a well-ventilated place. Keep container tightly closed.	
Store in a well-ventilated place. Keep cool.	
Store locked up.	
Dispose of contents/container in accordance with local/regional/national/internat	ional regulations.
Classification system:	
NFPA ratings (scale 0 - 4)	
Health = 0	
Fire = 3	
0 Reactivity = 0	
HMIS-ratings (scale 0 - 4)	
HEALTH TO Health = *0	
Fire 3 Fire = 3	
REACTIVITY 0 Reactivity = 0	
Other hazards	
Results of PBT and vPvB assessment	
PBT: Not applicable.	
vPvB: Not applicable.	

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· **Description:** Mixture of the substances listed below with nonhazardous additions.

(Contd. on page 3)

USA

Printing date 07/03/2023

Reviewed on 07/03/2023

Trade name: SHS11 JET BLACK MIXING TINT

	-		
(Contd.	of	page	2)

· Dangerous components:		
	n-butyl acetate	25-50%
	heptan-2-one	2.5-10%
1333-86-4	Carbon black	2.5-10%
108-65-6	2-methoxy-1-methylethyl acetate	≤2.5%
64742-95-6	Solvent naphtha (petroleum), light arom.	≤2.5%

4 First-aid measures

- · Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- *Most important symptoms and effects, both acute and delayed* No further relevant information available.
- *Indication of any immediate medical attention and special treatment needed* No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Dilute with plenty of water.
- Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:
- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- Dispose contaminated material as waste according to section 13.
- Ensure adequate ventilation.

110-43-0 heptan-2-one

- Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.
- Protective Action Criteria for Chemicals

• PAC-1: 123-86-4 n-butyl acetate

5 ppm 150 ppm

(Contd. on page 4)

Printing date 07/03/2023

Reviewed on 07/03/2023

Trade name: SHS11 JET BLACK MIXING TINT

		(Contd. of page
1333-86-4	Carbon black	9 mg/m³
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
7664-38-2	phosphoric acid	3 mg/m ³
556-67-2	octamethylcyclotetrasiloxane	30 ppm
PAC-2:		
123-86-4	n-butyl acetate	200 ppm
110-43-0	heptan-2-one	670 ppm
1333-86-4	Carbon black	99 mg/m³
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppn
7664-38-2	phosphoric acid	30 mg/m ³
556-67-2	octamethylcyclotetrasiloxane	68 ppm
PAC-3:		
123-86-4	n-butyl acetate	3000* ppn
110-43-0	heptan-2-one	4000* ppn
1333-86-4	Carbon black	590 mg/m
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppn
7664-38-2	phosphoric acid	150 mg/m
556-67-2	octamethylcyclotetrasiloxane	130 ppm

7 Handling and storage

· Handling:

- Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
 Open and handle receptacle with care.
 Prevent formation of aerosols.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke.
 Protect against electrostatic charges.
 Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see section 7.

· Control parameters

• Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

(Contd. on page 5)

USA

Printing date 07/03/2023

Reviewed on 07/03/2023

Trade name: SHS11 JET BLACK MIXING TINT

		(Contd. of page
123-86	δ-4 n-butyl acetate	
PEL	Long-term value: 710 mg/m³, 150 ppm	
REL	Short-term value: 950 mg/m³, 200 ppm Long-term value: 710 mg/m³, 150 ppm	
TLV	Short-term value: 150 ppm Long-term value: 50 ppm	
110-43	-0 heptan-2-one	
PEL	Long-term value: 465 mg/m³, 100 ppm	
REL	Long-term value: 465 mg/m³, 100 ppm	
TLV	Long-term value: 50 ppm	
1333-8	6-4 Carbon black	
PEL	Long-term value: 3.5 mg/m³	
REL	Long-term value: 3.5* mg/m³ *0.1 in presence of PAHs;See Pocket Guide Apps.A+C	
TLV	Long-term value: 3* mg/m³ *inhalable fraction, A3	
108-65	-6 2-methoxy-1-methylethyl acetate	
14/551	Long-term value: 50 ppm	

· Exposure controls

· Personal protective equipment:

• General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Store protective clothing separately.

• Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

• Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)

USA

(Contd. of page 5)

Safety Data Sheet acc. to OSHA HCS

Printing date 07/03/2023

Reviewed on 07/03/2023

Trade name: SHS11 JET BLACK MIXING TINT

• Eye protection:



Tightly sealed goggles

9 Physical and chemical properties · Information on basic physical and chemical properties · General Information · Appearance: Form: Liquid Color: Black · Odor: Characteristic · Odor threshold: Not determined. · pH-value: Not determined (pH N/A in solvent coatings) · Change in condition Melting point/Melting range: Undetermined. Boiling point/Boiling range: 124-128 °C (255.2-262.4 °F) 27 °C (80.6 °F) · Flash point: · Flammability (solid, gaseous): Flammable. · Auto igniting: 370 °C (698 °F) Not determined. · Decomposition temperature: · Ignition temperature: Product is not selfigniting. • Danger of explosion: Product is not explosive. However, formation of explosive air/ vapor mixtures are possible. · Explosion limits: Lower: 1.2 Vol % 7.5 Vol % Upper: 10.7 hPa (8 mm Hg) · Vapor pressure at 20 °C (68 °F): · Vapor pressure at 50 °C (122 °F): 55 hPa (41.3 mm Hg) 1.0522 g/cm³ (8.7806 lbs/gal) · Density at 20 °C (68 °F): Not determined. · Relative density · Vapor density Not determined. · Evaporation rate Not determined. · Solubility in / Miscibility with Water: Fully miscible. · Partition coefficient (n-octanol/water): Not determined. · Viscosity: Dynamic: Not determined. Kinematic: Not determined. · Solvent content: Organic solvents: 39.1 %

(Contd. on page 7)

USA

Printing date 07/03/2023

Reviewed on 07/03/2023

Trade name: SHS11 JET BLACK MIXING TINT

		(Contd. of page 6)
VOC content:	39.06 %	
	393.3 g/l / 3.28 lb/gal	
Solids content:	62.6 %	
· Other information	No further relevant information available.	

10 Stability and reactivity

· Reactivity No further relevant information available.

- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- Acute toxicity:

· LD/LC50 values that are relevant for classification:

123-86-4 n-butyl acetate

Oral	LD50	13,100 mg/kg (rat)
Dermal	LD50	13,100 mg/kg (rat) >5,000 mg/kg (rabbit)
Inhalative	LC50/4 h	>21 mg/l (rat)

· Primary irritant effect:

- on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

The product can cause inheritable damage.

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

- 1333-86-4 Carbon black
- · NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.

(Contd. on page 8)

2B

USA

Printing date 07/03/2023

Reviewed on 07/03/2023

Trade name: SHS11 JET BLACK MIXING TINT

(Contd. of page 7)

- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:
- Water hazard class 2 (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.
- Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

UN1263 Paint
Paint
PAINT
3 Flammable liquids
3
3 Flammable liquids
3

Printing date 07/03/2023

Reviewed on 07/03/2023

Trade name: SHS11 JET BLACK MIXING TINT

	(Contd. of page
· Environmental hazards: · Marine pollutant:	No
· Special precautions for user	Warning: Flammable liquids
Hazard identification number (Kemler code):	
EMS Number:	F-E,S-E
Stowage Category	A
Transport in bulk according to Annex II of	
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 60 L
,	On cargo aircraft only: 220 L
· IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 1263 PAINT, 3, III

15 Regulatory information

 $^{\cdot}$ Safety, health and environmental regulations/legislation specific for the substance or mixture $^{\cdot}$ Sara

Section 31	3 (Specific toxic chemical listings):	
7664-38-2	phosphoric acid	
TSCA (Tox	ric Substances Control Act):	
123-86-4	n-butyl acetate	ACTIVE
110-43-0	heptan-2-one	ACTIVE
1333-86-4	Carbon black	ACTIVE
108-65-6	2-methoxy-1-methylethyl acetate	ACTIVE
64742-95-6	Solvent naphtha (petroleum), light arom.	ACTIVE
7664-38-2	phosphoric acid	ACTIVE
556-67-2	octamethylcyclotetrasiloxane	ACTIVE
Hazardous	Air Pollutants	
None of the	e ingredients is listed.	
Propositio	n 65	
Chemicals	known to cause cancer:	
1333-86-4	Carbon black	
Chemicals	known to cause reproductive toxicity for females:	
None of the	e ingredients is listed.	

- USA

Printing date 07/03/2023

Reviewed on 07/03/2023

Trade name: SHS11 JET BLACK MIXING TINT

(Contd. of page 9)

A4

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

TLV (Threshold Limit Value)

1333-86-4 Carbon black

· NIOSH-Ca (National Institute for Occupational Safety and Health)

1333-86-4 Carbon black

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



· Signal word Danger

· Hazard-determining components of labeling: n-butyl acetate Carbon black Solvent naphtha (petroleum), light arom. Hazard statements Flammable liquid and vapor. May cause genetic defects. May cause cancer. May cause drowsiness or dizziness. · Precautionary statements Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapors/spray Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. In case of fire: Use CO2, powder or water spray to extinguish. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. (Contd. on page 11)

Printing date 07/03/2023

Reviewed on 07/03/2023

Trade name: SHS11 JET BLACK MIXING TINT

(Contd. of page 10)

- National regulations:
- Additional classification according to Decree on Hazardous Materials: Carcinogenic hazardous material group III (dangerous).
- *Information about limitation of use:* Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact: Product Safety Dept.
- Date of preparation / last revision 07/03/2023
- Abbreviations and acronyms: IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety **OSHA: Occupational Safety & Health** TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit Flammable Liquids 3: Flammable liquids – Category 3 Germ Cell Mutagenicity 1B: Germ cell mutagenicity - Category 1B Carcinogenicity 1B: Carcinogenicity - Category 1B Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) - Category 3 * * Data compared to the previous version altered.

USA -