



Safety Data Sheet acc. to OSHA HCS

Printing date 08/06/2018

Reviewed on 12/05/2017

1 Identification

- **Product identifier**
- **Trade name:** MPB MP SERIES BINDER
- **Article number:** MPB
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Lusid Technologies
5195 West 4700 South
KEARNS, UT 84118
USA
www.lusid.biz
- **Information department:** Product safety department
- **Emergency telephone number:**
24 Hrs Emergency Contact:
INFOTRAC
1-800-535-5053

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS07

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H336 May cause drowsiness or dizziness.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02 GHS07

- **Signal word** Warning

- **Hazard-determining components of labeling:**

n-butyl acetate

(Contd. on page 2)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/06/2018

Reviewed on 12/05/2017

Trade name: MPB MP SERIES BINDER

(Contd. of page 1)

bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate

· **Hazard statements**

Flammable liquid and vapor.
May cause an allergic skin reaction.
May cause drowsiness or dizziness.

· **Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting/equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Avoid breathing dust/fume/gas/mist/vapors/spray
Use only outdoors or in a well-ventilated area.
Contaminated work clothing must not be allowed out of the workplace.
Wear protective gloves/protective clothing/eye protection/face protection.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
Call a poison center/doctor if you feel unwell.
Specific treatment (see on this label).
If skin irritation or rash occurs: Get medical advice/attention.
Wash contaminated clothing before reuse.
In case of fire: Use for extinction: CO₂, powder or water spray.
Store in a well-ventilated place. Keep container tightly closed.
Store in a well-ventilated place. Keep cool.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



· **HMIS-ratings (scale 0 - 4)**

| | | |
|------------|---|----------------|
| HEALTH | 0 | Health = 0 |
| FIRE | 3 | Fire = 3 |
| REACTIVITY | 0 | Reactivity = 0 |

· **Other hazards**

· **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

| | | |
|----------|-----------------|--------|
| 123-86-4 | n-butyl acetate | 10-25% |
| 110-43-0 | heptan-2-one | 10-25% |

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/06/2018

Reviewed on 12/05/2017

Trade name: **MPB MP SERIES BINDER**

(Contd. of page 2)

41556-26-7 bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate

≤2.5%

4 First-aid measures

- **Description of first aid measures**
- **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

- **PAC-1:**

| | | |
|-----------|----------------------|-----------------------|
| 123-86-4 | n-butyl acetate | 5 ppm |
| 110-43-0 | heptan-2-one | 150 ppm |
| 1330-20-7 | xylene | 130 ppm |
| 122-99-6 | 2-Phenoxyethanol | 1.5 ppm |
| 100-41-4 | ethylbenzene | 33 ppm |
| 77-58-7 | dibutyltin dilaurate | 1.1 mg/m ³ |

(Contd. on page 4)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/06/2018

Reviewed on 12/05/2017

Trade name: MPB MP SERIES BINDER

(Contd. of page 3)

| · PAC-2: | | |
|-----------------|-------------------------|----------------------|
| 123-86-4 | <i>n</i> -butyl acetate | 200 ppm |
| 110-43-0 | heptan-2-one | 670 ppm |
| 1330-20-7 | xylene | 920* ppm |
| 122-99-6 | 2-Phenoxyethanol | 16 ppm |
| 100-41-4 | ethylbenzene | 1100* ppm |
| 77-58-7 | dibutyltin dilaurate | 8 mg/m ³ |
| · PAC-3: | | |
| 123-86-4 | <i>n</i> -butyl acetate | 3000* ppm |
| 110-43-0 | heptan-2-one | 4000* ppm |
| 1330-20-7 | xylene | 2500* ppm |
| 122-99-6 | 2-Phenoxyethanol | 97 ppm |
| 100-41-4 | ethylbenzene | 1800* ppm |
| 77-58-7 | dibutyltin dilaurate | 48 mg/m ³ |

7 Handling and storage

- **Handling:**
- **Precautions for safe handling** No special precautions are necessary if used correctly.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
At this time, the remaining constituent has no known exposure limits.

| 123-86-4 n-butyl acetate | |
|---------------------------------|---|
| PEL | Long-term value: 710 mg/m ³ , 150 ppm |
| REL | Short-term value: 950 mg/m ³ , 200 ppm Long-term value: 710 mg/m ³ , 150 ppm |
| TLV | Short-term value: 712 mg/m ³ , 150 ppm Long-term value: 238 mg/m ³ , 50 ppm |
| 110-43-0 heptan-2-one | |
| PEL | Long-term value: 465 mg/m ³ , 100 ppm |
| REL | Long-term value: 465 mg/m ³ , 100 ppm |

(Contd. on page 5)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/06/2018

Reviewed on 12/05/2017

Trade name: **MPB MP SERIES BINDER**

(Contd. of page 4)

TLV Long-term value: 233 mg/m³, 50 ppm

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

· **Breathing equipment:** Not required.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Liquid

Color: Clear

· **Odor:** Characteristic

· **Odor threshold:** Not determined.

· **pH-value:** Not determined (pH N/A in solvent coatings)

· **Change in condition**

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: 124 °C (255.2 °F)

· **Flash point:** 27 °C (80.6 °F)

· **Flammability (solid, gaseous):** Not applicable.

(Contd. on page 6)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/06/2018

Reviewed on 12/05/2017

Trade name: **MPB MP SERIES BINDER**

(Contd. of page 5)

| | |
|---|--|
| · Ignition temperature: | 370 °C (698 °F) |
| · Decomposition temperature: | Not determined. |
| · Auto igniting: | Product is not selfigniting. |
| · Danger of explosion: | Product is not explosive. However, formation of explosive air/vapor mixtures are possible. |
| · Explosion limits: | |
| Lower: | 1 Vol % |
| Upper: | 7.5 Vol % |
| · Vapor pressure at 20 °C (68 °F): | 10.7 hPa (8 mm Hg) |
| · Density at 20 °C (68 °F): | 1.03 g/cm ³ (8.5954 lbs/gal) |
| · Relative density | Not determined. |
| · Vapor density | Not determined. |
| · Evaporation rate | Not determined. |
| · Solubility in / Miscibility with Water: | Not miscible or difficult to mix. |
| · Partition coefficient (n-octanol/water): | Not determined. |
| · Viscosity: | |
| Dynamic: | Not determined. |
| Kinematic: | Not determined. |
| · Solvent content: | |
| Organic solvents: | 35.3 % |
| VOC content: | 35.30 % |
| | 364.3 g/l / 3.04 lb/gal |
| · Solids content: | 64.6 % |
| · Other information | No further relevant information available. |

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **LD/LC50 values that are relevant for classification:**

110-43-0 heptan-2-one

| | | |
|------|------|-------------------|
| Oral | LD50 | 1,670 mg/kg (rat) |
|------|------|-------------------|

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/06/2018

Reviewed on 12/05/2017

Trade name: MPB MP SERIES BINDER

(Contd. of page 6)

| | | |
|--------|------|-----------------------|
| Dermal | LD50 | 12,600 mg/kg (rabbit) |
|--------|------|-----------------------|

- **Primary irritant effect:**

- **on the skin:** No irritant effect.

- **on the eye:** No irritating effect.

- **Sensitization:** Sensitization possible through skin contact.

- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

| | | |
|-----------|--------------|----|
| 1330-20-7 | xylene | 3 |
| 100-41-4 | ethylbenzene | 2B |

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**

- **Aquatic toxicity:** No further relevant information available.

- **Persistence and degradability** No further relevant information available.

- **Behavior in environmental systems:**

- **Bioaccumulative potential** No further relevant information available.

- **Mobility in soil** No further relevant information available.

- **Additional ecological information:**

- **General notes:**

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**

- **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- **Uncleaned packagings:**

- **Recommendation:** Disposal must be made according to official regulations.

USA

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS



Printing date 08/06/2018

Reviewed on 12/05/2017

Trade name: **MPB MP SERIES BINDER**

(Contd. of page 7)

14 Transport information

| | |
|--|--|
| <ul style="list-style-type: none"> · UN-Number · DOT, IMDG, IATA | UN1263 |
| <ul style="list-style-type: none"> · UN proper shipping name · DOT · IMDG, IATA | Paint PAINT |
| <ul style="list-style-type: none"> · Transport hazard class(es) · DOT | <div style="text-align: center;">  <p>FLAMMABLE LIQUID 3</p> </div> |
| <ul style="list-style-type: none"> · Class · Label | 3 Flammable liquids 3 |
| | |
| <ul style="list-style-type: none"> · IMDG, IATA | <div style="text-align: center;">  <p>3</p> </div> |
| <ul style="list-style-type: none"> · Class · Label | 3 Flammable liquids 3 |
| <ul style="list-style-type: none"> · Packing group · DOT, IMDG, IATA | III |
| <ul style="list-style-type: none"> · Environmental hazards: · Marine pollutant: | No |
| <ul style="list-style-type: none"> · Special precautions for user · Danger code (Kemler): · EMS Number: · Stowage Category | Warning: Flammable liquids 30 F-E, <u>S</u> -E A |
| <ul style="list-style-type: none"> · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | Not applicable. |
| <ul style="list-style-type: none"> · Transport/Additional information: · DOT · Quantity limitations | On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L |
| | |
| <ul style="list-style-type: none"> · IMDG · Limited quantities (LQ) · Excepted quantities (EQ) | 5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml |
| <ul style="list-style-type: none"> · UN "Model Regulation": | UN 1263 PAINT, 3, III |

USA

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/06/2018

Reviewed on 12/05/2017

Trade name: **MPB MP SERIES BINDER**

(Contd. of page 8)

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

- **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

- **Section 313 (Specific toxic chemical listings):**

1330-20-7 xylene

122-99-6 2-Phenoxyethanol

100-41-4 ethylbenzene

- **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

- **Proposition 65**

- **Chemicals known to cause cancer:**

100-41-4 ethylbenzene

- **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

- **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

- **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

- **Carcinogenic categories**

- **EPA (Environmental Protection Agency)**

1330-20-7 xylene

I

100-41-4 ethylbenzene

D

- **TLV (Threshold Limit Value established by ACGIH)**

1330-20-7 xylene

A4

100-41-4 ethylbenzene

A3

77-58-7 dibutyltin dilaurate

A4

- **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02 GHS07

- **Signal word** Warning

- **Hazard-determining components of labeling:**

n-butyl acetate

bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate

- **Hazard statements**

Flammable liquid and vapor.

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/06/2018

Reviewed on 12/05/2017

Trade name: MPB MP SERIES BINDER

(Contd. of page 9)

May cause an allergic skin reaction.

May cause drowsiness or dizziness.

· **Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a poison center/doctor if you feel unwell.

Specific treatment (see on this label).

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

In case of fire: Use for extinction: CO₂, powder or water spray.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Environment protection department.

· **Contact:** Product Safety Dept.

· **Date of preparation / last revision** 08/06/2018 / 2

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flam. Liq. 3: Flammable liquids – Category 3

Skin Sens. 1: Skin sensitisation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

· * **Data compared to the previous version altered.**