

**Safety Data Sheet**  
*acc. to OSHA HCS*

Printing date 02/10/2016

Reviewed on 02/10/2016

**1 Identification**

- **Product identifier**
- **Trade name:** GSR-M MEDIUM PU REDUCER
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
GlobalStar Industrial  
Lusid Technologies  
5195 West 4700 South  
KEARNS, UT 84118  
USA  
1-877-973-7600  
www.Globalstar.online
- **Information department:** Product safety department
- **Emergency telephone number:** 1-800-535-5053

**2 Hazard(s) identification**

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 02/10/2016

Reviewed on 02/10/2016

**Trade name: GSR-M MEDIUM PU REDUCER**

(Contd. of page 1)

· **Hazard pictograms**



· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

*toluene  
n-butyl acetate  
butanone*

· **Hazard statements**

*Highly flammable liquid and vapor.  
Causes skin irritation.  
Causes serious eye irritation.  
Suspected of damaging fertility or the unborn child.  
May cause drowsiness or dizziness.  
May cause damage to organs through prolonged or repeated exposure.  
May be fatal if swallowed and enters airways.*

· **Precautionary statements**

*Keep away from heat/sparks/open flames/hot surfaces. No smoking.  
Use explosion-proof electrical/ventilating/lighting/equipment.  
Do not breathe dust/fume/gas/mist/vapors/spray.  
Wear protective gloves / eye protection / face protection.  
Ground/bond container and receiving equipment.  
Use only non-sparking tools.  
Take precautionary measures against static discharge.  
Wash thoroughly after handling.  
Use only outdoors or in a well-ventilated area.  
Obtain special instructions before use.  
Do not handle until all safety precautions have been read and understood.  
**IF SWALLOWED:** Immediately call a POISON CENTER/ doctor.  
**If on skin (or hair):** Take off immediately all contaminated clothing. Rinse skin with water/shower.  
**If in eyes:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
Specific treatment (see on this label).  
**IF INHALED:** Remove person to fresh air and keep comfortable for breathing.  
Call a POISON CENTER/doctor if you feel unwell.  
**IF exposed or concerned:** Get medical advice/attention.  
**If skin irritation occurs:** Get medical advice/attention.  
**If eye irritation persists:** Get medical advice/attention.  
Get medical advice/attention if you feel unwell.  
Do NOT induce vomiting.  
**In case of fire:** Use for extinction: CO2, powder or water spray.  
Take off contaminated clothing and wash it before reuse.  
Store locked up.*

(Contd. on page 3)

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 02/10/2016

Reviewed on 02/10/2016

**Trade name: GSR-M MEDIUM PU REDUCER**

(Contd. of page 2)

Store in a well-ventilated place. Keep container tightly closed.  
Store in a well-ventilated place. Keep cool.  
Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



· **HMIS-ratings (scale 0 - 4)**



· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

**3 Composition/information on ingredients**

· **Chemical characterization: Mixtures**

· **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

108-88-3	toluene	25-50%
123-86-4	n-butyl acetate	25-50%
78-93-3	butanone	25-50%

**4 First-aid measures**

· **Description of first aid measures**

· **General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:** If symptoms persist consult doctor.

· **Information for doctor:**

· **Most important symptoms and effects, both acute and delayed** No further relevant information available.

(Contd. on page 4)

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 02/10/2016

Reviewed on 02/10/2016

**Trade name: GSR-M MEDIUM PU REDUCER**

(Contd. of page 3)

- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

**5 Fire-fighting measures**

- **Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture**  
During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

**6 Accidental release measures**

- **Personal precautions, protective equipment and emergency procedures**  
Mount respiratory protective device.  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

**7 Handling and storage**

- **Handling:**
- **Precautions for safe handling**  
Ensure good ventilation/exhaustion at the workplace.  
Open and handle receptacle with care.  
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.  
Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.

(Contd. on page 5)

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 02/10/2016

Reviewed on 02/10/2016

**Trade name: GSR-M MEDIUM PU REDUCER**

(Contd. of page 4)

- **Further information about storage conditions:**  
Keep receptacle tightly sealed.  
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

**8 Exposure controls/personal protection**

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

**108-88-3 toluene**

PEL	Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift
REL	Short-term value: 560 mg/m <sup>3</sup> , 150 ppm Long-term value: 375 mg/m <sup>3</sup> , 100 ppm
TLV	Long-term value: 75 mg/m <sup>3</sup> , 20 ppm BEI

**123-86-4 n-butyl acetate**

PEL	Long-term value: 710 mg/m <sup>3</sup> , 150 ppm
REL	Short-term value: 950 mg/m <sup>3</sup> , 200 ppm Long-term value: 710 mg/m <sup>3</sup> , 150 ppm
TLV	Short-term value: (950) NIC-712 mg/m <sup>3</sup> , (200) NIC-150 ppm Long-term value: (713) NIC-238 mg/m <sup>3</sup> , (150) NIC-50 ppm

**78-93-3 butanone**

PEL	Long-term value: 590 mg/m <sup>3</sup> , 200 ppm
REL	Short-term value: 885 mg/m <sup>3</sup> , 300 ppm Long-term value: 590 mg/m <sup>3</sup> , 200 ppm
TLV	Short-term value: 885 mg/m <sup>3</sup> , 300 ppm Long-term value: 590 mg/m <sup>3</sup> , 200 ppm BEI

(Contd. on page 6)

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 02/10/2016

Reviewed on 02/10/2016

**Trade name: GSR-M MEDIUM PU REDUCER**

(Contd. of page 5)

**· Ingredients with biological limit values:**

**108-88-3 toluene**

BEI 0.02 mg/L  
Medium: blood  
Time: prior to last shift of workweek  
Parameter: Toluene

0.03 mg/L  
Medium: urine  
Time: end of shift  
Parameter: Toluene

0.3 mg/g creatinine  
Medium: urine  
Time: end of shift  
Parameter: o-Cresol with hydrolysis (background)

**78-93-3 butanone**

BEI 2 mg/L  
Medium: urine  
Time: end of shift  
Parameter: MEK

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.
- Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.  
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

(Contd. on page 7)

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 02/10/2016

Reviewed on 02/10/2016

**Trade name: GSR-M MEDIUM PU REDUCER**

(Contd. of page 6)

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

**9 Physical and chemical properties**

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

· <b>Form:</b>	Liquid
· <b>Color:</b>	Clear
· <b>Odor:</b>	Characteristic
· <b>Odor threshold:</b>	Not determined.

· **pH-value:** Not determined.

· **Change in condition**

· <b>Melting point/Melting range:</b>	Undetermined.
· <b>Boiling point/Boiling range:</b>	79 °C (174 °F)

· **Flash point:** -4 °C (25 °F)

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:** 370 °C (698 °F)

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· **Explosion limits:**

· <b>Lower:</b>	1.2 Vol %
· <b>Upper:</b>	11.5 Vol %

· **Vapor pressure at 20 °C (68 °F):** 105 hPa (79 mm Hg)

· **Density at 20 °C (68 °F):** 0.85133 g/cm<sup>3</sup> (7.104 lbs/gal)

· **Relative density** Not determined.

(Contd. on page 8)

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 02/10/2016

Reviewed on 02/10/2016

**Trade name: GSR-M MEDIUM PU REDUCER**

(Contd. of page 7)

- **Vapor density** Not determined.
- **Evaporation rate** Not determined.
- **Solubility in / Miscibility with Water:** Not miscible or difficult to mix.
- **Partition coefficient (n-octanol/water):** Not determined.
- **Viscosity:**
  - Dynamic:** Not determined.
  - Kinematic:** Not determined.
- **Solvent content:**
  - Organic solvents:** 100.0 %
  - VOC content:** 100.0 %
  - Coating VOC 851.3 g/l / 7.10 lb/gl
  - Material VOC 851.3 g/l / 7.10 lb/gl
- **Other information** No further relevant information available.

**10 Stability and reactivity**

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

**11 Toxicological information**

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

**108-88-3 toluene**

Oral	LD50	5000 mg/kg (rat)
Dermal	LD50	12124 mg/kg (rabbit)
Inhalative	LC50/4 h	5320 mg/l (mouse)

- **Primary irritant effect:**
  - on the skin:** Irritant to skin and mucous membranes.
  - on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

(Contd. on page 9)



**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 02/10/2016

Reviewed on 02/10/2016

**Trade name: GSR-M MEDIUM PU REDUCER**

(Contd. of page 8)

*Irritant*

**· Carcinogenic categories**

**· IARC (International Agency for Research on Cancer)**

108-88-3 toluene

3

**· NTP (National Toxicology Program)**

None of the ingredients is listed.

**· OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

**12 Ecological information**

**· Toxicity**

- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.

**· Behavior in environmental systems:**

- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.

**· Additional ecological information:**

**· General notes:**

Water hazard class 2 (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.

**· Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

**13 Disposal considerations**

**· Waste treatment methods**

**· Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

**· Uncleaned packagings:**

- **Recommendation:** Disposal must be made according to official regulations.

**14 Transport information**

**· UN-Number**

**· DOT, IMDG, IATA**

UN1263

(Contd. on page 10)

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 02/10/2016

Reviewed on 02/10/2016

**Trade name: GSR-M MEDIUM PU REDUCER**

(Contd. of page 9)

· **UN proper shipping name**  
· **DOT, IATA** Paint  
· **IMDG** PAINT

· **Transport hazard class(es)**  
· **DOT**



· **Class** 3 Flammable liquids  
· **Label** 3

· **IMDG, IATA**



· **Class** 3 Flammable liquids  
· **Label** 3

· **Packing group**  
· **DOT, IMDG, IATA** II

· **Environmental hazards:** Not applicable.

· **Special precautions for user** Warning: Flammable liquids  
· **Danger code (Kemler):** 33  
· **EMS Number:** F-E, S-E  
· **Stowage Category** B

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.

· **Transport/Additional information:**

· **DOT**  
· **Quantity limitations** On passenger aircraft/rail: 5 L  
On cargo aircraft only: 60 L

· **IMDG**  
· **Limited quantities (LQ)** 5L  
· **Excepted quantities (EQ)** Code: E2  
Maximum net quantity per inner packaging: 30 ml  
Maximum net quantity per outer packaging: 500 ml

· **UN "Model Regulation":** UN 1263 PAINT, 3, II

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 02/10/2016

Reviewed on 02/10/2016

**Trade name: GSR-M MEDIUM PU REDUCER**

(Contd. of page 10)

**15 Regulatory information**

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

108-88-3 toluene

78-93-3 butanone

· **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

· **Proposition 65**

· **Chemicals known to cause cancer:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for females:**

108-88-3 toluene

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

108-88-3 toluene

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

108-88-3 toluene

II

78-93-3 butanone

I

· **TLV (Threshold Limit Value established by ACGIH)**

108-88-3 toluene

A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02

GHS07

GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**

toluene

(Contd. on page 12)

**Safety Data Sheet**  
*acc. to OSHA HCS*

Printing date 02/10/2016

Reviewed on 02/10/2016

**Trade name: GSR-M MEDIUM PU REDUCER**

(Contd. of page 11)

*n-butyl acetate*

*butanone*

**· Hazard statements**

*Highly flammable liquid and vapor.*

*Causes skin irritation.*

*Causes serious eye irritation.*

*Suspected of damaging fertility or the unborn child.*

*May cause drowsiness or dizziness.*

*May cause damage to organs through prolonged or repeated exposure.*

*May be fatal if swallowed and enters airways.*

**· Precautionary statements**

*Keep away from heat/sparks/open flames/hot surfaces. No smoking.*

*Use explosion-proof electrical/ventilating/lighting/equipment.*

*Do not breathe dust/fume/gas/mist/vapors/spray.*

*Wear protective gloves / eye protection / face protection.*

*Ground/bond container and receiving equipment.*

*Use only non-sparking tools.*

*Take precautionary measures against static discharge.*

*Wash thoroughly after handling.*

*Use only outdoors or in a well-ventilated area.*

*Obtain special instructions before use.*

*Do not handle until all safety precautions have been read and understood.*

*IF SWALLOWED: Immediately call a POISON CENTER/ doctor.*

*If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.*

*If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.*

*Continue rinsing.*

*Specific treatment (see on this label).*

*IF INHALED: Remove person to fresh air and keep comfortable for breathing.*

*Call a POISON CENTER/doctor if you feel unwell.*

*IF exposed or concerned: Get medical advice/attention.*

*If skin irritation occurs: Get medical advice/attention.*

*If eye irritation persists: Get medical advice/attention.*

*Get medical advice/attention if you feel unwell.*

*Do NOT induce vomiting.*

*In case of fire: Use for extinction: CO2, powder or water spray.*

*Take off contaminated clothing and wash it before reuse.*

*Store locked up.*

*Store in a well-ventilated place. Keep container tightly closed.*

*Store in a well-ventilated place. Keep cool.*

*Dispose of contents/container in accordance with local/regional/national/international regulations.*

**· Chemical safety assessment:** *A Chemical Safety Assessment has not been carried out.*

**16 Other information**

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

(Contd. on page 13)

**Safety Data Sheet**  
**acc. to OSHA HCS**

Printing date 02/10/2016

Reviewed on 02/10/2016

**Trade name: GSR-M MEDIUM PU REDUCER**

(Contd. of page 12)

- **Department issuing SDS:** Environment protection department.
- **Contact:** Product Safety Dept.
- **Date of preparation / last revision** 02/10/2016 / -
- **Abbreviations and acronyms:**
  - ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
  - IMDG: International Maritime Code for Dangerous Goods
  - DOT: US Department of Transportation
  - IATA: International Air Transport Association
  - ACGIH: American Conference of Governmental Industrial Hygienists
  - EINECS: European Inventory of Existing Commercial Chemical Substances
  - ELINCS: European List of Notified Chemical Substances
  - CAS: Chemical Abstracts Service (division of the American Chemical Society)
  - NFPA: National Fire Protection Association (USA)
  - HMIS: Hazardous Materials Identification System (USA)
  - VOC: Volatile Organic Compounds (USA, EU)
  - LC50: Lethal concentration, 50 percent
  - LD50: Lethal dose, 50 percent
  - PBT: Persistent, Bioaccumulative and Toxic
  - vPvB: very Persistent and very Bioaccumulative
  - NIOSH: National Institute for Occupational Safety
  - OSHA: Occupational Safety & Health
  - TLV: Threshold Limit Value
  - PEL: Permissible Exposure Limit
  - REL: Recommended Exposure Limit
  - BEI: Biological Exposure Limit
  - Flam. Liq. 2: Flammable liquids, Hazard Category 2
  - Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2
  - Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A
  - Repr. 2: Reproductive toxicity, Hazard Category 2
  - STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3
  - STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2
  - Asp. Tox. 1: Aspiration hazard, Hazard Category 1