



## Safety Data Sheet acc. to OSHA HCS

Printing date 02/21/2020

Reviewed on 02/21/2020

### 1 Identification

- **Product identifier**
- **Trade name:** GTP310 2K URETHANE PRIMER
- **Article number:** GTP310
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
Lusid Technologies  
4725 S Camp Kearns Road  
Kearns, UT 84118  
USA  
www.lusidtechnologies.com
- **Information department:** Product safety department
- **Emergency telephone number:**  
24 Hrs Emergency Contact:  
INFOTRAC  
1-800-535-5053

### 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.

Repr. 2 H361 Suspected of damaging fertility or the unborn child.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

USA

# Safety Data Sheet

acc. to OSHA HCS

Printing date 02/21/2020

Reviewed on 02/21/2020

Trade name: **GTP310 2K URETHANE PRIMER**

(Contd. of page 1)

- **Hazard pictograms**



GHS02 GHS07 GHS08

- **Signal word** Danger

- **Hazard-determining components of labeling:**

titanium dioxide

- **Hazard statements**

Highly flammable liquid and vapor.

Causes skin irritation.

Suspected of causing cancer.

Suspected of damaging fertility or the unborn child.

- **Precautionary statements**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Wash thoroughly after handling.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If exposed or concerned: Get medical advice/attention.

Specific treatment (see on this label).

Take off contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

In case of fire: Use for extinction: CO<sub>2</sub>, powder or water spray.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Classification system:**

- **NFPA ratings (scale 0 - 4)**



Health = 1

Fire = 3

Reactivity = 0

- **HMIS-ratings (scale 0 - 4)**



HEALTH 1 Health = 1

FIRE 3 Fire = 3

REACTIVITY 0 Reactivity = 0

- **Other hazards**

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

USA

(Contd. on page 3)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 02/21/2020

Reviewed on 02/21/2020

Trade name: **GTP310 2K URETHANE PRIMER**

(Contd. of page 2)

## 3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

1330-20-7	xylene	25-50%
13463-67-7	titanium dioxide	10-25%
7727-43-7	barium sulphate, natural	2.5-10%
123-86-4	n-butyl acetate	2.5-10%
78-93-3	butanone	2.5-10%
1332-58-7	Kaolin	≤2.5%
112926-00-8	Precipitated silica (Silica-Amorphous)	≤2.5%
100-41-4	ethylbenzene	≤2.5%
108-88-3	toluene	≤2.5%

## 4 First-aid measures

- **Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**  
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

## 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

## \* 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.

(Contd. on page 4)

USA

# Safety Data Sheet

acc. to OSHA HCS

Printing date 02/21/2020

Reviewed on 02/21/2020

**Trade name: GTP310 2K URETHANE PRIMER**

(Contd. of page 3)

**· Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

**· Protective Action Criteria for Chemicals**
**· PAC-1:**

1330-20-7	xylene	130 ppm
13463-67-7	titanium dioxide	30 mg/m <sup>3</sup>
7727-43-7	barium sulphate, natural	15 mg/m <sup>3</sup>
123-86-4	n-butyl acetate	5 ppm
78-93-3	butanone	200 ppm
112926-00-8	Precipitated silica (Silica-Amorphous)	18 mg/m <sup>3</sup>
100-41-4	ethylbenzene	33 ppm
108-88-3	toluene	67 ppm
110-43-0	heptan-2-one	150 ppm
77-58-7	dibutyltin dilaurate	1.1 mg/m <sup>3</sup>
1333-86-4	Carbon black	9 mg/m <sup>3</sup>
14808-60-7	Quartz (SiO <sub>2</sub> )	0.075 mg/m <sup>3</sup>
57-55-6	Propylene glycol	30 mg/m <sup>3</sup>
78-83-1	butanol	150 ppm
108-83-8	2,6-dimethylheptan-4-one	75 ppm
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
34590-94-8	Dipropylene glycol monomethyl ether	150 ppm
70657-70-4	2-methoxypropyl acetate	50 ppm

**· PAC-2:**

1330-20-7	xylene	920* ppm
13463-67-7	titanium dioxide	330 mg/m <sup>3</sup>
7727-43-7	barium sulphate, natural	170 mg/m <sup>3</sup>
123-86-4	n-butyl acetate	200 ppm
78-93-3	butanone	2700* ppm
112926-00-8	Precipitated silica (Silica-Amorphous)	200 mg/m <sup>3</sup>
100-41-4	ethylbenzene	1100* ppm
108-88-3	toluene	560 ppm
110-43-0	heptan-2-one	670 ppm
77-58-7	dibutyltin dilaurate	8 mg/m <sup>3</sup>
1333-86-4	Carbon black	99 mg/m <sup>3</sup>
14808-60-7	Quartz (SiO <sub>2</sub> )	33 mg/m <sup>3</sup>
57-55-6	Propylene glycol	1,300 mg/m <sup>3</sup>
78-83-1	butanol	1,300 ppm
108-83-8	2,6-dimethylheptan-4-one	330 ppm
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm
34590-94-8	Dipropylene glycol monomethyl ether	1700* ppm
70657-70-4	2-methoxypropyl acetate	1,000 ppm

(Contd. on page 5)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 02/21/2020

Reviewed on 02/21/2020

Trade name: **GTP310 2K URETHANE PRIMER**

(Contd. of page 4)

· <b>PAC-3:</b>		
1330-20-7	xylene	2500* ppm
13463-67-7	titanium dioxide	2,000 mg/m <sup>3</sup>
7727-43-7	barium sulphate, natural	990 mg/m <sup>3</sup>
123-86-4	n-butyl acetate	3000* ppm
78-93-3	butanone	4000* ppm
112926-00-8	Precipitated silica (Silica-Amorphous)	1,200 mg/m <sup>3</sup>
100-41-4	ethylbenzene	1800* ppm
108-88-3	toluene	3700* ppm
110-43-0	heptan-2-one	4000* ppm
77-58-7	dibutyltin dilaurate	48 mg/m <sup>3</sup>
1333-86-4	Carbon black	590 mg/m <sup>3</sup>
14808-60-7	Quartz (SiO <sub>2</sub> )	200 mg/m <sup>3</sup>
57-55-6	Propylene glycol	7,900 mg/m <sup>3</sup>
78-83-1	butanol	8000* ppm
108-83-8	2,6-dimethylheptan-4-one	2000* ppm
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm
34590-94-8	Dipropylene glycol monomethyl ether	9900** ppm
70657-70-4	2-methoxypropyl acetate	5,000 ppm

## 7 Handling and storage

- **Handling:**
- **Precautions for safe handling** Open and handle receptacle with care.
- **Information about protection against explosions and fires:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.  
Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**  
Keep receptacle tightly sealed.  
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

## 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**  
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.  
At this time, the remaining constituent has no known exposure limits.

(Contd. on page 6)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 02/21/2020

Reviewed on 02/21/2020

**Trade name: GTP310 2K URETHANE PRIMER**

(Contd. of page 5)

**1330-20-7 xylene**

PEL	Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
REL	Short-term value: 655 mg/m <sup>3</sup> , 150 ppm Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
TLV	Short-term value: 651 mg/m <sup>3</sup> , 150 ppm Long-term value: 434 mg/m <sup>3</sup> , 100 ppm BEI

**7727-43-7 barium sulphate, natural**

PEL	Long-term value: 15* 5** mg/m <sup>3</sup> *total dust **respirable fraction
REL	Long-term value: 10* 5** mg/m <sup>3</sup> *total dust **respirable fraction
TLV	Long-term value: 5* mg/m <sup>3</sup> *inhalable fraction; E

**123-86-4 n-butyl acetate**

PEL	Long-term value: 710 mg/m <sup>3</sup> , 150 ppm
REL	Short-term value: 950 mg/m <sup>3</sup> , 200 ppm Long-term value: 710 mg/m <sup>3</sup> , 150 ppm
TLV	Short-term value: 712 mg/m <sup>3</sup> , 150 ppm Long-term value: 238 mg/m <sup>3</sup> , 50 ppm

**78-93-3 butanone**

PEL	Long-term value: 590 mg/m <sup>3</sup> , 200 ppm
REL	Short-term value: 885 mg/m <sup>3</sup> , 300 ppm Long-term value: 590 mg/m <sup>3</sup> , 200 ppm
TLV	Short-term value: 885 mg/m <sup>3</sup> , 300 ppm Long-term value: 590 mg/m <sup>3</sup> , 200 ppm BEI

**1332-58-7 Kaolin**

PEL	Long-term value: 15* 5** mg/m <sup>3</sup> *total dust **respirable fraction
REL	Long-term value: 10* 5** mg/m <sup>3</sup> *total dust **respirable fraction
TLV	Long-term value: 2* mg/m <sup>3</sup> E; as respirable fraction

**112926-00-8 Precipitated silica (Silica-Amorphous)**

PEL	20mppcf or 80mg/m <sup>3</sup> /%SiO <sub>2</sub>
REL	Long-term value: 6 mg/m <sup>3</sup> See Pocket Guide App. C
TLV	TLV withdrawn

**100-41-4 ethylbenzene**

PEL	Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
REL	Short-term value: 545 mg/m <sup>3</sup> , 125 ppm Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
TLV	Long-term value: 87 mg/m <sup>3</sup> , 20 ppm BEI

(Contd. on page 7)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 02/21/2020

Reviewed on 02/21/2020

**Trade name: GTP310 2K URETHANE PRIMER**

(Contd. of page 6)

**108-88-3 toluene**

PEL	Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift
REL	Short-term value: 560 mg/m <sup>3</sup> , 150 ppm Long-term value: 375 mg/m <sup>3</sup> , 100 ppm
TLV	Long-term value: 75 mg/m <sup>3</sup> , 20 ppm BEI

**· Ingredients with biological limit values:**
**1330-20-7 xylene**

BEI	1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids
-----	--

**78-93-3 butanone**

BEI	2 mg/L Medium: urine Time: end of shift Parameter: MEK
-----	---

**100-41-4 ethylbenzene**

BEI	0.7 g/g creatinine Medium: urine Time: end of shift at end of workweek Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)
-	Medium: end-exhaled air Time: not critical Parameter: Ethyl benzene (semi-quantitative)

**108-88-3 toluene**

BEI	0.02 mg/L Medium: blood Time: prior to last shift of workweek Parameter: Toluene
	0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene
	0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background)

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing.  
Wash hands before breaks and at the end of work.

(Contd. on page 8)



# Safety Data Sheet

acc. to OSHA HCS

Printing date 02/21/2020

Reviewed on 02/21/2020

Trade name: **GTP310 2K URETHANE PRIMER**

(Contd. of page 7)

Store protective clothing separately.  
Avoid contact with the skin.  
Avoid contact with the eyes and skin.

- **Breathing equipment:** Not required.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.  
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Tightly sealed goggles

## 9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

**Form:** Liquid

**Color:** Grey

- **Odor:** Characteristic

- **Odor threshold:** Not determined.

- **pH-value:** Not determined (pH N/A in solvent coatings)

- **Change in condition**

**Melting point/Melting range:** Undetermined.

**Boiling point/Boiling range:** 79 °C (174.2 °F)

- **Flash point:** -4 °C (24.8 °F)

- **Flammability (solid, gaseous):** Not applicable.

- **Ignition temperature:** 370 °C (698 °F)

- **Decomposition temperature:** Not determined.

- **Auto igniting:** Product is not selfigniting.

(Contd. on page 9)

USA



# Safety Data Sheet

acc. to OSHA HCS

Printing date 02/21/2020

Reviewed on 02/21/2020

Trade name: **GTP310 2K URETHANE PRIMER**

(Contd. of page 8)

· <b>Danger of explosion:</b>	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· <b>Explosion limits:</b>	
<b>Lower:</b>	1.1 Vol %
<b>Upper:</b>	7 Vol %
· <b>Vapor pressure at 20 °C (68 °F):</b>	6.7 hPa (5 mm Hg)
· <b>Density at 20 °C (68 °F):</b>	1.34 g/cm <sup>3</sup> (11.1823 lbs/gal)
· <b>Relative density</b>	Not determined.
· <b>Vapor density</b>	Not determined.
· <b>Evaporation rate</b>	Not determined.
· <b>Solubility in / Miscibility with Water:</b>	Not miscible or difficult to mix.
· <b>Partition coefficient (n-octanol/water):</b>	Not determined.
· <b>Viscosity:</b>	
<b>Dynamic:</b>	Not determined.
<b>Kinematic:</b>	Not determined.
· <b>Solvent content:</b>	
<b>Organic solvents:</b>	38.0 %
<b>VOC content:</b>	37.97 %
	505.6 g/l / 4.22 lb/gal
<b>Solids content:</b>	62.0 %
· <b>Other information</b>	No further relevant information available.

## 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

## 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

### 1330-20-7 xylene

Oral	LD50	4,300 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** No irritating effect.
- **Sensitization:** No sensitizing effects known.

(Contd. on page 10)

USA

# Safety Data Sheet

acc. to OSHA HCS

Printing date 02/21/2020

Reviewed on 02/21/2020

Trade name: **GTP310 2K URETHANE PRIMER**

(Contd. of page 9)

- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:  
Irritant

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

1330-20-7	xylene	3
14807-96-6	Talc (Mg <sub>3</sub> H <sub>2</sub> (SiO <sub>3</sub> ) <sub>4</sub> )	3
13463-67-7	titanium dioxide	2B
112926-00-8	Precipitated silica (Silica-Amorphous)	3
100-41-4	ethylbenzene	2B
108-88-3	toluene	3
1333-86-4	Carbon black	2B
14808-60-7	Quartz (SiO <sub>2</sub> )	1

- **NTP (National Toxicology Program)**

14808-60-7	Quartz (SiO <sub>2</sub> )	K
------------	----------------------------	---

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

## 12 Ecological information

- **Toxicity**

- **Aquatic toxicity:** No further relevant information available.

- **Persistence and degradability** No further relevant information available.

- **Behavior in environmental systems:**

- **Bioaccumulative potential** No further relevant information available.

- **Mobility in soil** No further relevant information available.

- **Additional ecological information:**

- **General notes:**

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

- **Other adverse effects** No further relevant information available.

## 13 Disposal considerations

- **Waste treatment methods**

- **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- **Uncleaned packagings:**

- **Recommendation:** Disposal must be made according to official regulations.

USA

(Contd. on page 11)

# Safety Data Sheet

acc. to OSHA HCS



Printing date 02/21/2020

Reviewed on 02/21/2020

Trade name: **GTP310 2K URETHANE PRIMER**

(Contd. of page 10)

## 14 Transport information

<ul style="list-style-type: none"> <li>· <b>UN-Number</b></li> <li>· <b>DOT, IMDG, IATA</b></li> </ul>	UN1263
<ul style="list-style-type: none"> <li>· <b>UN proper shipping name</b></li> <li>· <b>DOT</b></li> <li>· <b>IMDG, IATA</b></li> </ul>	Paint PAINT
<ul style="list-style-type: none"> <li>· <b>Transport hazard class(es)</b></li> <li>· <b>DOT</b></li> </ul>	<div style="text-align: center;">  </div>
<ul style="list-style-type: none"> <li>· <b>Class</b></li> <li>· <b>Label</b></li> </ul>	3 Flammable liquids 3
<ul style="list-style-type: none"> <li>· <b>IMDG, IATA</b></li> </ul>	<div style="text-align: center;">  </div>
<ul style="list-style-type: none"> <li>· <b>Class</b></li> <li>· <b>Label</b></li> </ul>	3 Flammable liquids 3
<ul style="list-style-type: none"> <li>· <b>Packing group</b></li> <li>· <b>DOT, IMDG, IATA</b></li> </ul>	II
<ul style="list-style-type: none"> <li>· <b>Environmental hazards:</b></li> <li>· <b>Marine pollutant:</b></li> </ul>	No
<ul style="list-style-type: none"> <li>· <b>Special precautions for user</b></li> <li>· <b>Hazard identification number (Kemler code):</b></li> <li>· <b>EMS Number:</b></li> <li>· <b>Stowage Category</b></li> </ul>	Warning: Flammable liquids 33 F-E, S-E B
<ul style="list-style-type: none"> <li>· <b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b></li> </ul>	Not applicable.
<ul style="list-style-type: none"> <li>· <b>Transport/Additional information:</b></li> <li>· <b>DOT</b></li> <li>· <b>Quantity limitations</b></li> </ul>	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L
<ul style="list-style-type: none"> <li>· <b>IMDG</b></li> <li>· <b>Limited quantities (LQ)</b></li> <li>· <b>Excepted quantities (EQ)</b></li> </ul>	5L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
<ul style="list-style-type: none"> <li>· <b>UN "Model Regulation":</b></li> </ul>	UN 1263 PAINT, 3, II

USA

(Contd. on page 12)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 02/21/2020

Reviewed on 02/21/2020

Trade name: **GTP310 2K URETHANE PRIMER**

(Contd. of page 11)

## 15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

### · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

### · Section 313 (Specific toxic chemical listings):

1330-20-7	xylene
7727-43-7	barium sulphate, natural
100-41-4	ethylbenzene
108-88-3	toluene

### · TSCA (Toxic Substances Control Act):

1330-20-7	xylene	ACTIVE
14807-96-6	Talc (Mg <sub>3</sub> H <sub>2</sub> (SiO <sub>3</sub> ) <sub>4</sub> )	ACTIVE
13463-67-7	titanium dioxide	ACTIVE
7727-43-7	barium sulphate, natural	ACTIVE
123-86-4	n-butyl acetate	ACTIVE
78-93-3	butanone	ACTIVE
1332-58-7	Kaolin	ACTIVE
100-41-4	ethylbenzene	ACTIVE
108-88-3	toluene	ACTIVE
110-43-0	heptan-2-one	ACTIVE
77-58-7	dibutyltin dilaurate	ACTIVE
1333-86-4	Carbon black	ACTIVE
8002-74-2	Paraffin waxes and Hydrocarbon waxes	ACTIVE
64742-95-6	Solvent naphtha (petroleum), light arom.	ACTIVE
14808-60-7	Quartz (SiO <sub>2</sub> )	ACTIVE
57-55-6	Propylene glycol	ACTIVE
78-83-1	butanol	ACTIVE
108-83-8	2,6-dimethylheptan-4-one	ACTIVE
108-65-6	2-methoxy-1-methylethyl acetate	ACTIVE
34590-94-8	Dipropylene glycol monomethyl ether	ACTIVE

### · Hazardous Air Pollutants

1330-20-7	xylene
100-41-4	ethylbenzene
108-88-3	toluene

### · Proposition 65

#### · Chemicals known to cause cancer:

13463-67-7	titanium dioxide
100-41-4	ethylbenzene
1333-86-4	Carbon black
14808-60-7	Quartz (SiO <sub>2</sub> )

#### · Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

(Contd. on page 13)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 02/21/2020

Reviewed on 02/21/2020

Trade name: **GTP310 2K URETHANE PRIMER**

(Contd. of page 12)

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

108-88-3 toluene

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

1330-20-7	xylene	I
7727-43-7	barium sulphate, natural	D, CBD(inh), NL(oral)
78-93-3	butanone	I
100-41-4	ethylbenzene	D
108-88-3	toluene	II

· **TLV (Threshold Limit Value established by ACGIH)**

1330-20-7	xylene	A4
14807-96-6	Talc (Mg3H2(SiO3)4)	A4
13463-67-7	titanium dioxide	A4
1332-58-7	Kaolin	A4
100-41-4	ethylbenzene	A3
108-88-3	toluene	A4
77-58-7	dibutyltin dilaurate	A4
1333-86-4	Carbon black	A4
14808-60-7	Quartz (SiO2)	A2

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

13463-67-7	titanium dioxide
1333-86-4	Carbon black
14808-60-7	Quartz (SiO2)

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**

titanium dioxide

· **Hazard statements**

Highly flammable liquid and vapor.

Causes skin irritation.

Suspected of causing cancer.

Suspected of damaging fertility or the unborn child.

· **Precautionary statements**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

(Contd. on page 14)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 02/21/2020

Reviewed on 02/21/2020

**Trade name: GTP310 2K URETHANE PRIMER**

(Contd. of page 13)

Ground/bond container and receiving equipment.  
 Use explosion-proof electrical/ventilating/lighting/equipment.  
 Use only non-sparking tools.  
 Take precautionary measures against static discharge.  
 Wash thoroughly after handling.  
 Wear protective gloves/protective clothing/eye protection/face protection.  
 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
 IF exposed or concerned: Get medical advice/attention.  
 Specific treatment (see on this label).  
 Take off contaminated clothing and wash it before reuse.  
 If skin irritation occurs: Get medical advice/attention.  
 In case of fire: Use for extinction: CO<sub>2</sub>, powder or water spray.  
 Store in a well-ventilated place. Keep cool.  
 Store locked up.  
 Dispose of contents/container in accordance with local/regional/national/international regulations.  
 · **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16 Other information

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

- **Department issuing SDS:** Environment protection department.
- **Contact:** Product Safety Dept.
- **Date of preparation / last revision** 02/21/2020 / 3
- **Abbreviations and acronyms:**  
 IMDG: International Maritime Code for Dangerous Goods  
 DOT: US Department of Transportation  
 IATA: International Air Transport Association  
 ACGIH: American Conference of Governmental Industrial Hygienists  
 EINECS: European Inventory of Existing Commercial Chemical Substances  
 ELINCS: European List of Notified Chemical Substances  
 CAS: Chemical Abstracts Service (division of the American Chemical Society)  
 NFPA: National Fire Protection Association (USA)  
 HMIS: Hazardous Materials Identification System (USA)  
 VOC: Volatile Organic Compounds (USA, EU)  
 LC50: Lethal concentration, 50 percent  
 LD50: Lethal dose, 50 percent  
 PBT: Persistent, Bioaccumulative and Toxic  
 vPvB: very Persistent and very Bioaccumulative  
 NIOSH: National Institute for Occupational Safety  
 OSHA: Occupational Safety & Health  
 TLV: Threshold Limit Value  
 PEL: Permissible Exposure Limit  
 REL: Recommended Exposure Limit  
 BEI: Biological Exposure Limit  
 Flam. Liq. 2: Flammable liquids – Category 2  
 Skin Irrit. 2: Skin corrosion/irritation – Category 2  
 Carc. 2: Carcinogenicity – Category 2  
 Repr. 2: Reproductive toxicity – Category 2
- **\* Data compared to the previous version altered.**

USA