

Safety Data Sheet
acc. to OSHA HCS

Printing date 09/08/2025

Reviewed on 09/08/2025

1 Identification

- **Product identifier**
- **Trade name:** P7.3.K1 2K URETHANE PRIMER
- **Article number:** P7.3.K1
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
GlobalStar is a product of Lusid Technologies Inc.
4725 S Camp Kearns Road
Kearns, UT 84118
(801) 966-5300
info@lusidtechnologies.com
- **Information department:** Product safety department
- **Emergency telephone number:**
24 Hrs Emergency Contact:
INFOTRAC
1-800-535-5053

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flammable Liquids 2

H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Carcinogenicity 1B

H350 May cause cancer. Route of exposure:
Inhalation.

Toxic to Reproduction 1B

H360 May damage fertility or the unborn child.

Specific Target Organ Toxicity - Repeated Exposure 2

H373 May cause damage to the hearing organs
through prolonged or repeated exposure.



GHS07

Skin Irritation 2

H315 Causes skin irritation.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/08/2025

Reviewed on 09/08/2025

Trade name: P7.3.K1 2K URETHANE PRIMER

(Contd. of page 1)

· Hazard pictograms



GHS02 GHS07 GHS08

· Signal word Danger

· Hazard-determining components of labeling:

Talc ($\text{Mg}_3\text{H}_2(\text{SiO}_3)_4$)
ethylbenzene
toluene
titanium dioxide

· Hazard statements

Highly flammable liquid and vapor.
Causes skin irritation.
May cause cancer. Route of exposure: Inhalation.
May damage fertility or the unborn child.
May cause damage to the hearing organs through prolonged or repeated exposure.

· Precautionary statements

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Keep container tightly closed.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting/equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Do not breathe dust/fume/gas/mist/vapors/spray.
Wash thoroughly after handling.
Wear protective gloves/protective clothing/eye protection/face protection.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
If exposed or concerned: Get medical advice/attention.
Specific treatment (see on this label).
Get medical advice/attention if you feel unwell.
Take off contaminated clothing and wash it before reuse.
If skin irritation occurs: Get medical advice/attention.
In case of fire: Use CO_2 , powder or water spray to extinguish.
Store in a well-ventilated place. Keep cool.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.

· Classification system:

· NFPA ratings (scale 0 - 4)



Health = 1
Fire = 3
Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = *1
Fire = 3
Reactivity = 0

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/08/2025

Reviewed on 09/08/2025

Trade name: P7.3.K1 2K URETHANE PRIMER

(Contd. of page 2)

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

1330-20-7	xylene	25-50%
14807-96-6	Talc (Mg ₃ H ₂ (SiO ₃) ₄)	2.5-10%
123-86-4	n-butyl acetate	2.5-10%
78-93-3	butanone	2.5-10%
13463-67-7	titanium dioxide	2.5-10%
7727-43-7	barium sulphate, natural	2.5-10%
100-41-4	ethylbenzene	≤2.5%
108-88-3	toluene	≤2.5%
77-58-7	dibutyltin dilaurate	≤2.5%

4 First-aid measures

- **Description of first aid measures**
- **General information:**
Immediately remove any clothing soiled by the product.
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

USA

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/08/2025

Reviewed on 09/08/2025

Trade name: P7.3.K1 2K URETHANE PRIMER

(Contd. of page 3)

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Protective Action Criteria for Chemicals

PAC-1:

1330-20-7	xylene	130 ppm
123-86-4	n-butyl acetate	5 ppm
78-93-3	butanone	200 ppm
13463-67-7	titanium dioxide	30 mg/m ³
7727-43-7	barium sulphate, natural	15 mg/m ³
100-41-4	ethylbenzene	33 ppm
9002-88-4	Polyethylene low density	16 mg/m ³
112926-00-8	Precipitated silica (Silica-Amorphous)	18 mg/m ³
108-88-3	toluene	67 ppm
110-43-0	heptan-2-one	150 ppm
77-58-7	dibutyltin dilaurate	1.1 mg/m ³
1333-86-4	Carbon black	9 mg/m ³
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
14808-60-7	Quartz (SiO ₂)	0.075 mg/m ³
57-55-6	Propylene glycol	30 mg/m ³
78-83-1	butanol	150 ppm

PAC-2:

1330-20-7	xylene	920* ppm
123-86-4	n-butyl acetate	200 ppm
78-93-3	butanone	2700* ppm
13463-67-7	titanium dioxide	330 mg/m ³
7727-43-7	barium sulphate, natural	170 mg/m ³
100-41-4	ethylbenzene	1100 ppm
9002-88-4	Polyethylene low density	170 mg/m ³
112926-00-8	Precipitated silica (Silica-Amorphous)	200 mg/m ³
108-88-3	toluene	560 ppm
110-43-0	heptan-2-one	670 ppm
77-58-7	dibutyltin dilaurate	3.8 mg/m ³

(Contd. on page 5)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/08/2025

Reviewed on 09/08/2025

Trade name: P7.3.K1 2K URETHANE PRIMER

(Contd. of page 4)

1333-86-4	Carbon black	290 mg/m ³
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm
14808-60-7	Quartz (SiO ₂)	8.3 mg/m ³
57-55-6	Propylene glycol	1,300 mg/m ³
78-83-1	butanol	1,300 ppm
PAC-3:		
1330-20-7	xylene	2500* ppm
123-86-4	n-butyl acetate	3000* ppm
78-93-3	butanone	4000* ppm
13463-67-7	titanium dioxide	2,000 mg/m ³
7727-43-7	barium sulphate, natural	990 mg/m ³
100-41-4	ethylbenzene	1800 ppm
9002-88-4	Polyethylene low density	1,000 mg/m ³
112926-00-8	Precipitated silica (Silica-Amorphous)	1,200 mg/m ³
108-88-3	toluene	3700 ppm
110-43-0	heptan-2-one	4000* ppm
77-58-7	dibutyltin dilaurate	23 mg/m ³
1333-86-4	Carbon black	1750 mg/m ³
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm
14808-60-7	Quartz (SiO ₂)	50 mg/m ³
57-55-6	Propylene glycol	7,900 mg/m ³
78-83-1	butanol	8000* ppm

7 Handling and storage

- Handling:**

- Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.

- Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.

- Conditions for safe storage, including any incompatibilities**

- Storage:**

- Requirements to be met by storerooms and receptacles:** Store in a cool location.

- Information about storage in one common storage facility:** Not required.

- Further information about storage conditions:**

Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.

- Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- Additional information about design of technical systems:** No further data; see section 7.

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/08/2025

Reviewed on 09/08/2025

Trade name: P7.3.K1 2K URETHANE PRIMER

(Contd. of page 5)

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

1330-20-7 xylene

PEL	Long-term value: 435 mg/m ³ , 100 ppm
REL	Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV	Long-term value: 20 ppm BEI, A4

123-86-4 n-butyl acetate

PEL	Long-term value: 710 mg/m ³ , 150 ppm
REL	Short-term value: 950 mg/m ³ , 200 ppm Long-term value: 710 mg/m ³ , 150 ppm
TLV	Short-term value: 712 mg/m ³ , 150 ppm Long-term value: 238 mg/m ³ , 50 ppm

78-93-3 butanone

PEL	Long-term value: 590 mg/m ³ , 200 ppm
REL	Short-term value: 885 mg/m ³ , 300 ppm Long-term value: 590 mg/m ³ , 200 ppm
TLV	Short-term value: 150 ppm Long-term value: 75 ppm BEI, Skin

7727-43-7 barium sulphate, natural

PEL	Long-term value: 15* 5** mg/m ³ *total dust **respirable fraction
REL	Long-term value: 10* 5** mg/m ³ *total dust **respirable fraction
TLV	Long-term value: 5* mg/m ³ *inhalable fraction; E

100-41-4 ethylbenzene

PEL	Long-term value: 435 mg/m ³ , 100 ppm
REL	Short-term value: 545 mg/m ³ , 125 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV	Long-term value: 20 ppm OTO, BEI, A3

108-88-3 toluene

PEL	Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift
REL	Short-term value: 560 mg/m ³ , 150 ppm Long-term value: 375 mg/m ³ , 100 ppm
TLV	Long-term value: 20 ppm BEI, OTO, A4

(Contd. on page 7)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/08/2025

Reviewed on 09/08/2025

Trade name: **P7.3.K1 2K URETHANE PRIMER**

(Contd. of page 6)

77-58-7 dibutyltin dilaurate

PEL Long-term value: 0.1 mg/m³
as Sn

REL Long-term value: 0.1 mg/m³
as Sn, Skin

TLV Short-term value: 0.2 mg/m³
Long-term value: 0.1 mg/m³
as Sn; A4; Skin

· Ingredients with biological limit values:**1330-20-7 xylene**

BEI 0.3 g/g creatinine
Medium: urine
Time: end of shift
Parameter: Methylhippuric acids

78-93-3 butanone

BEI 2 mg/L
Medium: urine
Time: end of shift
Parameter: Methyl ethyl ketone (nonspecific)

100-41-4 ethylbenzene

BEI 0.15 g/g creatinine
Medium: urine
Time: end of shift
Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific)

108-88-3 toluene

BEI 0.02 mg/L
Medium: blood
Time: prior to last shift of workweek
Parameter: Toluene

0.03 mg/L
Medium: urine
Time: end of shift
Parameter: Toluene

0.3 mg/g creatinine
Medium: urine
Time: end of shift
Parameter: o-Cresol with hydrolysis (background)

· Additional information: The lists that were valid during the creation were used as basis.**· Exposure controls****· Personal protective equipment:****· General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

(Contd. on page 8)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/08/2025

Reviewed on 09/08/2025

Trade name: P7.3.K1 2K URETHANE PRIMER

(Contd. of page 7)

- **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

Form:

Liquid

Color:

Grey

- **Odor:**

Characteristic

- **Odor threshold:**

Not determined.

- **pH-value:**

Not determined (pH N/A in solvent coatings)

- **Change in condition**

Melting point/Melting range:

Undetermined.

Boiling point/Boiling range:

79-80.5 °C (174.2-176.9 °F)

- **Flash point:**

-4 °C (24.8 °F)

- **Flammability:**

Highly flammable.

- **Auto igniting:**

370 °C (698 °F)

- **Decomposition temperature:**

Not determined.

- **Ignition temperature:**

Product is not selfigniting.

- **Danger of explosion:**

Product is not explosive. However, formation of explosive air/ vapor mixtures are possible.

(Contd. on page 9)

-USA-

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/08/2025

Reviewed on 09/08/2025

Trade name: P7.3.K1 2K URETHANE PRIMER

(Contd. of page 8)

- | | |
|---|--|
| · Explosion limits: | |
| Lower: | 1.1 Vol % |
| Upper: | 7 Vol % |
| · Vapor pressure at 20 °C (68 °F): | 6.7-8.2 hPa (5-6.2 mm Hg) |
| · Density at 20 °C (68 °F): | 1.3447 g/cm ³ (11.2215 lbs/gal) |
| · Relative density | Not determined. |
| · Vapor density | Not determined. |
| · Evaporation rate | Not determined. |
| · Solubility in / Miscibility with Water: | Fully miscible. |
| · Partition coefficient (n-octanol/water): | Not determined. |
| · Viscosity: | |
| Dynamic: | Not determined. |
| Kinematic: | Not determined. |
| · Solvent content: | |
| Organic solvents: | 55.6 % |
| VOC content: | 55.57 % |
| | 516.2 g/l / 4.31 lb/gal |
| · Solids content: | 61.5 % |
| · Other information | No further relevant information available. |

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
 - **Acute toxicity:**
 - **LD/LC50 values that are relevant for classification:**
- | | | |
|------------------|------|----------------------|
| 1330-20-7 xylene | | |
| Oral | LD50 | 4,300 mg/kg (rat) |
| Dermal | LD50 | 2,000 mg/kg (rabbit) |
- **Primary irritant effect:**
 - **on the skin:** Irritant to skin and mucous membranes.
 - **on the eye:** No irritating effect.
 - **Sensitization:** No sensitizing effects known.

(Contd. on page 10)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/08/2025

Reviewed on 09/08/2025

Trade name: P7.3.K1 2K URETHANE PRIMER

(Contd. of page 9)

- Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

- Carcinogenic categories**

- IARC (International Agency for Research on Cancer)**

1330-20-7	xylene	3
14807-96-6	Talc (Mg ₃ H ₂ (SiO ₃) ₄)	2A
13463-67-7	titanium dioxide	2B
100-41-4	ethylbenzene	2B
9002-88-4	Polyethylene low density	3
112926-00-8	Precipitated silica (Silica-Amorphous)	3
108-88-3	toluene	3
1333-86-4	Carbon black	2B
14808-60-7	Quartz (SiO ₂)	1

- NTP (National Toxicology Program)**

14808-60-7	Quartz (SiO ₂)	K
------------	----------------------------	---

- OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- Toxicity**

- Aquatic toxicity:** No further relevant information available.

- Persistence and degradability** No further relevant information available.

- Behavior in environmental systems:**

- Bioaccumulative potential** No further relevant information available.

- Mobility in soil** No further relevant information available.

- Additional ecological information:**

- General notes:**

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- Results of PBT and vPvB assessment**

- PBT:** Not applicable.

- vPvB:** Not applicable.

- Other adverse effects** No further relevant information available.

13 Disposal considerations

- Waste treatment methods**

- Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- Uncleaned packagings:**

- Recommendation:** Disposal must be made according to official regulations.

(Contd. on page 11)

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/08/2025



Reviewed on 09/08/2025

Trade name: P7.3.K1 2K URETHANE PRIMER

(Contd. of page 10)

· Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information

· UN-Number	UN1263
· DOT, IMDG, IATA	
· UN proper shipping name	Paint
· DOT	PAINT
· IMDG, IATA	
· Transport hazard class(es)	
· DOT	
	
· Class	3 Flammable liquids
· Label	3
· IMDG, IATA	
	
· Class	3 Flammable liquids
· Label	3
· Packing group	
· DOT, IMDG, IATA	II
· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Warning: Flammable liquids
· Hazard identification number (Kemler code):	33
· EMS Number:	F-E, S-E
· Stowage Category	B
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· DOT	
· Quantity limitations	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

(Contd. on page 12)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/08/2025

Reviewed on 09/08/2025

Trade name: P7.3.K1 2K URETHANE PRIMER

(Contd. of page 11)

· UN "Model Regulation":

UN 1263 PAINT, 3, II

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

1330-20-7 xylene

7727-43-7 barium sulphate, natural

100-41-4 ethylbenzene

108-88-3 toluene

· TSCA (Toxic Substances Control Act):

1330-20-7 xylene

ACTIVE

14807-96-6 Talc (Mg₃H₂(SiO₃)₄)

ACTIVE

123-86-4 n-butyl acetate

ACTIVE

78-93-3 butanone

ACTIVE

13463-67-7 titanium dioxide

ACTIVE

7727-43-7 barium sulphate, natural

ACTIVE

100-41-4 ethylbenzene

ACTIVE

1332-58-7 Kaolin

ACTIVE

9002-88-4 Polyethylene low density

ACTIVE

108-88-3 toluene

ACTIVE

110-43-0 heptan-2-one

ACTIVE

77-58-7 dibutyltin dilaurate

ACTIVE

1333-86-4 Carbon black

ACTIVE

108-65-6 2-methoxy-1-methylethyl acetate

ACTIVE

14808-60-7 Quartz (SiO₂)

ACTIVE

57-55-6 Propylene glycol

ACTIVE

78-83-1 butanol

ACTIVE

· Hazardous Air Pollutants

1330-20-7 xylene

100-41-4 ethylbenzene

108-88-3 toluene

· Proposition 65

· Chemicals known to cause cancer:

13463-67-7 titanium dioxide

100-41-4 ethylbenzene

1333-86-4 Carbon black

14808-60-7 Quartz (SiO₂)

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

(Contd. on page 13)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/08/2025

Reviewed on 09/08/2025

Trade name: P7.3.K1 2K URETHANE PRIMER

(Contd. of page 12)

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

108-88-3 toluene

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

1330-20-7	xylene	I
78-93-3	butanone	I
7727-43-7	barium sulphate, natural	D, CBD(inh), NL(oral)
100-41-4	ethylbenzene	D
108-88-3	toluene	II

· **TLV (Threshold Limit Value)**

1330-20-7	xylene	A4
14807-96-6	Talc (Mg ₃ H ₂ (SiO ₃) ₄)	A4
13463-67-7	titanium dioxide	A4
100-41-4	ethylbenzene	A3
1332-58-7	Kaolin	A4
108-88-3	toluene	A4
77-58-7	dibutyltin dilaurate	A4
1333-86-4	Carbon black	A4
14808-60-7	Quartz (SiO ₂)	A2

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

13463-67-7	titanium dioxide
1333-86-4	Carbon black
14808-60-7	Quartz (SiO ₂)

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**

Talc (Mg₃H₂(SiO₃)₄)

ethylbenzene

toluene

titanium dioxide

· **Hazard statements**

Highly flammable liquid and vapor.

Causes skin irritation.

May cause cancer. Route of exposure: Inhalation.

May damage fertility or the unborn child.

May cause damage to the hearing organs through prolonged or repeated exposure.

(Contd. on page 14)

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/08/2025

Reviewed on 09/08/2025

Trade name: **P7.3.K1 2K URETHANE PRIMER**

(Contd. of page 13)

Precautionary statements

Obtain special instructions before use.
 Do not handle until all safety precautions have been read and understood.
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
 Keep container tightly closed.
 Ground/bond container and receiving equipment.
 Use explosion-proof electrical/ventilating/lighting/equipment.
 Use only non-sparking tools.
 Take precautionary measures against static discharge.
 Do not breathe dust/fume/gas/mist/vapors/spray.
 Wash thoroughly after handling.
 Wear protective gloves/protective clothing/eye protection/face protection.
 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 IF exposed or concerned: Get medical advice/attention.
 Specific treatment (see on this label).
 Get medical advice/attention if you feel unwell.
 Take off contaminated clothing and wash it before reuse.
 If skin irritation occurs: Get medical advice/attention.
 In case of fire: Use CO₂, powder or water spray to extinguish.
 Store in a well-ventilated place. Keep cool.
 Store locked up.
 Dispose of contents/container in accordance with local/regional/national/international regulations.

National regulations:

Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Department issuing SDS: Environment protection department.

Contact: Product Safety Dept.

Date of preparation / last revision 09/08/2025 / 6

Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods
 DOT: US Department of Transportation
 IATA: International Air Transport Association
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 NFPA: National Fire Protection Association (USA)
 HMIS: Hazardous Materials Identification System (USA)
 VOC: Volatile Organic Compounds (USA, EU)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative
 NIOSH: National Institute for Occupational Safety
 OSHA: Occupational Safety & Health
 TLV: Threshold Limit Value
 PEL: Permissible Exposure Limit
 REL: Recommended Exposure Limit
 BEI: Biological Exposure Limit
 Flammable Liquids 2: Flammable liquids – Category 2
 Skin Irritation 2: Skin corrosion/irritation – Category 2

(Contd. on page 15)

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/08/2025

Reviewed on 09/08/2025

Trade name: P7.3.K1 2K URETHANE PRIMER

(Contd. of page 14)

*Carcinogenicity 1B: Carcinogenicity – Category 1B**Toxic to Reproduction 1B: Reproductive toxicity – Category 1B**Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) – Category 2**** Data compared to the previous version altered.**

USA