

Safety Data Sheet acc. to OSHA HCS

Printing date 08/26/2025

Reviewed on 08/26/2025

1 Identification

- **Product identifier**
- **Trade name:** 928WN0006 FLEET WHITE
- **Article number:** 928WN0006
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
NorthStar is a product of Lusid Technologies Inc
4725 S Camp Kearns Road
Kearns, UT 84118
(801) 966-5300
info@lusidtechnologies.com
- **Information department:** Product safety department
- **Emergency telephone number:**
24 Hrs Emergency Contact:
INFOTRAC
1-800-535-5053

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flammable Liquids 3 H226 Flammable liquid and vapor.



GHS08 Health hazard

Carcinogenicity 2 H351 Suspected of causing cancer. Route of exposure: Inhalation.
Toxic to Reproduction 1B H360 May damage fertility or the unborn child.



GHS07

Sensitization - Skin 1 H317 May cause an allergic skin reaction.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02



GHS07



GHS08

(Contd. on page 2)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/26/2025

Reviewed on 08/26/2025

Trade name: 928WN0006 FLEET WHITE

(Contd. of page 1)

· **Signal word** Danger

· **Hazard-determining components of labeling:**

titanium dioxide
2-ethylhexanoic acid
ethylbenzene
bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate

· **Hazard statements**

Flammable liquid and vapor.
May cause an allergic skin reaction.
Suspected of causing cancer. Route of exposure: Inhalation.
May damage fertility or the unborn child.

· **Precautionary statements**

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Keep container tightly closed.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting/equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Avoid breathing dust/fume/gas/mist/vapors/spray
Contaminated work clothing must not be allowed out of the workplace.
Wear protective gloves/protective clothing/eye protection/face protection.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
If exposed or concerned: Get medical advice/attention.
Specific treatment (see on this label).
If skin irritation or rash occurs: Get medical advice/attention.
Wash contaminated clothing before reuse.
In case of fire: Use CO₂, powder or water spray to extinguish.
Store in a well-ventilated place. Keep cool.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



· **HMIS-ratings (scale 0 - 4)**



· **Other hazards**

· **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Mixture of the substances listed below with nonhazardous additions.

(Contd. on page 3)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/26/2025

Reviewed on 08/26/2025

Trade name: 928WN0006 FLEET WHITE

(Contd. of page 2)

· Dangerous components:		
13463-67-7	titanium dioxide	10-25%
123-86-4	n-butyl acetate	10-25%
110-43-0	heptan-2-one	10-25%
123-54-6	pentane-2,4-dione	≤2.5%
100-41-4	ethylbenzene	≤2.5%
149-57-5	2-ethylhexanoic acid	≤2.5%
41556-26-7	bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate	≤2.5%

4 First-aid measures

- **Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

(Contd. on page 4)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/26/2025

Reviewed on 08/26/2025

Trade name: 928WN0006 FLEET WHITE

(Contd. of page 3)

· Protective Action Criteria for Chemicals

· PAC-1:

13463-67-7	titanium dioxide	30 mg/m ³
123-86-4	n-butyl acetate	5 ppm
110-43-0	heptan-2-one	150 ppm
123-54-6	pentane-2,4-dione	75 ppm
1330-20-7	xylene	130 ppm
100-41-4	ethylbenzene	33 ppm
149-57-5	2-ethylhexanoic acid	15 mg/m ³
108-38-3	m-xylene	130 ppm
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
77-58-7	dibutyltin dilaurate	1.1 mg/m ³
122-99-6	2-phenoxyethanol	1.5 ppm
1333-86-4	Carbon black	9 mg/m ³
14808-60-7	Quartz (SiO ₂)	0.075 mg/m ³
34590-94-8	Dipropylene glycol monomethyl ether	150 ppm
7664-38-2	phosphoric acid	3 mg/m ³
57-55-6	Propylene glycol	30 mg/m ³
78-83-1	butanol	150 ppm
108-83-8	2,6-dimethylheptan-4-one	75 ppm
70657-70-4	2-methoxypropyl acetate	50 ppm

· PAC-2:

13463-67-7	titanium dioxide	330 mg/m ³
123-86-4	n-butyl acetate	200 ppm
110-43-0	heptan-2-one	670 ppm
123-54-6	pentane-2,4-dione	110 ppm
1330-20-7	xylene	920* ppm
100-41-4	ethylbenzene	1100 ppm
149-57-5	2-ethylhexanoic acid	99 mg/m ³
108-38-3	m-xylene	920 ppm
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm
77-58-7	dibutyltin dilaurate	3.8 mg/m ³
122-99-6	2-phenoxyethanol	16 ppm
1333-86-4	Carbon black	290 mg/m ³
14808-60-7	Quartz (SiO ₂)	8.3 mg/m ³
34590-94-8	Dipropylene glycol monomethyl ether	1700* ppm
7664-38-2	phosphoric acid	30 mg/m ³
57-55-6	Propylene glycol	1,300 mg/m ³
78-83-1	butanol	1,300 ppm
108-83-8	2,6-dimethylheptan-4-one	330 ppm
70657-70-4	2-methoxypropyl acetate	1,000 ppm

· PAC-3:

13463-67-7	titanium dioxide	2,000 mg/m ³
123-86-4	n-butyl acetate	3000* ppm

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/26/2025

Reviewed on 08/26/2025

Trade name: 928WN0006 FLEET WHITE

		(Contd. of page 4)
110-43-0	heptan-2-one	4000* ppm
123-54-6	pentane-2,4-dione	200 ppm
1330-20-7	xylene	2500* ppm
100-41-4	ethylbenzene	1800 ppm
149-57-5	2-ethylhexanoic acid	590 mg/m ³
108-38-3	m-xylene	2500* ppm
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm
77-58-7	dibutyltin dilaurate	23 mg/m ³
122-99-6	2-phenoxyethanol	97 ppm
1333-86-4	Carbon black	1750 mg/m ³
14808-60-7	Quartz (SiO ₂)	50 mg/m ³
34590-94-8	Dipropylene glycol monomethyl ether	9900** ppm
7664-38-2	phosphoric acid	150 mg/m ³
57-55-6	Propylene glycol	7,900 mg/m ³
78-83-1	butanol	8000* ppm
108-83-8	2,6-dimethylheptan-4-one	2000* ppm
70657-70-4	2-methoxypropyl acetate	5,000 ppm

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
 Ensure good ventilation/exhaustion at the workplace.
 Open and handle receptacle with care.
 Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
 Keep ignition sources away - Do not smoke.
 Protect against electrostatic charges.
 Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see section 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
 The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
 At this time, the other constituents have no known exposure limits.

(Contd. on page 6)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/26/2025

Reviewed on 08/26/2025

Trade name: 928WN0006 FLEET WHITE

(Contd. of page 5)

123-86-4 n-butyl acetate

PEL	Long-term value: 710 mg/m ³ , 150 ppm
REL	Short-term value: 950 mg/m ³ , 200 ppm Long-term value: 710 mg/m ³ , 150 ppm
TLV	Short-term value: 712 mg/m ³ , 150 ppm Long-term value: 238 mg/m ³ , 50 ppm

110-43-0 heptan-2-one

PEL	Long-term value: 465 mg/m ³ , 100 ppm
REL	Long-term value: 465 mg/m ³ , 100 ppm
TLV	Long-term value: 50 ppm

123-54-6 pentane-2,4-dione

TLV	Long-term value: 102 mg/m ³ , 25 ppm Skin
-----	---

100-41-4 ethylbenzene

PEL	Long-term value: 435 mg/m ³ , 100 ppm
REL	Short-term value: 545 mg/m ³ , 125 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV	Long-term value: 20 ppm OTO, BEI, A3

149-57-5 2-ethylhexanoic acid

TLV	Long-term value: 5* mg/m ³ *as inhalable fraction and vapor
-----	---

Ingredients with biological limit values:**100-41-4 ethylbenzene**

BEI	0.15 g/g creatinine Medium: urine Time: end of shift Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific)
-----	--

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Store protective clothing separately.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/26/2025

Reviewed on 08/26/2025

Trade name: 928WN0006 FLEET WHITE

(Contd. of page 6)

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

Form:	Liquid
Color:	White
Odor:	Characteristic
Odor threshold:	Not determined.

- **pH-value:** Not determined (pH N/A in solvent coatings)

- **Change in condition**

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	124-128 °C (255.2-262.4 °F)

- **Flash point:** 27 °C (80.6 °F)

- **Flammability:** Flammable.

- **Auto igniting:** 370 °C (698 °F)

- **Decomposition temperature:** Not determined.

- **Ignition temperature:** Product is not selfigniting.

- **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

- **Explosion limits:**

Lower:	1 Vol %
Upper:	7.5 Vol %

- **Vapor pressure at 20 °C (68 °F):** 10.7 hPa (8 mm Hg)

- **Vapor pressure at 50 °C (122 °F):** 55 hPa (41.3 mm Hg)

- **Density at 20 °C (68 °F):** 1.2818 g/cm³ (10.6966 lbs/gal)

- **Relative density** Not determined.

- **Vapor density** Not determined.

- **Evaporation rate** Not determined.

- **Solubility in / Miscibility with**

- **Water:** Not miscible or difficult to mix.

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/26/2025

Reviewed on 08/26/2025

Trade name: 928WN0006 FLEET WHITE

(Contd. of page 7)

- **Partition coefficient (n-octanol/water):** Not determined.

- **Viscosity:**

- **Dynamic:** Not determined.

- **Kinematic:** Not determined.

- **Solvent content:**

- **Organic solvents:** 25.5 %

- **VOC content:** 25.49 %
370.3 g/l / 3.09 lb/gal

- **Solids content:** 71.1 %

- **Other information** No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.

- **Chemical stability**

- **Thermal decomposition / conditions to be avoided:**

- No decomposition if used according to specifications.

- **Possibility of hazardous reactions** No dangerous reactions known.

- **Conditions to avoid** No further relevant information available.

- **Incompatible materials:** No further relevant information available.

- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**

- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

110-43-0 heptan-2-one

Oral	LD50	1,670 mg/kg (rat)
Dermal	LD50	12,600 mg/kg (rabbit)

- **Primary irritant effect:**

- **on the skin:** No irritant effect.

- **on the eye:** No irritating effect.

- **Sensitization:** Sensitization possible through skin contact.

- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

13463-67-7	titanium dioxide	2B
1330-20-7	xylene	3
100-41-4	ethylbenzene	2B
95-47-6	o-xylene	3
106-42-3	p-xylene	3

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/26/2025

Reviewed on 08/26/2025

Trade name: 928WN0006 FLEET WHITE

(Contd. of page 8)

108-38-3	m-xylene	3
1333-86-4	Carbon black	2B
14808-60-7	Quartz (SiO ₂)	1
· NTP (National Toxicology Program)		
14808-60-7	Quartz (SiO ₂)	K
· OSHA-Ca (Occupational Safety & Health Administration)		
None of the ingredients is listed.		

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- | | |
|----------------------------------|--------|
| · UN-Number | |
| · DOT, IMDG, IATA | UN1263 |
| · UN proper shipping name | |
| · DOT | Paint |
| · IMDG, IATA | PAINT |

(Contd. on page 10)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/26/2025

Reviewed on 08/26/2025

Trade name: 928WN0006 FLEET WHITE

(Contd. of page 9)

· **Transport hazard class(es)**· **DOT**· **Class**

3 Flammable liquids

· **Label**

3

· **IMDG, IATA**· **Class**

3 Flammable liquids

· **Label**

3

· **Packing group**· **DOT, IMDG, IATA**

III

· **Environmental hazards:**· **Marine pollutant:**

No

· **Special precautions for user**

Warning: Flammable liquids

· **Hazard identification number (Kemler code):** 30· **EMS Number:**

F-E, S-E

· **Stowage Category**

A

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

Not applicable.

· **Transport/Additional information:**· **DOT**· **Quantity limitations**

On passenger aircraft/rail: 60 L

On cargo aircraft only: 220 L

· **IMDG**· **Limited quantities (LQ)**

5L

· **Excepted quantities (EQ)**

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· **UN "Model Regulation":**

UN 1263 PAINT, 3, III

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**
No further relevant information available.

· **Sara**· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

(Contd. on page 11)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/26/2025

Reviewed on 08/26/2025

Trade name: 928WN0006 FLEET WHITE

(Contd. of page 10)

Section 313 (Specific toxic chemical listings):

1330-20-7	xylene
100-41-4	ethylbenzene
95-47-6	o-xylene
106-42-3	p-xylene
108-38-3	m-xylene
122-99-6	2-phenoxyethanol
7664-38-2	phosphoric acid

TSCA (Toxic Substances Control Act):

13463-67-7	titanium dioxide	ACTIVE
123-86-4	n-butyl acetate	ACTIVE
110-43-0	heptan-2-one	ACTIVE
123-54-6	pentane-2,4-dione	ACTIVE
1330-20-7	xylene	ACTIVE
100-41-4	ethylbenzene	ACTIVE
149-57-5	2-ethylhexanoic acid	ACTIVE
95-47-6	o-xylene	ACTIVE
106-42-3	p-xylene	ACTIVE
108-38-3	m-xylene	ACTIVE
64742-47-8	Distillates (petroleum), hydrotreated light	ACTIVE
41556-26-7	bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate	ACTIVE
108-65-6	2-methoxy-1-methylethyl acetate	ACTIVE
82919-37-7	methyl 1,2,2,6,6-pentamethyl-4-piperidylsebacate	ACTIVE
77-58-7	dibutyltin dilaurate	ACTIVE
122-99-6	2-phenoxyethanol	ACTIVE
51274-00-1	BAYFERROX 3910	ACTIVE
1333-86-4	Carbon black	ACTIVE
1047-16-1	Quinacridone	ACTIVE
64742-95-6	Solvent naphtha (petroleum), light arom.	ACTIVE
147-14-8	Phthalocyanine Blue	ACTIVE
14808-60-7	Quartz (SiO ₂)	ACTIVE
34590-94-8	Dipropylene glycol monomethyl ether	ACTIVE
7664-38-2	phosphoric acid	ACTIVE
57-55-6	Propylene glycol	ACTIVE
78-83-1	butanol	ACTIVE
108-83-8	2,6-dimethylheptan-4-one	ACTIVE

Hazardous Air Pollutants

1330-20-7	xylene
100-41-4	ethylbenzene
95-47-6	o-xylene
106-42-3	p-xylene
108-38-3	m-xylene

(Contd. on page 12)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/26/2025

Reviewed on 08/26/2025

Trade name: 928WN0006 FLEET WHITE

(Contd. of page 11)

· Proposition 65

· Chemicals known to cause cancer:

13463-67-7	titanium dioxide
100-41-4	ethylbenzene
1333-86-4	Carbon black
14808-60-7	Quartz (SiO ₂)

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

1330-20-7	xylene	I
100-41-4	ethylbenzene	D
95-47-6	o-xylene	I
106-42-3	p-xylene	I
108-38-3	m-xylene	I

· TLV (Threshold Limit Value)

13463-67-7	titanium dioxide	A4
1330-20-7	xylene	A4
100-41-4	ethylbenzene	A3
95-47-6	o-xylene	A4
106-42-3	p-xylene	A4
108-38-3	m-xylene	A4
77-58-7	dibutyltin dilaurate	A4
1333-86-4	Carbon black	A4
14808-60-7	Quartz (SiO ₂)	A2

· NIOSH-Ca (National Institute for Occupational Safety and Health)

13463-67-7	titanium dioxide
1333-86-4	Carbon black
14808-60-7	Quartz (SiO ₂)

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



GHS02 GHS07 GHS08

· Signal word Danger

· Hazard-determining components of labeling:

titanium dioxide

(Contd. on page 13)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/26/2025

Reviewed on 08/26/2025

Trade name: 928WN0006 FLEET WHITE

(Contd. of page 12)

2-ethylhexanoic acid

ethylbenzene

bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate

Hazard statements

Flammable liquid and vapor.

May cause an allergic skin reaction.

Suspected of causing cancer. Route of exposure: Inhalation.

May damage fertility or the unborn child.

Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If exposed or concerned: Get medical advice/attention.

Specific treatment (see on this label).

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

In case of fire: Use CO₂, powder or water spray to extinguish.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Department issuing SDS: Environment protection department.

Contact: Product Safety Dept.

Date of preparation / last revision 08/26/2025 / 5

Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

(Contd. on page 14)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/26/2025

Reviewed on 08/26/2025

Trade name: 928WN0006 FLEET WHITE

(Contd. of page 13)

*BEI: Biological Exposure Limit**Flammable Liquids 3: Flammable liquids – Category 3**Sensitization - Skin 1: Skin sensitisation – Category 1**Carcinogenicity 2: Carcinogenicity – Category 2**Toxic to Reproduction 1B: Reproductive toxicity – Category 1B**** Data compared to the previous version altered.**

USA