

Printing date 05/31/2023

Reviewed on 05/31/2023

Page 1/11

## 1 Identification

- · Product identifier
- · Trade name: <u>AV.005 HARDENER</u>
- · Article number: AV.005
- · Details of the supplier of the safety data sheet
- Manufacturer/Supplier: Lusid Technologies 4725 S Camp Kearns Road Kearns, UT 840118
- Information department: Product safety department
   Emergency telephone number: 24 Hrs Emergency Contact: INFOTRAC 1-800-535-5053

## 2 Hazard(s) identification

Flammable Liquids 3	H226 Flammable liquid and vapor.
GHS08 Health haza	ard
Sensitization - Respiratory 1	H334 May cause allergy or asthma symptoms or breathing difficulties inhaled.
Carcinogenicity 2	H351 Suspected of causing cancer.
GHS07 Skin Irritation 2	H315 Causes skin irritation.
Eye Irritation 2A	H319 Causes serious eye irritation.
Sensitization - Skin 1	H317 May cause an allergic skin reaction.

USA

# Safety Data Sheet acc. to OSHA HCS

Printing date 05/31/2023

Reviewed on 05/31/2023

Trade name: AV.005 HARDENER

(Contd. of page 1) · Hazard pictograms GHS02 GHS08 · Signal word Danger · Hazard-determining components of labeling: 4-chloro-alpha, alpha, alpha-trifluorotoluene poly(hexamethylene diisocyanate) · Hazard statements Flammable liquid and vapor. Causes skin irritation. Causes serious eye irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. Suspected of causing cancer. · Precautionary statements Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapors/spray Wash thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. [In case of inadequate ventilation] wear respiratory protection. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/attention. Specific treatment (see on this label). Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. If experiencing respiratory symptoms: Call a poison center/doctor. Wash contaminated clothing before reuse. In case of fire: Use CO2, powder or water spray to extinguish. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. · Classification system: · NFPA ratings (scale 0 - 4) Health = 2Fire = 2Reactivity = 0(Contd. on page 3)

Printing date 05/31/2023

Reviewed on 05/31/2023

#### Trade name: AV.005 HARDENER

(Contd. of page 2)

50-100%

25-50%

#### · HMIS-ratings (scale 0 - 4)



#### · Other hazards

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

#### 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- **Description:** Mixture of the substances listed below with nonhazardous additions.

#### · Dangerous components:

	98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene
--	---------	---

28182-81-2 poly(hexamethylene diisocyanate)

#### 4 First-aid measures

#### · Description of first aid measures

· General information: Immediately remove any clothing soiled by the product.

#### · After inhalation:

- Supply fresh air and to be sure call for a doctor.
- In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- *Most important symptoms and effects, both acute and delayed* No further relevant information available.
- *Indication of any immediate medical attention and special treatment needed* No further relevant information available.

#### 5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

## 6 Accidental release measures

• Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.

(Contd. on page 4)

– USA

Printing date 05/31/2023

Reviewed on 05/31/2023

#### Trade name: AV.005 HARDENER

		(Contd. of page 3)
<ul> <li>Environment</li> </ul>	tal precautions:	
Dilute with ple	enty of water.	
Do not allow t	o enter sewers/ surface or ground water.	
· Methods and	I material for containment and cleaning up:	
Absorb with li	quid-binding material (sand, diatomite, acid binders, universal binde	ers, sawdust).
Dispose conta	aminated material as waste according to section 13.	
Ensure adequ	late ventilation.	
Reference to	other sections	
See Section 7	7 for information on safe handling.	
See Section 8	B for information on personal protection equipment.	
See Section 1	13 for disposal information.	
· Protective A	ction Criteria for Chemicals	
· PAC-1:		
28182-81-2 p	ooly(hexamethylene diisocyanate)	7.8 mg/m³
822-06-0 h	nexamethylene-di-isocyanate	0.018 ppm
· PAC-2:		
28182-81-2 p	poly(hexamethylene diisocyanate)	86 mg/m³
822-06-0 h	nexamethylene-di-isocyanate	0.2 ppm
· PAC-3:		
28182-81-2 p	ooly(hexamethylene diisocyanate)	510 mg/m³
822-06-0 h	nexamethylene-di-isocyanate	3 ррт

## 7 Handling and storage

· Handling:

- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. Prevent formation of aerosols.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke.
   Protect against electrostatic charges.
   Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- Specific end use(s) No further relevant information available.

### 8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see section 7.

- · Control parameters
- **Components with limit values that require monitoring at the workplace:** The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- Additional information: The lists that were valid during the creation were used as basis.

(Contd. on page 5)

Printing date 05/31/2023

Reviewed on 05/31/2023

#### Trade name: AV.005 HARDENER

(Contd. of page 4)

- Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the eyes and skin.
- · Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

• Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

Information on basic physical and General Information	chemical properties	
Appearance:		
Form:	Fluid	
Color:	According to product specification	
Odor:	Characteristic	
Odor threshold:	Not determined.	
pH-value:	Not determined (pH N/A in solvent coatings)	
Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	139 °C (282.2 °F)	
Flash point:	47 °C (116.6 °F)	

Printing date 05/31/2023

Reviewed on 05/31/2023

Trade name: AV.005 HARDENER

	(Contd. of page 5)
· Flammability (solid, gaseous):	Flammable.
· Decomposition temperature:	Not determined.
· Ignition temperature:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/ vapor mixtures are possible.
· Explosion limits: Lower: Upper:	Not determined. Not determined.
<ul> <li>Vapor pressure at 20 °C (68 °F):</li> <li>Vapor pressure at 50 °C (122 °F):</li> </ul>	0 hPa 38.6 hPa (29 mm Hg)
<ul> <li>Density at 20 °C (68 °F):</li> <li>Relative density</li> <li>Vapor density</li> <li>Evaporation rate</li> </ul>	1.2643 g/cm <sup>3</sup> (10.5506 lbs/gal) Not determined. Not determined. Not determined.
<ul> <li>Solubility in / Miscibility with Water:</li> </ul>	Fully miscible.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity: Dynamic: Kinematic:	Not determined. Not determined.
<ul> <li>Solvent content: VOC content:</li> </ul>	0.00 % 0.0 g/l / 0.00 lb/gal
Solids content:	38.2 %
· Other information	No further relevant information available.

## 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

## 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- on the eye: Irritating effect.

(Contd. on page 7)

<sup>-</sup> USA

(Contd. of page 6)

## Safety Data Sheet acc. to OSHA HCS

Printing date 05/31/2023

Reviewed on 05/31/2023

#### Trade name: AV.005 HARDENER

<ul> <li>Sensitization: Sensitization possible through inhalation. Sensitization possible through skin contact.</li> <li>Additional toxicological information: The product shows the following dangers according to internally approved calculation methods for preparations: Harmful Irritant</li> </ul>	
· Carcinogenic categories	
· IARC (International Agency for Research on Cancer)	
98-56-6 4-chloro-alpha,alpha,alpha-trifluorotoluene 2B	
· NTP (National Toxicology Program)	
None of the ingredients is listed.	
· OSHA-Ca (Occupational Safety & Health Administration)	
None of the ingredients is listed.	

## 12 Ecological information

#### · Toxicity

- Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- Additional ecological information:

#### · General notes:

Water hazard class 2 (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- vPvB: Not applicable.
- Other adverse effects No further relevant information available.

## 13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- **Recommendation:** Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

(Contd. on page 8)

Printing date 05/31/2023

Reviewed on 05/31/2023

Trade name: AV.005 HARDENER

(Contd. of page 7)

UN-Number	
DOT, IMDG, IATA	UN1263
UN proper shipping name	
DOT IMDG, IATA	Paint mixture PAINT mixture
Transport hazard class(es)	
DOT	
Class	3 Flammable liquids
Label	3
IMDG, IATA	
Class	3 Flammable liquids
Label	3
Packing group DOT, IMDG, IATA	III
Environmental hazards: Marine pollutant:	No
Special precautions for user	Warning: Flammable liquids
Hazard identification number (Kemler code): EMS Number:	
Stowage Category	F-E, <u>S-E</u> A
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 1263 PAINT MIXTURE, 3, III

(Contd. on page 9)

Printing date 05/31/2023

Reviewed on 05/31/2023

## Trade name: AV.005 HARDENER

(Contd. of page 8)

	health and environmental regulations/legislation specific for the substance or mixture er relevant information available.
	355 (extremely hazardous substances):
	the ingredients is listed.
	313 (Specific toxic chemical listings):
	hexamethylene-di-isocyanate
	Foxic Substances Control Act):
•	onents have the value ACTIVE.
Hazardo	ous Air Pollutants
822-06-0	hexamethylene-di-isocyanate
Proposi	
Chemica	als known to cause cancer:
98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene
Chemica	als known to cause reproductive toxicity for females:
None of	the ingredients is listed.
Chemica	als known to cause reproductive toxicity for males:
None of	the ingredients is listed.
Chemica	als known to cause developmental toxicity:
None of	the ingredients is listed.
Carcino	genic categories
EPA (En	vironmental Protection Agency)
None of	the ingredients is listed.
TLV (Th	reshold Limit Value)
None of	the ingredients is listed.
NIOSH-0	Ca (National Institute for Occupational Safety and Health)
None of	the ingredients is listed.
The prod	<b>bel elements</b> duct is classified and labeled according to the Globally Harmonized System (GHS). <b>pictograms</b>
GHS02	GHS08 vord Danger

poly(hexamethylene diisocyanate) **Hazard statements** Flammable liquid and vapor. Causes skin irritation. Causes serious eye irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Printing date 05/31/2023

Reviewed on 05/31/2023

#### Trade name: AV.005 HARDENER

(Contd. of page 9)
May cause an allergic skin reaction.
Suspected of causing cancer.
· Precautionary statements
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat/sparks/open flames/hot surfaces No smoking.
Keep container tightly closed.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting/equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Avoid breathing dust/fume/gas/mist/vapors/spray
Wash thoroughly after handling.
Contaminated work clothing must not be allowed out of the workplace.
Wear protective gloves/protective clothing/eye protection/face protection.
[In case of inadequate ventilation] wear respiratory protection.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy
to do. Continue rinsing.
IF exposed or concerned: Get medical advice/attention.
Specific treatment (see on this label).
Take off contaminated clothing and wash it before reuse.
If skin irritation or rash occurs: Get medical advice/attention.
If eye irritation persists: Get medical advice/attention.
If experiencing respiratory symptoms: Call a poison center/doctor.
Wash contaminated clothing before reuse.
In case of fire: Use CO2, powder or water spray to extinguish.
Store in a well-ventilated place. Keep cool.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.
• <b>Chemical safety assessment:</b> A Chemical Safety Assessment has not been carried out.
Chemical salely assessment. A Chemical Salely Assessment has not been camed out.
6 Other information

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Environment protection department.

- Contact: Product Safety Dept.
- · Date of preparation / last revision 05/31/2023
- Abbreviations and acronyms: IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit

(Contd. on page 11)

USA

Printing date 05/31/2023

Reviewed on 05/31/2023

### Trade name: AV.005 HARDENER

Flammable Liquids 3: Flammable liquids – Category 3 Skin Irritation 2: Skin corrosion/irritation – Category 2 Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A Sensitization - Respiratory 1: Respiratory sensitisation – Category 1 Sensitization - Skin 1: Skin sensitisation – Category 1 Carcinogenicity 2: Carcinogenicity – Category 2

\* Data compared to the previous version altered.

(Contd. of page 10)

USA