



Safety Data Sheet acc. to OSHA HCS

Printing date 02/06/2020

Reviewed on 02/06/2020

1 Identification

- **Product identifier**
- **Trade name:** 100WN0006 WHITE ACRYLIC ENAMEL
- **Article number:** 100WN0006
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Lusid Technologies
4725 S Camp Kearns Road
Kearns, UT 84118
USA
www.lusidtechnologies.com
- **Information department:** Product safety department
- **Emergency telephone number:**
24 Hrs Emergency Contact:
INFOTRAC
1-800-535-5053

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS08 Health hazard

Muta. 1B H340 May cause genetic defects.

Carc. 1B H350 May cause cancer.

STOT RE 1 H372 Causes damage to the central nervous system through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Acute Tox. 4 H332 Harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Acute 3 H402 Harmful to aquatic life.

(Contd. on page 2)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/06/2020

Reviewed on 02/06/2020

Trade name: 100WN0006 WHITE ACRYLIC ENAMEL

(Contd. of page 1)

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

· **Label elements**

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

xylene

titanium dioxide

Stoddard solvent

Naphtha (petroleum), hydrotreated light

2-butanone oxime

· **Hazard statements**

Flammable liquid and vapor.

Harmful if inhaled.

Causes skin irritation.

May cause an allergic skin reaction.

May cause genetic defects.

May cause cancer.

Causes damage to the central nervous system through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

Harmful to aquatic life.

Harmful to aquatic life with long lasting effects.

· **Precautionary statements**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Contaminated work clothing must not be allowed out of the workplace.

Avoid release to the environment.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Immediately call a poison center/doctor.

Specific treatment (see on this label).

Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF exposed or concerned: Get medical advice/attention.

Call a poison center/doctor if you feel unwell.

Get medical advice/attention if you feel unwell.

(Contd. on page 3)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/06/2020

Reviewed on 02/06/2020

Trade name: 100WN0006 WHITE ACRYLIC ENAMEL

(Contd. of page 2)

Take off contaminated clothing and wash it before reuse.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

In case of fire: Use for extinction: CO₂, powder or water spray.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 1

Fire = 3

Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**



Health = *1

Fire = 3

Reactivity = 0

· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

13463-67-7	titanium dioxide	10-25%
1330-20-7	xylene	10-25%
64742-49-0	Naphtha (petroleum), hydrotreated light	2.5-10%
123-86-4	n-butyl acetate	2.5-10%
8052-41-3	Stoddard solvent	2.5-10%
110-43-0	heptan-2-one	2.5-10%
64742-95-6	Solvent naphtha (petroleum), light arom.	2.5-10%
100-41-4	ethylbenzene	≤2.5%
96-29-7	2-butanone oxime	≤2.5%

4 First-aid measures

· **Description of first aid measures**

· **General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· **After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

(Contd. on page 4)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/06/2020

Reviewed on 02/06/2020

Trade name: 100WN0006 WHITE ACRYLIC ENAMEL

(Contd. of page 3)

- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

- **PAC-1:**

13463-67-7	titanium dioxide	30 mg/m ³
1330-20-7	xylene	130 ppm
123-86-4	n-butyl acetate	5 ppm
8052-41-3	Stoddard solvent	300 mg/m ³
110-43-0	heptan-2-one	150 ppm
100-41-4	ethylbenzene	33 ppm
96-29-7	2-butanone oxime	30 ppm
108-38-3	m-xylene	130 ppm
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
112-34-5	2-(2-butoxyethoxy)ethanol	30 ppm
122-99-6	2-Phenoxyethanol	1.5 ppm

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/06/2020

Reviewed on 02/06/2020

Trade name: 100WN0006 WHITE ACRYLIC ENAMEL

(Contd. of page 4)

149-57-5	2-ethylhexanoic acid	15 mg/m ³
1333-86-4	Carbon black	9 mg/m ³
34590-94-8	Dipropylene glycol monomethyl ether	150 ppm
108-83-8	2,6-dimethylheptan-4-one	75 ppm
14808-60-7	Quartz (SiO ₂)	0.075 mg/m ³
57-55-6	Propylene glycol	30 mg/m ³
78-83-1	butanol	150 ppm
70657-70-4	2-methoxypropyl acetate	50 ppm
7664-38-2	phosphoric acid	3 mg/m ³

PAC-2:

13463-67-7	titanium dioxide	330 mg/m ³
1330-20-7	xylene	920* ppm
123-86-4	n-butyl acetate	200 ppm
8052-41-3	Stoddard solvent	1,800 mg/m ³
110-43-0	heptan-2-one	670 ppm
100-41-4	ethylbenzene	1100* ppm
96-29-7	2-butanone oxime	56 ppm
108-38-3	m-xylene	920 ppm
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm
112-34-5	2-(2-butoxyethoxy)ethanol	33 ppm
122-99-6	2-Phenoxyethanol	16 ppm
149-57-5	2-ethylhexanoic acid	99 mg/m ³
1333-86-4	Carbon black	99 mg/m ³
34590-94-8	Dipropylene glycol monomethyl ether	1700* ppm
108-83-8	2,6-dimethylheptan-4-one	330 ppm
14808-60-7	Quartz (SiO ₂)	33 mg/m ³
57-55-6	Propylene glycol	1,300 mg/m ³
78-83-1	butanol	1,300 ppm
70657-70-4	2-methoxypropyl acetate	1,000 ppm
7664-38-2	phosphoric acid	30 mg/m ³

PAC-3:

13463-67-7	titanium dioxide	2,000 mg/m ³
1330-20-7	xylene	2500* ppm
123-86-4	n-butyl acetate	3000* ppm
8052-41-3	Stoddard solvent	29500** mg/m ³
110-43-0	heptan-2-one	4000* ppm
100-41-4	ethylbenzene	1800* ppm
96-29-7	2-butanone oxime	250 ppm
108-38-3	m-xylene	2500* ppm
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm
112-34-5	2-(2-butoxyethoxy)ethanol	200 ppm
122-99-6	2-Phenoxyethanol	97 ppm
149-57-5	2-ethylhexanoic acid	590 mg/m ³

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/06/2020

Reviewed on 02/06/2020

Trade name: 100WN0006 WHITE ACRYLIC ENAMEL

(Contd. of page 5)

1333-86-4	Carbon black	590 mg/m ³
34590-94-8	Dipropylene glycol monomethyl ether	9900** ppm
108-83-8	2,6-dimethylheptan-4-one	2000* ppm
14808-60-7	Quartz (SiO ₂)	200 mg/m ³
57-55-6	Propylene glycol	7,900 mg/m ³
78-83-1	butanol	8000* ppm
70657-70-4	2-methoxypropyl acetate	5,000 ppm
7664-38-2	phosphoric acid	150 mg/m ³

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
*Ensure good ventilation/exhaustion at the workplace.
 Open and handle receptacle with care.
 Prevent formation of aerosols.*
- **Information about protection against explosions and fires:**
*Keep ignition sources away - Do not smoke.
 Protect against electrostatic charges.
 Keep respiratory protective device available.*
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** *No special requirements.*
- **Information about storage in one common storage facility:** *Not required.*
- **Further information about storage conditions:** *Keep receptacle tightly sealed.*
- **Specific end use(s)** *No further relevant information available.*

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** *No further data; see item 7.*
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
*The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
 At this time, the other constituents have no known exposure limits.*

1330-20-7 xylene

PEL	Long-term value: 435 mg/m ³ , 100 ppm
REL	Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV	Short-term value: 651 mg/m ³ , 150 ppm Long-term value: 434 mg/m ³ , 100 ppm BEI

123-86-4 n-butyl acetate

PEL	Long-term value: 710 mg/m ³ , 150 ppm
REL	Short-term value: 950 mg/m ³ , 200 ppm Long-term value: 710 mg/m ³ , 150 ppm

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/06/2020

Reviewed on 02/06/2020

Trade name: 100WN0006 WHITE ACRYLIC ENAMEL

(Contd. of page 6)

TLV Short-term value: 712 mg/m³, 150 ppm
Long-term value: 238 mg/m³, 50 ppm

8052-41-3 Stoddard solvent

PEL Long-term value: 2900 mg/m³, 500 ppm

REL Long-term value: 350 mg/m³
Ceiling limit value: 1800* mg/m³
*15-min

TLV Long-term value: 525 mg/m³, 100 ppm

110-43-0 heptan-2-one

PEL Long-term value: 465 mg/m³, 100 ppm

REL Long-term value: 465 mg/m³, 100 ppm

TLV Long-term value: 233 mg/m³, 50 ppm

100-41-4 ethylbenzene

PEL Long-term value: 435 mg/m³, 100 ppm

REL Short-term value: 545 mg/m³, 125 ppm
Long-term value: 435 mg/m³, 100 ppm

TLV Long-term value: 87 mg/m³, 20 ppm
BEI

96-29-7 2-butanone oxime

WEEL Long-term value: 10 ppm
DSEN

· **Ingredients with biological limit values:**

1330-20-7 xylene

BEI 1.5 g/g creatinine
Medium: urine
Time: end of shift
Parameter: Methylhippuric acids

100-41-4 ethylbenzene

BEI 0.7 g/g creatinine
Medium: urine
Time: end of shift at end of workweek
Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)

-

Medium: end-exhaled air

Time: not critical

Parameter: Ethyl benzene (semi-quantitative)

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Store protective clothing separately.
Avoid contact with the skin.
Avoid contact with the eyes and skin.

(Contd. on page 8)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/06/2020

Reviewed on 02/06/2020

Trade name: 100WN0006 WHITE ACRYLIC ENAMEL

(Contd. of page 7)

- **Breathing equipment:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

· Form:	Liquid
· Color:	White
· Odor:	Characteristic
· Odor threshold:	Not determined.

- **pH-value:** Not determined (pH N/A in solvent coatings)

- **Change in condition**

· Melting point/Melting range:	Undetermined.
· Boiling point/Boiling range:	124 °C (255.2 °F)

- **Flash point:** 27 °C (80.6 °F)

- **Flammability (solid, gaseous):** Not applicable.

- **Ignition temperature:** 500 °C (932 °F)

- **Decomposition temperature:** Not determined.

- **Auto igniting:** Product is not selfigniting.

- **Danger of explosion:** Product is not explosive. However, formation of explosive air/ vapor mixtures are possible.

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/06/2020

Reviewed on 02/06/2020

Trade name: 100WN0006 WHITE ACRYLIC ENAMEL

(Contd. of page 8)

· Explosion limits:	
Lower:	1.1 Vol %
Upper:	7 Vol %
· Vapor pressure at 20 °C (68 °F):	6.7 hPa (5 mm Hg)
· Density at 20 °C (68 °F):	1.163 g/cm ³ (9.7052 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	35.3 %
VOC content:	38.92 %
	490.2 g/l / 4.09 lb/gal
Solids content:	57.8 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **LD/LC50 values that are relevant for classification:**

1330-20-7 xylene

Oral	LD50	4,300 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)

64742-95-6 Solvent naphtha (petroleum), light arom.

Oral	LD50	>6,800 mg/kg (rat)
Dermal	LD50	>3,400 mg/kg (rab)
Inhalative	LC50/4 h	>10.2 mg/l (rat)

(Contd. on page 10)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/06/2020

Reviewed on 02/06/2020

Trade name: 100WN0006 WHITE ACRYLIC ENAMEL

(Contd. of page 9)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** No irritating effect.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Harmful
Irritant
The product can cause inheritable damage.

· **Carcinogenic categories**· **IARC (International Agency for Research on Cancer)**

13463-67-7	titanium dioxide	2B
1330-20-7	xylene	3
100-41-4	ethylbenzene	2B
95-47-6	o-xylene	3
106-42-3	p-xylene	3
108-38-3	m-xylene	3
136-52-7	cobalt(II) 2-ethylhexanoate	2B
1333-86-4	Carbon black	2B
14808-60-7	Quartz (SiO ₂)	1

· **NTP (National Toxicology Program)**

14808-60-7	Quartz (SiO ₂)	K
------------	----------------------------	---

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**
Water hazard class 3 (Self-assessment): extremely hazardous for water
Do not allow product to reach ground water, water course or sewage system, even in small quantities.
Danger to drinking water if even extremely small quantities leak into the ground.
Harmful to aquatic organisms
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

USA

(Contd. on page 11)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/06/2020

Reviewed on 02/06/2020



Trade name: 100WN0006 WHITE ACRYLIC ENAMEL

(Contd. of page 10)

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- | | |
|---|---|
| UN-Number | UN1263 |
| DOT, IMDG, IATA | UN1263 |
| UN proper shipping name | Paint |
| DOT | PAINT |
| IMDG, IATA | PAINT |
| Transport hazard class(es) | |
| DOT | |
|  | |
| Class | 3 Flammable liquids |
| Label | 3 |
| | |
| IMDG, IATA | |
|  | |
| Class | 3 Flammable liquids |
| Label | 3 |
| Packing group | III |
| DOT, IMDG, IATA | III |
| Environmental hazards: | |
| Marine pollutant: | No |
| Special precautions for user | Warning: Flammable liquids |
| Hazard identification number (Kemler code): | 30 |
| EMS Number: | F-E, S-E |
| Stowage Category | A |
| Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | Not applicable. |
| Transport/Additional information: | |
| DOT | |
| Quantity limitations | On passenger aircraft/rail: 60 L
On cargo aircraft only: 220 L |

(Contd. on page 12)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/06/2020

Reviewed on 02/06/2020

Trade name: 100WN0006 WHITE ACRYLIC ENAMEL

(Contd. of page 11)

- | | |
|--|--|
| <ul style="list-style-type: none"> · IMDG · Limited quantities (LQ) · Excepted quantities (EQ) | <p>5L
Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml</p> |
| <ul style="list-style-type: none"> · UN "Model Regulation": | <p>UN 1263 PAINT, 3, III</p> |

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**

- **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

- **Section 313 (Specific toxic chemical listings):**

1330-20-7	xylene
100-41-4	ethylbenzene
95-47-6	o-xylene
106-42-3	p-xylene
108-38-3	m-xylene
136-52-7	cobalt(II) 2-ethylhexanoate
112-34-5	2-(2-butoxyethoxy)ethanol
122-99-6	2-Phenoxyethanol
7664-38-2	phosphoric acid

- **TSCA (Toxic Substances Control Act):**

13463-67-7	titanium dioxide	ACTIVE
1330-20-7	xylene	ACTIVE
123-86-4	n-butyl acetate	ACTIVE
8052-41-3	Stoddard solvent	ACTIVE
110-43-0	heptan-2-one	ACTIVE
100-41-4	ethylbenzene	ACTIVE
96-29-7	2-butanone oxime	ACTIVE
95-47-6	o-xylene	ACTIVE
106-42-3	p-xylene	ACTIVE
108-38-3	m-xylene	ACTIVE
64742-47-8	Distillates (petroleum), hydrotreated light	ACTIVE
108-65-6	2-methoxy-1-methylethyl acetate	ACTIVE
136-52-7	cobalt(II) 2-ethylhexanoate	ACTIVE
51274-00-1	ALPHA-IRON(III) OXIDE	ACTIVE
64742-95-6	Solvent naphtha (petroleum), light arom.	ACTIVE
112-34-5	2-(2-butoxyethoxy)ethanol	ACTIVE
122-99-6	2-Phenoxyethanol	ACTIVE
149-57-5	2-ethylhexanoic acid	ACTIVE
1333-86-4	Carbon black	ACTIVE

(Contd. on page 13)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/06/2020

Reviewed on 02/06/2020

Trade name: 100WN0006 WHITE ACRYLIC ENAMEL

(Contd. of page 12)

1047-16-1	Quinacridone	ACTIVE
147-14-8	Phthalocyanine Blue	ACTIVE
34590-94-8	Dipropylene glycol monomethyl ether	ACTIVE
108-83-8	2,6-dimethylheptan-4-one	ACTIVE
14808-60-7	Quartz (SiO ₂)	ACTIVE
57-55-6	Propylene glycol	ACTIVE
78-83-1	butanol	ACTIVE
7664-38-2	phosphoric acid	ACTIVE

· Hazardous Air Pollutants

1330-20-7	xylene
100-41-4	ethylbenzene
95-47-6	o-xylene
106-42-3	p-xylene
108-38-3	m-xylene
136-52-7	cobalt(II) 2-ethylhexanoate

· Proposition 65
· Chemicals known to cause cancer:

13463-67-7	titanium dioxide
100-41-4	ethylbenzene
1333-86-4	Carbon black
14808-60-7	Quartz (SiO ₂)

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories
· EPA (Environmental Protection Agency)

1330-20-7	xylene	I
100-41-4	ethylbenzene	D
95-47-6	o-xylene	I
106-42-3	p-xylene	I
108-38-3	m-xylene	I

· TLV (Threshold Limit Value established by ACGIH)

13463-67-7	titanium dioxide	A4
1330-20-7	xylene	A4
100-41-4	ethylbenzene	A3
95-47-6	o-xylene	A4
106-42-3	p-xylene	A4
108-38-3	m-xylene	A4
1333-86-4	Carbon black	A4
14808-60-7	Quartz (SiO ₂)	A2

(Contd. on page 14)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/06/2020

Reviewed on 02/06/2020

Trade name: 100WN0006 WHITE ACRYLIC ENAMEL

(Contd. of page 13)

· NIOSH-Ca (National Institute for Occupational Safety and Health)	
13463-67-7	titanium dioxide
1333-86-4	Carbon black
14808-60-7	Quartz (SiO ₂)

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

xylene

titanium dioxide

Stoddard solvent

Naphtha (petroleum), hydrotreated light

2-butanone oxime

· **Hazard statements**

Flammable liquid and vapor.

Harmful if inhaled.

Causes skin irritation.

May cause an allergic skin reaction.

May cause genetic defects.

May cause cancer.

Causes damage to the central nervous system through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

Harmful to aquatic life.

Harmful to aquatic life with long lasting effects.

· **Precautionary statements**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Contaminated work clothing must not be allowed out of the workplace.

Avoid release to the environment.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Immediately call a poison center/doctor.

Specific treatment (see on this label).

Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF exposed or concerned: Get medical advice/attention.

(Contd. on page 15)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/06/2020

Reviewed on 02/06/2020

Trade name: 100WN0006 WHITE ACRYLIC ENAMEL

(Contd. of page 14)

Call a poison center/doctor if you feel unwell.
 Get medical advice/attention if you feel unwell.
 Take off contaminated clothing and wash it before reuse.
 If skin irritation or rash occurs: Get medical advice/attention.
 Wash contaminated clothing before reuse.
 In case of fire: Use for extinction: CO₂, powder or water spray.
 Store in a well-ventilated place. Keep cool.
 Store locked up.
 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **National regulations:**

- **Additional classification according to Decree on Hazardous Materials:**

Carcinogenic hazardous material group III (dangerous).

- **Information about limitation of use:**

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** Environment protection department.

- **Contact:** Product Safety Dept.

- **Date of preparation / last revision** 02/06/2020 / 3

- **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Muta. 1B: Germ cell mutagenicity – Category 1B

Carc. 1B: Carcinogenicity – Category 1B

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 3: Hazardous to the aquatic environment - acute aquatic hazard – Category 3

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

- *** Data compared to the previous version altered.**