

Safety Data Sheet acc. to OSHA HCS

Printing date 08/26/2025

Reviewed on 08/26/2025

1 Identification

- **Product identifier**
- **Trade name:** 935WN0006 FLEET WHITE
- **Article number:** 935WN0006
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
 NorthStar is a product of Lusid Technologies Inc
 4725 S Camp Kearns Road
 Kearns, UT 84118
 (801) 966-5300
 info@lusidtechnologies.com
- **Information department:** Product safety department
- **Emergency telephone number:**
 24 Hrs Emergency Contact:
 INFOTRAC
 1-800-535-5053

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flammable Liquids 2

H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Carcinogenicity 2

H351 Suspected of causing cancer. Route of exposure: Inhalation.

Toxic to Reproduction 1B

H360 May damage fertility or the unborn child.



GHS07

Eye Irritation 2A

H319 Causes serious eye irritation.

Sensitization - Skin 1

H317 May cause an allergic skin reaction.

Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/26/2025

Reviewed on 08/26/2025

Trade name: 935WN0006 FLEET WHITE

(Contd. of page 1)

· Hazard pictograms



GHS02 GHS07 GHS08

· Signal word Danger

· Hazard-determining components of labeling:

titanium dioxide
 n-butyl acetate
 2-ethylhexanoic acid
 4-chloro-alpha,alpha,alpha-trifluorotoluene
 bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate

· Hazard statements

Highly flammable liquid and vapor.
 Causes serious eye irritation.
 May cause an allergic skin reaction.
 Suspected of causing cancer. Route of exposure: Inhalation.
 May damage fertility or the unborn child.
 May cause drowsiness or dizziness.

· Precautionary statements

Obtain special instructions before use.
 Do not handle until all safety precautions have been read and understood.
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
 Ground/bond container and receiving equipment.
 Use explosion-proof electrical/ventilating/lighting/equipment.
 Use only non-sparking tools.
 Take precautionary measures against static discharge.
 Avoid breathing dust/fume/gas/mist/vapors/spray
 Wash thoroughly after handling.
 Use only outdoors or in a well-ventilated area.
 Contaminated work clothing must not be allowed out of the workplace.
 Wear protective gloves/protective clothing/eye protection/face protection.
 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 IF exposed or concerned: Get medical advice/attention.
 Call a poison center/doctor if you feel unwell.
 Specific treatment (see on this label).
 If skin irritation or rash occurs: Get medical advice/attention.
 If eye irritation persists: Get medical advice/attention.
 Wash contaminated clothing before reuse.
 In case of fire: Use CO2, powder or water spray to extinguish.
 Store in a well-ventilated place. Keep container tightly closed.
 Store in a well-ventilated place. Keep cool.
 Store locked up.
 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Classification system:

· NFPA ratings (scale 0 - 4)



Health = 2
 Fire = 3
 Reactivity = 0

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/26/2025

Reviewed on 08/26/2025

Trade name: 935WN0006 FLEET WHITE

(Contd. of page 2)

· HMIS-ratings (scale 0 - 4)

HEALTH	2	Health = 2
FIRE	3	Fire = 3
REACTIVITY	0	Reactivity = 0

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:

13463-67-7	titanium dioxide	10-25%
123-86-4	n-butyl acetate	10-25%
110-43-0	heptan-2-one	10-25%
67-64-1	acetone	2.5-10%
98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene	2.5-10%
41556-26-7	bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate	≤2.5%
149-57-5	2-ethylhexanoic acid	≤2.5%
100-41-4	ethylbenzene	≤2.5%

4 First-aid measures

- **Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture** No further relevant information available.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/26/2025

Reviewed on 08/26/2025

Trade name: 935WN0006 FLEET WHITE

(Contd. of page 3)

- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Dilute with plenty of water.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· PAC-1:

13463-67-7	titanium dioxide	30 mg/m ³
123-86-4	n-butyl acetate	5 ppm
110-43-0	heptan-2-one	150 ppm
67-64-1	acetone	200 ppm
1330-20-7	xylene	130 ppm
149-57-5	2-ethylhexanoic acid	15 mg/m ³
100-41-4	ethylbenzene	33 ppm
108-38-3	m-xylene	130 ppm
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
77-58-7	dibutyltin dilaurate	1.1 mg/m ³
122-99-6	2-phenoxyethanol	1.5 ppm
1333-86-4	Carbon black	9 mg/m ³
14808-60-7	Quartz (SiO ₂)	0.075 mg/m ³
34590-94-8	Dipropylene glycol monomethyl ether	150 ppm
7664-38-2	phosphoric acid	3 mg/m ³
57-55-6	Propylene glycol	30 mg/m ³
78-83-1	butanol	150 ppm
108-83-8	2,6-dimethylheptan-4-one	75 ppm
70657-70-4	2-methoxypropyl acetate	50 ppm

· PAC-2:

13463-67-7	titanium dioxide	330 mg/m ³
123-86-4	n-butyl acetate	200 ppm
110-43-0	heptan-2-one	670 ppm
67-64-1	acetone	3200* ppm
1330-20-7	xylene	920* ppm
149-57-5	2-ethylhexanoic acid	99 mg/m ³

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/26/2025

Reviewed on 08/26/2025

Trade name: 935WN0006 FLEET WHITE

(Contd. of page 4)

100-41-4	ethylbenzene	1100 ppm
108-38-3	m-xylene	920 ppm
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm
77-58-7	dibutyltin dilaurate	3.8 mg/m ³
122-99-6	2-phenoxyethanol	16 ppm
1333-86-4	Carbon black	290 mg/m ³
14808-60-7	Quartz (SiO ₂)	8.3 mg/m ³
34590-94-8	Dipropylene glycol monomethyl ether	1700* ppm
7664-38-2	phosphoric acid	30 mg/m ³
57-55-6	Propylene glycol	1,300 mg/m ³
78-83-1	butanol	1,300 ppm
108-83-8	2,6-dimethylheptan-4-one	330 ppm
70657-70-4	2-methoxypropyl acetate	1,000 ppm

PAC-3:

13463-67-7	titanium dioxide	2,000 mg/m ³
123-86-4	n-butyl acetate	3000* ppm
110-43-0	heptan-2-one	4000* ppm
67-64-1	acetone	5700* ppm
1330-20-7	xylene	2500* ppm
149-57-5	2-ethylhexanoic acid	590 mg/m ³
100-41-4	ethylbenzene	1800 ppm
108-38-3	m-xylene	2500* ppm
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm
77-58-7	dibutyltin dilaurate	23 mg/m ³
122-99-6	2-phenoxyethanol	97 ppm
1333-86-4	Carbon black	1750 mg/m ³
14808-60-7	Quartz (SiO ₂)	50 mg/m ³
34590-94-8	Dipropylene glycol monomethyl ether	9900** ppm
7664-38-2	phosphoric acid	150 mg/m ³
57-55-6	Propylene glycol	7,900 mg/m ³
78-83-1	butanol	8000* ppm
108-83-8	2,6-dimethylheptan-4-one	2000* ppm
70657-70-4	2-methoxypropyl acetate	5,000 ppm

7 Handling and storage

Handling:

Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

(Contd. on page 6)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/26/2025

Reviewed on 08/26/2025

Trade name: 935WN0006 FLEET WHITE

(Contd. of page 5)

- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see section 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
At this time, the other constituents have no known exposure limits.

123-86-4 n-butyl acetate

PEL	Long-term value: 710 mg/m ³ , 150 ppm
REL	Short-term value: 950 mg/m ³ , 200 ppm Long-term value: 710 mg/m ³ , 150 ppm
TLV	Short-term value: 712 mg/m ³ , 150 ppm Long-term value: 238 mg/m ³ , 50 ppm

110-43-0 heptan-2-one

PEL	Long-term value: 465 mg/m ³ , 100 ppm
REL	Long-term value: 465 mg/m ³ , 100 ppm
TLV	Long-term value: 50 ppm

67-64-1 acetone

PEL	Long-term value: 2400 mg/m ³ , 1000 ppm
REL	Long-term value: 590 mg/m ³ , 250 ppm
TLV	Short-term value: 1187 mg/m ³ , 500 ppm Long-term value: 594 mg/m ³ , 250 ppm A4, BEI

149-57-5 2-ethylhexanoic acid

TLV	Long-term value: 5* mg/m ³ *as inhalable fraction and vapor
-----	---

100-41-4 ethylbenzene

PEL	Long-term value: 435 mg/m ³ , 100 ppm
REL	Short-term value: 545 mg/m ³ , 125 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV	Long-term value: 20 ppm OTO, BEI, A3

- **Ingredients with biological limit values:**

67-64-1 acetone

BEI	25 mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific)
-----	--

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/26/2025

Reviewed on 08/26/2025

Trade name: 935WN0006 FLEET WHITE

(Contd. of page 6)

100-41-4 ethylbenzene

BEI 0.15 g/g creatinine

Medium: urine

Time: end of shift

Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific)

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Store protective clothing separately.
Avoid contact with the eyes.
Avoid contact with the eyes and skin.
- **Breathing equipment:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

- **Information on basic physical and chemical properties**
- **General Information**
- **Appearance:**

Form:	Liquid
Color:	White
Odor:	Characteristic

(Contd. on page 8)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/26/2025

Reviewed on 08/26/2025

Trade name: 935WN0006 FLEET WHITE

(Contd. of page 7)

· Odor threshold:	Not determined.
· pH-value:	Not determined (pH N/A in solvent coatings)
· Change in condition Melting point/Melting range: Boiling point/Boiling range:	Undetermined. 55.8-56.6 °C (132.4-133.9 °F)
· Flash point:	<-18 °C (<-0.4 °F)
· Flammability:	Highly flammable.
· Auto igniting:	370 °C (698 °F)
· Decomposition temperature:	Not determined.
· Ignition temperature:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits: Lower: Upper:	1 Vol % 7.5 Vol %
· Vapor pressure at 20 °C (68 °F): · Vapor pressure at 50 °C (122 °F):	10.7 hPa (8 mm Hg) 55 hPa (41.3 mm Hg)
· Density at 20 °C (68 °F): · Relative density · Vapor density · Evaporation rate	1.2248 g/cm ³ (10.221 lbs/gal) Not determined. Not determined. Not determined.
· Solubility in / Miscibility with Water:	Fully miscible.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity: Dynamic: Kinematic:	Not determined. Not determined.
· Solvent content: Organic solvents: VOC content:	35.3 % 27.93 % 450.1 g/l / 3.76 lb/gal
Solids content:	63.3 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.

(Contd. on page 9)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/26/2025

Reviewed on 08/26/2025

Trade name: 935WN0006 FLEET WHITE

(Contd. of page 8)

· **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

· **Information on toxicological effects**· **Acute toxicity:**· **LD/LC50 values that are relevant for classification:****110-43-0 heptan-2-one**

Oral	LD50	1,670 mg/kg (rat)
Dermal	LD50	12,600 mg/kg (rabbit)

· **Primary irritant effect:**· **on the skin:** No irritant effect.· **on the eye:** Irritating effect.· **Sensitization:** Sensitization possible through skin contact.· **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

· **Carcinogenic categories**· **IARC (International Agency for Research on Cancer)**

13463-67-7	titanium dioxide	2B
98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene	2B
1330-20-7	xylene	3
100-41-4	ethylbenzene	2B
95-47-6	o-xylene	3
106-42-3	p-xylene	3
108-38-3	m-xylene	3
1333-86-4	Carbon black	2B
14808-60-7	Quartz (SiO ₂)	1

· **NTP (National Toxicology Program)**

14808-60-7	Quartz (SiO ₂)	K
------------	----------------------------	---

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

· **Toxicity**· **Aquatic toxicity:** No further relevant information available.· **Persistence and degradability** No further relevant information available.· **Behavior in environmental systems:**· **Bioaccumulative potential** No further relevant information available.· **Mobility in soil** No further relevant information available.· **Additional ecological information:**· **General notes:**

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/26/2025

Reviewed on 08/26/2025

Trade name: 935WN0006 FLEET WHITE

(Contd. of page 9)

- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport information

- | | |
|---|----------------------------|
| · UN-Number | UN1263 |
| · DOT, IMDG, IATA | |
| · UN proper shipping name | Paint |
| · DOT | PAINT |
| · IMDG, IATA | |
| · Transport hazard class(es) | |
| · DOT | |
|  | |
| · Class | 3 Flammable liquids |
| · Label | 3 |
| · IMDG, IATA | |
|  | |
| · Class | 3 Flammable liquids |
| · Label | 3 |
| · Packing group | II |
| · DOT, IMDG, IATA | |
| · Environmental hazards: | |
| · Marine pollutant: | No |
| · Special precautions for user | Warning: Flammable liquids |
| · Hazard identification number (Kemler code): | 33 |
| · EMS Number: | F-E, S-E |
| · Stowage Category | B |

(Contd. on page 11)

-USA-

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/26/2025

Reviewed on 08/26/2025

Trade name: 935WN0006 FLEET WHITE

(Contd. of page 10)

- | | |
|---|---|
| · Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code | Not applicable. |
| · Transport/Additional information: | |
| · DOT | |
| · Quantity limitations | On passenger aircraft/rail: 5 L
On cargo aircraft only: 60 L |
| · IMDG | |
| · Limited quantities (LQ) | 5L |
| · Excepted quantities (EQ) | Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml |
| · UN "Model Regulation": | UN 1263 PAINT, 3, II |

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
No further relevant information available.

- **Sara**

- **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

- **Section 313 (Specific toxic chemical listings):**

1330-20-7 xylene

100-41-4 ethylbenzene

95-47-6 o-xylene

106-42-3 p-xylene

108-38-3 m-xylene

122-99-6 2-phenoxyethanol

7664-38-2 phosphoric acid

- **TSCA (Toxic Substances Control Act):**

13463-67-7	titanium dioxide	ACTIVE
123-86-4	n-butyl acetate	ACTIVE
110-43-0	heptan-2-one	ACTIVE
67-64-1	acetone	ACTIVE
98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene	ACTIVE
1330-20-7	xylene	ACTIVE
41556-26-7	bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate	ACTIVE
149-57-5	2-ethylhexanoic acid	ACTIVE
100-41-4	ethylbenzene	ACTIVE
95-47-6	o-xylene	ACTIVE
106-42-3	p-xylene	ACTIVE
108-38-3	m-xylene	ACTIVE
64742-47-8	Distillates (petroleum), hydrotreated light	ACTIVE
82919-37-7	methyl 1,2,2,6,6-pentamethyl-4-piperidylsebacate	ACTIVE

(Contd. on page 12)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/26/2025

Reviewed on 08/26/2025

Trade name: 935WN0006 FLEET WHITE

(Contd. of page 11)

108-65-6	2-methoxy-1-methylethyl acetate	ACTIVE
77-58-7	dibutyltin dilaurate	ACTIVE
122-99-6	2-phenoxyethanol	ACTIVE
51274-00-1	BAYFERROX 3910	ACTIVE
1333-86-4	Carbon black	ACTIVE
1047-16-1	Quinacridone	ACTIVE
64742-95-6	Solvent naphtha (petroleum), light arom.	ACTIVE
147-14-8	Phthalocyanine Blue	ACTIVE
14808-60-7	Quartz (SiO ₂)	ACTIVE
34590-94-8	Dipropylene glycol monomethyl ether	ACTIVE
7664-38-2	phosphoric acid	ACTIVE
57-55-6	Propylene glycol	ACTIVE
78-83-1	butanol	ACTIVE
108-83-8	2,6-dimethylheptan-4-one	ACTIVE

· Hazardous Air Pollutants

1330-20-7	xylene
100-41-4	ethylbenzene
95-47-6	o-xylene
106-42-3	p-xylene
108-38-3	m-xylene

· Proposition 65

· Chemicals known to cause cancer:

13463-67-7	titanium dioxide
98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene
100-41-4	ethylbenzene
1333-86-4	Carbon black
14808-60-7	Quartz (SiO ₂)

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

67-64-1	acetone	I
1330-20-7	xylene	I
100-41-4	ethylbenzene	D
95-47-6	o-xylene	I
106-42-3	p-xylene	I
108-38-3	m-xylene	I

· TLV (Threshold Limit Value)

13463-67-7	titanium dioxide	A4
------------	------------------	----

(Contd. on page 13)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/26/2025

Reviewed on 08/26/2025

Trade name: 935WN0006 FLEET WHITE

(Contd. of page 12)

67-64-1	acetone	A4
1330-20-7	xylene	A4
100-41-4	ethylbenzene	A3
95-47-6	o-xylene	A4
106-42-3	p-xylene	A4
108-38-3	m-xylene	A4
77-58-7	dibutyltin dilaurate	A4
1333-86-4	Carbon black	A4
14808-60-7	Quartz (SiO ₂)	A2

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

13463-67-7	titanium dioxide
1333-86-4	Carbon black
14808-60-7	Quartz (SiO ₂)

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**

titanium dioxide
 n-butyl acetate
 2-ethylhexanoic acid
 4-chloro- α,α,α -trifluorotoluene
 bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate

· **Hazard statements**

Highly flammable liquid and vapor.
 Causes serious eye irritation.
 May cause an allergic skin reaction.
 Suspected of causing cancer. Route of exposure: Inhalation.
 May damage fertility or the unborn child.
 May cause drowsiness or dizziness.

· **Precautionary statements**

Obtain special instructions before use.
 Do not handle until all safety precautions have been read and understood.
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
 Ground/bond container and receiving equipment.
 Use explosion-proof electrical/ventilating/lighting/equipment.
 Use only non-sparking tools.
 Take precautionary measures against static discharge.
 Avoid breathing dust/fume/gas/mist/vapors/spray
 Wash thoroughly after handling.
 Use only outdoors or in a well-ventilated area.
 Contaminated work clothing must not be allowed out of the workplace.
 Wear protective gloves/protective clothing/eye protection/face protection.
 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

(Contd. on page 14)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/26/2025

Reviewed on 08/26/2025

Trade name: 935WN0006 FLEET WHITE

(Contd. of page 13)

IF INHALED: Remove person to fresh air and keep comfortable for breathing.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
IF exposed or concerned: Get medical advice/attention.
Call a poison center/doctor if you feel unwell.
Specific treatment (see on this label).
If skin irritation or rash occurs: Get medical advice/attention.
If eye irritation persists: Get medical advice/attention.
Wash contaminated clothing before reuse.
In case of fire: Use CO2, powder or water spray to extinguish.
Store in a well-ventilated place. Keep container tightly closed.
Store in a well-ventilated place. Keep cool.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.
 • **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** Environment protection department.
- **Contact:** Product Safety Dept.
- **Date of preparation / last revision** 08/26/2025 / 7
- **Abbreviations and acronyms:**
 - IMDG: International Maritime Code for Dangerous Goods
 - DOT: US Department of Transportation
 - IATA: International Air Transport Association
 - EINECS: European Inventory of Existing Commercial Chemical Substances
 - ELINCS: European List of Notified Chemical Substances
 - CAS: Chemical Abstracts Service (division of the American Chemical Society)
 - NFPA: National Fire Protection Association (USA)
 - HMIS: Hazardous Materials Identification System (USA)
 - VOC: Volatile Organic Compounds (USA, EU)
 - LC50: Lethal concentration, 50 percent
 - LD50: Lethal dose, 50 percent
 - PBT: Persistent, Bioaccumulative and Toxic
 - vPvB: very Persistent and very Bioaccumulative
 - NIOSH: National Institute for Occupational Safety
 - OSHA: Occupational Safety & Health
 - TLV: Threshold Limit Value
 - PEL: Permissible Exposure Limit
 - REL: Recommended Exposure Limit
 - BEI: Biological Exposure Limit
 - Flammable Liquids 2: Flammable liquids – Category 2
 - Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A
 - Sensitization - Skin 1: Skin sensitisation – Category 1
 - Carcinogenicity 2: Carcinogenicity – Category 2
 - Toxic to Reproduction 1B: Reproductive toxicity – Category 1B
 - Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3
- *** Data compared to the previous version altered.**

USA