

Safety Data Sheet acc. to OSHA HCS

Printing date 07/30/2025

Reviewed on 07/29/2025

1 Identification

- **Product identifier**
- **Trade name:** 0H4.112 LEMON YELLOW
- **Article number:** 0H4.112
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
GlobalStar is a product of Lusid Technologies Inc.
4725 S Camp Kearns Road
Kearns, UT 84118
(801) 966-5300
info@lusidtechnologies.com
- **Information department:** Product safety department
- **Emergency telephone number:**
24 Hrs Emergency Contact:
INFOTRAC
1-800-535-5053

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flammable Liquids 3

H226 Flammable liquid and vapor.



GHS08 Health hazard

Germ Cell Mutagenicity 1B

H340 May cause genetic defects.

Carcinogenicity 1B

H350 May cause cancer.

Toxic to Reproduction 2

H361 Suspected of damaging fertility or the unborn child.

Specific Target Organ Toxicity - Repeated Exposure 2

H373 May cause damage to the hearing organs through prolonged or repeated exposure.

Aspiration Hazard 1

H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irritation 2

H315 Causes skin irritation.

Sensitization - Skin 1

H317 May cause an allergic skin reaction.

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/30/2025

Reviewed on 07/29/2025

Trade name: 0H4.112 LEMON YELLOW

(Contd. of page 1)

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02 GHS07 GHS08

- **Signal word** Danger

- **Hazard-determining components of labeling:**

Solvent naphtha (petroleum), light arom.

ethylbenzene

toluene

2-butanone oxime

- **Hazard statements**

Flammable liquid and vapor.

Causes skin irritation.

May cause an allergic skin reaction.

May cause genetic defects.

May cause cancer.

Suspected of damaging fertility or the unborn child.

May cause damage to the hearing organs through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

- **Precautionary statements**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Immediately call a poison center/doctor.

Specific treatment (see on this label).

Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF exposed or concerned: Get medical advice/attention.

Get medical advice/attention if you feel unwell.

Take off contaminated clothing and wash it before reuse.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

In case of fire: Use CO₂, powder or water spray to extinguish.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/30/2025

Reviewed on 07/29/2025

Trade name: 0H4.112 LEMON YELLOW

(Contd. of page 2)

- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



Health = 1
Fire = 3
Reactivity = 0

- **HMIS-ratings (scale 0 - 4)**



Health = *1
Fire = 3
Reactivity = 0

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

64742-95-6	Solvent naphtha (petroleum), light arom.	10-50%
108-65-6	2-methoxy-1-methylethyl acetate	10-25%
123-86-4	n-butyl acetate	10-25%
1330-20-7	xylene	10-25%
100-41-4	ethylbenzene	0-≤2.5%
96-29-7	2-butanone oxime	≤2.5%
108-88-3	toluene	0-≤2.5%

4 First-aid measures

- **Description of first aid measures**
- **General information:**
Immediately remove any clothing soiled by the product.
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

USA

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/30/2025

Reviewed on 07/29/2025

Trade name: 0H4.112 LEMON YELLOW

(Contd. of page 3)

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Dilute with plenty of water.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· PAC-1:

108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
123-86-4	n-butyl acetate	5 ppm
1330-20-7	xylene	130 ppm
100-41-4	ethylbenzene	33 ppm
96-29-7	2-butanone oxime	8.0 mg/m ³
108-88-3	toluene	67 ppm
71-43-2	benzene	52 ppm
108-83-8	2,6-dimethylheptan-4-one	75 ppm
14808-60-7	Quartz (SiO ₂)	0.075 mg/m ³

· PAC-2:

108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm
123-86-4	n-butyl acetate	200 ppm
1330-20-7	xylene	920* ppm
100-41-4	ethylbenzene	1100 ppm
96-29-7	2-butanone oxime	150 mg/m ³
108-88-3	toluene	560 ppm
71-43-2	benzene	800 ppm
108-83-8	2,6-dimethylheptan-4-one	330 ppm
14808-60-7	Quartz (SiO ₂)	8.3 mg/m ³

(Contd. on page 5)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/30/2025

Reviewed on 07/29/2025

Trade name: 0H4.112 LEMON YELLOW

(Contd. of page 4)

· PAC-3:		
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm
123-86-4	n-butyl acetate	3000* ppm
1330-20-7	xylene	2500* ppm
100-41-4	ethylbenzene	1800 ppm
96-29-7	2-butanone oxime	880 mg/m3
108-88-3	toluene	3700 ppm
71-43-2	benzene	4000* ppm
108-83-8	2,6-dimethylheptan-4-one	2000* ppm
14808-60-7	Quartz (SiO ₂)	50 mg/m3

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see section 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
At this time, the remaining constituent has no known exposure limits.

108-65-6 2-methoxy-1-methylethyl acetate	
WEEL	Long-term value: 50 ppm
123-86-4 n-butyl acetate	
PEL	Long-term value: 710 mg/m ³ , 150 ppm
REL	Short-term value: 950 mg/m ³ , 200 ppm Long-term value: 710 mg/m ³ , 150 ppm
TLV	Short-term value: 712 mg/m ³ , 150 ppm Long-term value: 238 mg/m ³ , 50 ppm

(Contd. on page 6)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/30/2025

Reviewed on 07/29/2025

Trade name: 0H4.112 LEMON YELLOW

(Contd. of page 5)

1330-20-7 xylene

PEL	Long-term value: 435 mg/m ³ , 100 ppm
REL	Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV	Long-term value: 20 ppm BEI, A4

100-41-4 ethylbenzene

PEL	Long-term value: 435 mg/m ³ , 100 ppm
REL	Short-term value: 545 mg/m ³ , 125 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV	Long-term value: 20 ppm OTO, BEI, A3

96-29-7 2-butanone oxime

WEEL	Long-term value: 10 ppm DSEN
------	---------------------------------

108-88-3 toluene

PEL	Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift
REL	Short-term value: 560 mg/m ³ , 150 ppm Long-term value: 375 mg/m ³ , 100 ppm
TLV	Long-term value: 20 ppm BEI, OTO, A4

Ingredients with biological limit values:**1330-20-7 xylene**

BEI	0.3 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids
-----	--

100-41-4 ethylbenzene

BEI	0.15 g/g creatinine Medium: urine Time: end of shift Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific)
-----	--

108-88-3 toluene

BEI	0.02 mg/L Medium: blood Time: prior to last shift of workweek Parameter: Toluene
	0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene
	0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background)

(Contd. on page 7)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/30/2025

Reviewed on 07/29/2025

Trade name: 0H4.112 LEMON YELLOW

(Contd. of page 6)

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
 Keep away from foodstuffs, beverages and feed.
 Immediately remove all soiled and contaminated clothing.
 Wash hands before breaks and at the end of work.
 Store protective clothing separately.
 Avoid contact with the skin.
 Avoid contact with the eyes and skin.
- **Breathing equipment:**
 In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**
 The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**
 The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

Form:

Liquid

Color:

Yellow

- **Odor:**

Characteristic

- **Odor threshold:**

Not determined.

- **pH-value:**

Not determined (pH N/A in solvent coatings)

- **Change in condition**

Melting point/Melting range:

Undetermined.

(Contd. on page 8)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/30/2025

Reviewed on 07/29/2025

Trade name: 0H4.112 LEMON YELLOW

(Contd. of page 7)

Boiling point/Boiling range:	124-128 °C (255.2-262.4 °F)
· Flash point:	27 °C (80.6 °F)
· Flammability:	Flammable.
· Auto igniting:	315 °C (599 °F)
· Decomposition temperature:	Not determined.
· Ignition temperature:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits:	
Lower:	0.7 Vol %
Upper:	10.8 Vol %
· Vapor pressure at 20 °C (68 °F):	10.7 hPa (8 mm Hg)
· Density at 20 °C (68 °F):	1.0624 g/cm ³ (8.8657 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	Fully miscible.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	≥63-68.3 %
VOC content:	≥62.96-68.26 %
	438.3 g/l / 3.66 lb/gal
Solids content:	58.7 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

-USA-

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/30/2025

Reviewed on 07/29/2025

Trade name: 0H4.112 LEMON YELLOW

(Contd. of page 8)

11 Toxicological information

· Information on toxicological effects

· Acute toxicity:

· LD/LC50 values that are relevant for classification:

64742-95-6 Solvent naphtha (petroleum), light arom.

Oral	LD50	>6,800 mg/kg (rat)
Dermal	LD50	>3,400 mg/kg (rab)
Inhalative	LC50/4 h	>10.2 mg/l (rat)

· Primary irritant effect:

· **on the skin:** Irritant to skin and mucous membranes.· **on the eye:** No irritating effect.· **Sensitization:** Sensitization possible through skin contact.

· Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

The product can cause inheritable damage.

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

1330-20-7	xylene	3
100-41-4	ethylbenzene	2B
108-88-3	toluene	3
71-43-2	benzene	1
1330-20-7	xylene	3
14808-60-7	Quartz (SiO ₂)	1

· NTP (National Toxicology Program)

71-43-2	benzene	K
14808-60-7	Quartz (SiO ₂)	K

· OSHA-Ca (Occupational Safety & Health Administration)

71-43-2	benzene
---------	---------

12 Ecological information

· Toxicity

· **Aquatic toxicity:** No further relevant information available.· **Persistence and degradability** No further relevant information available.

· Behavior in environmental systems:

· **Bioaccumulative potential** No further relevant information available.· **Mobility in soil** No further relevant information available.

· Additional ecological information:

· General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

· Results of PBT and vPvB assessment

· **PBT:** Not applicable.· **vPvB:** Not applicable.

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/30/2025

Reviewed on 07/29/2025

Trade name: 0H4.112 LEMON YELLOW

(Contd. of page 9)

· **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport information

- | | |
|---|----------------------------|
| · UN-Number | UN1263 |
| · DOT, IMDG, IATA | |
| · UN proper shipping name | Paint |
| · DOT | PAINT |
| · IMDG, IATA | |
| · Transport hazard class(es) | |
| · DOT | |
|  | |
| · Class | 3 Flammable liquids |
| · Label | 3 |
| · IMDG, IATA | |
|  | |
| · Class | 3 Flammable liquids |
| · Label | 3 |
| · Packing group | III |
| · DOT, IMDG, IATA | |
| · Environmental hazards: | Not applicable. |
| · Special precautions for user | Warning: Flammable liquids |
| · Hazard identification number (Kemler code): | 30 |
| · EMS Number: | F-E, S-E |
| · Stowage Category | A |
| · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | Not applicable. |

(Contd. on page 11)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/30/2025

Reviewed on 07/29/2025

Trade name: 0H4.112 LEMON YELLOW

(Contd. of page 10)

· **Transport/Additional information:**

· **DOT**

· **Quantity limitations**

On passenger aircraft/rail: 60 L

On cargo aircraft only: 220 L

· **IMDG**

· **Limited quantities (LQ)**

5L

· **Excepted quantities (EQ)**

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· **UN "Model Regulation":**

UN 1263 PAINT, 3, III

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

1330-20-7 xylene

100-41-4 ethylbenzene

108-88-3 toluene

71-43-2 benzene

· **TSCA (Toxic Substances Control Act):**

64742-95-6 Solvent naphtha (petroleum), light arom.

ACTIVE

108-65-6 2-methoxy-1-methylethyl acetate

ACTIVE

123-86-4 n-butyl acetate

ACTIVE

1330-20-7 xylene

ACTIVE

100-41-4 ethylbenzene

ACTIVE

96-29-7 2-butanone oxime

ACTIVE

108-88-3 toluene

ACTIVE

71-43-2 benzene

ACTIVE

108-83-8 2,6-dimethylheptan-4-one

ACTIVE

14808-60-7 Quartz (SiO₂)

ACTIVE

· **Hazardous Air Pollutants**

1330-20-7 xylene

100-41-4 ethylbenzene

108-88-3 toluene

71-43-2 benzene

· **Proposition 65**

· **Chemicals known to cause cancer:**

100-41-4 ethylbenzene

71-43-2 benzene

14808-60-7 Quartz (SiO₂)

(Contd. on page 12)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/30/2025

Reviewed on 07/29/2025

Trade name: 0H4.112 LEMON YELLOW

(Contd. of page 11)

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

71-43-2 benzene

· **Chemicals known to cause developmental toxicity:**

108-88-3 toluene

71-43-2 benzene

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

1330-20-7	xylene	I
100-41-4	ethylbenzene	D
108-88-3	toluene	II
71-43-2	benzene	A, K/L
110-54-3	n-hexane	II
1330-20-7	xylene	I

· **TLV (Threshold Limit Value)**

1330-20-7	xylene	A4
100-41-4	ethylbenzene	A3
108-88-3	toluene	A4
71-43-2	benzene	A1
1330-20-7	xylene	A4
14808-60-7	Quartz (SiO ₂)	A2

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

71-43-2	benzene
14808-60-7	Quartz (SiO ₂)

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**

Solvent naphtha (petroleum), light arom.

ethylbenzene

toluene

2-butanone oxime

· **Hazard statements**

Flammable liquid and vapor.

Causes skin irritation.

May cause an allergic skin reaction.

May cause genetic defects.

May cause cancer.

Suspected of damaging fertility or the unborn child.

(Contd. on page 13)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/30/2025

Reviewed on 07/29/2025

Trade name: 0H4.112 LEMON YELLOW

(Contd. of page 12)

*May cause damage to the hearing organs through prolonged or repeated exposure.**May be fatal if swallowed and enters airways.***Precautionary statements***Obtain special instructions before use.**Do not handle until all safety precautions have been read and understood.**Keep away from heat/sparks/open flames/hot surfaces. - No smoking.**Keep container tightly closed.**Ground/bond container and receiving equipment.**Use explosion-proof electrical/ventilating/lighting/equipment.**Use only non-sparking tools.**Take precautionary measures against static discharge.**Do not breathe dust/fume/gas/mist/vapors/spray.**Wash thoroughly after handling.**Contaminated work clothing must not be allowed out of the workplace.**Wear protective gloves/protective clothing/eye protection/face protection.**If swallowed: Immediately call a poison center/doctor.**Specific treatment (see on this label).**Do NOT induce vomiting.**If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.**If exposed or concerned: Get medical advice/attention.**Get medical advice/attention if you feel unwell.**Take off contaminated clothing and wash it before reuse.**If skin irritation or rash occurs: Get medical advice/attention.**Wash contaminated clothing before reuse.**In case of fire: Use CO₂, powder or water spray to extinguish.**Store in a well-ventilated place. Keep cool.**Store locked up.**Dispose of contents/container in accordance with local/regional/national/international regulations.***National regulations:****Additional classification according to Decree on Hazardous Materials:***Carcinogenic hazardous material group III (dangerous).***Information about limitation of use:***Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.***Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.***Department issuing SDS:** Environment protection department.**Contact:** Product Safety Dept.**Date of preparation / last revision** 07/30/2025 / 4**Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

(Contd. on page 14)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/30/2025

Reviewed on 07/29/2025

Trade name: 0H4.112 LEMON YELLOW

(Contd. of page 13)

*PBT: Persistent, Bioaccumulative and Toxic**vPvB: very Persistent and very Bioaccumulative**NIOSH: National Institute for Occupational Safety**OSHA: Occupational Safety & Health**TLV: Threshold Limit Value**PEL: Permissible Exposure Limit**REL: Recommended Exposure Limit**BEI: Biological Exposure Limit**Flammable Liquids 3: Flammable liquids – Category 3**Skin Irritation 2: Skin corrosion/irritation – Category 2**Sensitization - Skin 1: Skin sensitisation – Category 1**Germ Cell Mutagenicity 1B: Germ cell mutagenicity – Category 1B**Carcinogenicity 1B: Carcinogenicity – Category 1B**Toxic to Reproduction 2: Reproductive toxicity – Category 2**Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) – Category 2**Aspiration Hazard 1: Aspiration hazard – Category 1**** Data compared to the previous version altered.**

USA