

## Safety Data Sheet acc. to OSHA HCS

Printing date 08/11/2025

Reviewed on 08/11/2025

### 1 Identification

- **Product identifier**
- **Trade name:** 128B SERIES BINDER
- **Article number:** 128B
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
 NorthStar is a product of Lusid Technologies Inc  
 4725 S Camp Kearns Road  
 Kearns, UT 84118  
 (801) 966-5300  
 info@lusidtechnologies.com
- **Information department:** Product safety department
- **Emergency telephone number:**  
 24 Hrs Emergency Contact:  
 INFOTRAC  
 1-800-535-5053

### 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flammable Liquids 2      H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Germ Cell Mutagenicity 1B    H340 May cause genetic defects.  
 Carcinogenicity 1A      H350 May cause cancer.



GHS07

Skin Irritation 2      H315 Causes skin irritation.  
 Eye Irritation 2A      H319 Causes serious eye irritation.  
 Sensitization - Skin 1    H317 May cause an allergic skin reaction.

- **Label elements**
- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 08/11/2025

Reviewed on 08/11/2025

Trade name: 128B SERIES BINDER

(Contd. of page 1)

## · Hazard pictograms



GHS02 GHS07 GHS08

## · Signal word Danger

## · Hazard-determining components of labeling:

4-chloro-alpha,alpha,alpha-trifluorotoluene  
Solvent naphtha (petroleum), light arom.  
2-butanone oxime  
ethylbenzene

## · Hazard statements

Highly flammable liquid and vapor.  
Causes skin irritation.  
Causes serious eye irritation.  
May cause an allergic skin reaction.  
May cause genetic defects.  
May cause cancer.

## · Precautionary statements

Obtain special instructions before use.  
Do not handle until all safety precautions have been read and understood.  
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
Keep container tightly closed.  
Ground/bond container and receiving equipment.  
Use explosion-proof electrical/ventilating/lighting/equipment.  
Use only non-sparking tools.  
Take precautionary measures against static discharge.  
Avoid breathing dust/fume/gas/mist/vapors/spray  
Wash thoroughly after handling.  
Contaminated work clothing must not be allowed out of the workplace.  
Wear protective gloves/protective clothing/eye protection/face protection.  
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
If exposed or concerned: Get medical advice/attention.  
Specific treatment (see on this label).  
Take off contaminated clothing and wash it before reuse.  
If skin irritation or rash occurs: Get medical advice/attention.  
If eye irritation persists: Get medical advice/attention.  
Wash contaminated clothing before reuse.  
In case of fire: Use CO<sub>2</sub>, powder or water spray to extinguish.  
Store in a well-ventilated place. Keep cool.  
Store locked up.  
Dispose of contents/container in accordance with local/regional/national/international regulations.

## · Classification system:

## · NFPA ratings (scale 0 - 4)



Health = 2  
Fire = 3  
Reactivity = 0

(Contd. on page 3)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 08/11/2025

Reviewed on 08/11/2025

Trade name: 128B SERIES BINDER

(Contd. of page 2)

## · HMIS-ratings (scale 0 - 4)

HEALTH	2	Health = *2
FIRE	3	Fire = 3
REACTIVITY	0	Reactivity = 0

- Other hazards
- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.

## 3 Composition/information on ingredients

- Chemical characterization: Mixtures
- Description: Mixture of the substances listed below with nonhazardous additions.

### · Dangerous components:

67-64-1	acetone	10-25%
1330-20-7	xylene	2.5-10%
107-87-9	pentan-2-one	2.5-10%
98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene	2.5-10%
123-86-4	n-butyl acetate	2.5-10%
110-43-0	heptan-2-one	2.5-10%
64742-95-6	Solvent naphtha (petroleum), light arom.	≤2.5%
96-29-7	2-butanone oxime	≤2.5%
100-41-4	ethylbenzene	≤2.5%
64-17-5	ethanol	≤2.5%
67-56-1	methanol	≤2.5%

## 4 First-aid measures

- Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- After inhalation:  
Supply fresh air and to be sure call for a doctor.  
In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact:  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- Most important symptoms and effects, both acute and delayed  
No further relevant information available.
- Indication of any immediate medical attention and special treatment needed  
No further relevant information available.

USA

(Contd. on page 4)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 08/11/2025

Reviewed on 08/11/2025

Trade name: 128B SERIES BINDER

(Contd. of page 3)

## 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

## 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**  
Dilute with plenty of water.  
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to section 13.  
Ensure adequate ventilation.
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

### · PAC-1:

67-64-1	acetone	200 ppm
1330-20-7	xylene	130 ppm
107-87-9	pentan-2-one	150 ppm
123-86-4	n-butyl acetate	5 ppm
110-43-0	heptan-2-one	150 ppm
96-29-7	2-butanone oxime	8.0 mg/m <sup>3</sup>
100-41-4	ethylbenzene	33 ppm
95-63-6	1,2,4-trimethylbenzene	140 ppm
64-17-5	ethanol	1,800 ppm
122-99-6	2-phenoxyethanol	1.5 ppm
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
67-56-1	methanol	530 ppm
64742-48-9	Naphtha (petroleum), hydrotreated heavy	350 mg/m <sup>3</sup>
8052-41-3	Stoddard solvent	1700 mg/m <sup>3</sup>
67-63-0	propan-2-ol	400 ppm
112-34-5	2-(2-butoxyethoxy)ethanol	200 mg/m <sup>3</sup>
149-57-5	2-ethylhexanoic acid	15 mg/m <sup>3</sup>

### · PAC-2:

67-64-1	acetone	3200* ppm
1330-20-7	xylene	920* ppm
107-87-9	pentan-2-one	830 ppm

(Contd. on page 5)

USA

# Safety Data Sheet

acc. to OSHA HCS

Printing date 08/11/2025

Reviewed on 08/11/2025

Trade name: 128B SERIES BINDER

(Contd. of page 4)

123-86-4	<i>n</i> -butyl acetate	200 ppm
110-43-0	heptan-2-one	670 ppm
96-29-7	2-butanone oxime	150 mg/m <sup>3</sup>
100-41-4	ethylbenzene	1100 ppm
95-63-6	1,2,4-trimethylbenzene	360 ppm
64-17-5	ethanol	3300* ppm
122-99-6	2-phenoxyethanol	16 ppm
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm
67-56-1	methanol	2100 ppm
64742-48-9	Naphtha (petroleum), hydrotreated heavy	1,800 mg/m <sup>3</sup>
8052-41-3	Stoddard solvent	1800 mg/m <sup>3</sup>
67-63-0	propan-2-ol	2000* ppm
112-34-5	2-(2-butoxyethoxy)ethanol	220 mg/m <sup>3</sup>
149-57-5	2-ethylhexanoic acid	99 mg/m <sup>3</sup>

· **PAC-3:**

67-64-1	acetone	5700* ppm
1330-20-7	xylene	2500* ppm
107-87-9	pentan-2-one	5000* ppm
123-86-4	<i>n</i> -butyl acetate	3000* ppm
110-43-0	heptan-2-one	4000* ppm
96-29-7	2-butanone oxime	880 mg/m <sup>3</sup>
100-41-4	ethylbenzene	1800 ppm
95-63-6	1,2,4-trimethylbenzene	470 ppm
64-17-5	ethanol	15000* ppm
122-99-6	2-phenoxyethanol	97 ppm
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm
67-56-1	methanol	7200 ppm
64742-48-9	Naphtha (petroleum), hydrotreated heavy	40,000 mg/m <sup>3</sup>
8052-41-3	Stoddard solvent	20000 mg/m <sup>3</sup>
67-63-0	propan-2-ol	12000** ppm
112-34-5	2-(2-butoxyethoxy)ethanol	1300 mg/m <sup>3</sup>
149-57-5	2-ethylhexanoic acid	590 mg/m <sup>3</sup>

## 7 Handling and storage

· **Handling:**· **Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.  
Open and handle receptacle with care.  
Prevent formation of aerosols.

· **Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.  
Keep respiratory protective device available.

(Contd. on page 6)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 08/11/2025

Reviewed on 08/11/2025

Trade name: 128B SERIES BINDER

(Contd. of page 5)

- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**  
Keep receptacle tightly sealed.  
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

## 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see section 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**  
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.  
At this time, the other constituents have no known exposure limits.

### 67-64-1 acetone

PEL	Long-term value: 2400 mg/m <sup>3</sup> , 1000 ppm
REL	Long-term value: 590 mg/m <sup>3</sup> , 250 ppm
TLV	Short-term value: 1187 mg/m <sup>3</sup> , 500 ppm Long-term value: 594 mg/m <sup>3</sup> , 250 ppm A4, BEI

### 1330-20-7 xylene

PEL	Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
REL	Short-term value: 655 mg/m <sup>3</sup> , 150 ppm Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
TLV	Long-term value: 20 ppm BEI, A4

### 107-87-9 pentan-2-one

PEL	Long-term value: 700 mg/m <sup>3</sup> , 200 ppm
REL	Long-term value: 530 mg/m <sup>3</sup> , 150 ppm
TLV	Short-term value: 529 mg/m <sup>3</sup> , 150 ppm

### 123-86-4 n-butyl acetate

PEL	Long-term value: 710 mg/m <sup>3</sup> , 150 ppm
REL	Short-term value: 950 mg/m <sup>3</sup> , 200 ppm Long-term value: 710 mg/m <sup>3</sup> , 150 ppm
TLV	Short-term value: 712 mg/m <sup>3</sup> , 150 ppm Long-term value: 238 mg/m <sup>3</sup> , 50 ppm

### 110-43-0 heptan-2-one

PEL	Long-term value: 465 mg/m <sup>3</sup> , 100 ppm
REL	Long-term value: 465 mg/m <sup>3</sup> , 100 ppm
TLV	Long-term value: 50 ppm

### 96-29-7 2-butanone oxime

WEEL	Long-term value: 10 ppm DSEN
------	---------------------------------

(Contd. on page 7)

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 08/11/2025

Reviewed on 08/11/2025

**Trade name: 128B SERIES BINDER**

(Contd. of page 6)

**100-41-4 ethylbenzene**

PEL	Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
REL	Short-term value: 545 mg/m <sup>3</sup> , 125 ppm Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
TLV	Long-term value: 20 ppm OTO, BEI, A3

**64-17-5 ethanol**

PEL	Long-term value: 1900 mg/m <sup>3</sup> , 1000 ppm
REL	Long-term value: 1900 mg/m <sup>3</sup> , 1000 ppm
TLV	Short-term value: 1880 mg/m <sup>3</sup> , 1000 ppm A3

**67-56-1 methanol**

PEL	Long-term value: 260 mg/m <sup>3</sup> , 200 ppm
REL	Short-term value: 325 mg/m <sup>3</sup> , 250 ppm Long-term value: 260 mg/m <sup>3</sup> , 200 ppm Skin
TLV	Short-term value: 328 mg/m <sup>3</sup> , 250 ppm Long-term value: 262 mg/m <sup>3</sup> , 200 ppm Skin; BEI

**Ingredients with biological limit values:****67-64-1 acetone**

BEI	25 mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific)
-----	--

**1330-20-7 xylene**

BEI	0.3 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids
-----	--

**100-41-4 ethylbenzene**

BEI	0.15 g/g creatinine Medium: urine Time: end of shift Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific)
-----	--

**67-56-1 methanol**

BEI	15 mg/L Medium: urine Time: end of shift Parameter: Methanol (background, nonspecific)
-----	---

• **Additional information:** The lists that were valid during the creation were used as basis.

• **Exposure controls**

• **Personal protective equipment:**

• **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing.  
Wash hands before breaks and at the end of work.  
Store protective clothing separately.  
Avoid contact with the eyes and skin.

(Contd. on page 8)



# Safety Data Sheet

acc. to OSHA HCS

Printing date 08/11/2025

Reviewed on 08/11/2025

Trade name: 128B SERIES BINDER

(Contd. of page 7)

- **Breathing equipment:**

*In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.*

- **Protection of hands:**



Protective gloves

*The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.*

*Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation*

- **Material of gloves**

*The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.*

- **Penetration time of glove material**

*The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.*

- **Eye protection:**



Tightly sealed goggles

## 9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

**Form:**

Liquid

**Color:**

Amber colored

- **Odor:**

Characteristic

- **Odor threshold:**

Not determined.

- **pH-value:**

Not determined (pH N/A in solvent coatings)

- **Change in condition**

**Melting point/Melting range:**

Undetermined.

**Boiling point/Boiling range:**

55.8-56.6 °C (132.4-133.9 °F)

- **Flash point:**

&lt;-18 °C (&lt;-0.4 °F)

- **Flammability:**

Highly flammable.

- **Auto igniting:**

465 °C (869 °F)

- **Decomposition temperature:**

Not determined.

- **Ignition temperature:**

Product is not selfigniting.

- **Danger of explosion:**

*Product is not explosive. However, formation of explosive air/ vapor mixtures are possible.*

(Contd. on page 9)

-USA-



# Safety Data Sheet

acc. to OSHA HCS

Printing date 08/11/2025

Reviewed on 08/11/2025

Trade name: 128B SERIES BINDER

(Contd. of page 8)

· <b>Explosion limits:</b>	
Lower:	2.6 Vol %
Upper:	13 Vol %
· <b>Vapor pressure at 20 °C (68 °F):</b>	
233 hPa (174.8 mm Hg)	
· <b>Vapor pressure at 50 °C (122 °F):</b>	
800 hPa (600 mm Hg)	
· <b>Density at 20 °C (68 °F):</b>	
1.0049 g/cm <sup>3</sup> (8.3859 lbs/gal)	
· <b>Relative density</b>	
Not determined.	
· <b>Vapor density</b>	
Not determined.	
· <b>Evaporation rate</b>	
Not determined.	
· <b>Solubility in / Miscibility with</b>	
<b>Water:</b>	
Fully miscible.	
· <b>Partition coefficient (n-octanol/water):</b>	
Not determined.	
· <b>Viscosity:</b>	
<b>Dynamic:</b>	
Not determined.	
<b>Kinematic:</b>	
Not determined.	
· <b>Solvent content:</b>	
<b>Organic solvents:</b>	
≥36-36.1 %	
<b>VOC content:</b>	
≥22.31-22.33 %	
263.3 g/l / 2.20 lb/gal	
<b>Solids content:</b>	
61.5 %	
· <b>Other information</b>	
No further relevant information available.	

## 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

## 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

**107-87-9 pentan-2-one**

Oral	LD50	1,600 mg/kg (rat)
Dermal	LD50	6,500 mg/kg (rabbit)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:** Sensitization possible through skin contact.

(Contd. on page 10)

USA

# Safety Data Sheet

acc. to OSHA HCS

Printing date 08/11/2025

Reviewed on 08/11/2025

Trade name: 128B SERIES BINDER

(Contd. of page 9)

- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

The product can cause inheritable damage.

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

1330-20-7	xylene	3
98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene	2B
100-41-4	ethylbenzene	2B
64-17-5	ethanol	1
136-52-7	cobalt(II) 2-ethylhexanoate	2A
67-63-0	propan-2-ol	3

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

## 12 Ecological information

- **Toxicity**

- **Aquatic toxicity:** No further relevant information available.

- **Persistence and degradability** No further relevant information available.

- **Behavior in environmental systems:**

- **Bioaccumulative potential** No further relevant information available.

- **Mobility in soil** No further relevant information available.

- **Additional ecological information:**

- **General notes:**

Water hazard class 3 (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

- **Other adverse effects** No further relevant information available.

## 13 Disposal considerations

- **Waste treatment methods**

- **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- **Uncleaned packagings:**

- **Recommendation:** Disposal must be made according to official regulations.

- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

USA

(Contd. on page 11)

# Safety Data Sheet

acc. to OSHA HCS



Printing date 08/11/2025

Reviewed on 08/11/2025

Trade name: 128B SERIES BINDER

(Contd. of page 10)

## 14 Transport information

· UN-Number	UN1263
· DOT, IMDG, IATA	
· UN proper shipping name	Paint
· DOT	PAINT
· IMDG, IATA	
· Transport hazard class(es)	
· DOT	
	
· Class	3 Flammable liquids
· Label	3
· IMDG, IATA	
	
· Class	3 Flammable liquids
· Label	3
· Packing group	
· DOT, IMDG, IATA	II
· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Warning: Flammable liquids
· Hazard identification number (Kemler code):	33
· EMS Number:	F-E, S-E
· Stowage Category	B
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· DOT	
· Quantity limitations	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, II

USA

(Contd. on page 12)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 08/11/2025

Reviewed on 08/11/2025

Trade name: 128B SERIES BINDER

(Contd. of page 11)

## 15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

### · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

### · Section 313 (Specific toxic chemical listings):

1330-20-7	xylene
100-41-4	ethylbenzene
95-63-6	1,2,4-trimethylbenzene
122-99-6	2-phenoxyethanol
67-56-1	methanol
136-52-7	cobalt(II) 2-ethylhexanoate
67-63-0	propan-2-ol
112-34-5	2-(2-butoxyethoxy)ethanol

### · TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

### · Hazardous Air Pollutants

1330-20-7	xylene
100-41-4	ethylbenzene
67-56-1	methanol
136-52-7	cobalt(II) 2-ethylhexanoate

### · Proposition 65

#### · Chemicals known to cause cancer:

98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene
100-41-4	ethylbenzene

#### · Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

#### · Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

#### · Chemicals known to cause developmental toxicity:

64-17-5	ethanol
67-56-1	methanol

### · Carcinogenic categories

#### · EPA (Environmental Protection Agency)

67-64-1	acetone	I
1330-20-7	xylene	I
100-41-4	ethylbenzene	D
95-63-6	1,2,4-trimethylbenzene	II

#### · TLV (Threshold Limit Value)

67-64-1	acetone	A4
1330-20-7	xylene	A4
100-41-4	ethylbenzene	A3

(Contd. on page 13)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 08/11/2025

Reviewed on 08/11/2025

Trade name: 128B SERIES BINDER

(Contd. of page 12)

64-17-5	ethanol	A3
67-63-0	propan-2-ol	A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**

4-chloro-alpha,alpha,alpha-trifluorotoluene

Solvent naphtha (petroleum), light arom.

2-butanone oxime

ethylbenzene

· **Hazard statements**

Highly flammable liquid and vapor.

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

May cause genetic defects.

May cause cancer.

· **Precautionary statements**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Specific treatment (see on this label).

Take off contaminated clothing and wash it before reuse.

If skin irritation or rash occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

Wash contaminated clothing before reuse.

In case of fire: Use CO<sub>2</sub>, powder or water spray to extinguish.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 14)

USA

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 08/11/2025

Reviewed on 08/11/2025

**Trade name: 128B SERIES BINDER**

(Contd. of page 13)

- **National regulations:**
- **Additional classification according to Decree on Hazardous Materials:**  
Carcinogenic hazardous material group III (dangerous).
- **Information about limitation of use:**  
Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.
- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** Environment protection department.
- **Contact:** Product Safety Dept.
- **Date of preparation / last revision** 08/11/2025 / 7
- **Abbreviations and acronyms:**  
 IMDG: International Maritime Code for Dangerous Goods  
 DOT: US Department of Transportation  
 IATA: International Air Transport Association  
 EINECS: European Inventory of Existing Commercial Chemical Substances  
 ELINCS: European List of Notified Chemical Substances  
 CAS: Chemical Abstracts Service (division of the American Chemical Society)  
 NFPA: National Fire Protection Association (USA)  
 HMIS: Hazardous Materials Identification System (USA)  
 VOC: Volatile Organic Compounds (USA, EU)  
 LC50: Lethal concentration, 50 percent  
 LD50: Lethal dose, 50 percent  
 PBT: Persistent, Bioaccumulative and Toxic  
 vPvB: very Persistent and very Bioaccumulative  
 NIOSH: National Institute for Occupational Safety  
 OSHA: Occupational Safety & Health  
 TLV: Threshold Limit Value  
 PEL: Permissible Exposure Limit  
 REL: Recommended Exposure Limit  
 BEI: Biological Exposure Limit  
 Flammable Liquids 2: Flammable liquids – Category 2  
 Skin Irritation 2: Skin corrosion/irritation – Category 2  
 Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A  
 Sensitization - Skin 1: Skin sensitisation – Category 1  
 Germ Cell Mutagenicity 1B: Germ cell mutagenicity – Category 1B  
 Carcinogenicity 1A: Carcinogenicity – Category 1A
- **\* Data compared to the previous version altered.**

USA