

Safety Data Sheet
acc. to OSHA HCS

Printing date 08/26/2025

Reviewed on 08/26/2025

1 Identification

- **Product identifier**
- **Trade name: 135K0099 URETHANE BLACK**
- **Article number: 135K0099**
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
NorthStar is a product of Lusid Technologies Inc
4725 S Camp Kearns Road
Kearns, UT 84118
(801) 966-5300
info@lusidtechnologies.com
- **Information department: Product safety department**
- **Emergency telephone number:**
24 Hrs Emergency Contact:
INFOTRAC
1-800-535-5053

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flammable Liquids 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Germ Cell Mutagenicity 1B H340 May cause genetic defects.
Carcinogenicity 1B H350 May cause cancer.
Aspiration Hazard 1 H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irritation 2 H315 Causes skin irritation.
Sensitization - Skin 1 H317 May cause an allergic skin reaction.

- **Label elements**
- **GHS label elements**
The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/26/2025

Reviewed on 08/26/2025

Trade name: 135K0099 URETHANE BLACK

(Contd. of page 1)

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**

Solvent naphtha (petroleum), light arom.
Naphtha (petroleum), hydrotreated light
Carbon black
2-butanone oxime

· **Hazard statements**

Highly flammable liquid and vapor.
Causes skin irritation.
May cause an allergic skin reaction.
May cause genetic defects.
May cause cancer.
May be fatal if swallowed and enters airways.

· **Precautionary statements**

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Keep container tightly closed.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting/equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Avoid breathing dust/fume/gas/mist/vapors/spray
Wash thoroughly after handling.
Contaminated work clothing must not be allowed out of the workplace.
Wear protective gloves/protective clothing/eye protection/face protection.
If swallowed: Immediately call a poison center/doctor.
Specific treatment (see on this label).
Do NOT induce vomiting.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
If exposed or concerned: Get medical advice/attention.
Take off contaminated clothing and wash it before reuse.
If skin irritation or rash occurs: Get medical advice/attention.
Wash contaminated clothing before reuse.
In case of fire: Use CO₂, powder or water spray to extinguish.
Store in a well-ventilated place. Keep cool.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 1
Fire = 3
Reactivity = 0

(Contd. on page 3)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/26/2025

Reviewed on 08/26/2025

Trade name: 135K0099 URETHANE BLACK

(Contd. of page 2)

· HMIS-ratings (scale 0 - 4)

HEALTH	1	Health = *1
FIRE	3	Fire = 3
REACTIVITY	0	Reactivity = 0

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

* 3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:

1330-20-7	xylene	25-50%
64742-95-6	Solvent naphtha (petroleum), light arom.	10-25%
123-86-4	n-butyl acetate	2.5-10%
64742-49-0	Naphtha (petroleum), hydrotreated light	2.5-10%
110-43-0	heptan-2-one	2.5-10%
1333-86-4	Carbon black	≤2.5%
96-29-7	2-butanone oxime	≤2.5%

4 First-aid measures

- **Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

* 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture** No further relevant information available.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/26/2025

Reviewed on 08/26/2025

Trade name: 135K0099 URETHANE BLACK

(Contd. of page 3)

- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Dilute with plenty of water.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

- **PAC-1:**

1330-20-7	xylene	130 ppm
123-86-4	n-butyl acetate	5 ppm
110-43-0	heptan-2-one	150 ppm
1333-86-4	Carbon black	9 mg/m ³
763-69-9	ethyl 3-ethoxypropionate	1.6 ppm
107-87-9	pentan-2-one	150 ppm
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
96-29-7	2-butanone oxime	8.0 mg/m ³
95-63-6	1,2,4-trimethylbenzene	140 ppm
7664-38-2	phosphoric acid	3 mg/m ³
8052-41-3	Stoddard solvent	1700 mg/m ³
77-58-7	dibutyltin dilaurate	1.1 mg/m ³
122-99-6	2-phenoxyethanol	1.5 ppm
100-41-4	ethylbenzene	33 ppm
112-34-5	2-(2-butoxyethoxy)ethanol	200 mg/m ³
149-57-5	2-ethylhexanoic acid	15 mg/m ³
556-67-2	octamethylcyclotetrasiloxane	360 mg/m ³

- **PAC-2:**

1330-20-7	xylene	920* ppm
123-86-4	n-butyl acetate	200 ppm
110-43-0	heptan-2-one	670 ppm
1333-86-4	Carbon black	290 mg/m ³
763-69-9	ethyl 3-ethoxypropionate	18 ppm
107-87-9	pentan-2-one	830 ppm
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm
96-29-7	2-butanone oxime	150 mg/m ³

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/26/2025

Reviewed on 08/26/2025

Trade name: 135K0099 URETHANE BLACK

(Contd. of page 4)

95-63-6	1,2,4-trimethylbenzene	360 ppm
7664-38-2	phosphoric acid	30 mg/m ³
8052-41-3	Stoddard solvent	1800 mg/m ³
77-58-7	dibutyltin dilaurate	3.8 mg/m ³
122-99-6	2-phenoxyethanol	16 ppm
100-41-4	ethylbenzene	1100 ppm
112-34-5	2-(2-butoxyethoxy)ethanol	220 mg/m ³
149-57-5	2-ethylhexanoic acid	99 mg/m ³
556-67-2	octamethylcyclotetrasiloxane	530 mg/m ³

· **PAC-3:**

1330-20-7	xylene	2500* ppm
123-86-4	n-butyl acetate	3000* ppm
110-43-0	heptan-2-one	4000* ppm
1333-86-4	Carbon black	1750 mg/m ³
763-69-9	ethyl 3-ethoxypropionate	110 ppm
107-87-9	pentan-2-one	5000* ppm
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm
96-29-7	2-butanone oxime	880 mg/m ³
95-63-6	1,2,4-trimethylbenzene	470 ppm
7664-38-2	phosphoric acid	150 mg/m ³
8052-41-3	Stoddard solvent	20000 mg/m ³
77-58-7	dibutyltin dilaurate	23 mg/m ³
122-99-6	2-phenoxyethanol	97 ppm
100-41-4	ethylbenzene	1800 ppm
112-34-5	2-(2-butoxyethoxy)ethanol	1300 mg/m ³
149-57-5	2-ethylhexanoic acid	590 mg/m ³
556-67-2	octamethylcyclotetrasiloxane	1600 mg/m ³

7 Handling and storage

· **Handling:**· **Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· **Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

· **Conditions for safe storage, including any incompatibilities**· **Storage:**

· **Requirements to be met by storerooms and receptacles:** Store in a cool location.

· **Information about storage in one common storage facility:** Not required.

· **Further information about storage conditions:**

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

(Contd. on page 6)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/26/2025

Reviewed on 08/26/2025

Trade name: 135K0099 URETHANE BLACK

(Contd. of page 5)

· **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

· **Additional information about design of technical systems:** No further data; see section 7.· **Control parameters**· **Components with limit values that require monitoring at the workplace:**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

1330-20-7 xylene

PEL	Long-term value: 435 mg/m ³ , 100 ppm
REL	Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV	Long-term value: 20 ppm BEI, A4

123-86-4 n-butyl acetate

PEL	Long-term value: 710 mg/m ³ , 150 ppm
REL	Short-term value: 950 mg/m ³ , 200 ppm Long-term value: 710 mg/m ³ , 150 ppm
TLV	Short-term value: 712 mg/m ³ , 150 ppm Long-term value: 238 mg/m ³ , 50 ppm

64742-49-0 Naphtha (petroleum), hydrotreated light

TLV	Long-term value: 100 ppm
	Skin, A3

110-43-0 heptan-2-one

PEL	Long-term value: 465 mg/m ³ , 100 ppm
REL	Long-term value: 465 mg/m ³ , 100 ppm
TLV	Long-term value: 50 ppm

1333-86-4 Carbon black

PEL	Long-term value: 3.5 mg/m ³
REL	Long-term value: 3.5* mg/m ³ *0.1 in presence of PAHs; See Pocket Guide Apps.A+C
TLV	Long-term value: 3* mg/m ³ *inhalable fraction, A3

96-29-7 2-butanone oxime

WEEL	Long-term value: 10 ppm
	DSEN

· **Ingredients with biological limit values:**

1330-20-7 xylene

BEI	0.3 g/g creatinine
	Medium: urine
	Time: end of shift
	Parameter: Methylhippuric acids

· **Additional information:** The lists that were valid during the creation were used as basis.

(Contd. on page 7)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/26/2025

Reviewed on 08/26/2025

Trade name: 135K0099 URETHANE BLACK

(Contd. of page 6)

- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
 Keep away from foodstuffs, beverages and feed.
 Immediately remove all soiled and contaminated clothing.
 Wash hands before breaks and at the end of work.
 Store protective clothing separately.
 Avoid contact with the skin.
 Avoid contact with the eyes and skin.
- **Breathing equipment:**
 In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**
 The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**
 The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form:	Liquid
Color:	Black
Odor:	Characteristic
Odor threshold:	Not determined.

· pH-value: Not determined (pH N/A in solvent coatings)

· Change in condition

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	124-128 °C (255.2-262.4 °F)

(Contd. on page 8)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/26/2025

Reviewed on 08/26/2025

Trade name: 135K0099 URETHANE BLACK

(Contd. of page 7)

· Flash point:	7 °C (44.6 °F)
· Flammability:	Highly flammable.
· Auto igniting:	370 °C (698 °F)
· Decomposition temperature:	Not determined.
· Ignition temperature:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits:	
Lower:	0.7 Vol %
Upper:	7.5 Vol %
· Vapor pressure at 20 °C (68 °F):	6.7-8.2 hPa (5-6.2 mm Hg)
· Density at 20 °C (68 °F):	0.9827 g/cm ³ (8.2006 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	Fully miscible.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	59.1 %
VOC content:	59.18 %
	560.0 g/l / 4.67 lb/gal
Solids content:	43.0 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

USA

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/26/2025

Reviewed on 08/26/2025

Trade name: 135K0099 URETHANE BLACK

(Contd. of page 8)

11 Toxicological information

- **Information on toxicological effects**

- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

1330-20-7 xylene

Oral	LD50	4,300 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)

- **Primary irritant effect:**

- **on the skin:** Irritant to skin and mucous membranes.

- **on the eye:** No irritating effect.

- **Sensitization:** Sensitization possible through skin contact.

- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

The product can cause inheritable damage.

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

1330-20-7	xylene	3
1333-86-4	Carbon black	2B
136-52-7	cobalt(II) 2-ethylhexanoate	2A
100-41-4	ethylbenzene	2B

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**

- **Aquatic toxicity:** No further relevant information available.

- **Persistence and degradability:** No further relevant information available.

- **Behavior in environmental systems:**

- **Bioaccumulative potential:** No further relevant information available.

- **Mobility in soil:** No further relevant information available.

- **Additional ecological information:**

- **General notes:**

Water hazard class 3 (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

- **Other adverse effects:** No further relevant information available.

USA

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/26/2025

Reviewed on 08/26/2025



Trade name: 135K0099 URETHANE BLACK

(Contd. of page 9)

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport information

- | | |
|---|----------------------------|
| UN-Number | UN1263 |
| DOT, IMDG, IATA | UN1263 |
| UN proper shipping name | Paint |
| DOT | PAINT |
| IMDG, IATA | PAINT |
| Transport hazard class(es) | |
| DOT | |
|  | |
| Class | 3 Flammable liquids |
| Label | 3 |
| | |
| IMDG, IATA | |
|  | |
| Class | 3 Flammable liquids |
| Label | 3 |
| Packing group | III |
| DOT, IMDG, IATA | III |
| Environmental hazards: | |
| Marine pollutant: | No |
| Special precautions for user | Warning: Flammable liquids |
| Hazard identification number (Kemler code): | 30 |
| EMS Number: | F-E, S-E |
| Stowage Category | A |
| Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | Not applicable. |

(Contd. on page 11)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/26/2025

Reviewed on 08/26/2025

Trade name: 135K0099 URETHANE BLACK

(Contd. of page 10)

- **Transport/Additional information:**
- **DOT**
- **Quantity limitations** On passenger aircraft/rail: 60 L
On cargo aircraft only: 220 L

- **IMDG**
- **Limited quantities (LQ)** 5L
- **Excepted quantities (EQ)** Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml

- **UN "Model Regulation":** UN 1263 PAINT, 3, III

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**

- **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

- **Section 313 (Specific toxic chemical listings):**

1330-20-7	xylene
95-63-6	1,2,4-trimethylbenzene
7664-38-2	phosphoric acid
136-52-7	cobalt(II) 2-ethylhexanoate
122-99-6	2-phenoxyethanol
100-41-4	ethylbenzene
112-34-5	2-(2-butoxyethoxy)ethanol

- **TSCA (Toxic Substances Control Act):**

1330-20-7	xylene	ACTIVE
64742-95-6	Solvent naphtha (petroleum), light arom.	ACTIVE
123-86-4	n-butyl acetate	ACTIVE
110-43-0	heptan-2-one	ACTIVE
1333-86-4	Carbon black	ACTIVE
763-69-9	ethyl 3-ethoxypropionate	ACTIVE
107-87-9	pentan-2-one	ACTIVE
108-65-6	2-methoxy-1-methylethyl acetate	ACTIVE
96-29-7	2-butanone oxime	ACTIVE
95-63-6	1,2,4-trimethylbenzene	ACTIVE
7664-38-2	phosphoric acid	ACTIVE
8052-41-3	Stoddard solvent	ACTIVE
136-52-7	cobalt(II) 2-ethylhexanoate	ACTIVE
77-58-7	dibutyltin dilaurate	ACTIVE
122-99-6	2-phenoxyethanol	ACTIVE
100-41-4	ethylbenzene	ACTIVE
112-34-5	2-(2-butoxyethoxy)ethanol	ACTIVE

(Contd. on page 12)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/26/2025

Reviewed on 08/26/2025

Trade name: 135K0099 URETHANE BLACK

(Contd. of page 11)

149-57-5	2-ethylhexanoic acid	ACTIVE
556-67-2	octamethylcyclotetrasiloxane	ACTIVE

· **Hazardous Air Pollutants**

1330-20-7	xylene
136-52-7	cobalt(II) 2-ethylhexanoate
100-41-4	ethylbenzene

· **Proposition 65**

· **Chemicals known to cause cancer:**

1333-86-4	Carbon black
100-41-4	ethylbenzene

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

1330-20-7	xylene	I
95-63-6	1,2,4-trimethylbenzene	II
100-41-4	ethylbenzene	D

· **TLV (Threshold Limit Value)**

1330-20-7	xylene	A4
1333-86-4	Carbon black	A4
77-58-7	dibutyltin dilaurate	A4
100-41-4	ethylbenzene	A3

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

1333-86-4	Carbon black
-----------	--------------

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**

Solvent naphtha (petroleum), light arom.

Naphtha (petroleum), hydrotreated light

Carbon black

2-butanone oxime

· **Hazard statements**

Highly flammable liquid and vapor.

Causes skin irritation.

(Contd. on page 13)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/26/2025

Reviewed on 08/26/2025

Trade name: 135K0099 URETHANE BLACK

(Contd. of page 12)

May cause an allergic skin reaction.
 May cause genetic defects.
 May cause cancer.
 May be fatal if swallowed and enters airways.

· **Precautionary statements**

Obtain special instructions before use.
 Do not handle until all safety precautions have been read and understood.
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
 Keep container tightly closed.
 Ground/bond container and receiving equipment.
 Use explosion-proof electrical/ventilating/lighting/equipment.
 Use only non-sparking tools.
 Take precautionary measures against static discharge.
 Avoid breathing dust/fume/gas/mist/vapors/spray
 Wash thoroughly after handling.
 Contaminated work clothing must not be allowed out of the workplace.
 Wear protective gloves/protective clothing/eye protection/face protection.
 If swallowed: Immediately call a poison center/doctor.
 Specific treatment (see on this label).
 Do NOT induce vomiting.
 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 IF exposed or concerned: Get medical advice/attention.
 Take off contaminated clothing and wash it before reuse.
 If skin irritation or rash occurs: Get medical advice/attention.
 Wash contaminated clothing before reuse.
 In case of fire: Use CO₂, powder or water spray to extinguish.
 Store in a well-ventilated place. Keep cool.
 Store locked up.
 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **National regulations:**

· **Additional classification according to Decree on Hazardous Materials:**

Carcinogenic hazardous material group III (dangerous).

· **Information about limitation of use:**

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Environment protection department.

· **Contact:** Product Safety Dept.

· **Date of preparation / last revision** 08/26/2025 / 4

· **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

(Contd. on page 14)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/26/2025

Reviewed on 08/26/2025

Trade name: 135K0099 URETHANE BLACK

(Contd. of page 13)

LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
BEI: Biological Exposure Limit
Flammable Liquids 2: Flammable liquids – Category 2
Skin Irritation 2: Skin corrosion/irritation – Category 2
Sensitization - Skin 1: Skin sensitisation – Category 1
Germ Cell Mutagenicity 1B: Germ cell mutagenicity – Category 1B
Carcinogenicity 1B: Carcinogenicity – Category 1B
Aspiration Hazard 1: Aspiration hazard – Category 1
· * **Data compared to the previous version altered.**

USA