

## Safety Data Sheet acc. to OSHA HCS

Printing date 07/29/2025

Reviewed on 07/29/2025

### 1 Identification

- **Product identifier**
- **Trade name:** 0D7.401 BASE WHITE PEARL
- **Article number:** 0D7.401
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
GlobalStar is a product of Lusid Technologies Inc.  
4725 S Camp Kearns Road  
Kearns, UT 84118  
(801) 966-5300  
info@lusidtechnologies.com
- **Information department:** Product safety department
- **Emergency telephone number:**  
24 Hrs Emergency Contact:  
INFOTRAC  
1-800-535-5053

### 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flammable Liquids 3

H226 Flammable liquid and vapor.



GHS08 Health hazard

Germ Cell Mutagenicity 1B

H340 May cause genetic defects.

Carcinogenicity 1B

H350 May cause cancer.



GHS07

Skin Irritation 2

H315 Causes skin irritation.

Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

USA

# Safety Data Sheet

acc. to OSHA HCS

Printing date 07/29/2025

Reviewed on 07/29/2025

Trade name: 0D7.401 BASE WHITE PEARL

(Contd. of page 1)

## · Hazard pictograms



GHS02 GHS07 GHS08

## · Signal word Danger

## · Hazard-determining components of labeling:

*n*-butyl acetate  
 titanium dioxide  
 Solvent naphtha (petroleum), light arom.  
 ethylbenzene

## · Hazard statements

Flammable liquid and vapor.  
 Causes skin irritation.  
 May cause genetic defects.  
 May cause cancer.  
 May cause drowsiness or dizziness.

## · Precautionary statements

Obtain special instructions before use.  
 Do not handle until all safety precautions have been read and understood.  
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
 Ground/bond container and receiving equipment.  
 Use explosion-proof electrical/ventilating/lighting/equipment.  
 Use only non-sparking tools.  
 Take precautionary measures against static discharge.  
 Avoid breathing dust/fume/gas/mist/vapors/spray  
 Wash thoroughly after handling.  
 Use only outdoors or in a well-ventilated area.  
 Wear protective gloves/protective clothing/eye protection/face protection.  
 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 IF exposed or concerned: Get medical advice/attention.  
 Call a poison center/doctor if you feel unwell.  
 Specific treatment (see on this label).  
 Take off contaminated clothing and wash it before reuse.  
 If skin irritation occurs: Get medical advice/attention.  
 In case of fire: Use CO<sub>2</sub>, powder or water spray to extinguish.  
 Store in a well-ventilated place. Keep container tightly closed.  
 Store in a well-ventilated place. Keep cool.  
 Store locked up.  
 Dispose of contents/container in accordance with local/regional/national/international regulations.

## · Classification system:

## · NFPA ratings (scale 0 - 4)



Health = 1  
 Fire = 3  
 Reactivity = 0

## · HMIS-ratings (scale 0 - 4)



Health = \*1  
 Fire = 3  
 Reactivity = 0

(Contd. on page 3)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 07/29/2025

Reviewed on 07/29/2025

Trade name: 0D7.401 BASE WHITE PEARL

(Contd. of page 2)

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

## 3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

|            |                                          |         |
|------------|------------------------------------------|---------|
| 123-86-4   | n-butyl acetate                          | 25-50%  |
| 1330-20-7  | xylene                                   | 10-25%  |
| 108-65-6   | 2-methoxy-1-methylethyl acetate          | 2.5-10% |
| 12001-26-2 | Mica                                     | 2.5-10% |
| 13463-67-7 | titanium dioxide                         | ≤2.5%   |
| 100-41-4   | ethylbenzene                             | ≤2.5%   |
| 64742-95-6 | Solvent naphtha (petroleum), light arom. | ≤2.5%   |

## 4 First-aid measures

- **Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**  
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

## 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

## 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**  
Prevent seepage into sewage system, workpits and cellars.  
Dilute with plenty of water.

(Contd. on page 4)

-USA-

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 07/29/2025

Reviewed on 07/29/2025

Trade name: 0D7.401 BASE WHITE PEARL

(Contd. of page 3)

· **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
 Dispose contaminated material as waste according to section 13.  
 Ensure adequate ventilation.

· **Reference to other sections**

See Section 7 for information on safe handling.  
 See Section 8 for information on personal protection equipment.  
 See Section 13 for disposal information.

· **Protective Action Criteria for Chemicals**

· **PAC-1:**

|            |                                 |                      |
|------------|---------------------------------|----------------------|
| 123-86-4   | <i>n</i> -butyl acetate         | 5 ppm                |
| 1330-20-7  | xylene                          | 130 ppm              |
| 108-65-6   | 2-methoxy-1-methylethyl acetate | 50 ppm               |
| 12001-26-2 | Mica                            | 9 mg/m <sup>3</sup>  |
| 13463-67-7 | titanium dioxide                | 30 mg/m <sup>3</sup> |
| 100-41-4   | ethylbenzene                    | 33 ppm               |
| 71-36-3    | butan-1-ol                      | 60 ppm               |
| 64-17-5    | ethanol                         | 1,800 ppm            |
| 108-83-8   | 2,6-dimethylheptan-4-one        | 75 ppm               |
| 67-56-1    | methanol                        | 530 ppm              |
| 7664-38-2  | phosphoric acid                 | 3 mg/m <sup>3</sup>  |
| 67-63-0    | propan-2-ol                     | 400 ppm              |

· **PAC-2:**

|            |                                 |                       |
|------------|---------------------------------|-----------------------|
| 123-86-4   | <i>n</i> -butyl acetate         | 200 ppm               |
| 1330-20-7  | xylene                          | 920* ppm              |
| 108-65-6   | 2-methoxy-1-methylethyl acetate | 1,000 ppm             |
| 12001-26-2 | Mica                            | 99 mg/m <sup>3</sup>  |
| 13463-67-7 | titanium dioxide                | 330 mg/m <sup>3</sup> |
| 100-41-4   | ethylbenzene                    | 1100 ppm              |
| 71-36-3    | butan-1-ol                      | 800 ppm               |
| 64-17-5    | ethanol                         | 3300* ppm             |
| 108-83-8   | 2,6-dimethylheptan-4-one        | 330 ppm               |
| 67-56-1    | methanol                        | 2100 ppm              |
| 7664-38-2  | phosphoric acid                 | 30 mg/m <sup>3</sup>  |
| 67-63-0    | propan-2-ol                     | 2000* ppm             |

· **PAC-3:**

|            |                                 |                         |
|------------|---------------------------------|-------------------------|
| 123-86-4   | <i>n</i> -butyl acetate         | 3000* ppm               |
| 1330-20-7  | xylene                          | 2500* ppm               |
| 108-65-6   | 2-methoxy-1-methylethyl acetate | 5000* ppm               |
| 12001-26-2 | Mica                            | 590 mg/m <sup>3</sup>   |
| 13463-67-7 | titanium dioxide                | 2,000 mg/m <sup>3</sup> |
| 100-41-4   | ethylbenzene                    | 1800 ppm                |
| 71-36-3    | butan-1-ol                      | 8000** ppm              |
| 64-17-5    | ethanol                         | 15000* ppm              |
| 108-83-8   | 2,6-dimethylheptan-4-one        | 2000* ppm               |

(Contd. on page 5)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 07/29/2025

Reviewed on 07/29/2025

Trade name: 0D7.401 BASE WHITE PEARL

(Contd. of page 4)

|           |                 |                       |
|-----------|-----------------|-----------------------|
| 67-56-1   | methanol        | 7200 ppm              |
| 7664-38-2 | phosphoric acid | 150 mg/m <sup>3</sup> |
| 67-63-0   | propan-2-ol     | 12000** ppm           |

## 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**  
Ensure good ventilation/exhaustion at the workplace.  
Open and handle receptacle with care.  
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.  
Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s):** No further relevant information available.

## 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see section 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**  
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.  
At this time, the other constituents have no known exposure limits.

### 123-86-4 n-butyl acetate

|     |                                                                                                       |
|-----|-------------------------------------------------------------------------------------------------------|
| PEL | Long-term value: 710 mg/m <sup>3</sup> , 150 ppm                                                      |
| REL | Short-term value: 950 mg/m <sup>3</sup> , 200 ppm<br>Long-term value: 710 mg/m <sup>3</sup> , 150 ppm |
| TLV | Short-term value: 712 mg/m <sup>3</sup> , 150 ppm<br>Long-term value: 238 mg/m <sup>3</sup> , 50 ppm  |

### 1330-20-7 xylene

|     |                                                                                                       |
|-----|-------------------------------------------------------------------------------------------------------|
| PEL | Long-term value: 435 mg/m <sup>3</sup> , 100 ppm                                                      |
| REL | Short-term value: 655 mg/m <sup>3</sup> , 150 ppm<br>Long-term value: 435 mg/m <sup>3</sup> , 100 ppm |
| TLV | Long-term value: 20 ppm<br>BEI, A4                                                                    |

### 108-65-6 2-methoxy-1-methylethyl acetate

|      |                         |
|------|-------------------------|
| WEEL | Long-term value: 50 ppm |
|------|-------------------------|

(Contd. on page 6)

USA

# Safety Data Sheet

acc. to OSHA HCS

Printing date 07/29/2025

Reviewed on 07/29/2025

Trade name: 0D7.401 BASE WHITE PEARL

(Contd. of page 5)

**12001-26-2 Mica**

|     |                                                                                   |
|-----|-----------------------------------------------------------------------------------|
| PEL | Long-term value: 20 mppcf ppm<br><1% crystalline silica                           |
| REL | Long-term value: 3* mg/m <sup>3</sup><br>*respirable dust; containing < 1% quartz |
| TLV | Long-term value: 0.1 mg/m <sup>3</sup><br>*Respirable particulate matter          |

**100-41-4 ethylbenzene**

|     |                                                                                                       |
|-----|-------------------------------------------------------------------------------------------------------|
| PEL | Long-term value: 435 mg/m <sup>3</sup> , 100 ppm                                                      |
| REL | Short-term value: 545 mg/m <sup>3</sup> , 125 ppm<br>Long-term value: 435 mg/m <sup>3</sup> , 100 ppm |
| TLV | Long-term value: 20 ppm<br>OTO, BEI, A3                                                               |

**Ingredients with biological limit values:****1330-20-7 xylene**

|     |                                                                                              |
|-----|----------------------------------------------------------------------------------------------|
| BEI | 0.3 g/g creatinine<br>Medium: urine<br>Time: end of shift<br>Parameter: Methylhippuric acids |
|-----|----------------------------------------------------------------------------------------------|

**100-41-4 ethylbenzene**

|     |                                                                                                                                      |
|-----|--------------------------------------------------------------------------------------------------------------------------------------|
| BEI | 0.15 g/g creatinine<br>Medium: urine<br>Time: end of shift<br>Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific) |
|-----|--------------------------------------------------------------------------------------------------------------------------------------|

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing.  
Wash hands before breaks and at the end of work.  
Store protective clothing separately.  
Avoid contact with the skin.  
Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to

(Contd. on page 7)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 07/29/2025

Reviewed on 07/29/2025

Trade name: 0D7.401 BASE WHITE PEARL

(Contd. of page 6)

be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Tightly sealed goggles

## 9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

**Form:** Liquid

**Color:** White

- **Odor:** Characteristic

- **Odor threshold:** Not determined.

- **pH-value:** Not determined (pH N/A in solvent coatings)

- **Change in condition**

**Melting point/Melting range:** Undetermined.

**Boiling point/Boiling range:** 124-128 °C (255.2-262.4 °F)

- **Flash point:** 27 °C (80.6 °F)

- **Flammability:** Flammable.

- **Auto igniting:** 315 °C (599 °F)

- **Decomposition temperature:** Not determined.

- **Ignition temperature:** Product is not selfigniting.

- **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

- **Explosion limits:**

**Lower:** 1.1 Vol %

**Upper:** 7.5 Vol %

- **Vapor pressure at 20 °C (68 °F):** 10.7 hPa (8 mm Hg)

- **Vapor pressure at 50 °C (122 °F):** 55 hPa (41.3 mm Hg)

- **Density at 20 °C (68 °F):** 1.0649 g/cm<sup>3</sup> (8.8866 lbs/gal)

- **Relative density** Not determined.

- **Vapor density** Not determined.

- **Evaporation rate** Not determined.

- **Solubility in / Miscibility with**

**Water:** Fully miscible.

- **Partition coefficient (n-octanol/water):** Not determined.

- **Viscosity:**

**Dynamic:** Not determined.

(Contd. on page 8)



# Safety Data Sheet

acc. to OSHA HCS

Printing date 07/29/2025

Reviewed on 07/29/2025

Trade name: 0D7.401 BASE WHITE PEARL

(Contd. of page 7)

|                            |                                            |
|----------------------------|--------------------------------------------|
| <b>Kinematic:</b>          | Not determined.                            |
| · <b>Solvent content:</b>  |                                            |
| <b>Organic solvents:</b>   | 63.1 %                                     |
| <b>VOC content:</b>        | 63.12 %                                    |
|                            | 580.8 g/l / 4.85 lb/gal                    |
| <b>Solids content:</b>     | 45.5 %                                     |
| · <b>Other information</b> | No further relevant information available. |

## 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

## 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

### 1330-20-7 xylene

|        |      |                      |
|--------|------|----------------------|
| Oral   | LD50 | 4,300 mg/kg (rat)    |
| Dermal | LD50 | 2,000 mg/kg (rabbit) |

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** No irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**  
The product shows the following dangers according to internally approved calculation methods for preparations:  
Irritant  
The product can cause inheritable damage.

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

|            |                  |    |
|------------|------------------|----|
| 1330-20-7  | xylene           | 3  |
| 13463-67-7 | titanium dioxide | 2B |
| 100-41-4   | ethylbenzene     | 2B |
| 64-17-5    | ethanol          | 1  |
| 67-63-0    | propan-2-ol      | 3  |

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

(Contd. on page 9)

USA



# Safety Data Sheet

acc. to OSHA HCS

Printing date 07/29/2025

Reviewed on 07/29/2025

Trade name: 0D7.401 BASE WHITE PEARL

(Contd. of page 8)

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

## 12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:** Not hazardous for water.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

## 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**  
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

## 14 Transport information

· **UN-Number**  
· **DOT, IMDG, IATA** UN1263

· **UN proper shipping name**  
· **DOT** Paint  
· **IMDG, IATA** PAINT

· **Transport hazard class(es)**· **DOT**

· **Class** 3 Flammable liquids

(Contd. on page 10)

USA

# Safety Data Sheet

acc. to OSHA HCS

Printing date 07/29/2025

Reviewed on 07/29/2025

Trade name: 0D7.401 BASE WHITE PEARL

(Contd. of page 9)

|                                                                                   |                                                                                                                  |
|-----------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------|
| · <b>Label</b>                                                                    | 3                                                                                                                |
| · <b>IMDG, IATA</b>                                                               |                                                                                                                  |
|  |                                                                                                                  |
| · <b>Class</b>                                                                    | 3 Flammable liquids                                                                                              |
| · <b>Label</b>                                                                    | 3                                                                                                                |
| · <b>Packing group</b>                                                            |                                                                                                                  |
| · <b>DOT, IMDG, IATA</b>                                                          | III                                                                                                              |
| · <b>Environmental hazards:</b>                                                   | Not applicable.                                                                                                  |
| · <b>Special precautions for user</b>                                             | Warning: Flammable liquids                                                                                       |
| · <b>Hazard identification number (Kemler code):</b>                              | 30                                                                                                               |
| · <b>EMS Number:</b>                                                              | F-E, S-E                                                                                                         |
| · <b>Stowage Category</b>                                                         | A                                                                                                                |
| · <b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b>  | Not applicable.                                                                                                  |
| · <b>Transport/Additional information:</b>                                        |                                                                                                                  |
| · <b>DOT</b>                                                                      |                                                                                                                  |
| · <b>Quantity limitations</b>                                                     | On passenger aircraft/rail: 60 L<br>On cargo aircraft only: 220 L                                                |
| · <b>IMDG</b>                                                                     |                                                                                                                  |
| · <b>Limited quantities (LQ)</b>                                                  | 5L                                                                                                               |
| · <b>Excepted quantities (EQ)</b>                                                 | Code: E1<br>Maximum net quantity per inner packaging: 30 ml<br>Maximum net quantity per outer packaging: 1000 ml |
| · <b>UN "Model Regulation":</b>                                                   | UN 1263 PAINT, 3, III                                                                                            |

## 15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**  
 · **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

|           |                 |
|-----------|-----------------|
| 1330-20-7 | xylene          |
| 100-41-4  | ethylbenzene    |
| 71-36-3   | butan-1-ol      |
| 67-56-1   | methanol        |
| 7664-38-2 | phosphoric acid |
| 67-63-0   | propan-2-ol     |

· **TSCA (Toxic Substances Control Act):**

|           |                 |        |
|-----------|-----------------|--------|
| 123-86-4  | n-butyl acetate | ACTIVE |
| 1330-20-7 | xylene          | ACTIVE |

(Contd. on page 11)

USA

# Safety Data Sheet

acc. to OSHA HCS

Printing date 07/29/2025

Reviewed on 07/29/2025

Trade name: 0D7.401 BASE WHITE PEARL

(Contd. of page 10)

|            |                                          |        |
|------------|------------------------------------------|--------|
| 108-65-6   | 2-methoxy-1-methylethyl acetate          | ACTIVE |
| 9004-36-8  | Cellulose Acetate Butyrate               | ACTIVE |
| 13463-67-7 | titanium dioxide                         | ACTIVE |
| 100-41-4   | ethylbenzene                             | ACTIVE |
| 71-36-3    | butan-1-ol                               | ACTIVE |
| 64742-95-6 | Solvent naphtha (petroleum), light arom. | ACTIVE |
| 64-17-5    | ethanol                                  | ACTIVE |
| 108-83-8   | 2,6-dimethylheptan-4-one                 | ACTIVE |
| 67-56-1    | methanol                                 | ACTIVE |
| 7664-38-2  | phosphoric acid                          | ACTIVE |
| 67-63-0    | propan-2-ol                              | ACTIVE |

· **Hazardous Air Pollutants**

|           |              |
|-----------|--------------|
| 1330-20-7 | xylene       |
| 100-41-4  | ethylbenzene |
| 67-56-1   | methanol     |

· **Proposition 65**· **Chemicals known to cause cancer:**

|            |                  |
|------------|------------------|
| 13463-67-7 | titanium dioxide |
| 100-41-4   | ethylbenzene     |

· **Chemicals known to cause reproductive toxicity for females:**

|                                    |  |
|------------------------------------|--|
| None of the ingredients is listed. |  |
|------------------------------------|--|

· **Chemicals known to cause reproductive toxicity for males:**

|                                    |  |
|------------------------------------|--|
| None of the ingredients is listed. |  |
|------------------------------------|--|

· **Chemicals known to cause developmental toxicity:**

|         |          |
|---------|----------|
| 64-17-5 | ethanol  |
| 67-56-1 | methanol |

· **Carcinogenic categories**· **EPA (Environmental Protection Agency)**

|           |              |   |
|-----------|--------------|---|
| 1330-20-7 | xylene       | I |
| 100-41-4  | ethylbenzene | D |
| 71-36-3   | butan-1-ol   | D |

· **TLV (Threshold Limit Value)**

|            |                  |    |
|------------|------------------|----|
| 1330-20-7  | xylene           | A4 |
| 13463-67-7 | titanium dioxide | A4 |
| 100-41-4   | ethylbenzene     | A3 |
| 64-17-5    | ethanol          | A3 |
| 67-63-0    | propan-2-ol      | A4 |

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

|            |                  |
|------------|------------------|
| 13463-67-7 | titanium dioxide |
|------------|------------------|

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 12)

USA

# Safety Data Sheet

acc. to OSHA HCS

Printing date 07/29/2025

Reviewed on 07/29/2025

Trade name: 0D7.401 BASE WHITE PEARL

(Contd. of page 11)

## · Hazard pictograms



GHS02 GHS07 GHS08

## · Signal word Danger

## · Hazard-determining components of labeling:

*n*-butyl acetate  
 titanium dioxide  
 Solvent naphtha (petroleum), light arom.  
 ethylbenzene

## · Hazard statements

Flammable liquid and vapor.  
 Causes skin irritation.  
 May cause genetic defects.  
 May cause cancer.  
 May cause drowsiness or dizziness.

## · Precautionary statements

Obtain special instructions before use.  
 Do not handle until all safety precautions have been read and understood.  
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
 Ground/bond container and receiving equipment.  
 Use explosion-proof electrical/ventilating/lighting/equipment.  
 Use only non-sparking tools.  
 Take precautionary measures against static discharge.  
 Avoid breathing dust/fume/gas/mist/vapors/spray  
 Wash thoroughly after handling.  
 Use only outdoors or in a well-ventilated area.  
 Wear protective gloves/protective clothing/eye protection/face protection.  
 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 IF exposed or concerned: Get medical advice/attention.  
 Call a poison center/doctor if you feel unwell.  
 Specific treatment (see on this label).  
 Take off contaminated clothing and wash it before reuse.  
 If skin irritation occurs: Get medical advice/attention.  
 In case of fire: Use CO<sub>2</sub>, powder or water spray to extinguish.  
 Store in a well-ventilated place. Keep container tightly closed.  
 Store in a well-ventilated place. Keep cool.  
 Store locked up.  
 Dispose of contents/container in accordance with local/regional/national/international regulations.

## · National regulations:

## · Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

## · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

USA

(Contd. on page 13)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 07/29/2025

Reviewed on 07/29/2025

Trade name: 0D7.401 BASE WHITE PEARL

(Contd. of page 12)

## 16 Other information

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

- **Department issuing SDS:** Environment protection department.
- **Contact:** Product Safety Dept.
- **Date of preparation / last revision** 07/29/2025 / 1
- **Abbreviations and acronyms:**
  - IMDG: International Maritime Code for Dangerous Goods
  - DOT: US Department of Transportation
  - IATA: International Air Transport Association
  - EINECS: European Inventory of Existing Commercial Chemical Substances
  - ELINCS: European List of Notified Chemical Substances
  - CAS: Chemical Abstracts Service (division of the American Chemical Society)
  - NFPA: National Fire Protection Association (USA)
  - HMIS: Hazardous Materials Identification System (USA)
  - VOC: Volatile Organic Compounds (USA, EU)
  - LC50: Lethal concentration, 50 percent
  - LD50: Lethal dose, 50 percent
  - PBT: Persistent, Bioaccumulative and Toxic
  - vPvB: very Persistent and very Bioaccumulative
  - NIOSH: National Institute for Occupational Safety
  - OSHA: Occupational Safety & Health
  - TLV: Threshold Limit Value
  - PEL: Permissible Exposure Limit
  - REL: Recommended Exposure Limit
  - BEI: Biological Exposure Limit
  - Flammable Liquids 3: Flammable liquids – Category 3
  - Skin Irritation 2: Skin corrosion/irritation – Category 2
  - Germ Cell Mutagenicity 1B: Germ cell mutagenicity – Category 1B
  - Carcinogenicity 1B: Carcinogenicity – Category 1B
  - Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3
- **\* Data compared to the previous version altered.**

USA