

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/18/2023

Reviewed on 05/18/2023

Page 1/11

1 Identification

- · Product identifier
- Trade name: SHS45 LEAD FREE ORANGE MIXING TINT
- · Article number: SHS45
- · Details of the supplier of the safety data sheet
- Manufacturer/Supplier: Lusid Technologies
 4725 S Camp Kearns Road Kearns, UT 840118
- Information department: Product safety department
 Emergency telephone number: 24 Hrs Emergency Contact: INFOTRAC 1-800-535-5053

2 Hazard(s) identification

· Classification of the substance or mixture

GHS02 Flame

Flammable Liquids 3

H226 Flammable liquid and vapor.

GHS07

Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness.

- · Label elements
- · GHS label elements
- The product is classified and labeled according to the Globally Harmonized System (GHS). Hazard pictograms



· Signal word Warning

- Hazard-determining components of labeling: n-butyl acetate
- Hazard statements
 Flammable liquid and vapor.
 May cause drowsiness or dizziness.

(Contd. on page 2)

- USA

Printing date 05/18/2023

Reviewed on 05/18/2023

Trade name: SHS45 LEAD FREE ORANGE MIXING TINT

	(Contd. of page 1)
Precautionary statements	
Keep away from heat/sparks/open flames/hot surfaces No smoking.	
Ground/bond container and receiving equipment.	
Use explosion-proof electrical/ventilating/lighting/equipment.	
Use only non-sparking tools.	
Take precautionary measures against static discharge.	
Avoid breathing dust/fume/gas/mist/vapors/spray	
Use only outdoors or in a well-ventilated area.	
Wear protective gloves/protective clothing/eye protection/face protection.	la ha u va v
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/	snower.
IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell.	
In case of fire: Use CO2, powder or water spray to extinguish.	
Store in a well-ventilated place. Keep container tightly closed.	
Store in a well-ventilated place. Keep container tightig closed.	
Store locked up.	
Dispose of contents/container in accordance with local/regional/national/international reg	ulations
· Classification system:	
· NFPA ratings (scale 0 - 4)	
Health = 0	
Fire = 3	
0 Reactivity = 0	
· HMIS-ratings (scale 0 - 4)	
FIRE 3 Fire = 3 $Papati i t = 0$	
REACTIVITY Reactivity = 0	
· Other hazards	
 Results of PBT and vPvB assessment 	
· PBT: Not applicable.	
· vPvB: Not applicable.	

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:		
123-86-4	n-butyl acetate	25-50%
110-43-0	heptan-2-one	≤2.5%

4 First-aid measures

· Description of first aid measures

- · General information: Immediately remove any clothing soiled by the product.
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Immediately rinse with water.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.

(Contd. on page 3)

⁻ USA

Printing date 05/18/2023

Reviewed on 05/18/2023

Trade name: SHS45 LEAD FREE ORANGE MIXING TINT

- · Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

· Extinguishing media

• Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- *Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.*
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- *Methods and material for containment and cleaning up:* Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.
- Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.
- Protective Action Criteria for Chemicals

· PAC-1:		
123-86-4	n-butyl acetate	5 ppm
110-43-0	heptan-2-one	150 ppm
1330-20-7	xylene	130 ppm
100-41-4	ethylbenzene	33 ppm
108-38-3	m-xylene	130 ppm
122-99-6	2-phenoxyethanol	1.5 ppm
14808-60-7	Quartz (SiO2)	0.075 mg/m³
57-55-6	Propylene glycol	30 mg/m ³
78-83-1	butanol	150 ppm
· PAC-2:		
123-86-4	n-butyl acetate	200 ppm
110-43-0	heptan-2-one	670 ppm
1330-20-7	xylene	920* ppm
100-41-4	ethylbenzene	1100* ppm
108-38-3	<i>m-xylene</i>	920 ppm
122-99-6	2-phenoxyethanol	16 ppm
14808-60-7	Quartz (SiO2)	33 mg/m³
I		(Contd. on page 4

(Contd. of page 2)

Printing date 05/18/2023

Reviewed on 05/18/2023

Trade name: SHS45 LEAD FREE ORANGE MIXING TINT

		(Contd. of page 3)		
57-55-6	Propylene glycol	1,300 mg/m³		
78-83-1	butanol	1,300 ppm		
· PAC-3:	· PAC-3:			
123-86-4	n-butyl acetate	3000* ppm		
110-43-0	heptan-2-one	4000* ppm		
1330-20-7	xylene	2500* ppm		
100-41-4	ethylbenzene	1800* ppm		
108-38-3	<i>m-xylene</i>	2500* ppm		
122-99-6	2-phenoxyethanol	97 ppm		
14808-60-7	Quartz (SiO2)	200 mg/m³		
57-55-6	Propylene glycol	7,900 mg/m³		
78-83-1	butanol	8000* ppm		

7 Handling and storage

· Handling:

- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see section 7.

· Control parameters

• Components with limit values that require monitoring at the workplace:

123-86-4 n-butyl acetate

- PEL Long-term value: 710 mg/m³, 150 ppm
- REL Short-term value: 950 mg/m³, 200 ppm Long-term value: 710 mg/m³, 150 ppm
- TLV Short-term value: 150 ppm Long-term value: 50 ppm

110-43-0 heptan-2-one

- PEL Long-term value: 465 mg/m³, 100 ppm
- REL Long-term value: 465 mg/m³, 100 ppm
- TLV Long-term value: 50 ppm

· Additional information: The lists that were valid during the creation were used as basis.

(Contd. on page 5)

USA

Printing date 05/18/2023

Reviewed on 05/18/2023

Trade name: SHS45 LEAD FREE ORANGE MIXING TINT

(Contd. of page 4)

- Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures: Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work.
- Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

• Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

Information on basic physical and General Information Appearance:	chemical properties	
Form:	Liquid	
Color:	Orange	
Odor:	Characteristic	
Odor threshold:	Not determined.	
pH-value:	Not determined (pH N/A in solvent coatings)	
Change in condition Melting point/Melting range: Boiling point/Boiling range:	Undetermined. 124-128 °C (255.2-262.4 °F)	
Flash point:	27 °C (80.6 °F)	
Flammability (solid, gaseous):	Flammable.	
Auto igniting:	370 °C (698 °F)	

Printing date 05/18/2023

Reviewed on 05/18/2023

Trade name: SHS45 LEAD FREE ORANGE MIXING TINT

	(Contd. of page 8
Decomposition temperature:	Not determined.
Ignition temperature:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air. vapor mixtures are possible.
Explosion limits:	
Lower:	1.2 Vol %
Upper:	7.5 Vol %
Vapor pressure at 20 °C (68 °F):	10.7 hPa (8 mm Hg)
Vapor pressure at 50 °C (122 °F):	55 hPa (41.3 mm Hg)
Density at 20 °C (68 °F):	1.0574 g/cm³ (8.824 lbs/gal)
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/wate	r): Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	31.3 %
VOC content:	31.26 %
	350.7 g/l / 2.93 lb/gal
Solids content:	66.8 %
Other information	No further relevant information available.

10 Stability and reactivity

· Reactivity No further relevant information available.

- · Chemical stability
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- Acute toxicity:

· LD/LC50 values that are relevant for classification:

123-86-4 n-butyl acetate

Oral LD50 13,100 mg/kg (rat)

(Contd. on page 7)

⁻ USA

Printing date 05/18/2023

Reviewed on 05/18/2023

Trade name: SHS45 LEAD FREE ORANGE MIXING TINT

			(Contd. of page 6
Dermal		>5,000 mg/kg (rabbit)	
Inhalative	LC50/4 h	>21 mg/l (rat)	
· Additional	n: No irrita : No irrita ion: No se toxicolo	nt effect. ing effect. nsitizing effects known. gical information:	
	rnational	ories Agency for Research on Cancer)	
1330-20-7	7 xylene		3
100-41-4	t ethylber	zene	2B
95-47-6	o-xylene		3
106-42-3	3 p-xylene		3
108-38-3	3 m-xylen	3	3
14808-60-7	7 Quartz	SiO2)	1
· NTP (Natio	onal Toxi	ology Program)	
14808-60-7	Quartz	SiO2)	K
· OSHA-Ca None of the		onal Safety & Health Administration)	

12 Ecological information

- · Toxicity
- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:
- Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 8)

(Contd. of page 7)

Safety Data Sheet acc. to OSHA HCS

Printing date 05/18/2023

Reviewed on 05/18/2023

Trade name: SHS45 LEAD FREE ORANGE MIXING TINT

• Uncleaned packagings:
 • Recommendation: Disposal must be made according to official regulations.

UN-Number DOT, IMDG, IATA	UN1993
UN proper shipping name DOT IMDG, IATA	Flammable liquids, n.o.s. (Butyl acetates) FLAMMABLE LIQUID, N.O.S. (BUTYL ACETATES)
Transport hazard class(es)	
DOT	
Class Label	3 Flammable liquids 3
IMDG, IATA	•
Class Label	3 Flammable liquids 3
Packing group DOT, IMDG, IATA	<i>III</i>
Environmental hazards:	Not applicable.
Special precautions for user Hazard identification number (Kemler code): EMS Number: Stowage Category	Warning: Flammable liquids 30 F-E, <u>S-E</u> A
<i>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</i>	Not applicable.
Transport/Additional information:	
DOT Quantity limitations	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L
IMDG Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

USA

Printing date 05/18/2023

· Sara

Reviewed on 05/18/2023

Trade name: SHS45 LEAD FREE ORANGE MIXING TINT

(Contd. of page 8)

· UN "Model Regulation":

UN 1993 FLAMMABLE LIQUID, N.O.S. (BUTYL ACETATES), 3, III

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
- · Section 355 (extremely hazardous substances): None of the ingredients is listed. Section 313 (Specific toxic chemical listings): 1330-20-7 xylene 100-41-4 ethylbenzene 95-47-6 o-xylene 106-42-3 p-xylene 108-38-3 m-xylene 122-99-6 2-phenoxyethanol TSCA (Toxic Substances Control Act): 123-86-4 n-butyl acetate ACTIVE ACTIVE 15793-73-4 Pigment Orange 34 110-43-0 heptan-2-one ACTIVE 1330-20-7 xylene ACTIVE 100-41-4 ethylbenzene ACTIVE 95-47-6 o-xylene ACTIVE 106-42-3 p-xylene ACTIVE 108-38-3 m-xylene ACTIVE 64742-47-8 Distillates (petroleum), hydrotreated light ACTIVE 122-99-6 2-phenoxyethanol ACTIVE 14808-60-7 Quartz (SiO2) ACTIVE 57-55-6 Propylene glycol ACTIVE 78-83-1 butanol ACTIVE · Hazardous Air Pollutants 1330-20-7 xylene 100-41-4 ethylbenzene 95-47-6 o-xylene 106-42-3 p-xylene 108-38-3 *m-xylene* · Proposition 65 · Chemicals known to cause cancer: 100-41-4 ethylbenzene 14808-60-7 Quartz (SiO2) · Chemicals known to cause reproductive toxicity for females: None of the ingredients is listed.

(Contd. on page 10)

USA

Printing date 05/18/2023

Reviewed on 05/18/2023

Trade name: SHS45 LEAD FREE ORANGE MIXING TINT

		(Contd. of page 9)
· Chemicals	s known to cause reproductive toxicity for males:	
None of the	e ingredients is listed.	
· Chemicals	s known to cause developmental toxicity:	
None of the	e ingredients is listed.	
· Carcinoge	nic categories	
· EPA (Envi	ronmental Protection Agency)	
1330-20-7	xylene	1
100-41-4	ethylbenzene	D
95-47-6	o-xylene	1
106-42-3	p-xylene	1
108-38-3	m-xylene	1
TLV (Thre	shold Limit Value)	
1330-20-1	7 xylene	A4
100-41-4	4 ethylbenzene	A3
95-47-0	6 o-xylene	A4
106-42-3	3 p-xylene	A4
108-38-3	3 m-xylene	A4
14808-60-1	7 Quartz (SiO2)	A2
· NIOSH-Ca	(National Institute for Occupational Safety and Health)	
14808-60-1	7 Quartz (SiO2)	

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS). • Hazard pictograms



· Signal word Warning

· Hazard-determining components of labeling: n-butyl acetate · Hazard statements Flammable liquid and vapor. May cause drowsiness or dizziness. · Precautionary statements Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapors/spray Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. In case of fire: Use CO2, powder or water spray to extinguish.

(Contd. on page 11)

USA

(Contd. of page 10)

Safety Data Sheet acc. to OSHA HCS

Printing date 05/18/2023

Reviewed on 05/18/2023

Trade name: SHS45 LEAD FREE ORANGE MIXING TINT

Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/region

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact: Product Safety Dept.
- · Date of preparation / last revision 05/18/2023
- Abbreviations and acronvms: IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit Flammable Liquids 3: Flammable liquids – Category 3 Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) - Category 3 ** Data compared to the previous version altered.