

# Safety Data Sheet

## BINDER ACRYLIC DTM MATT

Safety Data Sheet dated 9/6/2017, version 2

### 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product identifier

Mixture identification:  
 Trade name: BINDER ACRYLIC DTM MATT  
 Trade code: 6B.4.K1  
 Product type and use: industrial varnishing

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use:  
 industrial painting  
 SU3 Industrial uses: Uses of substances as such or in preparations\* at industrial sites  
 SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)  
 PC9a Coatings and paints, thinners, paint removers  
 Uses advised against:

SU21 Consumer uses: Private households (= general public = consumers)

#### 1.3. Details of the supplier of the safety data sheet

Company:  
 GÉNÉRALE DE PEINTURE, 70 rue Cortambert, 75116 Paris - France  
 +33 (0)1 75 29 35 59

Competent person responsible for the safety data sheet:

matt@lusid.biz

#### 1.4. Emergency telephone number

matt@lusid.biz  
 Emergency US – 1-800-535-5053 Outside US - +1-352-323-3500 InfoTrac Contract # 89244

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

EC regulation criteria 1272/2008 (CLP)

- ⚠ Warning, Flam. Liq. 3, Flammable liquid and vapour.
- ⚠ Warning, Skin Sens. 1, May cause an allergic skin reaction.
- ⚠ Warning, STOT SE 3, May cause drowsiness or dizziness.  
 Aquatic Chronic 3, Harmful to aquatic life with long lasting effects.

Adverse physicochemical, human health and environmental effects:

No other hazards

#### 2.2. Label elements

Hazard pictograms:



Warning

Hazard statements:

- H226 Flammable liquid and vapour.
- H317 May cause an allergic skin reaction.
- H336 May cause drowsiness or dizziness.
- H412 Harmful to aquatic life with long lasting effects.

Precautionary statements:

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P273 Avoid release to the environment.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.

## Safety Data Sheet

### BINDER ACRYLIC DTM MATT

P312 Call a POISON CENTER/ doctor/if you feel unwell.

P370+P378 In case of fire: Use ... to extinguish.

Special Provisions:

None

Contains

n-butyl acetate

HYDROCARBONS , C9, AROMATICS

4,4'-Isopropylidene-diphenol, polymer reaction products with 1-chloro-2,3-epoxypropane:  
average molecular mass 850-1150

Special provisions according to Annex XVII of REACH and subsequent amendments:

None

#### 2.3. Other hazards

vPvB Substances: None - PBT Substances: None

Other Hazards:

No other hazards

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

N.A.

### 3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name	Ident. Number	Classification
>= 20% - < 25%	n-butyl acetate	Index number: 607-025-00-1 CAS: 123-86-4 EC: 204-658-1	<ul style="list-style-type: none"> <li>⚠ 2.6/3 Flam. Liq. 3 H226</li> <li>⚠ 3.8/3 STOT SE 3 H336</li> <li>EUH066</li> </ul>
>= 5% - < 7%	2-methoxy-1-methylethyl acetate	Index number: 607-195-00-7 CAS: 108-65-6 EC: 203-603-9	<ul style="list-style-type: none"> <li>⚠ 2.6/3 Flam. Liq. 3 H226</li> </ul>
>= 3% - < 5%	xylene [4]	Index number: 601-022-00-9 CAS: 1330-20-7 EC: 215-535-7	<ul style="list-style-type: none"> <li>⚠ 2.6/3 Flam. Liq. 3 H226</li> <li>⚠ 3.1/4/Inhal Acute Tox. 4 H332</li> <li>⚠ 3.1/4/Dermal Acute Tox. 4 H312</li> <li>⚠ 3.3/2 Eye Irrit. 2 H319</li> <li>⚠ 3.8/3 STOT SE 3 H335</li> <li>⚠ 3.2/2 Skin Irrit. 2 H315</li> <li>⚠ 3.9/2 STOT RE 2 H373</li> <li>⚠ 3.10/1 Asp. Tox. 1 H304</li> </ul>
>= 3% - < 5%	HYDROCARBONS , C9, AROMATICS	EC: 918-668-5	<ul style="list-style-type: none"> <li>⚠ 2.6/3 Flam. Liq. 3 H226</li> <li>⚠ 4.1/C2 Aquatic Chronic 2 H411</li> <li>⚠ 3.8/3 STOT SE 3 H335</li> <li>⚠ 3.10/1 Asp. Tox. 1 H304</li> <li>⚠ 3.8/3 STOT SE 3 H336</li> <li>EUH066</li> <li>DECLP (CLP)*</li> </ul>
>= 1% - < 3%	4,4'-Isopropylidene-diphenol, polymer reaction products with 1-chloro-2,3-epoxypropane:		<ul style="list-style-type: none"> <li>⚠ 3.4.2/1-1A-1B Skin Sens. 1,1A, 1B H317</li> </ul>

## Safety Data Sheet

### BINDER ACRYLIC DTM MATT

	average molecular mass 850-1150		
>= 0.5% - < 1%	2-butoxyethyl acetate; butylglycol acetate	Index number: CAS: EC:	607-038-00-2 112-07-2 203-933-3
			<ul style="list-style-type: none"> <li>⚠ 3.1/4/Dermal Acute Tox. 4 H312</li> <li>⚠ 3.1/4/Oral Acute Tox. 4 H302</li> <li>⚠ 3.1/4/Inhal Acute Tox. 4 H332</li> </ul>
>= 0.25% - < 0.5%	2-methylpropan-1-ol	Index number: CAS: EC:	603-108-00-1 78-83-1 201-148-0
			<ul style="list-style-type: none"> <li>⚠ 2.6/3 Flam. Liq. 3 H226</li> <li>⚠ 3.8/3 STOT SE 3 H335</li> <li>⚠ 3.2/2 Skin Irrit. 2 H315</li> <li>⚠ 3.3/1 Eye Dam. 1 H318</li> <li>⚠ 3.8/3 STOT SE 3 H336</li> </ul>
>= 0.25% - < 0.5%	ethylbenzene	Index number: CAS: EC:	601-023-00-4 100-41-4 202-849-4
			<ul style="list-style-type: none"> <li>⚠ 2.6/2 Flam. Liq. 2 H225</li> <li>⚠ 3.1/4/Inhal Acute Tox. 4 H332</li> <li>⚠ 3.9/2 STOT RE 2 H373</li> <li>⚠ 3.10/1 Asp. Tox. 1 H304</li> </ul>
185 ppm	2,6-dimethylheptan-4-one; di-isobutyl ketone	Index number: CAS: EC:	606-005-00-X 108-83-8 203-620-1
			<ul style="list-style-type: none"> <li>⚠ 2.6/3 Flam. Liq. 3 H226</li> <li>⚠ 3.8/3 STOT SE 3 H335</li> </ul>

#### 4. FIRST AID MEASURES

##### 4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap.

Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediately and dispose off safely.

In case of eyes contact:

In case of Ingestion:

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

##### 4.2. Most important symptoms and effects, both acute and delayed

None

##### 4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

None

#### 5. FIRE-FIGHTING MEASURES

##### 5.1. Extinguishing media

Suitable extinguishing media:

In case of fire: Use ... to extinguish.

Extinguishing media which must not be used for safety reasons:

None in particular.

##### 5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

##### 5.3. Advice for firefighters

6B.4.K1/2

Page n. 3 of 13

## Safety Data Sheet

### BINDER ACRYLIC DTM MATT

Use suitable breathing apparatus .  
 Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
 Move undamaged containers from immediate hazard area if it can be done safely.

#### 6. ACCIDENTAL RELEASE MEASURES

##### 6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.  
 Remove all sources of ignition.  
 Remove persons to safety.  
 See protective measures under point 7 and 8.

##### 6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.  
 Retain contaminated washing water and dispose it.  
 In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

##### 6.3. Methods and material for containment and cleaning up

Wash with plenty of water.

##### 6.4. Reference to other sections

See also section 8 and 13

#### 7. HANDLING AND STORAGE

##### 7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.  
 Don't use empty container before they have been cleaned.  
 Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.  
 Contaminated clothing should be changed before entering eating areas.  
 Do not eat or drink while working.  
 See also section 8 for recommended protective equipment.

##### 7.2. Conditions for safe storage, including any incompatibilities

Always keep the containers tightly closed.  
 Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.  
 Keep away from food, drink and feed.  
 Incompatible materials:  
 None in particular.  
 Instructions as regards storage premises:  
 Cool and adequately ventilated.

##### 7.3. Specific end use(s)

None in particular

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

##### 8.1. Control parameters

n-butyl acetate - CAS: 123-86-4  
 ACGIH - TWA(8h): 50 ppm - STEL: 150 ppm - Notes: Eye and URT irr  
 OEL 8h - 150 ppm  
 OEL short - 200 ppm  
 2-methoxy-1-methylethyl acetate - CAS: 108-65-6  
 ACGIH - TWA: 275 mg/m<sup>3</sup>, 50 ppm - STEL: 550 mg/m<sup>3</sup>, 100 ppm - Notes: H  
 EU - TWA(8h): 275 mg/m<sup>3</sup>, 50 ppm - STEL: 550 mg/m<sup>3</sup>, 100 ppm - Notes: Skin  
 xylene [4] - CAS: 1330-20-7  
 MAK - TWA: 100 ppm - STEL: 200 ppm - Notes: D, Skin  
 EU - TWA(8h): 221 mg/m<sup>3</sup>, 50 ppm - STEL: 442 mg/m<sup>3</sup>, 100 ppm - Notes: Skin  
 ACGIH - TWA(8h): 100 ppm - STEL: 150 ppm - Notes: A4, BEI - URT and eye irr, CNS impair

## Safety Data Sheet

### BINDER ACRYLIC DTM MATT

#### HYDROCARBONS , C9, AROMATICS

TLV TWA - 100 mg/mq

2-butoxyethyl acetate; butylglycol acetate - CAS: 112-07-2

EU - TWA(8h): 133 mg/m<sup>3</sup>, 20 ppm - STEL: 333 mg/m<sup>3</sup>, 50 ppm - Notes: Skin

ACGIH - TWA(8h): 20 ppm - Notes: A3 - Hemolysis

2-methylpropan-1-ol - CAS: 78-83-1

ACGIH - TWA(8h): 50 ppm - Notes: Skin and eye irr

ethylbenzene - CAS: 100-41-4

EU - TWA(8h): 442 mg/m<sup>3</sup>, 100 ppm - STEL: 884 mg/m<sup>3</sup>, 200 ppm - Notes: Skin

ACGIH - TWA(8h): 20 ppm - Notes: A3, BEI - URT irr, kidney dam (nephropathy), cochlear impair

2,6-dimethylheptan-4-one; di-isobutyl ketone - CAS: 108-83-8

ACGIH - TWA(8h): 25 ppm - Notes: URT and eye irr

#### DNEL Exposure Limit Values

n-butyl acetate - CAS: 123-86-4

Worker Industry: 960 ppm - Consumer: 859.7 ppm - Exposure: Human Inhalation - Frequency: Short Term, systemic effects

Worker Industry: 960 ppm - Consumer: 859.7 ppm - Exposure: Human Inhalation - Frequency: Short Term, local effects

Worker Industry: 480 ppm - Consumer: 102.34 ppm - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Worker Industry: 480 ppm - Consumer: 102.34 ppm - Exposure: Human Inhalation - Frequency: Long Term, local effects

2-methoxy-1-methylethyl acetate - CAS: 108-65-6

Worker Industry: 153.5 mg/kg - Consumer: 54.8 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Worker Industry: 275 mg/m<sup>3</sup> - Consumer: 33 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Consumer: 1.67 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

xylene [4] - CAS: 1330-20-7

Worker Industry: 289 mg/m<sup>3</sup> - Consumer: 174 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Short Term, local effects

Worker Industry: 180 mg/kg - Consumer: 108 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Worker Industry: 77 mg/m<sup>3</sup> - Consumer: 14.8 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Consumer: 1.6 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

Worker Industry: 289 mg/m<sup>3</sup> - Consumer: 174 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Short Term, systemic effects

#### HYDROCARBONS , C9, AROMATICS

Worker Industry: 25 mg/kg - Consumer: 11 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Worker Industry: 150 mg/m<sup>3</sup> - Consumer: 32 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Consumer: 11 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

2-butoxyethyl acetate; butylglycol acetate - CAS: 112-07-2

Consumer: 18 mg/kg - Exposure: Human Oral - Frequency: Short Term, systemic effects

Consumer: 4.3 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

Consumer: 166 mg/kg - Exposure: Human Inhalation - Frequency: Short Term, local effects

Worker Industry: 20 ppm - Consumer: 67 mg/kg - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Worker Industry: 50 ppm - Consumer: 199 mg/kg - Exposure: Human Inhalation - Frequency: Short Term, local effects

2-methylpropan-1-ol - CAS: 78-83-1

Worker Industry: 310 mg/m<sup>3</sup> - Consumer: 55 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, local effects

## Safety Data Sheet

### BINDER ACRYLIC DTM MATT

Consumer: 25 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

**PNEC Exposure Limit Values**

- n-butyl acetate - CAS: 123-86-4
  - Target: Fresh Water - Value: 0.18 mg/l
  - Target: Marine water - Value: 0.018 mg/l
  - Target: Freshwater sediments - Value: 0.981 mg/kg
  - Target: Marine water sediments - Value: 0.0981 mg/kg
  - Target: Soil (agricultural) - Value: 0.0903 mg/kg - Notes: occasional release
- 2-methoxy-1-methylethyl acetate - CAS: 108-65-6
  - Target: Air - Value: 0.635 mg/l
  - Target: Microorganisms in sewage treatments - Value: 100 mg/l
  - Target: Freshwater sediments - Value: 3.29 mg/kg
  - Target: Marine water sediments - Value: 0.329 mg/kg
  - Target: Marine water - Value: 0.0635 mg/l
- xylene [4] - CAS: 1330-20-7
  - Target: Marine water - Value: 0.327 mg/l
  - Target: Air - Value: 0.327 mg/l - Type of hazard: emissione saltuaria
  - Target: Freshwater sediments - Value: 12.46 mg/kg
  - Target: Marine water sediments - Value: 12.46 mg/kg
  - Target: Soil (agricultural) - Value: 2.31 mg/kg
- 2-butoxyethyl acetate; butylglycol acetate - CAS: 112-07-2
  - Target: Fresh Water - Value: 304 mg/l
  - Target: Marine water - Value: 304 mg/l
  - Target: Microorganisms in sewage treatments - Value: 90 mg/l
- 2-methylpropan-1-ol - CAS: 78-83-1
  - Target: Marine water sediments - Value: 0.152 mg/kg
  - Target: Soil (agricultural) - Value: 0.0699 mg/kg
  - Target: Fresh Water - Value: 0.4 mg/l
  - Target: Marine water - Value: 0.04 mg/l
  - Target: Freshwater sediments - Value: 1.52 mg/kg - Notes: emisionne saltuaria

#### 8.2. Exposure controls

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

NBR (nitrile rubber). protection against splashing

Respiratory protection:

Mask with filter "A" , brown colour

Thermal Hazards:

None

Environmental exposure controls:

None

Appropriate engineering controls:

None

---

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

Properties	Value	Method:	Notes
Appearance and colour:	liquid gray	--	--
Odour:	solvent	--	--
Odour threshold:	solvent	--	--

## Safety Data Sheet

### BINDER ACRYLIC DTM MATT

pH:	N.A.	--	--
Melting point / freezing point:	N.A.	--	--
Initial boiling point and boiling range:	N.A.	--	--
Flash point:	25 ° C	--	--
Evaporation rate:	N.A.	--	--
Solid/gas flammability:	N.A.	--	--
Upper/lower flammability or explosive limits:	N.A.	--	--
Vapour pressure:	N.A.	--	--
Vapour density:	>1	--	--
Relative density:	1.38	--	--
Solubility in water:	none	--	--
Solubility in oil:	soluble	--	--
Partition coefficient (n-octanol/water):	N.A.	--	--
Auto-ignition temperature:	N.A.	--	--
Decomposition temperature:	N.A.	--	--
Viscosity:	22" ford 8	--	--
Explosive properties:	N.A.	--	--
Oxidizing properties:	N.A.	--	--

#### 9.2. Other information

Properties	Value	Method:	Notes
Miscibility:	none	--	--
Fat Solubility:	soluble	--	--
Conductivity:	N.A.	--	--
Substance Groups relevant properties	N.A.	--	--

## 10. STABILITY AND REACTIVITY

### 10.1. Reactivity

Stable under normal conditions

6B.4.K1/2

Page n. 7 of 13



## Safety Data Sheet

### BINDER ACRYLIC DTM MATT

#### 10.2. Chemical stability

Stable under normal conditions

#### 10.3. Possibility of hazardous reactions

It may generate toxic gases on contact with powerful oxidising agents, and powerful reducing agents.

It may catch fire on contact with powerful oxidising agents.

#### 10.4. Conditions to avoid

Stable under normal conditions.

#### 10.5. Incompatible materials

Avoid contact with combustible materials. The product could catch fire.

#### 10.6. Hazardous decomposition products

None.

---

## 11. TOXICOLOGICAL INFORMATION

### 11.1. Information on toxicological effects

Toxicological information of the product:

N.A.

Toxicological information of the main substances found in the product:

n-butyl acetate - CAS: 123-86-4

a) acute toxicity:

Test: LC50 - Route: Inhalation - Species: Rat > 21.2 mg/l - Duration: 4h

Test: LD50 - Route: Oral - Species: Rat 10760 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit > 14000 mg/kg

2-methoxy-1-methylethyl acetate - CAS: 108-65-6

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Mouse 8532 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit 5001 mg/kg

Test: LC50 - Route: Inhalation - Species: Mouse > 35.7 mg/l - Duration: 4h - Notes: 6 hours

h) STOT-single exposure:

Test: Eye Irritant Positive

Test: Skin Irritant Positive

xylene [4] - CAS: 1330-20-7

a) acute toxicity:

Test: LC50 - Route: Inhalation - Species: Rat 20 mg/l - Duration: 4h

Test: LD50 - Route: Oral - Species: Mouse 5627 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit > 5000 mg/kg

HYDROCARBONS , C9, AROMATICS

a) acute toxicity:

Test: LC50 - Route: Inhalation - Species: Rat > 6193 mg/m3 - Duration: 4h

Test: LD50 - Route: Oral - Species: Rat = 3592 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit > 3160 mg/kg

4,4'-Isopropylidene-diphenol, polymer reaction products with 1-chloro-2,3-epoxypropane: average molecular mass 850-1150

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 2000 mg/kg

Test: LD50 - Route: Skin - Species: Rat > 2000 mg/kg

2-butoxyethyl acetate; butylglycol acetate - CAS: 112-07-2

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat 1880 mg/kg - Notes: bw

Test: LD50 - Route: Skin - Species: Rabbit 1500 mg/kg - Notes: bw

Test: LC50 - Route: Inhalation - Species: Rat > 400 ppm - Duration: 4h

2-methylpropan-1-ol - CAS: 78-83-1

a) acute toxicity:

Test: LC50 - Route: Inhalation - Species: Rat > 18.18 mg/l - Duration: 6H - Notes: 6h

Test: LD50 - Route: Oral - Species: Rat > 2460 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit > 2460 mg/kg



## Safety Data Sheet

### BINDER ACRYLIC DTM MATT

- b) skin corrosion/irritation:  
Test: Skin Irritant Positive
- c) serious eye damage/irritation:  
Test: Eye Irritant Positive
- ethylbenzene - CAS: 100-41-4
- a) acute toxicity:  
Test: LD50 - Route: Oral - Species: Rat 3500 mg/kg  
Test: LD50 - Route: Skin - Species: Rabbit 5000 mg/kg  
Test: LC50 - Route: Inhalation - Species: Rat 4000 ppm - Duration: 4h

n-butyl acetate - CAS: 123-86-4

LD (RAT) oral, 10770 mg/kg

2-methoxy-1-methylethyl acetate - CAS: 108-65-6

LD50 (RAT) oral. 8532 mg/Kg

LD50 (RAT) derm. >5000 mg/kg

xylene [4] - CAS: 1330-20-7

LD50 (RAT) ORAL: 5000 MG/KG

If not differently specified, the information required in Regulation (EU)2015/830 listed below must be considered as N.A.:

- a) acute toxicity;
- b) skin corrosion/irritation;
- c) serious eye damage/irritation;
- d) respiratory or skin sensitisation;
- e) germ cell mutagenicity;
- f) carcinogenicity;
- g) reproductive toxicity;
- h) STOT-single exposure;
- i) STOT-repeated exposure;
- j) aspiration hazard.

---

## 12. ECOLOGICAL INFORMATION

### 12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

Do not use when plants are in flower: the product is toxic for bees.

n-butyl acetate - CAS: 123-86-4

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 62 mg/l - Duration h: 96

Endpoint: EC50 - Species: Daphnia = 205 mg/l - Duration h: 48

2-methoxy-1-methylethyl acetate - CAS: 108-65-6

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 180 mg/l - Duration h: 96

Endpoint: EC50 - Species: Daphnia = 380 mg/l - Duration h: 48

Endpoint: EC50 - Species: Algae = 2000 mg/l - Duration h: 72

xylene [4] - CAS: 1330-20-7

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Daphnia = 1 mg/l - Duration h: 24

Endpoint: EC50 - Species: Algae = 4.36 mg/l - Duration h: 73

Endpoint: LC50 - Species: Fish = 2.6 mg/l - Duration h: 96

Endpoint: NOEC - Species: Algae = 0.44 mg/l - Duration h: 73

Endpoint: NOEC - Species: Daphnia = 1.57 mg/l - Notes: 21g

Endpoint: NOEC - Species: Fish = 1.4 mg/l - Notes: 56g

HYDROCARBONS , C9, AROMATICS

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 9.22 mg/l - Duration h: 96

2-butoxyethyl acetate; butylglycol acetate - CAS: 112-07-2

a) Aquatic acute toxicity:

## Safety Data Sheet

### BINDER ACRYLIC DTM MATT

Endpoint: LC50 - Species: Fish = 28 mg/l - Duration h: 96  
 Endpoint: EC50 - Species: Daphnia = 1570 mg/l - Duration h: 72  
 Endpoint: EC50 - Species: Algae = 37 mg/l - Duration h: 48

ethylbenzene - CAS: 100-41-4

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Algae = 1.7 mg/l - Duration h: 96

Endpoint: EC50 - Species: Algae = 2.6 mg/l - Duration h: 72

Endpoint: LC50 - Species: Fish = 4.2 mg/l - Duration h: 96

Endpoint: EC50 - Species: Daphnia = 2 mg/l - Duration h: 48

#### 12.2. Persistence and degradability

None

n-butyl acetate - CAS: 123-86-4

Biodegradability: Easily biodegradable - Test: N.A. - Duration h: N.A. - %: 83 - Notes: 28 days

2-methoxy-1-methylethyl acetate - CAS: 108-65-6

Biodegradability: Easily biodegradable - Test: N.A. - Duration h: N.A. - %: N.A. - Notes: N.A.

xylene [4] - CAS: 1330-20-7

Biodegradability: Easily biodegradable - Test: N.A. - Duration h: N.A. - %: N.A. - Notes: N.A.

HYDROCARBONS , C9, AROMATICS

Biodegradability: Easily biodegradable - Test: N.A. - Duration h: N.A. - %: N.A. - Notes: N.A.

2-methylpropan-1-ol - CAS: 78-83-1

Biodegradability: Easily biodegradable - Test: N.A. - Duration h: N.A. - %: N.A. - Notes: N.A.

#### 12.3. Bioaccumulative potential

2-methoxy-1-methylethyl acetate - CAS: 108-65-6

Bioaccumulation: Not bioaccumulative - Test: N.A. N.A. - Duration h: N.A. - Notes: N.A.

#### 12.4. Mobility in soil

2-methoxy-1-methylethyl acetate - CAS: 108-65-6

Mobility in soil: Mobile - Test: N.A. N.A. - Duration h: N.A. - Notes: fast evaporating

#### 12.5. Results of PBT and vPvB assessment

vPvB Substances: None - PBT Substances: None

#### 12.6. Other adverse effects

None

---

## 13. DISPOSAL CONSIDERATIONS

### 13.1. Waste treatment methods

Recover if possible. In so doing, comply with the local and national regulations currently in force.

---

## 14. TRANSPORT INFORMATION



### 14.1. UN number

ADR-UN Number: 1263

IATA-UN Number: 1263

IMDG-UN Number: 1263

### 14.2. UN proper shipping name

ADR-Shipping Name: PAINT

IATA-Shipping Name: PAINT

IMDG-Shipping Name: PAINT

## Safety Data Sheet

### BINDER ACRYLIC DTM MATT

- 14.3. Transport hazard class(es)**
- |                                     |    |  |
|-------------------------------------|----|--|
| ADR-Class:                          | 3  |  |
| ADR - Hazard identification number: | 30 |  |
| IATA-Class:                         | 3  |  |
| IATA-Label:                         | 3  |  |
| IMDG-Class:                         | 3  |  |
- 14.4. Packing group**
- |                     |     |
|---------------------|-----|
| ADR-Packing Group:  | III |
| IATA-Packing group: | III |
| IMDG-Packing group: | III |
- 14.5. Environmental hazards**
- |                              |    |
|------------------------------|----|
| ADR-Environmental Pollutant: | No |
| IMDG-Marine pollutant:       | No |
- 14.6. Special precautions for user**
- |   |              |
|---|--------------|
| ADR-Subsidiary risks:                             | -            |
| ADR-S.P.:   | 163 640E 650 |
| ADR-Transport category (Tunnel restriction code): | (D/E)        |
| IATA-Passenger Aircraft:                          | 355          |
| IATA-Subsidiary risks:                            | -            |
| IATA-Cargo Aircraft:                              | 366          |
| IATA-S.P.:  | A3 A72       |
| IATA-ERG:   | 3L           |
| IMDG-EmS:   | F-E , S-E    |
| IMDG-Subsidiary risks:                            | -            |
| IMDG-Stowage and handling:                        | Category A   |
| IMDG-Segregation:                                 | -            |
- 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**
- N.A.

---

## 15. REGULATORY INFORMATION

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 67/548/EEC (Classification, packaging and labelling of dangerous substances). Dir. 99/45/EEC (Classification, packaging and labelling of dangerous preparations). Dir. 98/24/EC (Risks related to chemical agents at work). Dir. 2000/39/EC (Occupational exposure limit values); Dir. 2006/8/CE. Regulation (CE) n. 1907/2006 (REACH), Regulation (CE) n.1272/2008 (CLP), Regulation (CE) n.790/2009.

Volatile Organic compounds - VOCs = 550.75 g/l

Volatile CMR substances = 0.01 %

Halogenated VOCs which are assigned the risk phrase R40 = 0.00 %

Organic Carbon - C = 0.27

Where applicable, refer to the following regulatory provisions :

- Directive 2012/18/EU (Seveso III)
- Regulation (EC) nr 648/2004 (detergents).
- Dir. 2004/42/EC (VOC directive)

Provisions related to directive EU 2012/18 (Seveso III):

- Seveso III category according to Annex 1, part 1
- Product belongs to category: P5c

### 15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for the mixture.

## Safety Data Sheet

### BINDER ACRYLIC DTM MATT

#### 16. OTHER INFORMATION

Full text of phrases referred to in Section 3:

- H226 Flammable liquid and vapour.
- H336 May cause drowsiness or dizziness.
- EUH066 Repeated exposure may cause skin dryness or cracking.
- H332 Harmful if inhaled.
- H312 Harmful in contact with skin.
- H319 Causes serious eye irritation.
- H335 May cause respiratory irritation.
- H315 Causes skin irritation.
- H373 May cause damage to organs through prolonged or repeated exposure if inhaled.
- H304 May be fatal if swallowed and enters airways.
- H411 Toxic to aquatic life with long lasting effects.
- H317 May cause an allergic skin reaction.
- H302 Harmful if swallowed.
- H318 Causes serious eye damage.
- H225 Highly flammable liquid and vapour.
- H373 May cause damage to organs through prolonged or repeated exposure.

Hazard class and hazard category	Code	Description
Flam. Liq. 2	2.6/2	Flammable liquid, Category 2
Flam. Liq. 3	2.6/3	Flammable liquid, Category 3
Acute Tox. 4	3.1/4/Dermal	Acute toxicity (dermal), Category 4
Acute Tox. 4	3.1/4/Inhal	Acute toxicity (inhalation), Category 4
Acute Tox. 4	3.1/4/Oral	Acute toxicity (oral), Category 4
Asp. Tox. 1	3.10/1	Aspiration hazard, Category 1
Skin Irrit. 2	3.2/2	Skin irritation, Category 2
Eye Dam. 1	3.3/1	Serious eye damage, Category 1
Eye Irrit. 2	3.3/2	Eye irritation, Category 2
Skin Sens. 1	3.4.2/1	Skin Sensitisation, Category 1
Skin Sens. 1,1A,1B	3.4.2/1-1A-1B	Skin Sensitisation, Category 1,1A,1B
STOT SE 3	3.8/3	Specific target organ toxicity - single exposure, Category 3
STOT RE 2	3.9/2	Specific target organ toxicity - repeated exposure, Category 2
Aquatic Chronic 2	4.1/C2	Chronic (long term) aquatic hazard, category 2
Aquatic Chronic 3	4.1/C3	Chronic (long term) aquatic hazard, category 3

Paragraphs modified from the previous revision:

#### 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE

## Safety Data Sheet

### BINDER ACRYLIC DTM MATT

COMPANY/UNDERTAKING  
 SECTION 2: Hazards identification  
 SECTION 3: Composition/information on ingredients  
 11. TOXICOLOGICAL INFORMATION  
 15. REGULATORY INFORMATION

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

<b>Classification according to Regulation (EC) Nr. 1272/2008</b>	<b>Classification procedure</b>
Flam. Liq. 3, H226	On basis of test data
Skin Sens. 1, H317	Calculation method
STOT SE 3, H336	Calculation method
Aquatic Chronic 3, H412	Calculation method

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre,  
 Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van  
 Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.