

Printing date 08/18/2025 Reviewed on 08/18/2025

#### 1 Identification

· Product identifier

· Trade name: SHS32 BLUE (GREEN SHADE) MIXING TINT

· Article number: SHS32

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

NorthStar is a product of Lusid Technologies Inc

4725 S Camp Kearns Road

Kearns, UT 84118 (801) 966-5300

info@lusidtechnologies.com

· Information department: Product safety department

· Emergency telephone number:

24 Hrs Emergency Contact:

INFOTRAC 1-800-535-5053

### 2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flammable Liquids 3

H226 Flammable liquid and vapor.



GHS08 Health hazard

Carcinogenicity 2

H351 Suspected of causing cancer.



GHS07

Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms







GHS02 GHS07 GHS08

· Signal word Warning

(Contd. on page 2)

Printing date 08/18/2025 Reviewed on 08/18/2025

Trade name: SHS32 BLUE (GREEN SHADE) MIXING TINT

(Contd. of page 1)

#### · Hazard-determining components of labeling:

n-butyl acetate ethylbenzene

### · Hazard statements

Flammable liquid and vapor.

Suspected of causing cancer.

May cause drowsiness or dizziness.

#### Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF exposed or concerned: Get medical advice/attention.

Call a poison center/doctor if you feel unwell.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- NFPA ratings (scale 0 4)



Health = 0 Fire = 3 Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 0 Fire = 3 Reactivity:

REACTIVITY 0 Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

# 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · **Description**: Mixture of the substances listed below with nonhazardous additions.

	•	Dang	erous	comp	oone	nts:
--	---	------	-------	------	------	------

	•	
123-86-4	n-butyl acetate	25-50%
110-43-0	heptan-2-one	10-25%

(Contd. on page 3)

Printing date 08/18/2025 Reviewed on 08/18/2025

Trade name: SHS32 BLUE (GREEN SHADE) MIXING TINT

(Contd. of page 2)
100-41-4 ethylbenzene ≤2.5%

#### 4 First-aid measures

- Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- · After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed

No further relevant information available.

· Indication of any immediate medical attention and special treatment needed

No further relevant information available.

### 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
- · Protective equipment: No special measures required.

#### 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

PAC-1:		
123-86-4	n-butyl acetate	5 ppm
110-43-0	heptan-2-one	150 ppm
1330-20-7	xylene	130 ppm
100-41-4	ethylbenzene	33 ppm
108-38-3	m-xylene	130 ppm
122-99-6	2-phenoxyethanol	1.5 ppm
14808-60-7	Quartz (SiO2)	0.075 mg/m
		(Contd. on page

USA

Printing date 08/18/2025 Reviewed on 08/18/2025

Trade name: SHS32 BLUE (GREEN SHADE) MIXING TINT

57.55.C	Due moderne achoral	(Contd. of page
	Propylene glycol	30 mg/m³
78-83-1	butanol	150 ppm
· PAC-2:		
123-86-4	n-butyl acetate	200 ppm
110-43-0	heptan-2-one	670 ppm
1330-20-7	xylene	920* ppm
100-41-4	ethylbenzene	1100 ppm
108-38-3	m-xylene	920 ppm
122-99-6	2-phenoxyethanol	16 ppm
14808-60-7	Quartz (SiO2)	8.3 mg/m3
57-55-6	Propylene glycol	1,300 mg/m
78-83-1	butanol	1,300 ppm
· PAC-3:		·
123-86-4	n-butyl acetate	3000* ppm
110-43-0	heptan-2-one	4000* ppm
1330-20-7	xylene	2500* ppm
100-41-4	ethylbenzene	1800 ppm
108-38-3	m-xylene	2500* ppm
122-99-6	2-phenoxyethanol	97 ppm
14808-60-7	Quartz (SiO2)	50 mg/m3
57-55-6	Propylene glycol	7,900 mg/m
78-83-1	butanol	8000* ppm

# 7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

# 8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see section 7.

(Contd. on page 5)

Printing date 08/18/2025 Reviewed on 08/18/2025

Trade name: SHS32 BLUE (GREEN SHADE) MIXING TINT

(Contd. of page 4)

#### · Control parameters

· Com	ponents with limit values that require monitoring at the workplace:
123-	86-4 n-butyl acetate
PEL	Long-term value: 710 mg/m³, 150 ppm
REL	Short-term value: 950 mg/m³, 200 ppm Long-term value: 710 mg/m³, 150 ppm
TLV	Short-term value: 712 mg/m³, 150 ppm Long-term value: 238 mg/m³, 50 ppm
110-4	43-0 heptan-2-one
PEL	Long-term value: 465 mg/m³, 100 ppm
REL	Long-term value: 465 mg/m³, 100 ppm
TLV	Long-term value: 50 ppm
100-4	41-4 ethylbenzene
PEL	Long-term value: 435 mg/m³, 100 ppm
REL	Short-term value: 545 mg/m³, 125 ppm Long-term value: 435 mg/m³, 100 ppm
TLV	Long-term value: 20 ppm

#### · Ingredients with biological limit values:

#### 100-41-4 ethylbenzene

OTO, BEI, A3

BEI 0.15 g/g creatinine

Medium: urine Time: end of shift

Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

#### Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 6)

Printing date 08/18/2025 Reviewed on 08/18/2025

Trade name: SHS32 BLUE (GREEN SHADE) MIXING TINT

(Contd. of page 5)

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

Physical and chemical prope	
Information on basic physical and o	chemical properties
General Information	
Appearance:	I favorial
Form: Color:	Liquid Green
· Odor:	Characteristic
Odor threshold:	Not determined.
pH-value:	Not determined (pH N/A in solvent coatings)
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	124-128 °C (255.2-262.4 °F)
Flash point:	27 °C (80.6 °F)
Flammability:	Flammable.
Auto igniting:	370 °C (698 °F)
Decomposition temperature:	Not determined.
Ignition temperature:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive a vapor mixtures are possible.
Explosion limits:	
Lower:	1 Vol %
Upper:	7.5 Vol %
Vapor pressure at 20 °C (68 °F):	10.7 hPa (8 mm Hg)
Vapor pressure at 50 °C (122 °F):	55 hPa (41.3 mm Hg)
Density at 20 °C (68 °F):	1.0503 g/cm³ (8.7648 lbs/gal)
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/wate	er): Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.

Printing date 08/18/2025 Reviewed on 08/18/2025

Trade name: SHS32 BLUE (GREEN SHADE) MIXING TINT

(Contd. of page 6) · Solvent content: Organic solvents: 39.0 % **VOC** content: 39.02 % 367.1 g/l / 3.06 lb/gal 65.0 % Solids content: No further relevant information available. · Other information

### 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

# 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

<ul> <li>LD/LC50 values that are relevant for classification</li> </ul>

#### 110-43-0 heptan-2-one

LD50 1,670 mg/kg (rat) Oral Dermal LD50 12,600 mg/kg (rabbit)

- · Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

· Carcinogenic categories

1330-20-7	xylene	3
100-41-4	ethylbenzene	21
95-47-6	o-xylene	3
106-42-3	p-xylene	3
108-38-3	m-xylene	3
14808-60-7	Quartz (SiO2)	1

# NTP (National Toxicology Program)

14808-60-7 Quartz (SiO2)

(Contd. on page 8)

Κ

Printing date 08/18/2025 Reviewed on 08/18/2025

Trade name: SHS32 BLUE (GREEN SHADE) MIXING TINT

(Contd. of page 7)

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

### 12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

### 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

### 14 Transport information

· UN-Number

· DOT, IMDG, IATA UN1263

· UN proper shipping name

· **DOT** Paint · **IMDG, IATA** PAINT

- · Transport hazard class(es)
- · DOT



· Class 3 Flammable liquids

(Contd. on page 9)

Printing date 08/18/2025 Reviewed on 08/18/2025

Trade name: SHS32 BLUE (GREEN SHADE) MIXING TINT

(Contd. of page 8) 3 · Label · IMDG, IATA · Class 3 Flammable liquids ·Label · Packing group · DOT, IMDG, IATA Ш · Environmental hazards: · Marine pollutant: No · Special precautions for user Warning: Flammable liquids Hazard identification number (Kemler code): 30 · EMS Number: F-E,<u>S-E</u> · Stowage Category · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. · Transport/Additional information: · Quantity limitations On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L · IMDG 5L · Limited quantities (LQ) Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

# 15 Regulatory information

· UN "Model Regulation":

· Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

UN 1263 PAINT, 3, III

· Sara

Sara	
· Section 35	55 (extremely hazardous substances):
None of the	e ingredients is listed.
· Section 31	3 (Specific toxic chemical listings):
1330-20-7	xylene
100-41-4	ethylbenzene
95-47-6	o-xylene
106-42-3	p-xylene
108-38-3	m-xylene
122-99-6	2-phenoxyethanol
	(Contd. on page 10)

Printing date 08/18/2025 Reviewed on 08/18/2025

Trade name: SHS32 BLUE (GREEN SHADE) MIXING TINT

T004 /T	is Outsetoness Osetter LA-Ou	(Contd. of p
	c Substances Control Act):	AC7
	n-butyl acetate	ACT ACT
	heptan-2-one	
1330-20-7		AC7
	ethylbenzene	AC7
	o-xylene	AC7
106-42-3		AC7
	m-xylene	AC7
	Distillates (petroleum), hydrotreated light	AC7
	2-phenoxyethanol	AC7
	Quartz (SiO2)	AC7
	Propylene glycol	AC7
78-83-1	butanol	AC1
	Air Pollutants	
1330-20-7		
	ethylbenzene	
95-47-6	· ·	
106-42-3 µ		
108-38-3	-	
Proposition		
Chemicals	known to cause cancer:	
	ethylbenzene	
14808-60-7	Quartz (SiO2)	
Chemicals	known to cause reproductive toxicity for females:	
None of the	ingredients is listed.	
Chemicals	known to cause reproductive toxicity for males:	
None of the	ingredients is listed.	
Chemicals	known to cause developmental toxicity:	
None of the	ingredients is listed.	
Carcinogen	nic categories	
	onmental Protection Agency)	
1330-20-7	kylene	
100-41-4	ethylbenzene	
95-47-6	o-xylene	
106-42-3 µ	o-xylene	
108-38-3	n-xylene	
TLV (Thres	hold Limit Value)	
1330-20-7	•	
100-41-4	ethylbenzene	
	o-xylene	
106-42-3	<u> </u>	
	m-xylene	
108-38-3	III-X YICIIC	

Printing date 08/18/2025 Reviewed on 08/18/2025

Trade name: SHS32 BLUE (GREEN SHADE) MIXING TINT

(Contd. of page 10)

#### · NIOSH-Ca (National Institute for Occupational Safety and Health)

14808-60-7 Quartz (SiO2)

#### · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms







GHS02 GHS07 GHS08

### · Signal word Warning

#### · Hazard-determining components of labeling:

n-butyl acetate ethylbenzene

#### · Hazard statements

Flammable liquid and vapor.

Suspected of causing cancer.

May cause drowsiness or dizziness.

#### · Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF exposed or concerned: Get medical advice/attention.

Call a poison center/doctor if you feel unwell.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact: Product Safety Dept.
- · Date of preparation / last revision 08/18/2025 / 4
- · Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

(Contd. on page 12)

Printing date 08/18/2025 Reviewed on 08/18/2025

Trade name: SHS32 BLUE (GREEN SHADE) MIXING TINT

(Contd. of page 11)

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit BEI: Biological Exposure Limit

Flammable Liquids 3: Flammable liquids – Category 3 Carcinogenicity 2: Carcinogenicity – Category 2

Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) - Category 3

\* Data compared to the previous version altered.

- USA