



Safety Data Sheet acc. to OSHA HCS

Printing date 09/26/2018

Reviewed on 12/05/2017

1 Identification

- **Product identifier**
- **Trade name:** 0H4.077 COURSE LENTICULAR ALUMINUM
- **Article number:** 0H4.077
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Lusid Technologies
5195 West 4700 South
KEARNS, UT 84118
USA
www.lusid.biz
- **Information department:** Product safety department
- **Emergency telephone number:**
24 Hrs Emergency Contact:
INFOTRAC
1-800-535-5053

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.

Water-react. 1 H260 In contact with water releases flammable gases, which may ignite spontaneously.



GHS08 Health hazard

Muta. 1B H340 May cause genetic defects.

Carc. 1B H350 May cause cancer.

STOT RE 2 H373 May cause damage to the hearing organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

(Contd. on page 2)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/26/2018

Reviewed on 12/05/2017

Trade name: 0H4.077 COURSE LENTICULAR ALUMINUM

(Contd. of page 1)

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02 GHS07 GHS08

- **Signal word** Danger

- **Hazard-determining components of labeling:**

Naphtha (petroleum), hydrotreated heavy ethylbenzene

Solvent naphtha (petroleum), light arom.

- **Hazard statements**

Flammable liquid and vapor.

In contact with water releases flammable gases, which may ignite spontaneously.

Causes skin irritation.

May cause genetic defects.

May cause cancer.

May cause damage to the hearing organs through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

- **Precautionary statements**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Do not allow contact with water.

Handle under inert gas. Protect from moisture.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Immediately call a poison center/doctor.

Specific treatment (see on this label).

Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If exposed or concerned: Get medical advice/attention.

Get medical advice/attention if you feel unwell.

Take off contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

Brush off loose particles from skin. Immerse in cool water/wrap in wet bandages.

In case of fire: Use for extinction: CO₂, sand, extinguishing powder.

Store in a dry place. Store in a closed container.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/26/2018

Reviewed on 12/05/2017

Trade name: 0H4.077 COURSE LENTICULAR ALUMINUM

(Contd. of page 2)

- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



Health = 1
Fire = 3
Reactivity = 2

The substance demonstrates unusual reactivity with water.

- **HMIS-ratings (scale 0 - 4)**



Health = *1
Fire = 3
Reactivity = 2

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

| | | |
|------------|------------------------------------------|---------|
| 7429-90-5 | aluminium powder (stabilised) | 25-50% |
| 108-65-6 | 2-methoxy-1-methylethyl acetate | 10-25% |
| 1330-20-7 | xylene | 10-25% |
| 107-98-2 | 1-methoxy-2-propanol | 10-25% |
| 64742-48-9 | Naphtha (petroleum), hydrotreated heavy | 10-25% |
| 123-86-4 | n-butyl acetate | 2.5-10% |
| 64742-95-6 | Solvent naphtha (petroleum), light arom. | 2.5-10% |
| 100-41-4 | ethylbenzene | 2.5-10% |

4 First-aid measures

- **Description of first aid measures**
- **General information:**
Immediately remove any clothing soiled by the product.
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**
No further relevant information available.

(Contd. on page 4)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/26/2018

Reviewed on 12/05/2017

Trade name: 0H4.077 COURSE LENTICULAR ALUMINUM

(Contd. of page 3)

- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
Extinguishing powder. Do not use water.
CO₂. Do not use water.
Sand. Do not use water.
Special powder for metal fires. Do not use water.
CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

- **PAC-1:**

| | | |
|------------|-----------------------------------------|-----------------------|
| 108-65-6 | 2-methoxy-1-methylethyl acetate | 50 ppm |
| 1330-20-7 | xylene | 130 ppm |
| 107-98-2 | 1-methoxy-2-propanol | 100 ppm |
| 64742-48-9 | Naphtha (petroleum), hydrotreated heavy | 350 mg/m ³ |
| 123-86-4 | n-butyl acetate | 5 ppm |
| 100-41-4 | ethylbenzene | 33 ppm |
| 71-36-3 | butan-1-ol | 60 ppm |

- **PAC-2:**

| | | |
|------------|-----------------------------------------|-------------------------|
| 108-65-6 | 2-methoxy-1-methylethyl acetate | 1,000 ppm |
| 1330-20-7 | xylene | 920* ppm |
| 107-98-2 | 1-methoxy-2-propanol | 160 ppm |
| 64742-48-9 | Naphtha (petroleum), hydrotreated heavy | 1,800 mg/m ³ |
| 123-86-4 | n-butyl acetate | 200 ppm |

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/26/2018

Reviewed on 12/05/2017

Trade name: 0H4.077 COURSE LENTICULAR ALUMINUM

(Contd. of page 4)

| | | |
|-----------------|-----------------------------------------|--------------------------|
| 100-41-4 | ethylbenzene | 1100* ppm |
| 71-36-3 | butan-1-ol | 800 ppm |
| · PAC-3: | | |
| 108-65-6 | 2-methoxy-1-methylethyl acetate | 5000* ppm |
| 1330-20-7 | xylene | 2500* ppm |
| 107-98-2 | 1-methoxy-2-propanol | 660 ppm |
| 64742-48-9 | Naphtha (petroleum), hydrotreated heavy | 40,000 mg/m ³ |
| 123-86-4 | n-butyl acetate | 3000* ppm |
| 100-41-4 | ethylbenzene | 1800* ppm |
| 71-36-3 | butan-1-ol | 8000** ppm |

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
At this time, the other constituents have no known exposure limits.

| | |
|-------------------------------------------------|--------------------------------------------------------------------------------------------------------------|
| 108-65-6 2-methoxy-1-methylethyl acetate | |
| WEEL | Long-term value: 50 ppm |
| 1330-20-7 xylene | |
| PEL | Long-term value: 435 mg/m ³ , 100 ppm |
| REL | Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm |
| TLV | Short-term value: 651 mg/m ³ , 150 ppm Long-term value: 434 mg/m ³ , 100 ppm BEI |

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/26/2018

Reviewed on 12/05/2017

Trade name: 0H4.077 COURSE LENTICULAR ALUMINUM

(Contd. of page 5)

107-98-2 1-methoxy-2-propanol

| | |
|-----|-------------------------------------------------------------------------------------------------------|
| REL | Short-term value: 540 mg/m ³ , 150 ppm Long-term value: 360 mg/m ³ , 100 ppm |
| TLV | Short-term value: 369 mg/m ³ , 100 ppm Long-term value: 184 mg/m ³ , 50 ppm |

123-86-4 n-butyl acetate

| | |
|-----|-------------------------------------------------------------------------------------------------------|
| PEL | Long-term value: 710 mg/m ³ , 150 ppm |
| REL | Short-term value: 950 mg/m ³ , 200 ppm Long-term value: 710 mg/m ³ , 150 ppm |
| TLV | Short-term value: 712 mg/m ³ , 150 ppm Long-term value: 238 mg/m ³ , 50 ppm |

100-41-4 ethylbenzene

| | |
|-----|-------------------------------------------------------------------------------------------------------|
| PEL | Long-term value: 435 mg/m ³ , 100 ppm |
| REL | Short-term value: 545 mg/m ³ , 125 ppm Long-term value: 435 mg/m ³ , 100 ppm |
| TLV | Long-term value: 87 mg/m ³ , 20 ppm BEI |

· **Ingredients with biological limit values:**

1330-20-7 xylene

| | |
|-----|----------------------------------------------------------------------------------------------|
| BEI | 1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids |
|-----|----------------------------------------------------------------------------------------------|

100-41-4 ethylbenzene

| | |
|-----|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| BEI | 0.7 g/g creatinine Medium: urine Time: end of shift at end of workweek Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative) |
| - | Medium: end-exhaled air Time: not critical Parameter: Ethyl benzene (semi-quantitative) |

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.
- Avoid contact with the skin.
- Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

(Contd. on page 7)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/26/2018

Reviewed on 12/05/2017

Trade name: 0H4.077 COURSE LENTICULAR ALUMINUM

(Contd. of page 6)

- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

| | |
|-----------------|-----------------|
| Form: | Liquid |
| Color: | Silver-colored |
| Odor: | Characteristic |
| Odor threshold: | Not determined. |

- **pH-value:** Not determined (pH N/A in solvent coatings)

- **Change in condition**

| | |
|------------------------------|---------------------|
| Melting point/Melting range: | Undetermined. |
| Boiling point/Boiling range: | 120.3 °C (248.5 °F) |

- **Flash point:** 27 °C (80.6 °F)

- **Flammability (solid, gaseous):** Not applicable.

- **Decomposition temperature:** Not determined.

- **Auto igniting:** Product is not selfigniting.

- **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

- **Explosion limits:**

| | |
|--------|-----------------|
| Lower: | Not determined. |
| Upper: | Not determined. |

(Contd. on page 8)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/26/2018

Reviewed on 12/05/2017

Trade name: 0H4.077 COURSE LENTICULAR ALUMINUM

(Contd. of page 7)

| | |
|---------------------------------------------------|--------------------------------------------|
| · Vapor pressure: | Not determined. |
| · Density at 20 °C (68 °F): | 1.01 g/cm ³ (8.4285 lbs/gal) |
| · Relative density | Not determined. |
| · Vapor density | Not determined. |
| · Evaporation rate | Not determined. |
| · Solubility in / Miscibility with Water: | Not miscible or difficult to mix. |
| · Partition coefficient (n-octanol/water): | Not determined. |
| · Viscosity: | |
| Dynamic: | Not determined. |
| Kinematic: | Not determined. |
| · Solvent content: | |
| Organic solvents: | 58.0 % |
| VOC content: | 58.01 % |
| | 651.1 g/l / 5.43 lb/gal |
| Solids content: | 30.0 % |
| · Other information | No further relevant information available. |

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** Contact with water releases flammable gases.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

1330-20-7 xylene

| | | |
|--------|------|----------------------|
| Oral | LD50 | 4,300 mg/kg (rat) |
| Dermal | LD50 | 2,000 mg/kg (rabbit) |

64742-48-9 Naphtha (petroleum), hydrotreated heavy

| | | |
|--------|------|--------------------|
| Oral | LD50 | >5,000 mg/kg (rat) |
| Dermal | LD50 | >3,000 mg/kg (rab) |

64742-95-6 Solvent naphtha (petroleum), light arom.

| | | |
|------------|----------|--------------------|
| Oral | LD50 | >6,800 mg/kg (rat) |
| Dermal | LD50 | >3,400 mg/kg (rab) |
| Inhalative | LC50/4 h | >10.2 mg/l (rat) |

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/26/2018

Reviewed on 12/05/2017

Trade name: 0H4.077 COURSE LENTICULAR ALUMINUM

(Contd. of page 8)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** No irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant
The product can cause inheritable damage.

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

| | | |
|-----------|--------------|----|
| 1330-20-7 | xylene | 3 |
| 100-41-4 | ethylbenzene | 2B |

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

USA

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS



Printing date 09/26/2018

Reviewed on 12/05/2017

Trade name: 0H4.077 COURSE LENTICULAR ALUMINUM

(Contd. of page 9)

14 Transport information

| | |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------|
| <ul style="list-style-type: none"> · UN-Number · DOT, IMDG, IATA | UN1263 |
| <ul style="list-style-type: none"> · UN proper shipping name · DOT · IMDG, IATA | Paint PAINT |
| <ul style="list-style-type: none"> · Transport hazard class(es) · DOT | <div style="text-align: center;">  </div> |
| <ul style="list-style-type: none"> · Class · Label | 3 Flammable liquids 3 |
| <ul style="list-style-type: none"> · IMDG, IATA | <div style="text-align: center;">  </div> |
| <ul style="list-style-type: none"> · Class · Label | 3 Flammable liquids 3 |
| <ul style="list-style-type: none"> · Packing group · DOT, IMDG, IATA | III |
| <ul style="list-style-type: none"> · Environmental hazards: | Not applicable. |
| <ul style="list-style-type: none"> · Special precautions for user · Danger code (Kemler): · EMS Number: · Stowage Category | Warning: Flammable liquids 39 F-E, S-E A |
| <ul style="list-style-type: none"> · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | Not applicable. |
| <ul style="list-style-type: none"> · Transport/Additional information: · DOT · Quantity limitations | On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L |
| <ul style="list-style-type: none"> · IMDG · Limited quantities (LQ) · Excepted quantities (EQ) | 5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml |
| <ul style="list-style-type: none"> · UN "Model Regulation": | UN 1263 PAINT, 3, III |

USA

(Contd. on page 11)

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/26/2018

Reviewed on 12/05/2017

Trade name: 0H4.077 COURSE LENTICULAR ALUMINUM

(Contd. of page 10)

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· Sara

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

| | |
|-----------|--------|
| 1330-20-7 | xylene |
|-----------|--------|

| | |
|----------|--------------|
| 100-41-4 | ethylbenzene |
|----------|--------------|

| | |
|---------|------------|
| 71-36-3 | butan-1-ol |
|---------|------------|

· **TSCA (Toxic Substances Control Act):**

| | |
|----------|---------------------------------|
| 108-65-6 | 2-methoxy-1-methylethyl acetate |
|----------|---------------------------------|

| | |
|-----------|--------|
| 1330-20-7 | xylene |
|-----------|--------|

| | |
|----------|----------------------|
| 107-98-2 | 1-methoxy-2-propanol |
|----------|----------------------|

| | |
|------------|-----------------------------------------|
| 64742-48-9 | Naphtha (petroleum), hydrotreated heavy |
|------------|-----------------------------------------|

| | |
|----------|-----------------|
| 123-86-4 | n-butyl acetate |
|----------|-----------------|

| | |
|------------|------------------------------------------|
| 64742-95-6 | Solvent naphtha (petroleum), light arom. |
|------------|------------------------------------------|

| | |
|----------|--------------|
| 100-41-4 | ethylbenzene |
|----------|--------------|

| | |
|---------|------------|
| 71-36-3 | butan-1-ol |
|---------|------------|

· **TSCA new (21st Century Act) (Substances not listed)**

| | |
|-----------|-------------------------------|
| 7429-90-5 | aluminium powder (stabilised) |
|-----------|-------------------------------|

· **Proposition 65**

· **Chemicals known to cause cancer:**

| | |
|----------|--------------|
| 100-41-4 | ethylbenzene |
|----------|--------------|

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

| | | |
|-----------|--------|---|
| 1330-20-7 | xylene | I |
|-----------|--------|---|

| | | |
|----------|--------------|---|
| 100-41-4 | ethylbenzene | D |
|----------|--------------|---|

| | | |
|---------|------------|---|
| 71-36-3 | butan-1-ol | D |
|---------|------------|---|

· **TLV (Threshold Limit Value established by ACGIH)**

| | | |
|-----------|--------|----|
| 1330-20-7 | xylene | A4 |
|-----------|--------|----|

| | | |
|----------|--------------|----|
| 100-41-4 | ethylbenzene | A3 |
|----------|--------------|----|

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 12)

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/26/2018

Reviewed on 12/05/2017

Trade name: 0H4.077 COURSE LENTICULAR ALUMINUM

(Contd. of page 11)

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**

Naphtha (petroleum), hydrotreated heavy ethylbenzene
Solvent naphtha (petroleum), light arom.

· **Hazard statements**

Flammable liquid and vapor.
In contact with water releases flammable gases, which may ignite spontaneously.
Causes skin irritation.
May cause genetic defects.
May cause cancer.
May cause damage to the hearing organs through prolonged or repeated exposure.
May be fatal if swallowed and enters airways.

· **Precautionary statements**

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Do not allow contact with water.
Handle under inert gas. Protect from moisture.
Keep container tightly closed.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting/equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Do not breathe dust/fume/gas/mist/vapors/spray.
Wash thoroughly after handling.
Wear protective gloves/protective clothing/eye protection/face protection.
If swallowed: Immediately call a poison center/doctor.
Specific treatment (see on this label).
Do NOT induce vomiting.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
If exposed or concerned: Get medical advice/attention.
Get medical advice/attention if you feel unwell.
Take off contaminated clothing and wash it before reuse.
If skin irritation occurs: Get medical advice/attention.
Brush off loose particles from skin. Immerse in cool water/wrap in wet bandages.
In case of fire: Use for extinction: CO₂, sand, extinguishing powder.
Store in a dry place. Store in a closed container.
Store in a well-ventilated place. Keep cool.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.

· **National regulations:**

· **Additional classification according to Decree on Hazardous Materials:**

Carcinogenic hazardous material group III (dangerous).

(Contd. on page 13)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/26/2018

Reviewed on 12/05/2017

Trade name: 0H4.077 COURSE LENTICULAR ALUMINUM

(Contd. of page 12)

· **Information about limitation of use:**

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Environment protection department.

· **Contact:** Product Safety Dept.

· **Date of preparation / last revision** 09/26/2018 / 2

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Liq. 3: Flammable liquids – Category 3

Water-react. 1: Substances and mixtures which in contact with water emit flammable gases – Category 1

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Muta. 1B: Germ cell mutagenicity – Category 1B

Carc. 1B: Carcinogenicity – Category 1B

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

· *** Data compared to the previous version altered.**

USA