

Safety Data Sheet acc. to OSHA HCS

Printing date 05/22/2026

Reviewed on 05/22/2026

1 Identification

- **Product identifier**
- **Trade name:** LP3030HS 2K HS URETHANE PRIMER
- **Article number:** LP3030HS
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
GlobalBase is a product of Lusid Technologies Inc.
4725 S Camp Kearns Road
Kearns, UT 84118
(801) 966-5300
info@lusidtechnologies.com
- **Information department:** Product safety department
- **Emergency telephone number:**
24 Hrs Emergency Contact
INFOTRAC
1-800-535-5053 CONTRACT 115477

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flammable Liquids 2

H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Carcinogenicity 1A

H350 May cause cancer. Route of exposure:
Inhalation.

Toxic to Reproduction 2

H361 Suspected of damaging fertility or the
unborn child.

Specific Target Organ Toxicity - Repeated Exposure 2 H373 May cause damage to the hearing organs
through prolonged or repeated exposure.


GHS07

Skin Irritation 2

H315 Causes skin irritation.

Eye Irritation 2A

H319 Causes serious eye irritation.

Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/22/2026

Reviewed on 05/22/2026

Trade name: LP3030HS 2K HS URETHANE PRIMER

(Contd. of page 1)

Hazard pictograms



GHS02 GHS07 GHS08

Signal word Danger

Hazard-determining components of labeling:

Talc ($\text{Mg}_3\text{H}_2(\text{SiO}_3)_4$)

n-butyl acetate

ethylbenzene

toluene

Hazard statements

Highly flammable liquid and vapor.

Causes skin irritation.

Causes serious eye irritation.

May cause cancer. Route of exposure: Inhalation.

Suspected of damaging fertility or the unborn child.

May cause drowsiness or dizziness.

May cause damage to the hearing organs through prolonged or repeated exposure.

Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If exposed or concerned: Get medical advice/attention.

Call a poison center/doctor if you feel unwell.

Specific treatment (see on this label).

Get medical advice/attention if you feel unwell.

Take off contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use CO₂, powder or water spray to extinguish.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

Classification system:

NFPA ratings (scale 0 - 4)



Health = 2

Fire = 3

Reactivity = 0

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/22/2026

Reviewed on 05/22/2026

Trade name: LP3030HS 2K HS URETHANE PRIMER

(Contd. of page 2)

· HMIS-ratings (scale 0 - 4)

HEALTH	2	Health = *2
FIRE	3	Fire = 3
REACTIVITY	0	Reactivity = 0

- Other hazards
- Results of PBT and vPvB assessment
- PBT: Not applicable
- vPvB: Not applicable

3 Composition/information on ingredients

- Chemical characterization: Mixtures
- Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:

123-86-4	n-butyl acetate	10-25%
110-43-0	heptan-2-one	10-25%
14807-96-6	Talc (Mg ₃ H ₂ (SiO ₃) ₄)	10-25%
1330-20-7	xylene	10-25%
67-64-1	acetone	2.5-10%
79-20-9	methyl acetate	2.5-10%
7727-43-7	barium sulphate, natural	2.5-10%
13463-67-7	titanium dioxide	≤2.5%
100-41-4	ethylbenzene	≤2.5%
108-88-3	toluene	≤2.5%
64-17-5	ethanol	≤2.5%

4 First-aid measures

- Description of first aid measures
- General information:
Immediately remove any clothing soiled by the product.
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact:
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- Information for doctor:
Most important symptoms and effects, both acute and delayed
No further relevant information available.
- Indication of any immediate medical attention and special treatment needed
No further relevant information available.

USA

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/22/2026

Reviewed on 05/22/2026

Trade name: LP3030HS 2K HS URETHANE PRIMER

(Contd. of page 3)

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Prevent seepage into sewage system, workpits and cellars.
Dilute with plenty of water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· PAC-1:

123-86-4	<i>n</i> -butyl acetate	5 ppm
110-43-0	heptan-2-one	75 ppm
1330-20-7	xylene	130 ppm
67-64-1	acetone	200 ppm
79-20-9	methyl acetate	250 ppm
7727-43-7	barium sulphate, natural	15 mg/m ³
13463-67-7	titanium dioxide	30 mg/m ³
100-41-4	ethylbenzene	33 ppm
108-88-3	toluene	67 ppm
64-17-5	ethanol	1800? ppm
77-58-7	dibutyltin dilaurate	1.1 mg/m ³
67-56-1	methanol	530 ppm
1333-86-4	Carbon black	9 mg/m ³
108-65-6	2-methoxy-1-methylethyl acetate	50? ppm
67-63-0	propan-2-ol	400 ppm

· PAC-2:

123-86-4	<i>n</i> -butyl acetate	200 ppm
110-43-0	heptan-2-one	130 ppm
1330-20-7	xylene	920 ppm
67-64-1	acetone	3200 ppm

(Contd. on page 5)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/22/2026

Reviewed on 05/22/2026

Trade name: LP3030HS 2K HS URETHANE PRIMER

(Contd. of page 4)

79-20-9	methyl acetate	1700 ppm
7727-43-7	barium sulphate, natural	170 mg/m3
13463-67-7	titanium dioxide	330 mg/m3
100-41-4	ethylbenzene	1100 ppm
108-88-3	toluene	560 ppm
64-17-5	ethanol	3300?* ppm
77-58-7	dibutyltin dilaurate	3.8 mg/m3
67-56-1	methanol	2100 ppm
1333-86-4	Carbon black	290 mg/m3
108-65-6	2-methoxy-1-methylethyl acetate	1000? ppm
67-63-0	propan-2-ol	2000 ppm

· **PAC-3:**

123-86-4	n-butyl acetate	3000 ppm
110-43-0	heptan-2-one	800 ppm
1330-20-7	xylene	2500 ppm
67-64-1	acetone	5700 ppm
79-20-9	methyl acetate	10000 ppm
7727-43-7	barium sulphate, natural	990 mg/m3
13463-67-7	titanium dioxide	2000 mg/m3
100-41-4	ethylbenzene	1800 ppm
108-88-3	toluene	3700 ppm
64-17-5	ethanol	15000* ppm
77-58-7	dibutyltin dilaurate	23 mg/m3
67-56-1	methanol	7200 ppm
1333-86-4	Carbon black	1750 mg/m3
108-65-6	2-methoxy-1-methylethyl acetate	5000?* ppm
67-63-0	propan-2-ol	12000 ppm

7 Handling and storage

· **Handling:**· **Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· **Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

· **Conditions for safe storage, including any incompatibilities**· **Storage:**· **Requirements to be met by storerooms and receptacles:** Store in a cool location.· **Information about storage in one common storage facility:** Not required· **Further information about storage conditions:**

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

(Contd. on page 6)

-USA-

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/22/2026

Reviewed on 05/22/2026

Trade name: LP3030HS 2K HS URETHANE PRIMER

(Contd. of page 5)

· **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

· **Additional information about design of technical systems:** No further data; see section 7.· **Control parameters**· **Components with limit values that require monitoring at the workplace:**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

123-86-4 n-butyl acetate

PEL Long-term value: 710 mg/m³, 150 ppm

REL Short-term value: 950 mg/m³, 200 ppm

Long-term value: 710 mg/m³, 150 ppm

TLV Short-term value: 712 mg/m³, 150 ppm

Long-term value: 238 mg/m³, 50 ppm

110-43-0 heptan-2-one

PEL Long-term value: 465 mg/m³, 100 ppm

REL Long-term value: 465 mg/m³, 100 ppm

TLV Long-term value: 50 ppm

1330-20-7 xylene

PEL Long-term value: 435 mg/m³, 100 ppm

REL Short-term value: 655 mg/m³, 150 ppm

Long-term value: 435 mg/m³, 100 ppm

TLV Long-term value: 20 ppm

BEI, A4

67-64-1 acetone

PEL Long-term value: 2400 mg/m³, 1000 ppm

REL Long-term value: 590 mg/m³, 250 ppm

TLV Short-term value: 1187 mg/m³, 500 ppm

Long-term value: 594 mg/m³, 250 ppm

A4, BEI

79-20-9 methyl acetate

PEL Long-term value: 610 mg/m³, 200 ppm

REL Short-term value: 760 mg/m³, 250 ppm

Long-term value: 610 mg/m³, 200 ppm

TLV Short-term value: 757 mg/m³, 250 ppm

Long-term value: 606 mg/m³, 200 ppm

7727-43-7 barium sulphate, natural

PEL Long-term value: 15* 5** mg/m³

*total dust **respirable fraction

REL Long-term value: 10* 5** mg/m³

*total dust **respirable fraction

TLV Long-term value: 5* mg/m³

*inhalable fraction; E

(Contd. on page 7)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/22/2026

Reviewed on 05/22/2026

Trade name: LP3030HS 2K HS URETHANE PRIMER

(Contd. of page 6)

100-41-4 ethylbenzene

PEL Long-term value: 435 mg/m³, 100 ppm
 REL Short-term value: 545 mg/m³, 125 ppm
 Long-term value: 435 mg/m³, 100 ppm
 TLV Long-term value: 20 ppm
 OTO, BEI, A3

108-88-3 toluene

PEL Long-term value: 200 ppm
 Ceiling limit value: 300; 500* ppm
 *10-min peak per 8-hr shift
 REL Short-term value: 560 mg/m³, 150 ppm
 Long-term value: 375 mg/m³, 100 ppm
 TLV Long-term value: 20 ppm
 BEI, OTO, A4

64-17-5 ethanol

PEL Long-term value: 1900 mg/m³, 1000 ppm
 REL Long-term value: 1900 mg/m³, 1000 ppm
 TLV Short-term value: 1880 mg/m³, 1000 ppm
 A3

Ingredients with biological limit values:**1330-20-7 xylene**

BEI 0.3 g/g creatinine
 Medium: urine
 Time: end of shift
 Parameter: Methylhippuric acids

67-64-1 acetone

BEI 25 mg/L
 Medium: urine
 Time: end of shift
 Parameter: Acetone (nonspecific)

100-41-4 ethylbenzene

BEI 0.15 g/g creatinine
 Medium: urine
 Time: end of shift
 Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific)

108-88-3 toluene

BEI 0.02 mg/L
 Medium: blood
 Time: prior to last shift of workweek
 Parameter: Toluene

0.03 mg/L
 Medium: urine
 Time: end of shift
 Parameter: Toluene

0.3 mg/g creatinine
 Medium: urine
 Time: end of shift
 Parameter: o-Cresol with hydrolysis (background)

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/22/2026

Reviewed on 05/22/2026

Trade name: LP3030HS 2K HS URETHANE PRIMER

(Contd. of page 7)

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
 Keep away from foodstuffs, beverages and feed.
 Immediately remove all soiled and contaminated clothing.
 Wash hands before breaks and at the end of work.
 Store protective clothing separately.
 Avoid contact with the eyes and skin.
- **Breathing equipment:**
 In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**
 The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**
 The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form:

Liquid

Color:

According to product specification

· Odor:

Characteristic

· Odor threshold:

Not determined

· pH-value:

Not determined (pH N/A in solvent coatings)

· Change in condition

Melting point/Melting range:

Undetermined

Boiling point/Boiling range:

55.8-56.6 °C (132.4-133.9 °F)

(Contd. on page 9)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/22/2026

Reviewed on 05/22/2026

Trade name: LP3030HS 2K HS URETHANE PRIMER

(Contd. of page 8)

· Flash point:	<-18 °C (<-0.4 °F)
· Flammability:	Highly flammable.
· Auto igniting:	370 °C (698 °F)
· Decomposition temperature:	Not determined
· Ignition temperature:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits:	
Lower:	1 Vol %
Upper:	7.5 Vol %
· Vapor pressure at 20 °C (68 °F):	10.7 hPa (8 mm Hg)
· Vapor pressure at 50 °C (122 °F):	55 hPa (41.3 mm Hg)
· Density at 20 °C (68 °F):	1.366 g/cm ³ (11.3993 lbs/gal)
· Relative density	Not determined
· Vapor density	Not determined
· Evaporation rate	Not determined
· Solubility in / Miscibility with Water:	Fully miscible.
· Partition coefficient (n-octanol/water):	Not determined
· Viscosity:	
Dynamic:	Not determined
Kinematic:	Not determined
· Solvent content:	
Organic solvents:	60.9 %
Water:	0.1 %
VOC content:	50.92 %
	507.7 g/l / 4.24 lb/gal
Solids content:	60.1 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

USA

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/22/2026

Reviewed on 05/22/2026

Trade name: LP3030HS 2K HS URETHANE PRIMER

(Contd. of page 9)

11 Toxicological information

- **Information on toxicological effects**

- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

110-43-0 heptan-2-one

Oral	LD50	1,670 mg/kg (rat)
Dermal	LD50	12,600 mg/kg (rabbit)

- **Primary irritant effect:**

- **on the skin:** Irritant to skin and mucous membranes.

- **on the eye:** Irritating effect.

- **Sensitization:** No sensitizing effects known.

- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

14807-96-6	Talc (Mg ₃ H ₂ (SiO ₃) ₄)	2A
1330-20-7	xylene	3
13463-67-7	titanium dioxide	2B
100-41-4	ethylbenzene	2B
108-88-3	toluene	3
64-17-5	ethanol	1
1333-86-4	Carbon black	2B
67-63-0	propan-2-ol	3

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**

- **Aquatic toxicity:** No further relevant information available.

- **Persistence and degradability** No further relevant information available.

- **Behavior in environmental systems:**

- **Bioaccumulative potential** No further relevant information available.

- **Mobility in soil** No further relevant information available.

- **Additional ecological information:**

- **General notes:** Not hazardous for water.

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable

- **vPvB:** Not applicable

- **Other adverse effects** No further relevant information available.

USA

(Contd. on page 11)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/22/2026

Reviewed on 05/22/2026

Trade name: LP3030HS 2K HS URETHANE PRIMER

(Contd. of page 10)

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport information

- | | |
|---|---|
| · UN-Number | UN1263 |
| · DOT, IMDG, IATA | |
| · UN proper shipping name | Paint |
| · DOT | PAINT |
| · IMDG, IATA | |
| · Transport hazard class(es) | |
| · DOT | |
|  | |
| · Class | 3 Flammable liquids |
| · Label | 3 |
| · IMDG, IATA | |
|  | |
| · Class | 3 Flammable liquids |
| · Label | 3 |
| · Packing group | II |
| · DOT, IMDG, IATA | |
| · Environmental hazards: | Not applicable |
| · Special precautions for user | Warning: Flammable liquids |
| · Hazard identification number (Kemler code): | 33 |
| · EMS Number: | F-E, S-E |
| · Stowage Category | B |
| · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | Not applicable |
| · Transport/Additional information: | |
| · DOT | |
| · Quantity limitations | On passenger aircraft/rail: 5 L
On cargo aircraft only: 60 L |

(Contd. on page 12)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/22/2026

Reviewed on 05/22/2026

Trade name: LP3030HS 2K HS URETHANE PRIMER

(Contd. of page 11)

- | | |
|--|---|
| <ul style="list-style-type: none"> · IMDG · Limited quantities (LQ) · Excepted quantities (EQ) | 5L
Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml |
| <ul style="list-style-type: none"> · UN "Model Regulation": | UN 1263 PAINT, 3, II |

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**

- **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

- **Section 313 (Specific toxic chemical listings):**

1330-20-7	xylene
7727-43-7	barium sulphate, natural
100-41-4	ethylbenzene
108-88-3	toluene
67-56-1	methanol
67-63-0	propan-2-ol

- **TSCA (Toxic Substances Control Act):**

All components have the value ACTIVE.

- **Hazardous Air Pollutants**

1330-20-7	xylene
100-41-4	ethylbenzene
108-88-3	toluene
67-56-1	methanol

- **Proposition 65**

- **Chemicals known to cause cancer:**

13463-67-7	titanium dioxide
100-41-4	ethylbenzene
1333-86-4	Carbon black

- **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

- **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

- **Chemicals known to cause developmental toxicity:**

108-88-3	toluene
64-17-5	ethanol
67-56-1	methanol

- **Carcinogenic categories**

- **EPA (Environmental Protection Agency)**

1330-20-7	xylene
-----------	--------

I

(Contd. on page 13)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/22/2026

Reviewed on 05/22/2026

Trade name: LP3030HS 2K HS URETHANE PRIMER

(Contd. of page 12)

67-64-1	acetone	I
7727-43-7	barium sulphate, natural	D, CBD(inh), NL(oral)
100-41-4	ethylbenzene	D
108-88-3	toluene	II

· **TLV (Threshold Limit Value)**

14807-96-6	Talc (Mg ₃ H ₂ (SiO ₃) ₄)	A4
1330-20-7	xylene	A4
67-64-1	acetone	A4
13463-67-7	titanium dioxide	A4
100-41-4	ethylbenzene	A3
108-88-3	toluene	A4
64-17-5	ethanol	A3
77-58-7	dibutyltin dilaurate	A4
1333-86-4	Carbon black	A4
67-63-0	propan-2-ol	A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

13463-67-7	titanium dioxide
1333-86-4	Carbon black

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**

Talc (Mg₃H₂(SiO₃)₄)

n-butyl acetate

ethylbenzene

toluene

· **Hazard statements**

Highly flammable liquid and vapor.

Causes skin irritation.

Causes serious eye irritation.

May cause cancer. Route of exposure: Inhalation.

Suspected of damaging fertility or the unborn child.

May cause drowsiness or dizziness.

May cause damage to the hearing organs through prolonged or repeated exposure.

· **Precautionary statements**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

(Contd. on page 14)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/22/2026

Reviewed on 05/22/2026

Trade name: LP3030HS 2K HS URETHANE PRIMER

(Contd. of page 13)

Do not breathe dust/fume/gas/mist/vapors/spray.
 Wash thoroughly after handling.
 Use only outdoors or in a well-ventilated area.
 Wear protective gloves/protective clothing/eye protection/face protection.
 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 IF exposed or concerned: Get medical advice/attention.
 Call a poison center/doctor if you feel unwell.
 Specific treatment (see on this label).
 Get medical advice/attention if you feel unwell.
 Take off contaminated clothing and wash it before reuse.
 If skin irritation occurs: Get medical advice/attention.
 If eye irritation persists: Get medical advice/attention.
 In case of fire: Use CO₂, powder or water spray to extinguish.
 Store in a well-ventilated place. Keep container tightly closed.
 Store in a well-ventilated place. Keep cool.
 Store locked up.
 Dispose of contents/container in accordance with local/regional/national/international regulations.

• **National regulations:**

• **Information about limitation of use:**

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

• **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

• **Contact:**

• **Date of preparation / last revision** 05/22/2026 / 5

• **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flammable Liquids 2: Flammable liquids – Category 2

Skin Irritation 2: Skin corrosion/irritation – Category 2

Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A

Carcinogenicity 1A: Carcinogenicity – Category 1A

Toxic to Reproduction 2: Reproductive toxicity – Category 2

Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3

(Contd. on page 15)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/22/2026

Reviewed on 05/22/2026

Trade name: LP3030HS 2K HS URETHANE PRIMER

(Contd. of page 14)

Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) – Category 2

· *** Data compared to the previous version altered.**

-USA-